

End My Exam 0:11:00 %
Course > Graded > Quiz 1 > Quiz 1
<
>
Quiz 1 Questions
Multiple Choice
1 point possible (graded, results hidden) Usually Motors require a motor driver because:
The ampere provided by Micro-controller is enough to drive a motor.
The voltage provided by a Micro-controller is not enough to drive a motor.
To convert analogue signals into digital signals.
Motor driver acts as the calibration circuit.
Submit You have used 1 of 1 attempt
Answer submitted.
 Answer submitted. Multiple Choice point possible (graded, results hidden)

End My E	xam 0:11:00 %
OUSB.	
36 Pin	Parallel Connector.
DB9.	
Submit	You have used 1 of 1 attempt
A nswer	submitted.
Answer	submitted.
lultiple	Choice
Iultiple	
lultiple point possib hich of the	Choice e (graded, results hidden) following are the types of HDMI?
lultiple point possib hich of the	Choice e (graded, results hidden) following are the types of HDMI?
lultiple point possib hich of the Type D	Choice e (graded, results hidden) following are the types of HDMI?
lultiple point possib hich of the Type D	Choice e (graded, results hidden) following are the types of HDMI?
Iultiple point possib hich of the Type D Type I.	Choice e (graded, results hidden) following are the types of HDMI?

End My E	xam	0:11:00	4 >			
CPU is	connect	ed with k	eyboard via interna	al bus.		
Memor	y sends	address t	o CPU through int	ernal addres	s bus for addr	essing purpose.
CPU is	connect	ed with m	onitor via externa	l bus.		
Submit	You ha	ve used 1	of 1 attempt			
Answer	submitt	ed.				
	Cl ' .	_				
-			d d - «			
ooint possibl ost inkjet, l	e (graded aser, and	l, results hi d thermal	printers use some	e ports to co	nnect a printer	to a computer in
ooint possibl ost inkjet, l	e (graded aser, and	l, results hi d thermal	printers use some	e ports to co	nnect a printer	to a computer ir
ooint possiblost inkjet, l	e (graded aser, and	l, results hi d thermal	printers use some	e ports to co	nnect a printer	to a computer in
ooint possible ost inkjet, left of the relationship of the relatio	e (graded aser, and and at pr	l, results hi d thermal	printers use some	e ports to co	nnect a printer	to a computer in
PS2.	e (graded aser, and and at pr	l, results hi d thermal	printers use some	e ports to co	nnect a printer	to a computer in
ooint possible ost inkjet, left days a lef	e (graded aser, and and at pr	l, results hi d thermal	printers use some	e ports to co	nnect a printer	to a computer in
ooint possible ost inkjet, left days a lef	e (graded aser, and and at pr	l, results hi	printers use some	e ports to co	nnect a printer	to a computer in

You are taking "Quiz 1" as a timed exam. The timer on the right shows the time remaining in the exam. To receive credit for problems, you must select "Submit" for each problem before you select "End My Exam". Show Less
End My Exam 0:11:00 %
communicate is called an interface.
Interfacing cannot be done between human and machine
Interface is only responsible for transmitting analog to digital signal
A and C
All of the mentioned
Submit You have used 1 of 1 attempt
Answer submitted.
Multiple Choice
1 point possible (graded, results hidden) Suppose two devices A and A' are communicating with a two bit data bus. In the bus controller e is used for read control and f is used for write control. What will happen if $e=1$, $f=0$, $e'=0$, $f'=1$:
A is writing to A'.
A is tri-stated.
Bus error or system failure.
A' is writing to A.

You have used 1 of 1 attempt

You are taking "Quiz 1" as a timed exam. The timer on the right shows the time remaining in the exam. To receive credit for problems, you must select "Submit" for each problem before you select "End My Exam". **Show Less**

End My Exam

0:11:00

Multiple Choice
1 point possible (graded, results hidden) Which of the following is false about External Bus Interface?
It can use serial transmission.
It can use parallel transmission.
lt is faster than internal buses.
All of the above.
None of the above.
Submit You have used 1 of 1 attempt
• Answer submitted.
Multiple Choice
1 point possible (graded, results hidden) Which of the following is false for a Peripheral Device?
It is often dependent on the host computer.
It forms part of the core computer architecture.
It increases the host computer's abilities.

End My Exa	am 0:11:00 %
1 Answer	submitted.
Лultiple С	Choice
point possible Vhich statem	(graded, results hidden) ent is true?
To disco disablec	nnect a device from a two bit bus only read and write control should be
Address	line in Bus is Bidirectional
Interface	e is only responsible for transmitting analog to digital signal
Control	Line in Bus is responsible for carrying binary data
All of th	e mentioned
Submit	You have used 1 of 1 attempt
1 Answer	submitted.
Multiple C	Choice
	(graded, results hidden) cable is used as an Ethernet port for long distances and without signal booster

End My Exa	m 0:11:00 %
Ocoaxial.	
Submit	You have used 1 of 1 attempt
Answer s	ubmitted.
ultiple C	hoice
•	(graded, results hidden) nts A and B started driving the bus at the same time which caused a short pecause
A and B	were reading from the bus at the same time.
A was re	ading and B was writing which caused the bus conflict
A and B	were writing at the same time.
Submit	You have used 1 of 1 attempt
Answer s	ubmitted.
ultiple C	hoice
•	(graded, results hidden) f a hardware port is to provide:

End My Exa	am 0:11:00 %
) None of	the above.
Submit	You have used 1 of 1 attempt
Answer	submitted.
ultiple (
•	e (graded, results hidden) ent is true for a calibration circuit?
A senso	r output is the input of it.
) It interfa	ices at low level devices.
The out	out of it is the input for a microcontroller.
	rts non-electrical signals to electrical signals for further processing by the
It conve Processi	rts non-electrical signals to electrical signals for further processing by the
It conve Processi	rts non-electrical signals to electrical signals for further processing by the ng unit.
It conve Processi All of th	rts non-electrical signals to electrical signals for further processing by the ng unit. em mentioned above.

End My E	w Less xam 0:11:00 ♥ >
_	
Externa	Il Input Interface.
Both of	them.
None c	of them.
Submit	You have used 1 of 1 attempt
3 Answer	submitted.
	∢ Previous

© All Rights Reserved

About Us

BracU Home

USIS

Course Catalog

Copyright - 2020