

Spring boot Guia 3 – Conexion Base de datos

Nombre : Miguel Abraham Lacruz Medina

Ficha : 3114733

Profesora : Diana Delgado

Curso : Analisis y desarrollo de software

```
shaggy@debian ~/D/P/i/individuos> doas docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
262cd4948410	mysql:latest	"docker-entrypoint.s..."	5 days ago	Up 17 seconds	0.0.0.0:3306->3306/tcp, :::3306->3306/tcp, 33060/tcp	some-mysql

```
shaggy@debian ~/D/P/i/individuos> █
```

- Iniciamos el servidor web ejecutando en la terminal de Visual Studio Code, **./mvnw spring-boot:run**

```

  26: Spring Boot :: (v4.0.3)

2026-03-10T23:26:49.024-05:00 INFO 8234 --- [initializers] [ restartedMain] com.indivudus.IndivudusApplication : Starting IndivudusApplication using Java 21.0.10 with PID 8234 (/home/shaggy/Documents/ProyectosJava/indivudus/Indivudus/target/classes started by shaggy in /home/shaggy/Documents/ProyectosJava/indivudus/Indivudus)
2026-03-10T23:26:49.043-05:00 INFO 8234 --- [initializers] [ restartedMain] com.indivudus.IndivudusApplication : No active profile set, falling back to 1 default profile: "default"
2026-03-10T23:26:49.196-05:00 INFO 8234 --- [initializers] [ restartedMain] e.devtools.DevtoolsDefaultsPostProcessor : Devtools property defaults activated: Set 'spring.devtools.add-properties' to 'false' to disable.
2026-03-10T23:26:49.197-05:00 INFO 8234 --- [initializers] [ restartedMain] e.devtools.DevtoolsDefaultsPostProcessor : For additional web related logging consider setting the 'logging.level.web' property to 'DEBUG'
2026-03-10T23:26:50.642-05:00 INFO 8234 --- [initializers] [ restartedMain] s.d.r.c.RepositoryConfigurationDelegate : Bootstrapping Spring Data JPA repositories in DEFAULT mode.
2026-03-10T23:26:50.779-05:00 INFO 8234 --- [initializers] [ restartedMain] s.d.r.c.RepositoryConfigurationDelegate : Finished Spring Data repository scanning in 112 ms. Found 1 JPA repository interface.
2026-03-10T23:26:52.151-05:00 INFO 8234 --- [initializers] [ restartedMain] o.s.boot.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2026-03-10T23:26:52.192-05:00 INFO 8234 --- [initializers] [ restartedMain] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2026-03-10T23:26:52.194-05:00 INFO 8234 --- [initializers] [ restartedMain] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/11.0.18]
2026-03-10T23:26:52.283-05:00 INFO 8234 --- [initializers] [ restartedMain] b.w.c.s.WebApplicationContextInitializer : Root WebApplicationContext: initialization completed in 3082 ms

2026-03-10T23:26:52.780-05:00 INFO 8234 --- [initializers] [ restartedMain] org.hibernate.orm.jpa : HHH000540: Initializing PersistenceContextInfo [name: default]
2026-03-10T23:26:52.888-05:00 INFO 8234 --- [initializers] [ restartedMain] org.hibernate.orm.core : HHH000001: Hibernate ORM core version 7.2.4.Final
2026-03-10T23:26:53.885-05:00 INFO 8234 --- [initializers] [ restartedMain] o.s.o.j.p.SpringPersistenceelInfo : No LoadTimeWeaver setup: ignoring JPA class transformer
2026-03-10T23:26:53.962-05:00 INFO 8234 --- [initializers] [ restartedMain] com.zaxxer.hikari.HikariDataSource : HikariPool-1 - Starting...
2026-03-10T23:26:54.489-05:00 INFO 8234 --- [initializers] [ restartedMain] com.zaxxer.hikari.Pool.HikariPool : HikariPool-1 - Added connection com.mysql.cj.jdbc.ConnectionImpl@6d80b0fc
2026-03-10T23:26:54.416-05:00 INFO 8234 --- [initializers] [ restartedMain] com.zaxxer.hikari.HikariDataSource : HikariPool-1 - Start completed.
2026-03-10T23:26:54.636-05:00 INFO 8234 --- [initializers] [ restartedMain] org.hibernate.orm.connections.pooling : HHH10001005: Database info:
Database JdbcUrl: jdbc:mysql://127.0.0.1:3306/prueba?useSSL=false&allowPublicKeyRetrieval=true&serverTimezone=UTC&autoReconnect=true
Database driver: MySQL
Database dialect: MySQLDialect
Database version: 9.6
Default catalog/schema: prueba/undefined
Autocommit mode: undefined/unknown
Isolation level: REPEATABLE READ [default REPEATABLE READ]
JDBC fetch size: none
Pool's DataSourceConnectionProvider
Minimum pool size: undefined/unknown
Maximum pool size: undefined/unknown

2026-03-10T23:26:56.695-05:00 INFO 8234 --- [initializers] [ restartedMain] org.hibernate.orm.core : HHH000489: No JTA platform available (set 'hibernate.transaction.jta.platform' to enable JTA platform integr
2026-03-10T23:26:56.847-05:00 INFO 8234 --- [initializers] [ restartedMain] j.LocalContainerEntityManagerFactoryBean : Initialized JPA EntityManagerFactory for persistence unit 'default'
2026-03-10T23:26:57.056-05:00 INFO 8234 --- [initializers] [ restartedMain] o.s.d.j.r.query.QueryEnhancerFactories : Hibernate is in classpath; If applicable, HQL parser will be used.
2026-03-10T23:26:57.343-05:00 WARN 8234 --- [initializers] [ restartedMain] JpaBaseConfigurations.JpaWebConfiguration : spring.jpa.open-in-view is enabled by default. Therefore, database queries may be performed during view rend
2026-03-10T23:26:58.242-05:00 INFO 8234 --- [initializers] [ restartedMain] o.s.boot.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path '/'
2026-03-10T23:26:58.260-05:00 INFO 8234 --- [initializers] [ restartedMain] com.indivudus.IndivudusApplication : Started IndivudusApplication on 10.22.23 seconds (process running for 11.245)

```

- Entramos a **localhost:8080/**




Individuos

Nombre	Apellido	Edad	Correo	Acciones
Miguel	Lacruz	19	Correo@	Ver
XD	Porqueno	300	algo@gmail.com	Ver
Hola	COmo estas	0	as@gmail.com	Ver
Miguel	Lacruz	19	Correo@gmail.com	Ver

- Se listaron correctamente los datos de la base de datos

Ingresamos al enlace localhost:8080/GuardarDemo



Individuos

Nombre	Apellido	Edad	Correo	Acciones
Miguel	Lacruz	19	Correo@	Ver
XD	Porqueno	300	algo@gmail.com	Ver
HOla	COmo estas	0	as@gmail.com	Ver
Miguel	Lacruz	19	Correo@gmail.com	Ver
Nuevo Nombre	Nuevo Apellido	30	Correo1@gmail.com	Ver

- Este nos regresara automaticamente a **localhost:8080/** y si todo salio bien, el nuevo usuario se vera en la lista como : **Nuevo Nombre, Nuevo Apellido, 30, [Correo1@gmail.com](#)**

Ahora al nuevo dato le damos clic a donde dice **Ver** a su derecha en **Acciones** para ver sus datos



Detalles

[Regresar](#)

Nombre APellido Edad Correo
Nuevo Nombre Nuevo Apellido 30 Correo1@gmail.com

- Se listo correctamente sus valores mostrando que todo esta ejecutando correctamente

PD : Para que nuestra base de Datos MySQL dentro de Docker Funcione correctamente debemos ingresar al archivo **application.properties** y la linea **spring.datasource.url** debemos ingresar al enlace lo siguiente : **allowPublicKeyRetrieval=true**

```
1  spring.application.name=individuos
2
3  # Agregar base de datos XD
4  # Puedes usar el localhost o el 127.0.0.1
5  spring.datasource.url=jdbc:mysql://127.0.0.1:3306/prueba?useSSL=false&allowPublicKeyRetrieval=true&serverTimezone=UTC&autoReconnect=true
6  spring.datasource.username=root
7  spring.datasource.password=12345
8  spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver
9
10 # El JPA sirve para mapear la base de datos con las tablas
11 spring.jpa.show-sql=true
12 spring.jpa.hibernate.ddl-auto=update
```

- Si eso no esta ingresado en el URL al ejecutar el proyecto de spring-boot tirara error de KEYS, esto como esta configurado el Docker de la base de datos por temas de seguridad.