

1. How do you create a ReplicaSet from scratch?

- ☐ Use the 'get pods' command.
- ☐ Use the 'scale' command to scale the deployment.
- ☐ Apply a JSON file that includes the number of desired replicas.
- ☒ Apply a YAML file with the 'kind' attribute set to 'ReplicaSet'.

✓ **Correct**

Correct! To create a ReplicaSet from scratch, apply a YAML file with the 'kind' attribute set to 'ReplicaSet'.

2. What Kubernetes object adds or deletes pods for scaling and redundancy?

- ☒ A ReplicaSet
- ☐ A Secret
- ☐ A DaemonSet
- ☐ A Config Map

✓ **Correct**

Correct! A ReplicaSet ensures the right number of pods are always up and running.

3. Which Kubernetes autoscaler type scales the Cluster?

- ☐ You cannot autoscale a Kubernetes Cluster.
- ☐ Vertical Pod Autoscaler (VPA)
- ☒ Cluster Autoscaler (CA)
- ☐ Horizontal Pod Autoscaler (HPA)

✓ **Correct**

Correct! The Cluster Autoscaler (CA) scales the Cluster in Kubernetes.

4. How do you prepare your application to enable rolling updates?

- ☐ Set the maxSurge to 50%.
- ☐ Set the maxSurge to 100%.
- ☐ Use autoscaling.
- ☒ Add liveness and readiness probes to deployments.

✓ **Correct**

Correct! Add liveness and readiness probes to deployments to enable rolling updates for an application.

6. What does a ConfigMap do?

- ☐ Provides sensitive information to your application
- ☐ Mounts a file using the volumes plugin
- ☐ Verifies that a Secret was created
- ☒ Provides variables for your application

✔ **Correct**

Correct! You can use a ConfigMap to provide variables for your application.

7. What are three ways to create a ConfigMap?

- ☒ By providing a ConfigMap YAML descriptor file

✔ **Correct**

Correct! A ConfigMap is created using string literals, using an existing property or 'key' = 'value' file, or by providing a ConfigMap YAML descriptor file.

- ☒ By using string literals

✔ **Correct**

Correct! A ConfigMap is created using string literals, using an existing property or 'key' = 'value' file, or by providing a ConfigMap YAML descriptor file.

- ☐ By adding another environment to the deployment descriptor

- ☒ By using an existing property or 'key' = 'value' file

✔ **Correct**

Correct! A ConfigMap is created using string literals, using an existing property or 'key' = 'value' file, or by providing a ConfigMap YAML descriptor file.

8. What are three ways to create a Secret?

☐ By providing a ConfigMap YAML descriptor file

☒ By using a string literal

 **Correct**

Correct! You create a Secret by using a string literal, by using environment variables, or by using volume mounts.

☒ By using environment variables

 **Correct**

Correct! You create a Secret by using a string literal, by using environment variables, or by using volume mounts.

☒ By using volume mounts

 **Correct**

Correct! You create a Secret by using a string literal, by using environment variables, or by using volume mounts.

10. What are the three required steps to bind the IBM Cloud Service to your Cluster?

☒ Provision an instance of the Service.

☒ **Correct**

Correct! The required steps to bind an IBM Cloud Service to your Cluster are: Provision an instance of the service, Bind the Service to your Cluster to create credentials, Store the credentials, and Configure your app to access the credentials.

☐ Erase the credential configuration file after credential setup.

☒ Configure your app to access the credentials.

☒ **Correct**

Correct! The required steps to bind an IBM Cloud Service to your Cluster are: Provision an instance of the service, Bind the Service to your Cluster to create credentials, Store the credentials, and Configure your app to access the credentials.

☒ Bind the Service to your Cluster to create credentials.

☒ **Correct**

Correct! The required steps to bind an IBM Cloud Service to your Cluster are: Provision an instance of the service, Bind the Service to your Cluster to create credentials, Store the credentials, and Configure your app to access the credentials.