Milling Condition Safety Monitor

Detecting Non-Optimal Cutting Parameters from Vibration and Current Signals

ME-446 Artificial Intelligence & Internet of Things — Complex Engineering Problem, Fall 2026 Department of Mechanical Engineering, NED University of Engineering and Technology, Karachi

Group	_____
Group members	_____
Submitted to	Course teacher, ME-446
Submission date	04 November 2026
Dataset	Piecuch & Żabiński, *Scientific Data* 12, 650 (2025), CC BY 4.0
Code and artifacts	This repository (`milling-cep/`)

Executive summary

This project builds an AI safety monitor for CNC milling. The public dataset used by Piecuch and Żabiński contains 968 milling cycles recorded with eight accelerometer channels and twelve current channels, under two radial depth-of-cut (RDOC) settings: an optimal 4.5 mm and an aggressive 8 mm. Instead of reproducing the authors' tool-wear model, this CEP treats RDOC as a categorical target and asks a new engineering question: **can a model detect a non-optimal, high-risk cut from the sensor signature alone, before the condition damages the tool or the machine?**

A random forest was selected from four candidates after grouped validation. At a tuned threshold of 0.444 it flags **96.2 %** of dangerous cycles (204 of 212) with **69.9 %** precision and an MCC of **0.762**. Leave-one-tool-out validation gives the same recall (0.962) and MCC 0.778, and a model trained without experiments P002 and P108 flags 97.8 % of the unseen dangerous experiment while clearing 100 % of the unseen optimal experiment. The main residual risk is a high false-alarm rate on one optimal tool (tool 7), which is traced to the dataset's confounded design: RDOC is constant within each tool and experiment, so tool identity, material batch and wear stage cannot be fully separated from the cutting condition.

The work delivers cleaned and audited data, a reproducible notebook, eleven publication-quality figures, a Streamlit dashboard, Tableau-ready extracts with a build guide, and this report.

1. Engineering problem formulation

1.1 Context

In CNC milling, the radial depth of cut controls how much of the cutter's diameter engages the workpiece. A conservative engagement (RDOC = 4.5 mm on a 10 mm cutter) is stable and is

used for normal production. A very large engagement (RDOC = 8 mm, i.e. 80 % of the diameter) raises the chip load, the cutting force and the spindle torque. If the setup, holder or fixture is not stiff enough, the result is chatter, overload, accelerated tool wear, scrap or a broken tool. The operator normally knows the programmed parameters, but a process monitor does not: it sees only vibration and current. The engineering value of the model is as an independent check that the machine is running the condition it is supposed to run, and as an alarm when an aggressive parameter set is used unintentionally or without the matching tool.

1.2 Objective and task type

Objective: classify each milling cycle as *optimal* (RDOC = 4.5 mm) or *non-optimal / dangerous* (RDOC = 8 mm) from the accelerometer and current statistics of that cycle.

Item	Definition
Task	Supervised binary **classification** (not regression, not wear estimation)
Target	`RDOC_class = 1` if RDOC = 8 mm, `0` if RDOC = 4.5 mm
Inputs	120 sensor statistics: 8 accelerometer channels and 12 current channels, each with min, max, mean, std, skew and kurtosis
Unit of analysis	One milling cycle (`Pxxx_Fyy_Czz`)
Grouping unit	Cutting tool (`ToolIndex`) — the leakage-safe validation unit
Positive class	Dangerous (minority: 212 of 968 cycles, 21.9 %)
Operational decision	Flag the cycle for operator attention; not an automatic machine stop

The task is a **process-monitoring** problem, not a tool-life problem. It is deliberately different from the source paper's wear regression and uses a target that the original authors did not model, which satisfies the CEP requirement for a novel analysis on an open dataset.

1.3 Significance of the variables

A larger radial engagement increases the engaged cutting-edge length and the chip cross-section. Cutting force and spindle torque rise roughly proportionally, which appears as a higher mean spindle/drive current, greater current fluctuation and higher vibration amplitude. The mean of the drive-axis acceleration is sensitive to the static force offset; the standard deviation of the drive and spindle currents is sensitive to load fluctuation; kurtosis and skew capture impulsive or chattering behaviour. These statistics are therefore not arbitrary features: they are the signatures that cutting mechanics predicts should change with RDOC.

---

2. Dataset

2.1 Source and licence

Piecuch, M. & Żabiński, T., *A new open dataset from a milling process – data for classification and estimation of tool life*, **Scientific Data 12, 650 (2025)**. DOI: 10.1038/s41597-025-04923-y

Data archive: DOI 10.6084/m9.figshare.28589216, licensed **CC BY 4.0**. Accessed October 2026. The raw files are kept unchanged in `data/raw/` (`FeatureAndMetadata_Milling.csv`, `metadata.xlsx`); the raw 25 GB time-series archive is not redistributed and was not available locally.

2.2 Structure

Property	Value
Milling cycles (rows)	968
Experiments (workpieces)	24
Layers	172
Cutting tools	14
Sensor statistics	120
Source metadata columns	11
Accelerometer channels	8
Current channels	12
Constant process settings	3200 rpm, 640 mm/min, 10 mm cutter
Dangerous cycles	212 (21.9 %)
Optimal cycles	756 (78.1 %)
Experiments / tools with both classes	0 / 0

Two independent sources (the feature CSV and `metadata.xlsx`) were cross-checked row for row. All nine shared metadata fields, the row order and the row count (968) match exactly, so the merge cannot silently misalign a cycle with its metadata.

---

3. Data audit and preprocessing

3.1 Audit findings

Check	Result	Decision
Missing values	0	None needed
Duplicate full rows	0	None
Duplicate sensor vectors	0	None
Infinite sensor values	0	None
Zero-variance sensor features	0	None
Constant predictors	`ToolRotation`, `FeedRate`, `ToolDiameter`	Excluded — no information
Censored cycles (`CycleToFailure = 0`)	14	Retained — valid failure records
Single-cycle experiment	P114	Retained — genuine early failure
Accelerometer values at the ADC floor	4 rows	Retained — genuine clipping
Rows with ≥ 5 features outside a 5×IQR fence	52	Flagged, **not deleted**
Experiments / tools containing both classes	0 / 0	Grouped validation required
Tool type 2 at RDOC = 8 mm	0 cycles	Discussed as a confound

The raw CSV has a UTF-8 BOM, a semicolon delimiter, a redundant first header row and mixed decimal conventions (comma decimals in metadata, dot decimals in sensor columns). These were parsed explicitly; the real header is on row 2. No row was deleted. Deleting the censored records, the single-cycle failure or the statistical outliers would remove exactly the difficult cases a safety monitor must handle, and the source paper treats them as valid observations.

3.2 Target and feature preparation

- **Target:** `RDOC_class = 1` for RDOC = 8 mm, `0` for 4.5 mm.
- **Features:** the 120 sensor statistics only. Identifiers, process settings, hardness, tool metadata and remaining-life counters are excluded, so the model cannot read the answer or a wear proxy directly.
- **Transform:** `signed_log1p(x) = sign(x)·ln(1+|x|)` compresses the very large raw ADC counts while preserving sign. It is applied to every feature for every model.
- **Scaling:** robust scaling (median/IQR) is added for logistic regression only; tree models do not need it.
- **Imbalance:** balanced class weights (logistic regression, random forest) and threshold selection. No SMOTE or random oversampling, because synthetic sensor vectors would no longer correspond to physically achievable cutting states.
- **Feature selection:** none. The models regularise or split on 120 correlated features directly; removing features on the full data before cross-validation would leak information.

3.3 Validation design

RDOC and ADOC are **constant within every experiment and every tool**. A random row split therefore places cycles from the same tool in both training and test, and a flexible model can memorise that tool's signature. This is leakage through grouping, not through a feature column.

Four schemes are used:

1. **5-fold tool-group cross-validation (primary).** Whole tools are held out; each fold contains at least one dangerous and one optimal tool. Hyperparameters are tuned inside each outer fold on the training tools only (nested grouped CV), so the outer estimate never sees the held-out tool during tuning.
2. **Leave-one-tool-out (stress test).** Fourteen folds, one tool each. This is the closest available proxy for deploying on a tool the model has never seen.
3. **Leave-one-experiment-out (sensitivity).** Twenty-four folds; tests generalisation to a new workpiece/layer structure.
4. **Random 5-fold (leakage control only).** Reported to quantify how optimistic a naive split is; it is never used to select the model or quote performance.

A chronological split is not appropriate here: the rows are individual cycles grouped by tool and experiment, not a continuous time series of one process, and the source file is ordered by experiment. A chronological cut would put whole tools and conditions on one side and reproduce the same confounding in a less controlled way. Grouping by tool is the technically justified split.


3.4 Leakage control: what the random split would have claimed

Model	ROC-AUC	PR-AUC	Recall	MCC
Random forest, random 5-fold	0.998	0.994	0.976	0.933
Random forest, tool-grouped 5-fold	0.942	0.688	0.892	0.742
Hist gradient boosting, random 5-fold	1.000	0.999	0.986	0.988
Hist gradient boosting, tool-grouped 5-fold	0.936	0.782	0.877	0.650


The random split inflates ROC-AUC by about 0.06 and PR-AUC by about 0.21–0.31. Presenting the random-split number would have been a serious methodological error, so the grouped results are used throughout this report.

---


4. Exploratory analysis and engineering insights




Top univariate sensor separations (descriptive, not group-validated)





Sensor patterns separate classes, but tool signatures are also visible






Wear is a second confound: dangerous tools also fail sooner







Insight 1 — the dangerous condition is a minority, so accuracy is misleading

Only 212 of 968 cycles (21.9 %), 8 of 24 experiments and 5 of 14 tools operate at RDOC = 8 mm. A classifier that always predicts "optimal" already scores 78.1 % accuracy while catching zero dangerous cycles. The report therefore leads with recall on the dangerous class, PR-AUC, MCC and the confusion matrix, and treats accuracy as a secondary descriptive number.

Insight 2 — RDOC is perfectly confounded with tool and experiment identity

Every tool and every experiment uses exactly one RDOC/ADOC combination. Tool type 2 is never used at RDOC = 8 mm, so the dangerous class is also entirely tool type 1. The dangerous group has a lower mean hardness (about 38 HRC versus 39 HRC) and a different remaining-life distribution. A model can therefore separate the classes by recognising the tool or the material rather than the cut. Grouped validation limits the optimism, but the confound cannot be removed by modelling; it is a property of the experimental design.

Insight 3 — the sensor signal is strong and physically plausible

The strongest univariate features are the mean acceleration on the drive axes (AUC 0.935–0.939) and the standard deviation of the drive/spindle currents (AUC 0.894–0.913). All are higher in the dangerous class. That is the direction cutting mechanics predicts for a larger radial engagement, so the separation is not an artefact of a few extreme rows.

Feature	Univariate ROC-AUC	Direction
Accelerometer – Y driving axle +Y – mean	0.939	higher in dangerous
Accelerometer – X driving axle +Z – mean	0.935	higher in dangerous
Current – driving axle X L1 – std	0.913	higher in dangerous
Current – driving axle X L3 – std	0.913	higher in dangerous
Current – driving axle X L2 – std	0.913	higher in dangerous
Current – spindle L1 – std	0.894	higher in dangerous
Current – spindle L2 – std	0.894	higher in dangerous
Current – spindle L3 – std	0.894	higher in dangerous

Insight 4 — wear is a competing explanation

Dangerous tools fail sooner: mean cycles to failure 22.7 versus 55.8 for optimal tools. Sensor features also drift as a tool wears, so part of the class separation may reflect wear stage rather than RDOC. The probability-versus-remaining-life view in the dashboard makes this visible; it is treated as a limitation, not hidden. The false alarms on tool 7 cluster late in tool life (mean normalised life 0.33), which is consistent with wear pushing an optimal tool into a dangerous-looking signature.

Insight 5 — material and tool type differ by class

Tool type 2 never appears at RDOC = 8 mm, and the dangerous group has lower hardness. These differences are plausible false-positive drivers: an optimal cut with a harder workpiece can produce higher forces and currents, and the model has no hardness input to distinguish the two causes. This is another reason to present the model as a screening alarm rather than a definitive diagnosis.

---

5. Models and validation

5.1 Candidate models and justification

Model	Why it is appropriate	Configuration
Dummy (prior)	Establishes the no-skill baseline for this class balance	Predicts the majority class
Logistic regression	Transparent linear reference; tests whether a simple decision boundary is enough with 120 correlated, heavy-tailed features	Balanced class weights, robust scaling, `C` tuned
Random forest	Captures thresholds and interactions across correlated vibration/current channels without hand-crafted features; robust to outliers and to the large ADC scale after the log transform	150 trees, balanced subsample weights, depth and leaf size tuned
Histogram gradient boosting	Strong modern tabular learner; tests whether boosting beats bagging on this dataset	Learning rate, leaf nodes and L2 tuned

All four were evaluated on exactly the same folds and the same feature matrix.

5.2 Primary comparison (5-fold tool-group CV, threshold 0.5)

Model	ROC-AUC	PR-AUC	Recall	Precision	F1	Specificity	MCC	Brier	Accuracy
Dummy (prior)	0.386	0.184	0.000	0.000	0.000	1.000	0.000	0.173	0.781
Logistic regression	0.940	0.733	0.948	0.663	0.781	0.865	0.725	0.093	0.883
Random forest	**0.942**	0.688	0.892	**0.724**	**0.799**	**0.905**	**0.742**	**0.082**	**0.902**
Hist gradient boosting	0.936	**0.782**	0.877	0.620	0.727	0.849	0.650	0.107	0.855

At the fixed 0.5 threshold the random forest has the best precision, F1, specificity, MCC, Brier and accuracy; logistic regression has slightly higher recall and a very similar ROC-AUC; gradient boosting has the best threshold-independent PR-AUC but the weakest operating point. Because a safety monitor can move its threshold, the selection was confirmed at the tuned operating point rather than at 0.5.

5.3 Threshold selection

The threshold was chosen on the pooled out-of-fold probabilities of the random forest by maximising F1. This gives **0.4437**, below 0.5 because the class is imbalanced and because a missed dangerous cut is more expensive than a false alarm.

Operating point	Threshold	Recall	Precision	F1
Max-F1 (selected)	0.444	0.962	0.699	0.810
Highest precision with recall ≥ 0.90	0.499	0.901	0.726	0.803

Raising the threshold to 0.499 buys 2.7 points of precision but costs 6.1 points of recall. For a safety application that is a bad trade, so 0.444 is retained. The dashboard exposes the threshold as a slider so the cost ratio can be changed by the user.

5.4 Selected model performance

Metric	5-fold tool groups	Leave-one-tool-out
Recall (dangerous)	0.962	0.962
Precision (dangerous)	0.699	0.718
F1 (dangerous)	0.810	0.823
MCC	0.762	0.778
Balanced accuracy	0.923	0.928
Specificity	0.884	0.894
ROC-AUC	0.942	0.950
PR-AUC	0.688	0.712
Brier score	0.082	0.076
Confusion matrix	668 TP-optimal / 88 FP / 8 FN / 204 TP-dangerous	676 / 80 / 8 / 204

The two estimates agree closely, which is the important result: the model is not dependent on one particular grouping of tools. Leave-one-experiment-out is higher (ROC-AUC 0.983, PR-AUC


0.895), because experiments share tools and layers and are therefore an easier holdout than a new tool.


The Brier score of 0.082 is low, but Figure 9 shows the probabilities are not perfectly calibrated: the model is conservative in the middle of the range and over-confident at the top (cycles scored around 0.87 are dangerous about 73 % of the time, not 87 %). Probabilities are therefore useful for ranking and for choosing a threshold, but they should not be read as exact risk without recalibration (Platt scaling or isotonic regression) on a larger tool sample.

---

6. Error analysis

6.1 Confusion matrix and curves





6.2 Where the errors are

Tool	Actual class	Cycles	Mean P(dangerous)	Flagged	Error type
2	Dangerous	48	0.732	100 %	—
3	Dangerous	44	0.746	100 %	—
4	Dangerous	41	0.712	92.7 %	3 missed
5	Dangerous	51	0.623	94.1 %	3 missed
6	Dangerous	28	0.676	92.9 %	2 missed
7	Optimal	124	0.563	**60.5 %**	**75 false alarms**
8	Optimal	116	0.149	5.2 %	6 false alarms
9	Optimal	149	0.026	0 %	—
10	Optimal	15	0.052	0 %	—
11	Optimal	1	0.022	0 %	—
101	Optimal	84	0.029	0 %	—
102	Optimal	82	0.006	0 %	—
103	Optimal	60	0.014	0 %	—
105	Optimal	125	0.104	5.6 %	7 false alarms

False alarms (88). 75 come from optimal tool 7, 7 from tool 105 and 6 from tool 8. Tool 7 has a mean probability of 0.563, close to the dangerous tools, and its false alarms occur mostly late in tool life. Its hardness and geometry apparently produce a signature that overlaps the dangerous class. This is the single largest deployment risk: in a production cell it would trigger an inspection on roughly three of every five tool-7 cycles.

Missed dangerous cycles (8). Three from tool 4, three from tool 5 and two from tool 6, spread across tool life rather than confined to the first cycle. Their probabilities sit just below the threshold, so a small threshold reduction would recover them at the cost of more false alarms. No dangerous tool is systematically missed, which is better than losing an entire tool.





Figure 11 makes the same point visually: the dangerous tools sit as compact high-probability boxes, while tool 7's optimal cycles overlap them.

The asymmetry matters: 8 missed dangerous cycles out of 212 is a 3.8 % miss rate, while 88 false alarms out of 756 optimal cycles is an 11.6 % false-alarm rate. For a decision-support alarm that a human filters, this is an acceptable starting point; for an automatic stop it would not be.

7. What the model has learned



Rank	Feature	Permutation importance (drop in ROC-AUC)
1	Accelerometer – X driving axle +Z – mean	0.00085 ± 0.00026
2	Accelerometer – Y driving axle +Y – mean	0.00076 ± 0.00052
3	Current – driving axle X L1 – std	0.00034 ± 0.00038
4	Current – driving axle X L2 – std	0.00027 ± 0.00033
5	Current – driving axle Y L3 – min	0.00014 ± 0.00001
6	Current – driving axle X L3 – std	0.00013 ± 0.00020
7	Current – spindle L2 – max	0.00007 ± 0.00006
8	Accelerometer – X driving axle +Z – kurtosis	0.00006 ± 0.00008
9	Accelerometer – spindle +Y – mean	0.00005 ± 0.00009
10	Current – spindle L3 – max	0.00005 ± 0.00004

The absolute importances are small because the 120 features are highly correlated: shuffling one channel leaves the others to compensate. The ranking is what matters. The model relies on drive-axis mean acceleration and drive/spindle current variability, exactly the quantities that cutting mechanics says should rise with radial engagement. It does not rely on an identifier, a wear counter or a process setting, because those columns are not in the feature matrix.

The top feature is the **mean** of the drive-axis acceleration, not a peak or a kurtosis. That makes sense for a static force offset: a deeper radial cut shifts the whole vibration signal upward, so its DC level is a robust indicator. Current **standard deviation** ranks next because a heavier, more interrupted cut produces a more variable load.

---

8. Demonstration on previously unseen cases

Two experiments were held out entirely: **P002** (RDOC = 8 mm, dangerous) and **P108** (RDOC = 4.5 mm, optimal). A fresh random forest with the selected hyperparameters was trained on the remaining 22 experiments (841 cycles) and applied to the 127 held-out cycles.

Experiment	Actual class	Cycles	Mean P(dangerous)	Min	Max	Flagged
P002	Dangerous	46	0.746	0.439	0.953	**97.8 %** (45/46)
P108	Optimal	81	0.006	0.000	0.046	**0 %** (0/81)

The single P002 miss is the **first cycle of the experiment** (`P002_F01_C1`, P = 0.439, just below the 0.444 threshold). A fresh tool has not yet developed the wear-driven increase in vibration and current, so its first cut looks marginal. This is a genuine engineering find, not a random failure: it argues for a rolling window or a two-cycle confirmation logic rather than a per-cycle verdict at the start of a tool's life.

The final saved model, which uses all 968 cycles, scores representative individual cycles through the same 120-feature interface a deployment would use:

Cycle	Experiment / tool	Actual	P(dangerous)	Decision
`P002_F12_C4`	P002 / tool 2	Dangerous	0.967	Flag
`P108_F12_C7`	P108 / tool 102	Optimal	0.000	Clear

This satisfies the CEP requirement to demonstrate the final model on at least two previously unseen input cases, and it also tests a held-out experiment rather than a re-scored training row.

---

9. Engineering interpretation

The classifier behaves like a **data-driven cutting-force monitor**. When the radial engagement increases from 4.5 mm to 8 mm, the chip load and the cutting force rise, the drive and spindle currents increase and become more variable, and the drive-axis vibration shifts upward. The forest combines several correlated channels into a decision boundary that separates the two conditions with 96 % recall at the selected operating point. The signal is therefore consistent with the mechanics of the process, not merely with the labels.

The model's errors are also interpretable. Tool 7 is an optimal tool whose signature overlaps the dangerous class, especially late in life; tools 4–6 occasionally produce a dangerous signature that falls just below the threshold. Both patterns point to the same physical reality: wear, material hardness and tool geometry move the sensor signature in the same direction as RDOC. A classifier trained on a design where these factors are perfectly confounded cannot fully attribute the signal to RDOC alone.

Consequence of an error. A false negative means a dangerous cut continues: higher force, faster wear, possible chatter, scrap or tool breakage. A false positive means an unnecessary retract or inspection, which costs cycle time but protects the machine. The threshold is therefore set to favour recall, and the recommended use is a human-in-the-loop alarm, not an automatic stop.

---

10. Limitations and threats to validity

1. **Confounded experimental design (major).** RDOC and ADOC are constant within each tool and experiment. Tool geometry, material batch, hardness and wear stage are entangled with the target. Grouped validation and held-out experiments reduce optimism but cannot establish that the model responds to RDOC alone.
2. **Wear confound (major).** Dangerous tools fail sooner and sensor statistics drift with remaining life. Part of the separation may be wear rather than cutting condition. The dashboard's probability-versus-life view exposes this; a dedicated early-life-only analysis would be the next step.
3. **Small number of tools.** 14 tools, only 5 dangerous. Each leave-one-tool-out fold removes a substantial fraction of one class, and a single unusual tool (tool 7) drives most false alarms.
4. **Pre-computed features, no raw waveforms.** The 25 GB raw archive was not available, so the window length, filtering and statistic set could not be optimised. The 120 statistics are the authors' choices, not necessarily the best for this target.
5. **Uncalibrated sensor units.** Values are raw ADC counts. The model and threshold are specific to this machine and acquisition chain; transferring them requires calibration to g and A and re-validation.
6. **Single machine and campaign.** No independent machine, spindle or material set is available, so external validity is unknown.

7. **Threshold is a policy choice.** 0.444 is the max-F1 point. A plant with different inspection and scrap costs should choose a different operating point; the dashboard makes this explicit.
8. **No causal claim.** The model is a association-based alarm. It should not be described as proof that RDOC causes the observed signature in every tool.

---

11. Recommendations

1. **Deploy as decision support.** Require two consecutive flagged cycles or a short rolling mean before retracting a tool. This directly addresses the P002 first-cycle miss and reduces nuisance alarms from isolated cycles.
2. **Add a tool-specific baseline.** Compare each cycle with that tool's own early-life signature (a z-score or residual) rather than a global threshold. This is the most promising way to reduce the tool-7 false alarms.
3. **Re-run a balanced confirmation experiment.** Cut the same tool at both RDOC levels and vary hardness independently. That design would break the confounding and turn the current association into a defensible causal estimate.
4. **Calibrate the channels.** Convert accelerometer and current data to g and A, document the acquisition settings, and re-validate before using the model on a second machine.
5. **Tune the threshold to the shop-floor cost ratio.** Expose recall, false-alarm rate and the expected number of inspections per shift, and let maintenance/quality agree on the operating point.
6. **Log the probability and top features per cycle.** A process engineer needs to see *why* a cycle was flagged; the dashboard's per-cycle sensor view and the permutation ranking support that.
7. **Monitor drift.** Re-check the score distribution monthly; a change in material, holder or spindle shifts the sensor baseline and invalidates the threshold.

---

12. Deliverables and reproducibility

12.1 Deliverables

CEP requirement	Delivered artifact
Raw dataset, unchanged	`data/raw/FeatureAndMetadata_Milling.csv`, `data/raw/metadata.xlsx`
Cleaned / transformed dataset	`data/processed/milling_clean.csv`, `features.csv`, `metadata.csv`, `folds.csv`, `sensor_long.csv`
Data audit and cleaning decisions	`data/processed/CLEANING_LOG.md`, `data/processed/audit.json`, `data/processed/data_dictionary.csv`
At least three visualisations	`figures/fig01–fig11` (11 figures)
Three to five engineering insights	`reports/EDA_INSIGHTS.md`, Section 4 of this report
At least three ML algorithms	Dummy, logistic regression, random forest, histogram gradient boosting
Leakage-safe training/testing	Nested 5-fold tool-group CV, leave-one-tool-out, leave-one-experiment-out, random-split control
Unseen-case demonstration	Held-out experiments P002 and P108 (Section 8)
Reproducible notebook	`notebooks/milling_cep_analysis.ipynb` (executed end to end, 0 errors)
Interactive dashboard	`dashboard/app.py` (Streamlit, six tabs, threshold slider, scoring, upload)
Live dashboard	https://milling-cep-iguwxgwerngzavkpz2aguj.streamlit.app
Tableau workbook support	`dashboard/tableau/*.csv` + `dashboard/tableau/README.md` build guide
Technical report	`reports/TECHNICAL_REPORT.md` / `.pdf`
Presentation	`reports/presentation/MILLING_CEP_SLIDES.pptx` / `.pdf` (13 slides)
Poster	`reports/poster/MILLING_CEP_POSTER.pdf` (A2)
Notebook export	`notebooks/exports/milling_cep_analysis.html` / `.pdf`

The Streamlit app is the working interactive dashboard delivered with the project. The CEP brief names Tableau Public (or an approved alternative) for the dashboard; the Tableau-ready extracts and the step-by-step build guide allow the same views to be assembled in Tableau Public without re-deriving any numbers. The `.twbx` workbook itself is a binary Tableau artifact and must be built in Tableau Desktop/Public — it is not generated by the Python pipeline.

12.2 Reproduce

```
# Python 3.12; dependencies in requirements.txt (numpy, pandas, scikit-learn,
# matplotlib, seaborn, plotly, streamlit, joblib, jupyter)
.venv/bin/python -m src.data                 # cleaning, audit, folds, long sensor table
.venv/bin/python scripts/02_eda.py           # figures 01-06, EDA_INSIGHTS.md
.venv/bin/python scripts/03_modeling.py      # model comparison, figures 07-10
.venv/bin/python scripts/05_select_rf.py     # final model, threshold, unseen cases, figure 11
.venv/bin/python scripts/06_tableau_export.py
.venv/bin/jupyter nbconvert --to notebook --execute notebooks/milling_cep_analysis.ipynb
streamlit run dashboard/app.py
```

Random seed: `20261025`. The notebook reproduces the same threshold (0.4437), the same selected-model metrics and the same unseen-case summary as the saved artifacts.

12.3 Environment

The project was developed with Python 3.12 in a local virtual environment. Hardware: ordinary laptop CPU, no GPU. The full modelling pipeline (03 + 05) runs in a few minutes; the executed notebook in about two minutes. The random forest is deliberately kept small (150 trees, depth ≤ 10) so the whole study is reproducible on a student machine.

---

13. Conclusion

A random forest can separate optimal from non-optimal milling conditions from vibration and current statistics with 96 % recall and an MCC of 0.76 under tool-grouped validation, and it generalises to held-out experiments. The result is engineering-plausible: the model keys on drive-axis mean acceleration and current variability, the quantities that cutting mechanics predicts will rise with radial engagement. The main caveat is equally clear: because RDOC is confounded with tool identity, material and wear, the model is a strong screening alarm rather than a causal instrument. With a tool-specific baseline, two-cycle confirmation logic, calibrated sensors and a balanced confirmation experiment, it could become a practical shop-floor safety monitor.

References

1. Piecuch, M. & Żabiński, T. A new open dataset from a milling process – data for classification and estimation of tool life. *Scientific Data* **12**, 650 (2025). https://doi.org/10.1038/s41597-025-04923-y
2. Piecuch, M. & Żabiński, T. Dataset for the above article. Figshare (2025). https://doi.org/10.6084/m9.figshare.28589216 (CC BY 4.0).
3. Pedregosa, F. et al. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research* **12**, 2825–2830 (2011).
4. Breiman, L. Random forests. *Machine Learning* **45**, 5–32 (2001).
5. Saito, T. & Rehmsmeier, M. The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets. *PLOS ONE* **10**, e0118432 (2015).
6. Chicco, D. & Jurman, G. The advantages of the Matthews correlation coefficient (MCC) over F1 score and accuracy in binary classification evaluation. *BMC Genomics* **21**, 6 (2020).
7. NED University of Engineering and Technology, Department of Mechanical Engineering. *ME-446 AI & IoT, Complex Engineering Problem — Fall 2026* (course brief).