

Context in DAX Formulas

INTRODUCTION TO DAX IN POWER BI



Jess Ahmet

Content Developer, Datacamp

Introduction to Context

- Enables dynamic analysis where results of a formula change to reflect the selected data
- There are 3 types of context: row, filter and query

Introduction to Row Context

- "The current row"

Introduction to Row Context

- "The current row"

Calculated Column

- Includes values from all columns within the current row

Introduction to Row Context

- "The current row"

Calculated Column

- Includes values from all columns within the current row

Item	Price	Tax	Price_with_tax
A	\$ 20	25%	\$25
B	\$ 45	0%	\$45
C	\$ 100	15%	\$115

Introduction to Row Context

- "The current row"

Measures

- Can apply when using iterator functions which compute calculations row by row
- Iterator functions can be identified by an `X` after the function name i.e `SUMX()`
- Syntax: `SUMX(<table>, <expression>)`

Introduction to Row Context

- "The current row"

Measures

- Can apply when using iterator functions which compute calculations row by row
- Iterator functions can be identified by an **X** after the function name i.e **SUMX()**
- Syntax: **SUMX(<table>, <expression>)**

Item	Price	Tax	Price_with_tax
A	\$ 20	25%	\$25
B	\$ 45	0%	\$45

Introduction to Row Context

- "The current row"

Measures

- Can apply when using iterator functions which compute calculations row by row
- Iterator functions can be identified by an **X** after the function name i.e **SUMX()**
- Syntax: **SUMX(<table>, <expression>)**

Item	Price	Tax	Price_w_tax
A	\$ 20	25%	\$25
B	\$ 45	0%	\$45
Total	-	-	\$ 70

- Example: **SUMX(Sales, Sales[Price] + (Sales[Price] * Sales[Tax]))**

Introduction to Filter Context

Filter context is a set of filters that have been applied before the calculation is carried out.

Filter context can be applied in several ways:

- Attributes in a row/column
- Via a slicer
- Through the filter pane
- In a calculated measure

Introduction to Filter Context

Filter context is a set of filters that have been applied before the calculation is carried out.

Example:

Color	Quantity
Blue	1,250
Green	200
Black	4,000

Introduction to Filter Context

Filter context is a set of filters that have been applied before the calculation is carried out.

Example:

Color	Quantity
Blue	1,250

Introduction to Filter Context

Filter context is a set of filters that have been applied before the calculation is carried out.

Example:

Color	Quantity
Blue	1,250
Green	200
Black	4,000

Introduction to Filter Context

Filter context is a set of filters that have been applied before the calculation is carried out.

Example:

	Socks	Shoes	T-shirt
Blue	200	800	250
Green	90	10	100
Black	2,000	800	1,200

Introduction to Filter Context

Filter context is a set of filters that have been applied before the calculation is carried out.

Example:

	Socks
Blue	200

Calculate Function

- Syntax: `CALCULATE(<expression>[, <filter1> [, <filter2> [, ...]])`
 - Expression: a measure or calculation to be evaluated. Must return a single value.
 - Filters:
 - Filters need to evaluate as a table
 - Filters should not clash with one another
 - `Sales[City]="London"` , `Sales[Country] <> "United Kingdom"`
 - `CALCULATE()` filters will always override filters from the visualization
- Example: `CALCULATE(SUM(Sales), Sales[Region]="EMEA")`

Let's practice!

INTRODUCTION TO DAX IN POWER BI

Creating DAX Measures

INTRODUCTION TO DAX IN POWER BI



Jess Ahmet

Content Developer, DataCamp

Let's practice!

INTRODUCTION TO DAX IN POWER BI