


Spring Boot Outh2

OAuth 2.x:

- It is a standard and framework which provides 3rd party security services to client application which are registered on behalf of end user.




Flow:


1. Browser making request to client Application.
 2. Client asking permission to third party.
 3. Third party Application asking confirmation (Grant) to end user.
 4. User confirmation.
 5. Data shared from 3rd party Application to Client App.
 6. Client gives response to end user.
- **The 3rd party Applications** are called **Authorization and Resource Servers** like Google, Facebook, GitHub, Twitter, LinkedIn ... etc.
 - **Client Applications** that are using OAuth2 is BookMyshow, redbus, yatra, MakeMyTrip, Avast, Zomato.. etc.
 - OAuth 2.x standard is widely used in small/medium scale/daily used, business application.
 - OAuth2 Provide SSO (Single Sign on) for multiple applications acting as a one Service.
 - OAuth2 may not be used for high level and Large scale applications like Banking, Creditcard, Stock Market, finance... etc. These applications use Spring Security ORM is used mostly.


Step 1: Register Client Application with Authorization Server

- Every Client Application (BookMyShow) must be registered with Authorization Server (Facebook)
Eg: BookMyShow --- Register with --> Facebook Server
- Client Application gets **clientId** and **clientSecret** (like Password) on Successful registration at Authorization Server.
- This is like one time setup between Client Application and Authorization Server.

**Step 2: End User must be Registered with Resource Server**

- User must be register and Login with 3rd party Resource Servers (Like facebook.com).
- User need to provide profile information, basic data, comments, posts, photos... etc.
- User Id and password will never be shared with Client Application.
- Only Users Public and General information is shared with Client Application.



Request Work flow of OAuth2:

1. End user makes request using browser to client application (BookMyshow) request for “verify using 3rd party service” ex: Facebook, Google... etc.
2. Client Application will ask for Grant from end user, which confirms that access user data.
3. End user has to provide Grant (Permission) to access data.
4. Client makes request to Authorization server using ClientId, secret, user grant.
5. Auth server verifies details and goes to token Management process.
A unique number is generated, called as Token which works for User+Client combination.
6. Now, client application makes request to resource Server using Access Token.
7. Resource server returns end user secure data to client.
8. Finally, Client App process the end user request and gives response.

One Time Setup for Google OAuth;

Steps to generate Client-id and secret in Google;

The screenshot shows the Google Cloud Console interface for a project named 'my-angular-app-309611'. The left sidebar is titled 'APIs & Services' and includes links for 'Enabled APIs & services', 'Library', 'Credentials' (highlighted with a red box), 'OAuth consent screen', 'Domain verification', and 'Page usage agreements'. The main content area is titled 'Credentials' and features a '+ CREATE CREDENTIALS' button (highlighted with a red box) and a 'DELETE' button. A dropdown menu is open from the '+ CREATE CREDENTIALS' button, showing options: 'API key' (Identifies your project using a simple API key to check quota and access), 'OAuth client ID' (Requests user consent so your app can access the user's data, highlighted with a red box), 'Service account' (Enables server-to-server, app-level authentication using robot accounts), and 'Help me choose' (Asks a few questions to help you decide which type of credential to use). Below the dropdown, there are sections for 'API Keys', 'OAuth 2.0 Client IDs', and 'Service Accounts', each with a table to display existing credentials. The 'OAuth 2.0 Client IDs' section is currently empty, showing 'No OAuth clients to display'.

API Create OAuth client ID - APIs & Services

console.cloud.google.com/apis/credentials/oauthclient?previousPage=%2Fapis%2Fcredentials%3Fproject%3Dmy-angular-app-30961...

Google Cloud my angular app Search Products, resources, docs (/)

APIs & Services

Enabled APIs & services

Library

Credentials

OAuth consent screen

Domain verification

Page usage agreements

Create OAuth client ID

A client ID is used to identify a single app to Google's OAuth servers. If your app runs on multiple platforms, each will need its own client ID. See [Setting up OAuth 2.0](#) for more information. [Learn more](#) about OAuth client types.

Application type *
Web application

Name *
Web client 1

The name of your OAuth 2.0 client. This name is only used to identify the client in the console and will not be shown to end users.

The domains of the URIs you add below will be automatically added to your [OAuth consent screen](#) as [authorized domains](#).

Authorized JavaScript origins ⓘ

For use with requests from a browser

+ ADD URI

Authorized redirect URIs ⓘ


For use with requests from a web server

URIs 1 *
http://localhost:8080/login/oauth2/code/google

+ ADD URI

Note: It may take 5 minutes to a few hours for settings to take effect


CREATE CANCEL



Example: Spring Boot and Google OAuth

Generate a new Spring Boot Project as ***spring-boot-oauth*** with following dependencies;

- X Spring Boot DevTools
- X Spring Security
- X OAuth2 Client
- X Spring Web



The screenshot shows the project structure of 'spring-boot-oauth' in an IDE. The project is a Spring Boot application with the following structure:

- spring-boot-oauth [boot] [devtools]
 - src/main/java
 - com.seshu.app1
 - SpringBootOAuthApplication.java
 - com.seshu.app1.config
 - SecurityConfig.java
 - com.seshu.app1.controller
 - SampleController.java
 - src/main/resources
 - static
 - templates
 - application.yml
 - src/test/java
 - JRE System Library [JavaSE-17]
 - Maven Dependencies
 - src
 - target
 - HELP.md
 - mvnw
 - mvnw.cmd
 - pom.xml

application.yml

```
spring:
  security:
    oauth2:
      client:
        registration:
          google:
            client-id: 982661621356-
            client-secret: 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y
            client-authentication-method: POST
            client-name: Google
            client-type: confidential
            provider: google-oauth
            redirect-uri: http://localhost:8080/login/oauth2/code/google
            scope: openid, email, profile
```

SampleController.java

```
package com.seshu.appl.controller;

import java.security.Principal;

import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.RestController;

@RestController
public class SampleController {
    @GetMapping("/")
    public String welcomeView() {
        return "Welcome to sample controller";
    }
    @GetMapping("/profile")
    public String profileView() {
        return "welcome to profile page";
    }
    @GetMapping(value = "/user")
    public Principal user(Principal principal) {
        return principal;
    }
}
```


SecurityConfig.java

```
package com.seshu.app1.config;

import org.springframework.context.annotation.Configuration;
import org.springframework.security.config.annotation.web.builders.HttpSecurity;
import org.springframework.security.config.annotation.web.configuration.WebSecurityConfigurerAdapter;

@Configuration
public class SecurityConfig extends WebSecurityConfigurerAdapter {
    @Override
    public void configure(HttpSecurity http) throws Exception {
        http.antMatcher("/**")
            .authorizeRequests()
            .antMatchers(new String[] { "/" })
            .permitAll()
            .anyRequest()
            .authenticated()
            .and()
            .oauth2Login();
    }
}
```

SpringBootOauthApplication.java

```
package com.seshu.app1;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;



@SpringBootApplication
public class SpringBootOauthApplication {
    public static void main(String[] args) {
        SpringApplication.run(SpringBootOauthApplication.class, args);
    }
}
```



Test the application

<http://localhost:8080/>



<http://localhost:8080/profile>



[illegible]A screenshot of a web browser window. The address bar shows 'localhost:8080/logout'. The page content consists of the text 'Are you sure you want to log out?' in a large, dark font, followed by a blue button labeled 'Log Out' in white text. The browser's tab bar shows a single tab titled 'Confirm Log Out?'. The browser's toolbar includes back, forward, and refresh buttons, as well as icons for bookmarks, extensions, and the user profile.

Please sign in

localhost:8080/login?logout

Login with OAuth 2.0

You have been signed out


Google



One Time setup for Facebook OAuth2:



Step 1: Go to the following url;

<https://developers.facebook.com/>

Select My Apps







springboot1 - + Add Product - F x +

developers.facebook.com/apps/1870601109997647/add/

Meta for Developers Docs Tools Support My Apps Search developer documentation Adishesu Dasari

springboot1 App ID: 1870601109997647 App Mode: Development Live App type: Consumer Help

IMPORTANT: For all email communications regarding compliance requirements, please ensure you are emailing from the contact email registered in App Dashboard, and that our address is in the to: field, not cc: or bcc:, or we will not receive your message. For details on the appeals process, please refer to this Developer Blog post. Thank you!

Add products to your app

We've streamlined the app creation process by surfacing the products and permissions needed to build the app type you selected.

Product	Description	Action
App Events	Understand how people engage with your business across apps, devices, platforms and websites.	Read Docs Set up
Audience Network	Monetize your app and grow revenue with ads from Meta advertisers.	Read Docs Set up
Facebook Login	The world's number one social login product.	Read Docs Set up
Instagram Basic Display	The Instagram Basic Display API allows users of	Read Docs Set up
Webhooks		Read Docs Set up
Fundraisers		Read Docs Set up

Meta for Developers Docs Tools Support My Apps Search developer documentation Adishesu Dasari

springboot1 App ID: 1870601109997647 App Mode: Development Live App type: Consumer Help

IMPORTANT: For all email communications regarding compliance requirements, please ensure you are emailing from the contact email registered in App Dashboard, and that our address is in the to: field, not cc: or bcc:, or we will not receive your message. For details on the appeals process, please refer to this Developer Blog post. Thank you!

Settings

Basic Advanced Roles Alerts App Review Products Add Product Facebook Login Activity Log

App ID	1870601109997647	App secret Show
Display name	springboot1	Namespace	
App domains		Contact email	adi.accent@yahoo.com
Privacy Policy URL	Privacy policy for Login dialog and app details	Terms of Service URL	Terms of Service for Login dialog and App Details
User data deletion	Data deletion instructions URL	App icon (1024 x 1024)	Discard Save changes

Only update the application.yml file of *spring-boot-oauth* project

```
spring:
  security:
    oauth2:
      client:
        registration:
          facebook:
            client-id: 1870601109997647
            client-secret: blce3649586841fa018bd3d9d3fa2174
```

Test the application

