

main.cpp

Run

Share

Clear

9

void info ()

10 {

11 cout<<"name : "<<name<<endl;

12 cout<<"id : "<<id<<endl;

13 cout<<"Cgpa : "<<cgpa <<endl;

14 }

15 };

16 int main ()

17 {

18

19 student s1,s2;

20 s1.name="etu";

21 s1.id=1;

22 s1.cgpa=3.88;

23 s1.info();

24 s2.name="Tasnim";

25 s2.id=2;

26 s2.cgpa=3.78;

27 s2.info();

28 return 0;

29 }

name :etu

id:1

Cgpa :3.88

name :Tasnim

id:2

Cgpa :3.78

=== Code Execution Successful ===

main.cpp

Run

Share

Clear

16

17 void input(float discount)

18 {

19 float discountprice, newprice;

20 discountprice=price*discount/100;

21 newprice=price-discountprice;

22 cout<<"Book details:"<<"\n"<<"title:"<<"title"<<"\n"<<"price:"

23 <<"price"<<"\n"<<"discount"<<"newprice"<<"endl;

24 }

25 };

26 int main ()

27 {

28 int discount;

29 Book b1;

30 b1.info();

31 cout<<"Enter discount:"<<"endl;

32 cin>>discount;

33 b1.input(discount);

34 return 0;

35 }

Output

Enter book title :
Untold story
Enter book author :
Anika tasnim
price:
9998.88
Enter discount:
34
Book details:
title:Untold story
price:9998.88
discount6599.26

=== Code Execution Successful ===



main.cpp



Share

Run

```
11
12     age=a;
13     else cout<<"invalid age "<<endl;
14     name=n;
15 }
16 int getage()
17 {
18     return age;
19 }
20 }
21
22 string getname(){
23     return name;
24 }
25
26 };
27 int main (){
28
29     person p1;
30     p1.setdata("Etu",22);
31     cout<<"name:"<<p1.getname()<<" "<<"age"<<p1.getage()<<endl;
```

Output

Clear

name:Etu age22

=== Code Execution Successful ===

```
main.cpp
8 void show():
9 ~myclass() { //destructor
10
11 };
12 myclass::myclass ()
13 {
14     cout<<"constructor"<<endl;
15     a=100;
16
17 }
18 void myclass::show(){
19     cout<<"value of a:"<<a<<endl;
20 }
21 myclass::~myclass (){
22     cout<<"destructor"<<endl;
23 }
24 int main(){
25     myclass m1,m2;
26     m1.show();
27     m2.show();
28     return 0;
}
```

```
constructor
constructor
value of a:100
value of a:100
destructor
destructor

=== Code Execution Successful ===
```


(12) W...Q. 19th...EEE 12...Quick...Get Int...Online...Online...Online...Download...gemini...CSE Ar...baust...+...New Chrome available

programiz.com/cpp-programming/online-compiler/

GmailYouTubeMaps

Programiz
C++ Online Compiler

Programiz PRO

main.cpp

34 }
35
36 void student::display() {
37 cout << "name:" << name << " age:" << age << " cgpa:" << cgpa
38 << endl;
39 }
40 student::~student() {
41 cout << "destructor" << endl;
42 }
43
44 int main() {
45 student s1;
46 student s2(" ");
47 student s3("N/A", 20, 3.5);
48 s1.display();
49 s2.display();
50 s3.display();
51 return 0;
52 }
53

Run

Share

Clear

Output

constructor
enter name:
anika tasnim
name:N/A age:0 cgpa:0
name:anika tasnim age:0 cgpa:0
name:N/A age:20 cgpa:3.5
destructor
destructor
destructor

=== Code Execution Successful ===

Search

27°C Partly cloudy 11:01 PM

Run

main.cpp

```
30     length = 1;
31     width = w;
32 }
33
34 void rectangle::display() {
35     cout << "length:" << length << "    width:" <<
        width << endl;
36 }
37
38 rectangle::~rectangle() {
39 }
40
41 int main() {
42     rectangle r1;
43     r1.display();
44 }
```

Output

Clear

length:1 width:1
length:2 width:3
invalid
length:1 width:1

=== Code Execution Successful ===

main.cpp

Share

Run

Clear

```
24 public:
25     student(string n, int a, int i, float c) : person(n, a) {
26         id = i;
27         cgpa = c;
28         cout << "student" << endl;
29     }
30     void displaystudent() {
31         displayperson();
32         cout << "id:" << id << " cgpa:" << cgpa << endl;
33     }
34 };
35
36 int main() {
37     student s1("etu", 22, 84, 3.96);
38     s1.displaystudent();
39     return 0;
40 }
41
```

```
person
student
name:etu age:22
id:84 cgpa:3.96

=== Code Execution Successful ===
```



main.cpp



Share

Run

19 string brand;
20 public:
21 car(int s, string b) : vehicle(s) {
22 brand = b;
23 cout << "car is called" << endl;
24 }
25 void display() {
26 displayspeed();
27 cout << "brand:" << brand << endl;
28 }
29 };
30
31 int main() {
32 car c(22, "toyota");
33 c.display();
34 return 0;
35 }
36

Output

Clear

vehicle is called
car is called
speed:22
brand:toyota

=== Code Execution Successful ===

Share

Run

main.cpp

25 };

26

27 class D : public B, public C {

28 public:

29 D() : A(23) {

30 cout << "D class" << endl;

31 }

32 void show() {

33 cout << "x:" << x << endl;

34 }

35 };

36

37 int main() {

38 D obj;

39 obj.show();

40 return 0;

41 }

42

Output

Clear

A class

B class

C class

D class

x:23

=== Code Execution Successful ===

main.cpp

```
36- : person(n, a), teacher(n, a, eid), researcher(n, a,
37-     area) {
38-     cout << "professor" << endl;
39- }
40- void show() {
41-     cout << "name:" << name << " age:" << age
42-         << " employee:" << employeeid
43-         << " research area:" << researcharea << endl;
44- }
45-
46- int main() {
47-     professor p("DR. Anika", 22, 1084, "Artificial
48-         Intelligence");
49-     p.show();
50-     return 0;
51- }
```

Output

Clear

person
teacher
researcher
professor
name:DR. Anika age:22 employee:1084 research area:Artificial
Intelligence

=== Code Execution Successful ===