



**THE UNIVERSITY OF AZAD JAMMU AND
KASHMIR, MUZAFFARABAD**
Department of Software Engineering



Submitted to:

Engr. Sidra Rafique

Course Title:

Data Structure and Algorithm

Course Code:

CS-2101

Session:

2024-2028

Lab No:

05

Roll No:

2024-SE-15

Submitted By:

Shahzad Ahmed Awan

Submission date:

November 29, 2025

Table of Contents

Lab 05 – Circular Linked List Implementation	3
1. Objective	3
2. Background	3
Advantages:.....	3
Disadvantages:	4
3. Algorithm	4
3.1 Singly Circular Linked List	4
3.2 Doubly Circular Linked List	4
4. Source Code Explanation	5
4.1 Singly Circular Linked List	5
4.2 Doubly Circular Linked List	7
5. Output Screenshots	9
5.1 Singly Circular Linked List	9
5.2 Doubly Circular Linked List	9
6. Conclusion	10
7. Reflection	10

Table of Figures

Figure 1: A Diagram Demonstrating Singly Circular Linked List	3
Figure 2: A Diagram Demonstrating Doubly Circular Linked List	3
Figure 3: Source Code for Singly Circular Linked List using OOP (Screenshot -1)	5
Figure 4: Source Code for Singly Circular Linked list using OOP (Screenshot -2).....	6
Figure 5: Source Code for Doubly Circular Linked List using OOP (Screenshot- 1)	7
Figure 6: Source Code for the Doubly Circular Linked List (Screenshot- 2)	8
Figure 7: Output for the Singly Circular linked List Code	9
Figure 8: Output for the Doubly linked List Code	9

Lab 05 – Circular Linked List Implementation

1. Objective

To implement Singly Circular Linked List (SCLL) and Doubly Circular Linked List (DCLL) in C++ to perform insertion, deletion, and traversal operations, demonstrating circular linking and bidirectional traversal.

2. Background

- **Singly Circular Linked List:**

- Each node points to the next node.
- The last node points back to the head, forming a circular structure.




Figure 1: A Diagram Demonstrating Singly Circular Linked List

- **Doubly Circular Linked List:**

- Each node contains `next` and `prev` pointers.
- Tail node points to head, and head's `prev` points to tail.
- Enables bidirectional traversal.




Figure 2: A Diagram Demonstrating Doubly Circular Linked List

Advantages:

- Efficient insertion/deletion at both ends.
- Traversal possible in both directions.

Disadvantages:

- Requires extra memory for `prev` pointer.
 - Slightly more complex than singly linked list.
-

3. Algorithm

3.1 Singly Circular Linked List

1. Start the program.
2. Define a Node structure with `data` and `next` pointer.
3. Implement functions:
 - `insertEnd()` – Insert node at the end.
 - `display()` – Print circular list starting from head.
4. Insert sample nodes and display the list.
5. End program.

3.2 Doubly Circular Linked List

1. Start the program.
2. Define Node structure with `data`, `prev`, and `next`.
3. Create `DoublyCircularList` class with `head` and `tail`.
4. Implement functions:
 - `insertAtBeginning()` – Insert node at start.
 - `insertAtEnd()` – Insert node at end.
 - `deleteFromBeginning()` – Remove first node.
 - `deleteFromEnd()` – Remove last node.
 - `displayForward()` – Traverse head → tail.
 - `displayBackward()` – Traverse tail → head.
5. Use a menu loop for repeated operations.
6. End program.

4. Source Code Explanation

4.1 Singly Circular Linked List

```
1  #include <iostream>
2  using namespace std;
3
4  // Node class
5  class Node {
6  public:
7      int data;
8      Node* next;
9
10     Node(int value) {
11         data = value;
12         next = nullptr;
13     }
14 };
15
16 // Singly Circular Linked List class
17 class CircularList {
18 private:
19     Node* head;
20
21 public:
22     CircularList() {
23         head = nullptr;
24     }
25
26     // Insert at the end of the list
27     void insertEnd(int value) {
28         Node* newNode = new Node(value);
29
30         // If list is empty
31         if (head == nullptr) {
32             head = newNode;
33             newNode->next = head; // circular
34             return;
35         }
36
37         // Find last node (next points to head)
38         Node* temp = head;
39         while (temp->next != head) {
40             temp = temp->next;
41         }
42
43         // Insert new node after last node
44         temp->next = newNode;
45         newNode->next = head; // maintain circular link
46     }
47 }
```

Figure 3: Source Code for Singly Circular Linked List using OOP (Screenshot -1)

```

48 | // Display list
49 | void display() {
50 |     if (head == nullptr) {
51 |         cout << "List is empty!" << endl;
52 |         return;
53 |     }
54 |
55 |     cout << "Circular Linked List: ";
56 |     Node* temp = head;
57 |
58 |     // Use do-while for circular traversal
59 |     do {
60 |         cout << temp->data << "->";
61 |         temp = temp->next;
62 |     } while (temp != head);
63 |
64 |     cout << endl;
65 | }
66 | };
67 |
68 | // Main function
69 | int main() {
70 |     CircularList list;
71 |
72 |     // Insert values
73 |     list.insertEnd(10);
74 |     list.insertEnd(20);
75 |     list.insertEnd(30);
76 |     list.insertEnd(40);
77 |
78 |     // Display list
79 |     list.display();
80 |
81 |     return 0;
82 | }
83 |

```

Figure 4: Source Code for Singly Circular Linked list using OOP (Screenshot -2)

- **insertEnd()**: Adds a node after last node; points it back to head.
- **display()**: Traverses from head until it returns to head.

4.2 Doubly Circular Linked List

```
1  #include <iostream>
2  using namespace std;
3
4  // Node class
5  class Node {
6  public:
7      int data;
8      Node* next;
9      Node* prev;
10
11     Node(int value) {
12         data = value;
13         next = nullptr;
14         prev = nullptr;
15     }
16 };
17
18 // Doubly Circular Linked List class
19 class DoublyCircularList {
20 private:
21     Node* head;
22
23 public:
24     DoublyCircularList() {
25         head = nullptr;
26     }
27
28     // Insert at the end
29     void insertEnd(int value) {
30         Node* newNode = new Node(value);
31
32         // If list is empty
33         if (head == nullptr) {
34             newNode->next = newNode;
35             newNode->prev = newNode;
36             head = newNode;
37             return;
38         }
39
40         // Otherwise insert at the end
41         Node* last = head->prev;
42
43         newNode->next = head; // new node points to head
44         newNode->prev = last; // new node points to last
45         last->next = newNode; // last's next is new node
46         head->prev = newNode; // head's prev is new node
47     }
48 }
```

Figure 5: Source Code for Doubly Circular Linked List using OOP (Screenshot- 1)

- **insertEnd()** – Adds a new node at the end by linking it between the last node and the head, keeping both next and prev circular.

```

49 // Display forward
50 void displayForward() {
51     if (head == nullptr) {
52         cout << "List is empty!" << endl;
53         return;
54     }
55
56     cout << "Doubly Circular Linked List (Forward): ";
57     Node* temp = head;
58
59     do {
60         cout << temp->data << "->";
61         temp = temp->next;
62     } while (temp != head);
63
64     cout << endl;
65 }
66
67 // Display backward
68 void displayBackward() {
69     if (head == nullptr) return;
70
71     cout << "Doubly Circular Linked List (Backward): ";
72     Node* temp = head->prev; // start from last node
73
74     do {
75         cout << temp->data << "->";
76         temp = temp->prev;
77     } while (temp != head->prev);
78
79     cout << endl;
80 }
81 };
82
83 // Main function
84 int main() {
85     DoublyCircularList list;
86
87     // Insert nodes
88     list.insertEnd(10);
89     list.insertEnd(20);
90     list.insertEnd(30);
91     list.insertEnd(40);
92
93     // Display outputs
94     list.displayForward();
95     list.displayBackward();
96
97     return 0;
98 }

```

Figure 6: Source Code for the Doubly Circular Linked List (Screenshot- 2)

- **displayForward()** – Prints the list from head to tail using `next` pointers.

- **displayBackward()** – Prints the list from tail to head using `prev` pointers.

displayBackward(): Prints tail → head.


Menu loop: Handles multiple operations with screen refresh.

5. Output Screenshots

5.1 Singly Circular Linked List

Expected Output:

Circular Linked List: 10 20 30 40




```
C:\Users\hp\Desktop\singly-c X + v
Circular Linked List: 10->20->30->40->
-----
Process exited after 0.4283 seconds with return value 0
Press any key to continue . . .
```

Figure 7: Output for the Singly Circular linked List Code

5.2 Doubly Circular Linked List

Expected Output:

Forward: 10 -> 20 -> 30 -> 40
Backward: 40 -> 30 -> 20 -> 10



```
C:\Users\hp\Desktop\Doublel X + v
Doubly Circular Linked List (Forward): 10->20->30->40->
Doubly Circular Linked List (Backward): 40->30->20->10->
-----
Process exited after 0.7378 seconds with return value 0
Press any key to continue . . . |
```

Figure 8: Output for the Doubly linked List Code

6. Conclusion

- Successfully implemented SCLL and DCLL with insertion, deletion, and traversal operations.
- Demonstrated circular linking, pointer manipulation, and bidirectional traversal in C++.

7. Reflection

- Improved understanding of dynamic memory and pointers.
- Learned differences between singly and doubly circular structures.
- Menu-driven operations improve user interactivity and readability.