




# **Artificial Intelligence (Machine Learning & Deep Learning) [Course]**

**Week 4 - Day 1 n Day 2 - Pandas**

**[See examples / code in GitHub code repository]**

**It is not about Theory, it is 20% Theory and 80% Practical –  
Technical/Development/Programming [Mostly Python based]**

- ❑ Pandas is a Python library used for working with data sets.
- ❑ It has functions for analyzing, cleaning, exploring, and manipulating data.
- ❑ The name "Pandas" has a reference to both "Panel Data", and "Python Data Analysis" and was created by Wes McKinney in 2008.



# python



## Applications of Pandas



### Reference:

<https://data-flair.training/blogs/applications-of-pandas/>


25




# Pandas – Key Concepts




❑ A data table is called a DataFrame.



❑ Pandas provides plotting your data out of the box, using the power of Matplotlib.



.plot.\*



DATA TYPE

STRENGTHS

AMOUNT OF DATA  
BEING ANALYZED

DATA TYPES

MEMORY USAGE

SPEED

pandas

Tabular

Data frame, Series

>500K rows

Can contain dissimilar  
data types

More

Slower

NumPy

Numerical

Arrays

<50K rows

Homogenous  
data types

Less

Faster





# Pandas – Key Concepts

dataframe

x	y
12.3	ace
3	tea
5.01	oil
2.3	tree

matrix

12.3	0.1
3.0	5.2
5.01	3.0
2.3	0.1

list


x	y
12.3	ace
3	tea
5.01	oil
2.3	tree
3	
$Y \sim x - 1$	
some text	

Characteristics	NumPy Array	Pandas Dataframe
Homogeneity	Arrays consist of only homogeneous elements (elements of same data type)	Dataframes have heterogeneous elements.
Mutability	Arrays are mutable	Dataframes are mutable
Access	Array elements can be accessed using integer positions.	Dataframes can be accessed using both integer position as well as index.
Flexibility	Arrays do not have flexibility to deal with dynamic data sequence and mixed data types.	Dataframes have that flexibility.
Data type	Array deals with numerical data.	Dataframes deal with tabular data.



Pandas dtype	Python type	NumPy type	Usage
object	str or mixed	string_, unicode_, mixed types	Text or mixed numeric and non-numeric values
int64	int	int_, int8, int16, int32, int64, uint8, uint16, uint32, uint64	Integer numbers
float64	float	float_, float16, float32, float64	Floating point numbers
bool	bool	bool_	True/False values
datetime64	NA	datetime64[ns]	Date and time values
timedelta[ns]	NA	NA	Differences between two datetimes
category	NA	NA	Finite list of text values

## DATA STRUCTURES IN PANDAS



## Creating DataFrames

	a	b	c
1	4	7	10
2	5	8	11
3	6	9	12

```
df = pd.DataFrame(  
    {"a" : [4, 5, 6],  
     "b" : [7, 8, 9],  
     "c" : [10, 11, 12]},  
    index = [1, 2, 3])  
Specify values for each column.
```

```
df = pd.DataFrame(  
    [[4, 7, 10],  
     [5, 8, 11],  
     [6, 9, 12]],  
    index=[1, 2, 3],  
    columns=['a', 'b', 'c'])  
Specify values for each row.
```

	a	b	c
N	v		

## Reshaping Data – Change layout, sorting, reindexing, renaming



`pd.melt(df)`  
Gather columns into rows.



`df.pivot(columns='var', values='val')`  
Spread rows into columns.



`pd.concat([df1, df2])`  
Append rows of DataFrames



`pd.concat([df1, df2], axis=1)`  
Append columns of DataFrames

`df.sort_values('mpg')`  
Order rows by values of a column (low to high).

`df.sort_values('mpg', ascending=False)`  
Order rows by values of a column (high to low).


`df.rename(columns = {'y':'year'})`  
Rename the columns of a DataFrame

`df.sort_index()`  
Sort the index of a DataFrame

`df.reset_index()`  
Reset index of DataFrame to row numbers, moving index to columns.

`df.drop(columns=['Length', 'Height'])`  
Drop columns from DataFrame

### Subset Observations - rows



### Subset Variables - columns



### Subsets - rows and columns

Use `df.loc[]` and `df.iloc[]` to select only rows, only columns or both.

## Python Pandas Cheat Sheet

<https://www.datasciencecentral.com/data-science-in-python-pandas-cheat-sheet/>

[https://pandas.pydata.org/Pandas\\_Cheat\\_Sheet.pdf](https://pandas.pydata.org/Pandas_Cheat_Sheet.pdf)

<https://www.datacamp.com/cheat-sheet/pandas-cheat-sheet-data-wrangling-in-python>



See code here: <https://github.com/ShahzadSarwar10/AI-ML-Explorer>

You should be able to analyze – each code statement, you should be able to see trace information – at each step of debugging. “DEBUGGING IS BEST STRATEGY TO LEARN A LANGUAGE.” So debug code files, line by line, analyze the values of variable – changing at each code statement. BEST STRATEGY TO LEARN DEEP.

Let's put best efforts.

Thanks.

Shahzad – Your AI – ML Instructor

25

## Exercises



# python





Thank you - for listening and participating

- ☐ Questions / Queries
- ☐ Suggestions/Recommendation
- ☐ Ideas.....?

Shahzad Sarwar  
Cognitive Convergence

<https://cognitiveconvergence.com>  
[shahzad@cognitiveconvergence.com](mailto:shahzad@cognitiveconvergence.com)

voice: +1 4242530744 (USA) +92-3004762901 (Pak)