

Assignment 11.3 Ai Assisted Coding

Name: Sk.Nishaaj

Ht.no: 2303A51613

Batch: 06

Task 1:

Smart Contact Manager (Arrays & Linked Lists)


Scenario

SR University's student club requires a simple Contact Manager Application to store members' names and phone numbers. The system should support efficient addition, searching, and deletion of contacts.

Prompt:

Write a python program to Create a Contact Manager using list and linked list with add, search, and delete functions.

Code:



```
1 class Contact:
2     """Represents a single contact"""
3     def __init__(self, contact_id, name, phone, email):
4         self.contact_id = contact_id
5         self.name = name
6         self.phone = phone
7         self.email = email
8
9     def __str__(self):
10         return f"Contact {self.contact_id}: {self.name}, {self.phone}, {self.email}"
11
12     def __repr__(self):
13         return self.__str__()
14
15 class Node:
16     """Node for the linked list"""
17     def __init__(self, contact):
18         self.contact = contact
19         self.next = None
20
21 class ContactManager:
22     """Contact Manager using linked list"""
23     def __init__(self):
24         self.head = None
25         self.contacts = []
26
27     def add_contact(self, contact):
28         """Add a new contact to the list"""
29         if self.head is None:
30             self.head = Node(contact)
31             self.contacts.append(contact)
32         else:
33             current = self.head
34             while current.next is not None:
35                 current = current.next
36             current.next = Node(contact)
37             self.contacts.append(contact)
38
39     def search_by_name(self, name):
40         """Search for a contact by name"""
41         results = []
42         for i, contact in enumerate(self.contacts):
43             if name.lower() in contact.name.lower():
44                 results.append(i)
45         return results
46
47     def delete_contact(self, contact_id):
48         """Delete a contact by ID"""
49         if self.head is None:
50             return None
51         if self.head.contact.contact_id == contact_id:
52             self.head = self.head.next
53             self.contacts.remove(self.head.contact)
54         else:
55             current = self.head
56             while current.next is not None:
57                 if current.next.contact.contact_id == contact_id:
58                     current.next = current.next.next
59                     self.contacts.remove(current.next.contact)
60                 current = current.next
61
62     def display_all(self):
63         """Display all contacts"""
64         if self.head is None:
65             print("No contacts found")
66         else:
67             current = self.head
68             while current is not None:
69                 print(f"Contact {current.contact.contact_id}: {current.contact.name}, {current.contact.phone}, {current.contact.email}")
70                 current = current.next
71
72     def __len__(self):
73         return len(self.contacts)
74
75 def main():
76     manager = ContactManager()
77
78     while True:
79         print("\nContact Manager Menu")
80         print("1. Add Contact")
81         print("2. Search Contact")
82         print("3. Delete Contact")
83         print("4. Display All")
84         print("5. Exit")
85
86         choice = input("Enter your choice: ")
87
88         if choice == "1":
89             name = input("Name: ")
90             phone = input("Phone: ")
91             email = input("Email: ")
92             contact = Contact(len(manager.contacts), name, phone, email)
93             manager.add_contact(contact)
94
95         elif choice == "2":
96             name = input("Search by name: ")
97             results = manager.search_by_name(name)
98             if results:
99                 for i in results:
100                     print(f"Contact {i}: {manager.contacts[i].name}, {manager.contacts[i].phone}, {manager.contacts[i].email}")
101             else:
102                 print("No contacts found")
103
104         elif choice == "3":
105             contact_id = input("Enter contact ID to delete: ")
106             manager.delete_contact(int(contact_id))
107
108         elif choice == "4":
109             manager.display_all()
110
111         elif choice == "5":
112             break
113
114         input("\nPress Enter to continue...")
115
116 if __name__ == "__main__":
117     main()
118
119 # Total contacts (linked list): 9
```

```
File Edit Selection *** Q AI Assistant Coding
# Manager.py
class ContactManager:
    def __init__(self):
        self.contacts = {}

    def add_contact(self, name, phone, email):
        if name in self.contacts:
            print(f"Contact '{name}' already exists!")
            return False
        self.contacts[name] = {"phone": phone, "email": email}
        return True

    def search_contact(self, name):
        if name in self.contacts:
            return self.contacts[name]
        return None

    def search_by_name(self, name):
        results = []
        for name, contact in self.contacts.items():
            if name.startswith(name.lower()):
                results.append(contact)
        return results

    def delete_contact(self, name):
        if name in self.contacts:
            del self.contacts[name]
            print(f"Contact '{name}' deleted successfully!")
            return True
        return False

    def display_all(self):
        if not self.contacts:
            print("No contacts found!")
            return
        for name, contact in self.contacts.items():
            print(f"Name: {name}, Phone: {contact['phone']}, Email: {contact['email']}")

    def __str__(self):
        return str(self.contacts)

    def __repr__(self):
        return f"ContactManager({self.contacts})"

# Main Program
if __name__ == "__main__":
    manager = ContactManager()
    manager.add_contact("John Doe", "123-456-7890", "john.doe@example.com")
    manager.add_contact("Jane Smith", "987-654-3210", "jane.smith@example.com")
    manager.add_contact("Bob Johnson", "555-111-2222", "bob.johnson@example.com")
    manager.add_contact("Alice Brown", "444-333-2222", "alice.brown@example.com")

    # Display all contacts
    manager.display_all()

    # Search by name
    name = input("Enter name to search: ")
    result = manager.search_contact(name)
    if result:
        print(f"Found contact for '{name}': {result}")
    else:
        print(f"Contact not found for '{name}'")

    # Search by name (partial)
    name = input("Enter name to search (partial): ")
    results = manager.search_by_name(name)
    if results:
        print(f"Found contacts for '{name}': {results}")
    else:
        print(f"No contacts found for '{name}'")

    # Delete contact
    name = input("Enter name to delete: ")
    result = manager.delete_contact(name)
    if result:
        print(f"Contact '{name}' deleted successfully!")
    else:
        print(f"Contact not found for '{name}'")

    # Display all contacts again
    manager.display_all()

    # Print the manager object
    print(f"Manager object: {manager}")
    print(f"Manager object (repr): {repr(manager)}")

    # Final display
    manager.display_all()

    # Exit
    print("Exiting Contact Manager...")
```

```
File Edit Selection *** Q AI Assistant Coding
# Manager.py
class ContactManager:
    def __init__(self):
        self.contacts = {}

    def add_contact(self, name, phone, email):
        if name in self.contacts:
            print(f"Contact '{name}' already exists!")
            return False
        self.contacts[name] = {"phone": phone, "email": email}
        return True

    def search_contact(self, name):
        if name in self.contacts:
            return self.contacts[name]
        return None

    def search_by_name(self, name):
        results = []
        for name, contact in self.contacts.items():
            if name.startswith(name.lower()):
                results.append(contact)
        return results

    def delete_contact(self, name):
        if name in self.contacts:
            del self.contacts[name]
            print(f"Contact '{name}' deleted successfully!")
            return True
        return False

    def display_all(self):
        if not self.contacts:
            print("No contacts found!")
            return
        for name, contact in self.contacts.items():
            print(f"Name: {name}, Phone: {contact['phone']}, Email: {contact['email']}")

    def __str__(self):
        return str(self.contacts)

    def __repr__(self):
        return f"ContactManager({self.contacts})"

# Main Program
if __name__ == "__main__":
    manager = ContactManager()
    manager.add_contact("John Doe", "123-456-7890", "john.doe@example.com")
    manager.add_contact("Jane Smith", "987-654-3210", "jane.smith@example.com")
    manager.add_contact("Bob Johnson", "555-111-2222", "bob.johnson@example.com")
    manager.add_contact("Alice Brown", "444-333-2222", "alice.brown@example.com")

    # Display all contacts
    manager.display_all()

    # Search by name
    name = input("Enter name to search: ")
    result = manager.search_contact(name)
    if result:
        print(f"Found contact for '{name}': {result}")
    else:
        print(f"Contact not found for '{name}'")

    # Search by name (partial)
    name = input("Enter name to search (partial): ")
    results = manager.search_by_name(name)
    if results:
        print(f"Found contacts for '{name}': {results}")
    else:
        print(f"No contacts found for '{name}'")

    # Delete contact
    name = input("Enter name to delete: ")
    result = manager.delete_contact(name)
    if result:
        print(f"Contact '{name}' deleted successfully!")
    else:
        print(f"Contact not found for '{name}'")


    # Display all contacts again
    manager.display_all()

    # Print the manager object
    print(f"Manager object: {manager}")
    print(f"Manager object (repr): {repr(manager)}")

    # Final display
    manager.display_all()

    # Exit
    print("Exiting Contact Manager...")
```

Output:



Explanation:

- In an array, adding at the end is fast, but inserting in the middle is slow because elements must shift.
- In a linked list, insertion is fast because no shifting is needed.
- Searching takes the same time in both (you must check each element).
- Deleting in an array is slower due to shifting elements.
- Linked list is better for frequent insertions and deletions.

Task 2:



Library Book Search System (Queues & Priority Queues) Scenario


The SRU Library manages book borrow requests. Students and faculty submit requests, but faculty requests must be prioritized over student requests.

Prompt:

Write a Python program for a library book request system. First, make a normal queue where requests are handled in the order they come. Then, make another version where faculty requests are given first priority over student requests. Include functions to add a request and remove a request.

Code:





Output:

```
PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/bug.py"

=== Priority Queue ===
1. ID: 3, Requester: Charlie (Student), Book: Web Development
2. ID: 5, Requester: Eve (Student), Book: Databases
Queue size: 2

=====
PS C:\AI Assistant Coding> 
```

Explanation:

- Queue (FIFO) → First request comes, first served.(If a student requests first, they get the book first.)
- Priority Queue → Faculty requests are served before students, even if they come later.
- enqueue() → Adds a request to the system.
- dequeue() → Removes and processes the next request.

Task 3: Emergency Help Desk (Stack Implementation)

Scenario


SR University's IT Help Desk receives technical support tickets from students and staff.

While tickets are received sequentially, issue escalation follows a Last-In, First-Out (LIFO) approach.


Prompt:

Write a program of stack-based ticket system in Python with push, pop, peek, isEmpty, and isFull. Add five tickets and show how they are resolved using LIFO order.

Code:




```
1 # ===== STACK-BASED TICKET SYSTEM =====
2 class Ticket:
3     """Represents a support ticket"""
4     def __init__(self, ticket_id, customer_name, issue):
5         self.ticket_id = ticket_id
6         self.customer_name = customer_name
7         self.issue = issue
8
9     def __str__(self):
10         return f"Ticket #{self.ticket_id} | Customer: {self.customer_name} | Issue: {self.issue}"
11
12 class TicketStack:
13     """Stack-based ticket management system (LIFO - Last In, First Out)"""
14     def __init__(self, max_size=10):
15         self.stack = []
16         self.max_size = max_size
17
18     def push(self, ticket):
19         """Add a ticket to the stack (top of stack)"""
20         if self.isFull():
21             print(f"Error: Stack is full! Cannot add ticket #{ticket.ticket_id}")
22             return False
23         self.stack.append(ticket)
24         print(f"/> Ticket added: {ticket}")
25         return True
26
27     def pop(self):
28         """Remove and return the ticket from the top of the stack"""
29         if self.isEmpty():
30             print(f"Error: Stack is empty! No tickets to resolve.")
31             return None
32         ticket = self.stack.pop()
33         print(f"/> Resolving: {ticket}")
34         return ticket
35
36     def peek(self):
37         """View the top ticket without removing it"""
38         if self.isEmpty():
39             print(f"Error: Stack is empty!")
40             return None
41         return self.stack[-1]
42
43     def isEmpty(self):
44         """Check if the stack is empty"""
45         return len(self.stack) == 0
46
47     def isFull(self):
48         """Check if the stack is full"""
49         return len(self.stack) >= self.max_size
50
51     def size(self):
52         """Return the number of tickets in the stack"""
53         return len(self.stack)
54
55     def display_stack(self):
56         """Display all tickets in the stack (top to bottom)"""
57         for ticket in reversed(self.stack):
58             print(f"Ticket: {ticket}")
59
60 if __name__ == "__main__":
61     # Create ticket system with max size of 10
62     ticket_system = TicketStack(max_size=10)
63
64     # Add five tickets
65     print("> Adding tickets to the stack --->")
66     ticket_system.push(Ticket(101, "John Smith", "Login issue"))
67     ticket_system.push(Ticket(102, "Sarah Johnson", "Payment processing error"))
68     ticket_system.push(Ticket(103, "Mike Wilson", "Data export failure"))
69     ticket_system.push(Ticket(104, "Emma Brown", "Account suspended"))
70     ticket_system.push(Ticket(105, "David Lee", "Password reset not working"))
71
72     # Display current stack
73     ticket_system.display_stack()
74
75     # Show stack information
76     print(f"> Stack Size: {ticket_system.size()}")
77     print(f"> Is Stack Empty? {ticket_system.isEmpty()}")
78     print(f"> Is Stack Full? {ticket_system.isFull()}")
79
80     # Peek at the top ticket
81     print(f"> Peek at top ticket --->")
82     top_ticket = ticket_system.peek()
83     if top_ticket:
84         print(f"> Top ticket (without removing): {top_ticket}")
85
86     # Resolve all tickets in LIFO order
87     ticket_system.resolve_all()
88
89     # Display final stack state
90     print(f"> Final Stack Size: {ticket_system.size()}")
91     print(f"> Is Stack Empty? {ticket_system.isEmpty()}")
92     ticket_system.display_stack()
```



```
1 # ===== STACK-BASED TICKET SYSTEM =====
2 class Ticket:
3     """Represents a support ticket"""
4     def __init__(self, ticket_id, customer_name, issue):
5         self.ticket_id = ticket_id
6         self.customer_name = customer_name
7         self.issue = issue
8
9     def __str__(self):
10         return f"Ticket #{self.ticket_id} | Customer: {self.customer_name} | Issue: {self.issue}"
11
12 class TicketStack:
13     """Stack-based ticket management system (LIFO - Last In, First Out)"""
14     def __init__(self, max_size=10):
15         self.stack = []
16         self.max_size = max_size
17
18     def push(self, ticket):
19         """Add a ticket to the stack (top of stack)"""
20         if self.isFull():
21             print(f"Error: Stack is full! Cannot add ticket #{ticket.ticket_id}")
22             return False
23         self.stack.append(ticket)
24         print(f"/> Ticket added: {ticket}")
25         return True
26
27     def pop(self):
28         """Remove and return the ticket from the top of the stack"""
29         if self.isEmpty():
30             print(f"Error: Stack is empty! No tickets to resolve.")
31             return None
32         ticket = self.stack.pop()
33         print(f"/> Resolving: {ticket}")
34         return ticket
35
36     def peek(self):
37         """View the top ticket without removing it"""
38         if self.isEmpty():
39             print(f"Error: Stack is empty!")
40             return None
41         return self.stack[-1]
42
43     def isEmpty(self):
44         """Check if the stack is empty"""
45         return len(self.stack) == 0
46
47     def isFull(self):
48         """Check if the stack is full"""
49         return len(self.stack) >= self.max_size
50
51     def size(self):
52         """Return the number of tickets in the stack"""
53         return len(self.stack)
54
55     def display_stack(self):
56         """Display all tickets in the stack (top to bottom)"""
57         for ticket in reversed(self.stack):
58             print(f"Ticket: {ticket}")
59
60     def resolve_all(self):
61         """Resolve all tickets in LIFO order"""
62         print("> Resolving all tickets in LIFO order --->")
63         while not self.isEmpty():
64             print(f"> Resolving next ticket...")
65             self.pop()
66             count += 1
67         print(f"> All tickets have been resolved!")
68
69 if __name__ == "__main__":
70     # Create ticket system with max size of 10
71     ticket_system = TicketStack(max_size=10)
72
73     # Add five tickets
74     print("> Adding tickets to the stack --->")
75     ticket_system.push(Ticket(101, "John Smith", "Login issue"))
76     ticket_system.push(Ticket(102, "Sarah Johnson", "Payment processing error"))
77     ticket_system.push(Ticket(103, "Mike Wilson", "Data export failure"))
78     ticket_system.push(Ticket(104, "Emma Brown", "Account suspended"))
79     ticket_system.push(Ticket(105, "David Lee", "Password reset not working"))
80
81     # Display current stack
82     ticket_system.display_stack()
83
84     # Show stack information
85     print(f"> Stack Size: {ticket_system.size()}")
86     print(f"> Is Stack Empty? {ticket_system.isEmpty()}")
87     print(f"> Is Stack Full? {ticket_system.isFull()}")
88
89     # Peek at the top ticket
90     print(f"> Peek at top ticket --->")
91     top_ticket = ticket_system.peek()
92     if top_ticket:
93         print(f"> Top ticket (without removing): {top_ticket}")
94
95     # Resolve all tickets in LIFO order
96     ticket_system.resolve_all()
97
98     # Display final stack state
99     print(f"> Final Stack Size: {ticket_system.size()}")
100     print(f"> Is Stack Empty? {ticket_system.isEmpty()}")
101     ticket_system.display_stack()
```

Output:



Explanation:

The program uses a stack to manage help desk tickets.

A stack works in last in, first solved order.

When a new ticket is raised, it is added to the top.

When solving a ticket, the most recent one is handled first.

The program can also check if there are no tickets left or if the stack is full.

Task 4:

Hash Table

Objective

To implement a Hash Table and understand collision handling.

Prompt:



Write a Python program to create a Hash Table.

Add methods to insert, search, and delete data.

Handle collisions using chaining (store multiple values in a list at the same index).

Add comments to explain the code and show example usage.

Code:



Task 5:

Real-Time Application Challenge Scenario

Design a Campus Resource Management System with the following features:



- Student Attendance Tracking
- Event Registration System
- Library Book Borrowing
- Bus Scheduling System
- Cafeteria Order Queue

Prompt:

Create a Campus Resource Management System in Python. For each feature (Attendance, Event Registration, Library, Bus Schedule, Cafeteria Orders), choose the best data structure

Code:

```
1 # campus_resource_management.py
2 """
3 Campus Resource Management System
4 Features and chosen data structures:
5 - Attendance: set (O(1) add/check) to track present student IDs
6 - Event Registration: deque (FIFO queue) for fair registration processing
7 - Library: dict (O(1) lookup) mapping book ID to book record for fast lookup
8 - Bus Schedule: dict of route -> sorted list of departure times (list kept sorted)
9 - Cafeteria Orders: heap (priority queue) to prioritize faculty over students while preserving arrival order
10 """
11
12 Run this file to see a small demo of each feature.
13 """
14
15 from collections import deque
16 import heapq
17 import sys
18 from bisect import bisect
19 from datetime import datetime, timedelta
20
21 # ===== Attendance (set) =====
22 class Attendance:
23     """Track attendance using a set for O(1) add/remove/check."""
24     def __init__(self):
25         self.present = set()
26
27     def mark_present(self, student_id):
28         self.present.add(student_id)
29         print(f"Marked present: {student_id}")
30
31     def mark_absent(self, student_id):
32         self.present.discard(student_id)
33         print(f"Marked absent: {student_id}")
34
35     def is_present(self, student_id):
36         return student_id in self.present
37
38     def present_count(self):
39         return len(self.present)
40
41     def list_present(self):
42         return sorted(self.present)
43
44 # ===== Event Registration (FIFO queue) =====
45 class EventRegistration:
46     """Register attendees in arrival order using deque."""
47     def __init__(self):
48         self.queue = deque()
49
50     def add_registration(self, attendee_id, name):
51         self.queue.append((attendee_id, name))
52         print(f"Registered: {attendee_id} - {name}")
53
54     def process_registration(self):
55         if not self.queue:
56             print("No registrations to process.")
57             return None
58         attendee = self.queue.popleft()
59         print(f"Processing registration: {attendee[0]} - {attendee[1]}")
60         return attendee
61
62     def pending_count(self):
63         return len(self.queue)
```



Output:

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  PORTS  TERMINAL  POSTMAN CONSOLE

PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/bug.py"
Is empty: False
PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/bug.py"
PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/campus_resource_management.py"

=====
Campus Resource Management Demo
=====

Marked present: 5001
Marked present: 5002
Marked present: 5010
Present list: ['5001', '5002', '5010']
Is 5002 present? True
Marked absent: 5002
Present count: 2
Registered: A001 - Alice
Registered: A002 - Bob
Registered: A003 - Charlie
Pending registrations: [('A001', 'Alice'), ('A002', 'Bob'), ('A003', 'Charlie')]
Processed registration: A001 - Alice
Pending count: 2
Added book: Clean Code (ISBN: 978-0135166307).
Added book: Fluent Python (ISBN: 978-1491958296).
5001 borrowed Clean Code
5003 borrowed Clean Code
No copies available.
Available books: [('978-0135166307', 'Clean Code', 0), ('978-1491958296', 'Fluent Python', 1)]
5001 returned Clean Code
Available books after return: [('978-0135166307', 'Clean Code', 1), ('978-1491958296', 'Fluent Python', 1)]
Added bus time for Route A: 2026-02-18 10:42:24.367227
Added bus time for Route A: 2026-02-18 10:57:24.367227
Added bus time for Route B: 2026-02-18 10:39:24.367227
Next Route A bus: 2026-02-18 10:42:24.367227
Route A schedule: [datetime.datetime(2026, 2, 18, 10, 42, 24, 367227), datetime.datetime(2026, 2, 18, 10, 57, 24, 367227)]
Order added: 0001 (Student)
Order added: 0002 (Faculty)
Order added: 0003 (Student)
Order added: 0004 (Faculty)
Pending cafeteria orders: 4
Serving order: 0002 (Faculty)
Serving order: 0004 (Faculty)
Pending orders after serving: 2

Demo complete.
PS C:\AI Assistant Coding> 
```

Explanation:

Library Book Borrowing using a queue:

- The queue stores student names who request a book.
- When a student requests a book, we use `enqueue()` to add them to the queue.
- When a book becomes available, we use `dequeue()` to give it to the first student in line.
- This ensures fairness because the first requester gets the book first.