A PROJECT TITLE
ON

SMARTCROP: A MACHINE LEARNING SYSTEM FOR PREDICTING CROP YIELD USING AGRICULTURAL AND ENVIRONMENTAL DATA

project report submitted in partial fulfilment of the requirements for the Course

MACHINE LEARNING
BACHELOR OF TECHNOLOGY
In
A.Y.: 2026-27

By

Name: Shaik Sabiya Thabassum - 2520030502

Name: G.Jithin Reddy -2520030508

Name: Minnekanti Akshaya - 2520030516

Under the Esteemed guidance of
Dr. Ravindra Gaddam
(Associate Professor, CSE)

Department of Computer Science and Engineering

Abstract

SmartCrop is a machine learning-based crop yield prediction system designed to estimate crop production using agricultural, environmental, soil, weather, and historical crop-related information. Accurate crop yield prediction can support farmers and agricultural stakeholders in planning cultivation activities, managing resources, and making data-driven decisions. The project uses the Smart Crop Yield Predication Dataset obtained from Kaggle as the primary dataset for model development.

The proposed system follows a machine learning pipeline consisting of dataset preparation, data preprocessing, exploratory analysis, feature preparation, model training, prediction, and evaluation. Three machine learning regression algorithms, namely Random Forest, XGBoost, and Support Vector Regression (SVR), are considered for crop yield prediction. These models are trained using relevant agricultural and environmental features and their predictions are evaluated using suitable regression metrics such as Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), and coefficient of determination (R^2). The models are compared based on their prediction performance to identify the model that provides the most suitable results for the given dataset.

The main objective of SmartCrop is to demonstrate how machine learning can be applied to agricultural data to estimate crop yield and support data-driven agricultural planning. The system provides a practical framework for transforming structured agricultural data into useful predictive insights. The project also demonstrates the importance of data preprocessing, feature selection, model comparison, and appropriate evaluation metrics in developing a reliable machine learning solution.

Keywords: Crop Yield Prediction, Machine Learning, Random Forest, XGBoost, Support Vector Regression, Smart Agriculture

1. Introduction

1.1 Purpose of the Project

Agriculture is strongly influenced by several environmental and agricultural factors such as soil characteristics, rainfall, temperature, humidity, crop type, and farming practices. Variations in these factors can directly affect crop growth and final yield. Traditionally, crop yield estimation has often depended on historical records, farmer experience, manual observations, and statistical methods. Although these approaches can provide useful information, they may not effectively capture complex relationships between multiple agricultural and environmental variables.

Machine learning provides an approach for analysing large amounts of structured agricultural data and identifying relationships between input variables and crop yield. SmartCrop applies machine learning algorithms to crop-related data to estimate expected yield. The system is intended to assist farmers and agricultural stakeholders by providing data-driven yield estimates that can support crop planning, resource management, and productivity-related decisions.

The project focuses on comparing multiple machine learning regression algorithms rather than depending on a single model. Random Forest, XGBoost, and Support Vector Regression are used because they can model

relationships between multiple input variables and a continuous crop-yield target. The predictions generated by these models are evaluated using standard regression metrics to understand their performance on the selected dataset.

1.2 Problem Statement

Crop yield depends on several interacting factors including soil properties, weather conditions, rainfall, temperature, humidity, crop characteristics, and historical agricultural information. Estimating yield manually or using simple relationships may not adequately represent these interactions. Therefore, the problem addressed by SmartCrop is to develop a machine learning-based regression system that uses relevant agricultural and environmental features to predict crop yield and compare different machine learning models using appropriate evaluation metrics.

1.3 Existing Methods and Disadvantages

Traditional crop yield estimation methods commonly use historical production records, statistical relationships, expert knowledge, and manually observed agricultural conditions. These approaches can be useful when sufficient historical information is available, but they may have difficulty representing nonlinear relationships between several environmental and agricultural variables. Changes in weather and soil conditions can also make direct estimation more difficult.

Machine learning approaches have been increasingly used for crop yield prediction because they can learn relationships from historical datasets. However, machine learning models can also face challenges such as noisy data, missing values, irrelevant features, overfitting, and differences between training and unseen data. The choice of algorithm and preprocessing strategy can significantly influence prediction performance. Therefore, comparing multiple models using suitable evaluation metrics is important.

Recent reviews of crop-yield prediction research report frequent use of Random Forest, Support Vector Machine/Regression, XGBoost and deep-learning approaches. They also highlight the importance of environmental and agricultural variables and appropriate preprocessing.

1.4 Proposed System

SmartCrop proposes a machine learning pipeline for crop yield prediction using the Smart Crop Yield Predication Dataset obtained from Kaggle. The system begins with dataset inspection and preprocessing, followed by preparation of relevant agricultural and environmental features. The processed dataset is then used to train three regression models: Random Forest, XGBoost, and Support Vector Regression. The trained models generate crop-yield predictions, which are evaluated using MAE, RMSE, and R^2. The model results are compared to understand the relative performance of the selected algorithms for the given dataset. The overall objective is to provide a structured and data-driven approach for crop yield estimation.

1.5 Research Objectives

1. To perform data inspection, preprocessing, and exploratory data analysis.
2. To identify and prepare relevant agricultural and environmental features for prediction.
3. To develop suitable machine learning regression models for crop yield prediction.
4. To train and evaluate Random Forest, XGBoost, and Support Vector Regression models.
5. To compare the performance of the models using Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), and R^2 metrics.
6. To analyse the prediction performance of the developed models and identify the most suitable model for the given dataset.
7. To demonstrate the application of machine learning for data-driven agricultural planning and crop yield estimation.

2. Literature Survey (recent studies from 2-3 years)

Review ten recent and directly relevant studies. Verify bibliographic details, DOI, volume, issue, pages/article number, and year before final submission.


S.No.	Title	Reference with DOI	Problem or gap addressed	Objective of the Research	Focus of the paper (Methods used)	Inference	Recommendations for future research
1	Crop Yield Prediction in Agriculture: A Comprehensive Review of Machine Learning and Deep Learning Approaches, with Insights for Future Research and Sustainability	Md. Abu Jabed and Masrah Azrifah Azmi Murad, Heliyon, 2024, Volume 10, Issue 24, Article e40836. DOI: 10.1016/j.heliyon.2024.e40836.	Crop yield is influenced by geographical, climatic, soil, and crop-related factors, making accurate prediction challenging.	To review the use of machine learning and deep learning techniques for crop yield prediction.	Random Forest, Support Vector Machine, Artificial Neural Networks, CNN, LSTM, DNN, and hybrid approaches.	Machine learning and deep learning can support crop yield estimation when suitable agricultural and environmental data are available.	Future work can investigate better feature selection, multimodal data, explainable AI, and robust models for different agricultural environments.
2	Crop Yield Prediction Using Machine Learning: An Extensive and Systematic Literature Review	Agricultural Technology-related systematic review, 2024. DOI: 10.1016/j.atech.2024.100718.	Crop yield prediction studies use different datasets, features, algorithms, and evaluation strategies,	To systematically review machine learning methods used for crop yield prediction.	The review covers Random Forest, Gradient Boosting, Support Vector Machine, Linear Regression, deep learning, and hybrid	Random Forest is frequently used, while recent research increasingly investigates ensemble and deep-learning methods.	Future research can focus on multimodal data, robust validation, feature selection, and improved generalization.

			making comparison difficult.		approaches.		
3	Multi-source Information Fusion-driven Corn Yield Prediction Using the Random Forest from the Perspective of Agricultural and Forestry Economic Management	X. Yang, Z. Hua, L. Li et al., Scientific Reports, 2024, Volume 14, Article 4052. DOI: 10.1038/s41598-024-54354-9.	Corn yield is affected by multiple agricultural and environmental factors, requiring models capable of combining different information sources.	To develop a corn-yield prediction approach using multi-source information and Random Forest.	Multi-source information fusion and Random Forest.	Combining multiple information sources with machine learning can be used for crop-yield prediction	Further work can investigate additional agricultural variables and improved modelling techniques.
4	Machine Learning Based Recommendation of Agricultural and Horticultural Crop Farming in India Under the Regime of NPK, Soil pH and Three Climatic Variables	Heliyon, 2024. DOI: 10.1016/j.heliyon.2024.e25112.	Selecting suitable crops requires considering soil nutrients and climatic conditions simultaneously.	To evaluate machine learning models using NPK, soil pH, temperature, rainfall, and humidity.	Support Vector Machine, XGBoost, Random Forest, KNN, and Decision Tree.	Machine learning can use soil and climatic variables to support agricultural crop recommendations.	Future systems can be developed into user-friendly agricultural decision-support applications.
5	Combining Production Ecology Principles with Random Forest to Model Potato Yield in China	Field Crops Research, Volume 319, 2024, Article 109619. DOI: 10.1016/j.fcr.2024.109619.	Yield modelling can be affected by extrapolation, measurement errors, and incomplete predictive information.	To combine production ecology knowledge with Random Forest for potato-yield modelling.	Random Forest and production ecology principles.	Soil and production-related information can provide important information for yield modelling.	Future work should investigate uncertainty and model performance beyond the training data range.
6	A Comparison of Random Forest Based Models for Agricultural Crop Yield Prediction	Manoj Varma, Praveen Kumar A., Kaushal Kumar Yadav, Satyam Verma, Prabhat Kumar and Ankit Kumar Singh, International Journal of Research in Agronomy, 2024, Volume 7, Issue 8S, pages 817–820. DOI: 10.33545/2618060X.2024.v7.i8Sk.1386.	[Gap] Different Random Forest-based strategies can produce different crop-yield prediction performance.	To compare Random Forest regression and Random Forest-based feature selection approaches.	Random Forest regression, Random Forest feature selection, and multiple linear regression.	Random Forest regression showed strong forecasting performance across the datasets studied inference	Future research can evaluate additional datasets, features, and machine learning algorithms.
7	From Data to Decisions: Crop Yield Prediction Through Tuned XGBoost and Explainable AI	IEEE, 2025 International Conference on Quantum Photonics, Artificial Intelligence, and Networking. DOI: 10.1109/QPAIN66474.2025.11172270.	Crop yield models can face issues related to feature selection, outliers, overfitting, and interpretability.	To develop a tuned XGBoost model combined with explainable AI techniques.	XGBoost and explainable AI techniques.	XGBoost can be used to model crop yield while explainability techniques can provide additional insight into model predictions.	Future work can investigate additional datasets, feature engineering, and explainable machine learning techniques.
8	Predicting Crop Yield Using XGBoost and Geospatial Data Fusion in	IEEE, 2025 International Conference on Recent Innovation in Science Engineering and Technology. DOI: 10.1109/ICRISET64803.2025.11252415.	Traditional methods may not capture complex soil, climate, and spatial	To develop an XGBoost-based crop yield prediction	XGBoost, meteorological data, soil information, and satellite/geospat	Combining multiple information sources with XGBoost can support crop-	Further validation across crops and geographical regions can improve

	Precision Agriculture		relationships.	model.	ial information.	yield prediction.	generalization
9	Machine Learning-Based Winter Wheat Yield Prediction Using Multisource Data	Agricultural Water Management, Volume 322, 2025, Article 109951. DOI: 10.1016/j.agwat.2025.109951.	Many crop-yield prediction approaches rely heavily on vegetation indices and meteorological information while other useful variables may be overlooked.	To predict winter wheat yield using multisource agricultural information.	Feature selection and machine learning models including XGBoost, Linear Regression, and Random Forest.	The study reported that XGBoost performed better than Linear Regression and Random Forest for the studied dataset, while feature selection improved performance in most cases.	Future work can investigate additional environmental variables and validate models across different regions.
10	Critical Evaluation of the Effects of a Cross-Validation Strategy and Machine Learning Optimization on the Prediction Accuracy and Transferability of a Soybean Yield Prediction Model Using UAV-Based Remote Sensing	Journal of Agriculture and Food Research, 2024. DOI: 10.1016/j.jafr.2024.101096.	Random validation strategies may not accurately represent how a yield model performs when applied outside its original spatial domain.	To evaluate machine learning validation and optimization strategies for soybean yield prediction.	Random Forest, XGBoost, LASSO regression, and stacked ensemble learning.	Spatial and leave-one-field-out validation can provide more realistic information about model transferability than conventional random cross-validation in spatial agricultural applications.	Future studies can investigate spatially aware validation and model transferability using larger agricultural datasets.

3. Methodology

3.1 Proposed System Flow Diagram



The proposed workflow begins with the Smart Crop Yield Predication Dataset. The data is inspected and prepared before being supplied to the machine learning algorithms. After preprocessing, the dataset is divided into training and testing data. Random Forest, XGBoost, and Support Vector Regression models are trained using the prepared features. The resulting predictions are evaluated using regression metrics and compared to identify the model that performs most suitably on the dataset.

3.2 Dataset Description

The dataset used in SmartCrop is the Smart Crop Yield Predication Dataset available through Kaggle. The dataset contains approximately 10,000 synthetic tabular records representing agricultural and environmental conditions. The dataset includes information related to crop type, soil characteristics, weather conditions, crop-management variables, and crop yield. Variables reported for the dataset include crop type, soil type, soil pH, rainfall, temperature, humidity, fertilizer usage, pesticide usage, irrigation method, previous crop history, and crop yield measured in tons per hectare. The crop yield value is used as the target variable for the regression task.

Dataset Source:
Kaggle – Smart Crop Yield Predication Dataset

Dataset URL:
https://www.kaggle.com/datasets/miadul/smart-crop-yield-predication-dataset

Dataset Type:
Synthetic tabular agricultural dataset

Approximate Number of Records:
10,000

Target Variable:
Crop Yield / Yield in tons per hectare

Major Feature Categories:

1. Crop-related information
2. Soil-related information
3. Weather and environmental information
4. Farm-management information
5. Historical crop information

3.3 Experimental Setup

The SmartCrop project can be implemented using Python and commonly used machine learning and data-analysis libraries.

Software Environment:
Programming Language: Python
Development Environment: Jupyter Notebook / Google Colab / VS Code
Operating System: Windows / Linux
Dataset Source: Kaggle

Major Libraries:
Pandas – dataset loading and manipulation
NumPy – numerical computation
Matplotlib – data visualization
Seaborn – exploratory data visualization

Scikit-learn – preprocessing, model development, and evaluation
XGBoost – XGBoost regression model

Hardware requirements include a standard computer or laptop capable of running Python-based data analysis and machine learning programs. The project does not require specialized hardware because the selected algorithms operate on structured tabular data.

3.4 Data Preprocessing

Data preprocessing is an important stage of the SmartCrop machine learning pipeline. The dataset is first inspected to understand its structure, feature types, missing values, and target variable.

The preprocessing process includes:

1. Data Inspection

The dataset is loaded and inspected to identify the number of records, columns, feature types, and target variable.

2. Missing-Value Analysis

The dataset is checked for missing or incomplete values. Appropriate handling is performed before model training.

3. Duplicate Analysis

Duplicate records are checked to prevent repeated observations from affecting model learning.

4. Categorical Feature Preparation

Categorical features such as crop type, soil type, irrigation method, or previous crop information are converted into a machine-readable numerical representation when required.

5. Numerical Feature Preparation

Numerical agricultural and environmental variables are checked for suitable ranges and consistency.

6. Outlier Analysis

Numerical variables can be examined for unusual values. Outlier treatment is applied only when justified by the characteristics of the dataset.

7. Feature and Target Separation

Input features are separated from the crop-yield target variable.

8. Train-Test Split

The processed data is divided into training and testing subsets so that model performance can be evaluated on previously unseen data.

9. Data Leakage Prevention

Preprocessing operations that learn information from the data should be fitted using the training data and then applied to the test data. This prevents information from the test set from influencing the model-training process.

3.5 Exploratory Data Analysis

Exploratory Data Analysis is performed to understand the distribution and relationships between the agricultural features and crop yield.

The analysis can include:

1. Distribution plots for numerical variables.
2. Frequency analysis of categorical variables.
3. Correlation analysis between numerical features.
4. Scatter plots between important features and crop yield.
5. Box plots for detecting possible outliers.
6. Crop-wise yield comparison.
7. Soil-related feature analysis.
8. Weather and rainfall relationship analysis.

3.6 Feature Engineering and Feature Selection (if applicable)

Feature engineering involves preparing the available variables so that machine learning algorithms can use them effectively. Agricultural and environmental features such as soil pH, rainfall, temperature, humidity, fertilizer usage, pesticide usage, irrigation information, crop type, and historical crop information can contribute to yield prediction.

Feature selection is useful for reducing irrelevant information and improving model efficiency. Correlation analysis and model-based feature importance can be used to understand the contribution of different features. Only information available before the target yield is known should be used as an input feature to avoid data leakage.

3.7 Model Building and Training

SmartCrop uses three machine learning regression algorithms: Random Forest, XGBoost, and Support Vector Regression.

3.7.1 Random Forest

Random Forest is an ensemble machine learning algorithm that combines multiple decision trees. Each tree produces a prediction and the results are combined to generate the final regression prediction. Random Forest can capture nonlinear relationships between agricultural variables and crop yield and is relatively robust to variations in tabular data.

3.7.2 XGBoost

XGBoost stands for Extreme Gradient Boosting. It is a boosting-based machine learning algorithm that builds a sequence of decision trees. Each new tree attempts to improve the errors made by previous trees. XGBoost is effective for structured tabular datasets and can model complex relationships between agricultural features and crop yield.

3.7.3 Support Vector Regression

Support Vector Regression, or SVR, is the regression version of Support Vector Machine. Instead of directly fitting every observation, SVR attempts to find a function that predicts values within an acceptable margin of error. SVR can model nonlinear relationships using suitable kernels and is useful for comparing a kernel-based regression approach with tree-based models.

The three models are trained using the same prepared dataset so that their performance can be compared fairly.

3.8 Hyperparameter Tuning(if applicable)

Hyperparameter tuning can be used to identify suitable model configurations. Important parameters may include the number of trees and tree depth for Random Forest, learning rate and number of estimators for XGBoost, and kernel, regularization parameter, and epsilon for SVR.

A systematic search method such as Grid Search or Randomized Search can be used together with cross-validation when implemented in the project. The selected parameters should be determined using only the training data to avoid test-data leakage

3.9 Model Evaluation

Since SmartCrop is a regression problem, regression evaluation metrics are used.

Mean Absolute Error (MAE):

MAE measures the average absolute difference between the actual and predicted crop-yield values.

$MAE = (1/n) \Sigma |y_i - \hat{y}_i|$

A lower MAE indicates smaller average prediction errors.

Root Mean Squared Error (RMSE):

RMSE measures the square root of the average squared prediction error.

$RMSE = \sqrt{[(1/n) \Sigma(y_i - \hat{y}_i)^2]}$

A lower RMSE indicates better prediction performance and gives greater weight to larger errors.

Coefficient of Determination (R^2):

R^2 measures how much of the variation in the target variable is explained by the model.

$R^2 = 1 - [\Sigma(y_i - \hat{y}_i)^2 / \Sigma(y_i - \bar{y})^2]$

A higher R^2 indicates that the model explains a larger proportion of the variation in crop yield.

4. Results and Discussion

4.1 Preprocessing Results

After preprocessing, the dataset was prepared for machine learning model development. The data was inspected for missing values, duplicate observations, feature types, and inconsistent entries. Categorical variables were prepared for machine learning, while numerical variables were retained in suitable numerical form.

The final dataset used for modelling consisted of the selected input features and the crop-yield target variable. The processed data was divided into training and testing subsets before model training.

Number of records before preprocessing: 10,000

Number of records after preprocessing: 10,000

Number of input features: 11

Number of target variables: 1

Training records: 7,000

Testing records: 3,000

4.2 Model Performance

Model	MAE	RMSE	R^2
Random Forest	4.28	5.32	0.9805
XGBoost	4.61	5.79	0.9759
Support Vector Regression	5.97	7.58	0.9604

4.3 Visual Results and discussion

The performance of the developed machine learning models was analysed using visualizations such as actual-versus-predicted plots, residual plots, and model comparison graphs. These visualizations help to understand the prediction accuracy and error patterns of the developed models.

The actual-versus-predicted plot shows the relationship between the actual crop yield values and the values predicted by the models. Predictions closer to the actual values indicate better model performance.

The residual plot shows the difference between the actual and predicted crop yield values. Smaller and more randomly distributed residuals indicate lower prediction error.

A model comparison graph can be used to compare Random Forest, XGBoost, and Support Vector Regression based on MAE, RMSE, and R^2. The model performance values are compared to understand the differences in prediction accuracy among the three models.

The results show that all three models are able to predict crop yield, with differences in their prediction errors and R^2 scores. These results demonstrate the applicability of machine learning techniques for crop yield prediction using agricultural and environmental data.

5. Conclusion

The SmartCrop system was developed as a machine learning-based system for predicting crop yield using agricultural, environmental, weather, and historical crop data. The dataset was inspected and preprocessed to prepare the required features for machine learning model development.Three machine learning models, namely Random Forest, XGBoost, and Support Vector Regression, were developed and evaluated using Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), and R^2 score. The models were compared based on their prediction performance and error values.The results demonstrate that machine learning techniques can be effectively applied to crop yield prediction. The developed SmartCrop system can support data-driven crop planning, resource management, and agricultural decision-making by providing crop yield estimates from relevant agricultural and environmental factors.

6. Future Work

- Use larger and more diverse agricultural datasets to improve the reliability of crop yield prediction.
- Evaluate additional machine learning algorithms and ensemble methods.
- Perform deeper hyperparameter optimization to improve model performance.
- Investigate explainable AI techniques to understand the factors influencing crop yield predictions.
- Validate the developed models using external agricultural datasets.
- Develop a deployable real-time or cloud-based crop yield prediction application.
- Incorporate real-time weather, soil, and environmental data for more accurate predictions.
- Continuously update the model using new agricultural data to improve its prediction capability.

7. References

[1] Van Klompenburg, T., Kassahun, A., & Catal, C. (2020). Crop yield prediction using machine learning: A systematic literature review. Computers and Electronics in Agriculture, 177, 105709. https://doi.org/10.1016/j.compag.2020.105709.

[2] Oikonomidis, A., Catal, C., & Kassahun, A. (2023). Deep learning for crop yield prediction: A systematic literature review. New Zealand Journal of Crop and Horticultural Science, 51(1), 1–26. https://doi.org/10.1080/01140671.2022.2032213.

[3] Jhajharia, K., Mathur, P., Jain, S., & Nijhawan, S. (2023). Crop yield prediction using machine learning and deep learning techniques. Procedia Computer Science, 218, 406–417. https://doi.org/10.1016/j.procs.2023.01.023.

[4] Morales, A., & Villalobos, F. J. (2023). Using machine learning for crop yield prediction in the past or the future. Frontiers in Plant Science, 14, 1128388. https://doi.org/10.3389/fpls.2023.1128388.

[5] Li, Q. C., Xu, S. W., Zhuang, J. Y., Liu, J. J., Zhou, Y., & Zhang, Z. X. (2023). Ensemble learning prediction of soybean yields in China based on meteorological data. Journal of Integrative Agriculture, 22(6), 1909–1927. https://doi.org/10.1016/j.jia.2023.02.011.

[6] Torgbor, B. A., Rahman, M. M., Brinkhoff, J., Sinha, P., & Robson, A. (2023). Integrating remote sensing and weather variables for mango yield prediction using a machine learning approach. Remote Sensing, 15(12), 3075. https://doi.org/10.3390/rs15123075.

[7] Dhaliwal, D. S., & Williams, M. M. (2024). Sweet corn yield prediction using machine learning models and field-level data. Precision Agriculture, 25(1), 51–64. https://doi.org/10.1007/s11119-023-10057-1.

[8] Clarke, A., Yates, D., Blanchard, C., Islam, M. Z., Ford, R., Rehman, S., & Walsh, R. (2024). The effect of dataset construction and data pre-processing on the eXtreme Gradient Boosting algorithm applied to head rice yield prediction in Australia. Computers and Electronics in Agriculture, 219, 108716. https://doi.org/10.1016/j.compag.2024.108716.

[9] Zare, H., Weber, T. K. D., Ingwersen, J., et al. (2024). Within-season crop yield prediction by a multi-model ensemble with integrated data assimilation. Field Crops Research, 308, 109293. https://doi.org/10.1016/j.fcr.2024.109293.

[10] Jabed, M. A., & Murad, M. A. A. (2024). Crop yield prediction in agriculture: A comprehensive review of machine learning and deep learning approaches, with insights for future research and sustainability. Heliyon, 10(24), e40836. https://doi.org/10.1016/j.heliyon.2024.e40836.

[11] Miadul. (2023). Smart Crop Yield Predication Dataset. Kaggle.

Signature of the Guide Course Instructor