

1.Pipes.c



```
GNU nano 8.7.1 pipes.c
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <string.h>

int main()
{
    int fd[2];
    pid_t pid;
    char message[] = "Hello from Parent";
    char buffer[100];

    pipe(fd);

    pid = fork();

    if (pid == 0)
    {
        // Child
        close(fd[1]);

        read(fd[0], buffer, sizeof(buffer));

        printf("Child received: %s\n", buffer);

        close(fd[0]);
    }
    else
    {
        // Parent
        close(fd[0]);

        write(fd[1], message, strlen(message) + 1);

        close(fd[1]);

        wait(NULL);
    }

    return 0;
}
```

OUTPUT SCREENSHOT:



```
sabiya@LAPTOP-DOV34MDC: ~$ nano pipes.c
sabiya@LAPTOP-DOV34MDC: ~$ gcc pipes.c -o shell
sabiya@LAPTOP-DOV34MDC: ~$ ./shell
Child received: Hello from Parent
sabiya@LAPTOP-DOV34MDC: ~$
```

2.Signals.c



```
GNU nano 8.7.1 signals.c
#include <stdio.h>
#include <stdlib.h>
#include <signal.h>

void myhandler(int signo)
{
    printf("\nSignal Received\n");
    printf("Signal Number = %d\n", signo);
    exit(1);
}

int main()
{
    signal(SIGSEGV, myhandler);

    int x = 0;

    printf("Enter the number : ");
    scanf("%d", &x);

    printf("The entered number is %d\n", x);

}
```

OUTPUT SCREENSHOT:



```
sabiya@LAPTOP-DOV34MDC:~$ nano signals.c
sabiya@LAPTOP-DOV34MDC:~$ nano signals.c
sabiya@LAPTOP-DOV34MDC:~$ gcc signals.c -o shell
sabiya@LAPTOP-DOV34MDC:~$ ./shell
Enter the number : 3
The entered number is 3
sabiya@LAPTOP-DOV34MDC:~$ |
```