CSS Combinators

CSS Task

Introduction

CSS combinators help us select HTML elements by looking at how they are connected to other elements. There are four main types of combinators.

1. Descendant Selector (space)

It selects all matching elements inside another element. They can be directly inside it or nested deeper.

```
Example:  div p { color: red; }
```

This makes all paragraphs inside a div red.

2. Child Selector (>)

It selects only the elements that are direct children of another element.

```
Example:  div > p { color: blue; }
```

This makes only the paragraphs directly inside a div blue.

3. Adjacent Sibling Selector (+)

It selects the first matching element immediately after another element. Both elements have the same parent.

```
Example:  h2 + p { color: green; }
```

This makes the paragraph just after an h2 heading green.

4. General Sibling Selector (~)

It selects all matching sibling elements that come after another element. Both elements have the same parent.

```
Example:  h2 ~ p { color: orange; }
```

This makes all paragraphs after an h2 heading orange, as long as they have the same parent.

Short Difference

Selector	Use
Descendant (space)	All matching elements inside
Child (>)	Direct children only
Adjacent (+)	The next matching sibling
General (~)	All matching siblings after it

Conclusion

CSS combinators are useful because they help us select elements easily. Each combinator works in a different way, depending on the relationship between HTML elements.