Chapter 1. Introduction

This software project is developed to automate the functionalities of a Big Bazaar Management System.The purpose of the software project is to develop the Management Information System (MIS) to automate the record keeping of customer entry, order entry and item entry with a view to enhance the decision making of the functionaries.

A MIS mainly consists of a computerized database, a collection of inter-related tables for a particular subject or purpose, capable to produce different reports relevant to the user. An application program is tied with the database for easy access and interface to the database. Using Application program or front-end, we can store, retrieve and manage all information in proper way.

This software, being simple in design and working, does not require much of training to users, and can be used as a powerful tool for automating a Big Bazaar Management System.

During coding and design of the software Project, Java NetBeans IDE, a powerful front-end tool is used for getting Graphical User Interface (GUI) based integrated platform and coding simplicity. As a back-end a powerful, open source RDBMS, MySQL is used as per requirement of the CBSE curriculum of Informatics Practices Course.

Chapter 2. Objective & Scope of the Project

The objective of the software project is to develop a computerized MIS to automate thefunctions of a Big Bazaar. This software project is also aimed to enhance the current record keeping system, which will help managers to retrieve the up-to-date information at right time in right shape.

The proposed software system is expected to do the following functionality-

To provide a user friendly, Graphical User Interface (GUI) based integrated and centralized environment for MIS activities.

The proposed system should maintain all the records and transactions, and should generate the required reports and information when required.

To provide graphical and user-friendly interface to interact with a centralized database based on client-server architecture.

To identify the critical operation procedure and possibilities of simplification using modern IT tools and practices.

In its current scope, the software enables user to retrieve and update the information from centralized database designed with MySQL . This software does not require much training time of the users due to limited functionality and simplicity.

During the development of Big Bazaar Management System project, Java NetBeans IDE, a powerful, open source event-driven form-based development environment is used for modular design and future expandability of the system.

Despite of the best effort of the developer, the following limitations and functional boundaries are visible, which limits the scope of this application software.

1. This software can store records and produce reports in pre-designed format in soft copy. There is no facility yet to produce customized reports. Only specified reports are covered.
2. There is no provision to calculate fine or penalty etc. for defaulter members; however it can be developed easily with the help of adding modules.
3. Some application area like deleting the record.

So far as future scope of the project is concerned, firstly it is open to any modular expansion i.e. other modules or functions can be designed and embedded to handle the user need in future. Any part of the software and reports can be modified independently without much effort.

Chapter 3. **Problem** Definition & Analysis

The hardest part of building a software system is deciding precisely what to build. No other part of the conceptual work is so difficult as establishing the detailed technical requirement. Defining and applying good, complete requirements are hard to work, and success in this endeavor has eluded many of us. Yet, we continue to make progress.

Problem definition describes the What of a system, not How . The quality of a software product is only as good as the process that creates it. Problem definition is one of the most crucial steps in this creation process. Without defining a problem, developers do not know what to build, customers do not know what to expect, and there is no way to validate that the built system satisfies the requirement.

Problem definition and Analysis is the activity that encompasses learning about the problem to be solved, understanding the needs of customer and users, trying to find out who the user really is, and understanding all the constraints on the solution. It includes all activities related to the following:

Identification and documentation of customer's or user's needs.

Creation of a document that describes the external behavior and the association constraints that will satisfies those needs.

Analysis and validation of the requirements documents to ensure consistency, completeness, and feasibility

Evolution of needs.

After the analysis of the functioning of a Public Library system, the proposed System is expected to do the following: -

To provide a user friendly, Graphical User Interface (GUI) based integrated and centralized environment for computerized Public Library System.

The proposed system should maintain all the records and transactions, and should generate the required reports and information when required.

To provide efficient and secured Information storage, flow and retrieval system, ensuring the integrity and validity of records.

To provide graphical and user-friendly interface to interact with a centralized database based on client-server architecture.

To identify the critical operation procedure and possibilities of simplification using modern IT tools and practices.

Chapter 4. System Implementation

The Hardware used:

While developing the system, the used hardware are:

Intel core i3 processor with 2.4 GHz.

4 GB of RAM.

AMD Radeon Graphics with 1 GB.

The Softwares used:

Microsoft Windows® 8

Java NetBeans 8.1 as Front-end Development environment.

MySQL as Back-end Sever with Database for Testing.

MS-Word 2010 for documentation.

SOURCE CODE

```
import java.applet.Applet;

import java.awt.*;

import java.awt.event.*;


/*

<applet code="Yash.class" width="900" height="700">

</applet>

*/

public class Yash extends Applet implements ActionListener

{

Button b1,b2;

TextField t1,t2,t3,t4,t5,t6,t7,t8,t9,t10,t11,t12,t13,t14,t15,t16,t17,t18,t19,tt1,tt2,tt3;

Font f,f1;

Label a,l1,l2,l3,l4,l5,l6,l7,l8,a1,a2,a3,a4,sr1,sr2,sr3,sr4,sr5,i1,i2,i3,i4,i5,tt4;

public void paint(Graphics g)

{

//g.drawString("Discounted  :- ",500,590);

g.drawString("Total Prize",110,570);

g.drawString("Discount(10%)",110,610);

setBackground(Color.cyan);

g.drawRect(20,20,850,650);

g.drawRoundRect(380,50,140,40,10,10);

}

public void init()
```

```
{
t1=new TextField(12);
t2=new TextField(12);
t3=new TextField(12);
t4=new TextField(12);
t5=new TextField(12);//
t6=new TextField(12);
t7=new TextField(12);
t8=new TextField(12);
t9=new TextField(12);
t10=new TextField(12);//
t11=new TextField(12);
t12=new TextField(12);
t13=new TextField(12);
t14=new TextField(12);
t15=new TextField(12);
t16=new TextField(12);
t17=new TextField(12);
t18=new TextField(12);
t19=new TextField(12);
tt1=new TextField(12);
tt2=new TextField(12);
tt3=new TextField(12);
f=new Font("Times new Roman",Font.BOLD,18);
f1=new Font("Times new Roman",Font.BOLD,13);
setLayout(null);
b1=new Button("Calculate");
```

```
b2=new Button("Reset");
a=new Label("YT Mall");
l1=new Label("Sr.No");
l2=new Label("Name of Item");
l3=new Label("Price/Item");
l4=new Label("Quantity");
l5=new Label("Price");
a1=new Label("Name of Custmor");
a2=new Label("Mobile No.");
a3=new Label("Address");
a4=new Label("City");
tt4=new Label("Discounted Bill:-");
sr1=new Label("1");
sr2=new Label("2");
sr3=new Label("3");
sr4=new Label("4");
sr5=new Label("5");

i1=new Label("T-Shirt");
i2=new Label("Shirt");
i3=new Label("Shrugs");
i4=new Label("jeans");
i5=new Label("Tops");
tt4.setBounds(470,575,100,20);
//l3.setBounds(350,240,80,20);
t5.setBounds(350,280,80,20);
t6.setBounds(350,330,80,20);
```

```
t7.setBounds(350,380,80,20);
t8.setBounds(350,430,80,20);
t9.setBounds(350,485,80,20);
t10.setBounds(500,280,80,20);
t11.setBounds(500,330,80,20);
t12.setBounds(500,380,80,20);
t13.setBounds(500,430,80,20);
t14.setBounds(500,485,80,20);
t15.setBounds(650,280,80,20);
t16.setBounds(650,330,80,20);
t17.setBounds(650,380,80,20);
t18.setBounds(650,430,80,20);
t19.setBounds(650,485,80,20);

i1.setBounds(150,280,70,20);
i2.setBounds(150,330,70,20);
i3.setBounds(150,380,70,20);
i4.setBounds(150,430,70,20);
i5.setBounds(150,485,70,20);

sr1.setBounds(60,280,30,20);
sr2.setBounds(60,330,30,20);
sr3.setBounds(60,380,30,20);
sr4.setBounds(60,430,30,20);
sr5.setBounds(60,485,30,20);
```

```
a1.setBounds(300,100,102,20);
a2.setBounds(300,130,102,20);
a3.setBounds(300,160,102,20);
a4.setBounds(300,190,102,20);
t1.setBounds(420,100,90,20);
t2.setBounds(420,130,90,20);
t3.setBounds(420,160,90,20);
t4.setBounds(420,190,90,20);

l1.setBounds(60,240,60,20);
l2.setBounds(150,240,100,20);
l3.setBounds(350,240,100,20);
l4.setBounds(500,240,100,20);
l5.setBounds(650,240,100,20);
i1.setBackground(Color.cyan);
i2.setBackground(Color.cyan);
i3.setBackground(Color.cyan);
i4.setBackground(Color.cyan);
i5.setBackground(Color.cyan);

sr1.setBackground(Color.cyan);
sr2.setBackground(Color.cyan);
sr3.setBackground(Color.cyan);
sr4.setBackground(Color.cyan);
sr5.setBackground(Color.cyan);
```

```
//BUTTON
b1.setBounds(390,530,70,20);
b2.setBounds(480,530,60,20);
tt1.setBounds(210,555,80,20);
tt2.setBounds(210,595,80,20);
tt3.setBounds(575,575,80,20);
sr1.setFont(f1);
sr2.setFont(f1);
sr3.setFont(f1);
sr4.setFont(f1);
sr5.setFont(f1);
i1.setFont(f1);
i2.setFont(f1);
i3.setFont(f1);
i4.setFont(f1);
i5.setFont(f1);


l1.setBackground(Color.cyan);
l2.setBackground(Color.cyan);
l3.setBackground(Color.cyan);
l4.setBackground(Color.cyan);
l5.setBackground(Color.cyan);

l2.setFont(f1);
```

```
l3.setFont(f1);
l4.setFont(f1);
l5.setFont(f1);
l1.setFont(f1);
tt4.setFont(f1);
a.setFont(f);
a.setBounds(402,60,98,20);
a.setBackground(Color.cyan);
tt4.setBackground(Color.cyan);
a1.setBackground(Color.cyan);
a2.setBackground(Color.cyan);
a3.setBackground(Color.cyan);
a4.setBackground(Color.cyan);
add(a);
add(a1);
add(a2);
add(a3);
add(a4);
add(t1);
add(t2);
add(t3);
add(t4);
add(t5);
add(t6);
add(t7);
add(t8);
add(t9);
```

```
add(t10);
add(t11);
add(t12);
add(t13);
add(t14);
add(t15);
add(t16);
add(t17);
add(t18);
add(t19);

add(tt1);
add(tt2);
add(tt4);
add(b1);
add(b2);
add(tt3);
add(l1);
add(l2);
add(l3);
add(l4);
add(l5);
add(sr1);
add(sr2);
add(sr3);
add(sr4);
add(sr5);
```

```
add(i1);
add(i2);
add(i3);
add(i4);
add(i5);
b1.addActionListener(this);
b2.addActionListener(this);
}
public void actionPerformed(ActionEvent e1)
{
String s=e1.getActionCommand(); //Calculate
if(s.equals("Calculate"));
{
int s1=Integer.parseInt(t5.getText());
int s2=Integer.parseInt(t10.getText());
int s3=s1*s2;
t15.setText(""+s3);

int s4=Integer.parseInt(t6.getText());
int s5=Integer.parseInt(t11.getText());
int s6=s4*s5;
t16.setText(""+s6);

int s7=Integer.parseInt(t7.getText());
int s8=Integer.parseInt(t12.getText());
int s9=s7*s8;
t17.setText(""+s9);
```

```
int w1=Integer.parseInt(t8.getText());
int w2=Integer.parseInt(t13.getText());
int w3=w1*w2;
t18.setText(""+w3);

int w4=Integer.parseInt(t9.getText());
int w5=Integer.parseInt(t14.getText());
int w6=w4*w5;
t19.setText(""+w6);

int w7=s3+s6+s9+w3+w6;
tt1.setText(""+w7);

float w8=0.1f*w7;
tt2.setText(""+w8);

float w9=w7+w8;
tt3.setText(""+w9);
}
if(s.equals("Reset"))
{
t1.setText("");
t2.setText("");
t3.setText("");
t4.setText("");
t5.setText("");
```

```
t6.setText("");
t7.setText("");
t8.setText("");
t9.setText("");
t10.setText("");
t11.setText("");
t12.setText("");
t13.setText("");
t14.setText("");
t15.setText("");
t16.setText("");
t17.setText("");
t18.setText("");
t19.setText("");
tt1.setText("");
tt2.setText("");
tt3.setText("");
}
}
}
```