

3D FACE RECOGNITION: A COMPREHENSIVE SURVEY AND ANALYSIS

SHAILESH KUMAR (224EC6013)

SPECIALIZATION : SIGNAL AND IMAGE PROCESSING

Department of Electronics and Communication Engineering

National Institute of Technology, Rourkela-769008, India



MOTIVATION

- TRADITIONAL 2D FACE RECOGNITION SYSTEMS ARE LIMITED BY CHANGES IN LIGHTING, FACIAL EXPRESSIONS, AND POSE VARIATIONS.
- 3D FACE RECOGNITION OFFERS IMPROVED ROBUSTNESS BY CAPTURING GEOMETRIC AND STRUCTURAL INFORMATION OF THE FACE.
- GROWING DEMANDS FOR SECURE AUTHENTICATION IN MOBILE DEVICES, SURVEILLANCE, AND AR/VR DRIVE INNOVATION IN LIGHTWEIGHT AND REAL-TIME SOLUTIONS.

REFERENCES: [1], [2], [3], [4]

INTRODUCTION

- 3D FACE RECOGNITION ANALYZES DEPTH AND SHAPE TO IDENTIFY INDIVIDUALS, OFFERING HIGHER ACCURACY IN UNCONSTRAINED ENVIRONMENTS.
- TYPICAL 3D DATA FORMATS INCLUDE POINT CLOUDS, MESHES, AND DEPTH MAPS.
- THE INTEGRATION OF 3D SENSORS IN CONSUMER DEVICES (E.G., SMARTPHONES, AR HEADSETS) HAS ACCELERATED THE FEASIBILITY OF REAL-WORLD APPLICATIONS.

REFERENCE: [1]




FIG 1: TAXONOMY OF 3D FACE RECOGNITION METHODS.




FIG. 2 3D FACE DATA REPRESENTATIONS.

PROBLEM FORMULATION

•CHALLENGES:

- DATA QUALITY VARIATION (E.G., LOW-RESOLUTION, SPARSE SCANS)
- OCCLUSIONS AND EXPRESSION-INDUCED DEFORMATIONS
- LACK OF LARGE-SCALE ANNOTATED 3D DATASETS
- HIGH COMPUTATIONAL COSTS

•GOALS:

- DESIGN ACCURATE, COMPACT, AND FAST MODELS
- ENHANCE ROBUSTNESS UNDER REAL-WORLD CONDITIONS

REFERENCES: [1], [3], [4]

SIMULATION RESULTS AND DISCUSSION

❑ CONVENTIONAL APPROACHES

- **LOCAL METHODS:** FEATURE EXTRACTION FROM FACIAL PARTS (E.G., LBP, SIFT, LDP)
 - ✓ ADVANTAGEOUS IN OCCLUDED SCENARIOS
 - ✓ E.G., LDP SCORED 99.3% ON FRGC V2
- **GLOBAL METHODS:** ENTIRE FACE USED FOR RECOGNITION; COMPUTATIONALLY EFFICIENT
- **HYBRID METHODS:** COMBINE LOCAL + GLOBAL FEATURES; BETTER ACCURACY

REFERENCE: [1]

❑ DEEP LEARNING-BASED APPROACHES

- **2D INPUT NETWORKS:** CONVERT 3D DATA TO 2D PROJECTIONS; LEVERAGE CNNs LIKE VGG AND RESNET
 - ✓ E.G., VGG-FACE ACHIEVED 99.2% ON BOSPHORUS
- **3D INPUT NETWORKS:** PROCESS RAW 3D DATA (E.G., POINT CLOUDS)
 - ✓ E.G., POINTNET++ SCORED 99.68% ON BOSPHORUS
- **GRAPH-BASED METHODS:** USE GRAPH CONVOLUTION ON FACIAL GEOMETRY
 - ✓ E.G., FACE-GCN ACHIEVED 88.45% ON BU4DFE
- REFERENCES: [1], [5]




FIG.3: 3D DEEP LEARNING-BASED FACE RECOGNITION

RECENT WORKS

❑ GEOMETRIC DEEP LEARNING WITH MOBILENETV2

- LIGHTWEIGHT ARCHITECTURE FOR EDGE DEVICES
- SUITABLE FOR REAL-TIME APPLICATIONS [2]

❑ MQFNET: MULTI-QUALITY FUSION NETWORK

- FUSES HIGH- AND LOW-QUALITY INPUTS TO IMPROVE ACCURACY UNDER DEGRADED CONDITIONS [3]

❑ LOW-QUALITY POINT CLOUD RECOGNITION

- OPTIMIZED FOR SPARSE, NOISY DATA
- REDUCES MEMORY AND COMPUTATION NEEDS [4]

❑ POINTNET++ WITH GPMM-BASED AUGMENTATION

- USES STATISTICAL SHAPE MODELS FOR BETTER GENERALIZATION [5]

DATASETS & DATA FORMATS

- **POPULAR DATASETS:** FRGC V2, BOSPHORUS, BU3D-FE, TEXAS-3D, LOCK3DFACE
- **DATA TYPES:** POINT CLOUDS, DEPTH MAPS / RANGE IMAGES.
- **3D CAPTURE:** ACHIEVED VIA STRUCTURED LIGHT, STEREO VISION, OR TIME-OF-FLIGHT SENSORS (E.G., INTEL REALSENSE, IPHONE TRUEDEPTH).
- **CONVERSION FROM 2D:** MULTIPLE 2D VIEWS OR SHAPE-FROM-SHADING TECHNIQUES CAN ESTIMATE 3D SHAPE FROM 2D PHOTOS, BUT WITH LESS ACCURACY.

REFERENCE: [1]

OBSERVATIONS AND INSIGHTS

- DEEP LEARNING DOMINATES WITH HIGH ACCURACY AND GENERALIZATION
- HYBRID AND GRAPH-BASED METHODS ARE EMERGING AS PROMISING ALTERNATIVES
- AUGMENTATION (E.G., GPMM, GANS) IMPROVES ROBUSTNESS TO DATA VARIABILITY
- REFERENCES: [1], [5]

OBSERVATIONS AND INSIGHTS

- EXPLORE LIGHTWEIGHT 3D MODELS OPTIMIZED FOR EDGE DEVICES AND MOBILE PLATFORMS.
- INVESTIGATE DATA-EFFICIENT LEARNING STRATEGIES SUCH AS SELF-SUPERVISED AND FEW-SHOT LEARNING FOR 3D FACE RECOGNITION.
- DEVELOP ROBUST 3D DATA AUGMENTATION TECHNIQUES USING GENERATIVE MODELS (E.G., GANS, 3DMMS)..
- STUDY FUSION OF 3D WITH OTHER MODALITIES (E.G., INFRARED, AUDIO) FOR MULTI-MODAL FACE RECOGNITION.
- DESIGN CUSTOM DATASETS REPRESENTING REGIONAL AND DEMOGRAPHIC DIVERSITY TO ENHANCE FAIRNESS AND GENERALIZATION.

REFERENCES: [1]–[5]

CONCLUSION

- 3D FACE RECOGNITION IS ADVANCING RAPIDLY WITH THE HELP OF DEEP LEARNING, ESPECIALLY UNDER REAL-WORLD, LOW-QUALITY, OR MOBILE CONDITIONS.
- FUTURE DIRECTIONS INCLUDE DATASET ENRICHMENT, REAL-TIME MOBILE DEPLOYMENT, AND LIGHTWEIGHT DEEP ARCHITECTURES.
- THIS POSTER FORMS THE FOUNDATION FOR UPCOMING RESEARCH WORK AIMED AT ADDRESSING THE ABOVE OPEN CHALLENGES.

REFERENCES: [1]–[5]

REFERENCES

1. Y. JING, X. LU, AND S. GAO, “3D FACE RECOGNITION: A COMPREHENSIVE SURVEY IN 2022,” *COMPUTATIONAL VISUAL MEDIA*, VOL. 9, NO. 4, PP. 657–685, DEC. 2023. [DOI: 10.1007/S41095-022-0317-1]
2. OLIVETTI, S. CALDERARA, AND R. CUCCHIARA, “GEOMETRIC DEEP LEARNING ON 3D FACE RECOGNITION USING MOBILENETV2,” IN *PROC. INT. CONF. ON PATTERN RECOGNITION (ICPR)*, JAN. 2020, PP. 1235–1242, DOI: 10.1109/ICPR48806.2021.9413170.
3. Y. LIN, B. FANG, AND Z. ZHANG, “MQFNET: MULTI-QUALITY FUSION NETWORK FOR 3D FACE RECOGNITION UNDER LOW-QUALITY CONDITIONS,” *SENSORS*, VOL. 21, NO. 9, PP. 2981–2995, MAY 2021, DOI: 10.3390/S21092981.
4. H. TAN, K. MU, AND Y. FENG, “LIGHTWEIGHT 3D FACE RECOGNITION BASED ON LOW-QUALITY POINT CLOUDS,” IN *IEEE ACCESS*, VOL. 8, PP. 204908–204917, NOV. 2020, DOI: 10.1109/ACCESS.2020.3037404.
5. Y. ZHANG, X. LI, AND H. WANG, “POINTNET++ BASED 3D FACE RECOGNITION WITH GPMM-BASED AUGMENTATION,” IN *PROC. IEEE CONF. ON COMPUTER VISION AND PATTERN RECOGNITION WORKSHOPS (CVPRW)*, JUN. 2021, PP. 145–154, DOI: 10.1109/CVPRW53098.2021.00022.