

TITLE HERE

A Thesis Proposal Presented to
The Faculty of the School of Statistics
univ

In Partial Fulfillment
of the Requirements for the Degree of
Master of Science in Statistics
1st Semester A.Y. 2025-2026

by
Shaine Rosewel Matala

```
knitr::opts_chunk$set(  
  echo = FALSE,  
  message = FALSE,  
  warning = FALSE  
)
```

Abstract

Contents

Abstract	2
1 Background	4
2 Methodology	4
2.1 Parametric bootstrap	4
2.2 Nonrank-based method	6
2.3 Results	7
3 Introduction	12
3.1 Background of the Study	12
3.2 Statement of the Problem	12
3.3 Objective of the Study	12
3.4 Study Hypothesis	12
3.5 Significance of the Study	12
3.6 Scope and Limitation	12
3.7 Definition of Terms	12
References	12
Appendices	12
Codes for algorithm 1	12
Codes for algorithm 2	16
Codes for simulation	22

1 Background

2 Methodology

The parametric bootstrap and nonrank-based method are introduced to calculate joint confidence regions to simultaneously quantify uncertainty. These are compared to current approaches from Klein et al. (2020): independent and Bonferroni.

Let $\theta_1, \theta_2, \dots, \theta_K$ be the true parameter values and $\hat{\theta}_1, \hat{\theta}_2, \dots, \hat{\theta}_K$ be the estimates obtained.

2.1 Parametric bootstrap

Let $\hat{\theta}_1, \hat{\theta}_2, \dots, \hat{\theta}_K$ be independent but not identically distributed estimates. For this study, it is assumed that $\hat{\theta}_k \sim N(\theta_k, \sigma_k^2)$, $k = 1, 2, \dots, K$, where σ_k^2 is known. Denote the corresponding ordered values by $\hat{\theta}_{(1)}, \hat{\theta}_{(2)}, \dots, \hat{\theta}_{(K)}$.

Algorithm 1 Computation of Joint Confidence Region via Parametric Bootstrap

1: **for** $b = 1, 2, \dots, B$ **do**

2: Generate $\hat{\theta}_{bk}^* \sim N(\hat{\theta}_k, \sigma_k^2)$, $i = 1, 2, \dots, K$ and let $\hat{\theta}_{b(1)}, \hat{\theta}_{b(2)}, \dots, \hat{\theta}_{b(K)}$ be the corresponding ordered values

	$k = 1$	$k = 2$	\dots	$k = K$
$b = 1$	$\hat{\theta}_{1(1)}^*$	$\hat{\theta}_{1(2)}^*$	\dots	$\hat{\theta}_{1(K)}^*$
$b = 2$	$\hat{\theta}_{2(1)}^*$	$\hat{\theta}_{2(2)}^*$	\dots	$\hat{\theta}_{2(K)}^*$
\vdots	\vdots	\vdots	\dots	\vdots
$b = B$	$\hat{\theta}_{B(1)}^*$	$\hat{\theta}_{B(2)}^*$	\dots	$\hat{\theta}_{B(K)}^*$

3: Compute

$$\hat{\sigma}_{b(k)}^* = \sqrt{\text{kth ordered value among } \{\hat{\theta}_{b1}^{*2} + \sigma_1^2, \hat{\theta}_{b2}^{*2} + \sigma_2^2, \dots, \hat{\theta}_{bK}^{*2} + \sigma_K^2\} - \hat{\theta}_{(k)}^{*2}}$$

4: Compute $t_b^* = \max_{1 \leq k \leq K} \left| \frac{\hat{\theta}_{b(k)}^* - \hat{\theta}_k^*}{\sigma_{b(k)}^*} \right|$

5: **end for**

6: Compute the $(1 - \alpha)$ -sample quantile of $t_1^*, t_2^*, \dots, t_B^*$, call this \hat{t} .

7: The joint confidence region of $\theta_{(1)}, \theta_{(2)}, \dots, \theta_{(K)}$ is given by

$$\mathfrak{R} = [\hat{\theta}_{(1)} \pm \hat{t} \times \hat{\sigma}_{(1)}] \times [\hat{\theta}_{(2)} \pm \hat{t} \times \hat{\sigma}_{(2)}] \times \dots \times [\hat{\theta}_{(K)} \pm \hat{t} \times \hat{\sigma}_{(K)}]$$

where $\hat{\sigma}_{(k)}$ is computed as

$$\hat{\sigma}_{(k)} = \sqrt{\text{kth ordered value among } \{\hat{\theta}_1^2 + \sigma_1^2, \hat{\theta}_2^2 + \sigma_2^2, \dots, \hat{\theta}_K^2 + \sigma_K^2\} - \hat{\theta}_{(k)}^2}$$

Algorithm 2 is used to calculate the coverage which is defined as the proportion of times that the true parameter values fall within the confidence interval for all K simultaneously. Ideally, this should be equal to 0.90 since $\alpha = 0.1$. It also calculates the average T_1, T_2 , and T_3 . Higher values of T_1 and T_2 indicate wider confidence intervals and are therefore less desirable, whereas higher values of T_3 are preferable.

Algorithm 2 Computation of Coverage Probability for Parametric Bootstrap

For given values of $\theta_1, \theta_2, \dots, \theta_K$ and thus $\theta_{(1)}, \theta_{(2)}, \dots, \theta_{(K)}$

1: **for** replications = 1, 2, \dots , 5000 **do**

2: Generate $\hat{\theta}_k \sim N(\theta_k, \sigma_k^2)$, for $k = 1, 2, \dots, K$

3: Compute the rectangular confidence region \mathfrak{R} using Algorithm 1.

4: Check if $(\theta_{(1)}, \theta_{(2)}, \dots, \theta_{(K)}) \in \mathfrak{R}$ and compute

$$\begin{aligned} T_1 &= \frac{1}{K} \sum_{k=1}^K |\Lambda_{Ok}| \\ T_2 &= \prod_{k=1}^K |\Lambda_{Ok}| \\ T_3 &= 1 - \frac{K + \sum_{k=1}^K |\Lambda_{Ok}|}{K^2} \end{aligned}$$

5: **end for**

6: Compute the proportion of times that the condition in step 4 is satisfied and the average of T_1, T_2 , and T_3 .

2.2 Nonrank-based method

The nonrank-based method assumes that $\hat{\boldsymbol{\theta}} = (\hat{\theta}_1, \hat{\theta}_2, \dots, \hat{\theta}_K) \sim N(\boldsymbol{\theta}, \boldsymbol{\Sigma})$. It accounts for potential correlation among items being ranked. For this case, an exchangeable correlation, $\boldsymbol{\rho}$ (See Equation 2.1.), is assumed and used in the calculation of the variance covariance matrix (See Equation 2.2.).

$$\boldsymbol{\rho} = (1 - \rho) \mathbf{I}_K + \rho \mathbf{1}_K \mathbf{1}_K' \quad (2.1)$$

$$\boldsymbol{\Sigma} = \boldsymbol{\Delta}^{1/2} \boldsymbol{\rho} \boldsymbol{\Delta}^{1/2} \quad (2.2)$$

where $\boldsymbol{\Delta} = \text{diag}\{\sigma_1^2, \sigma_2^2, \dots, \sigma_K^2\}$, with known σ_k 's and ρ is studied for 0.1, 0.5, 0.9.

Algorithm 3 Computation of Joint Confidence Region via Nonrank-based Method

Let the data consist of $\hat{\theta}_1, \dots, \hat{\theta}_K$ and suppose Σ is known

- 1: **for** $b = 1, 2, \dots, B$ **do**
- 2: Generate $\hat{\theta}_b^* \sim N_K(\hat{\theta}, \Sigma)$ and write $\hat{\theta}_b^* = (\hat{\theta}_{b1}^*, \hat{\theta}_{b2}^*, \dots, \hat{\theta}_{bK}^*)'$
- 3: Compute $t_b^* = \max_{1 \leq k \leq K} \left| \frac{\hat{\theta}_{bk}^* - \hat{\theta}_k}{\sigma_k} \right|$
- 4: **end for**
- 5: Compute the $(1 - \alpha)$ -sample quantile of $t_1^*, t_2^*, \dots, t_B^*$, call this \hat{t} .
- 6: The joint confidence region of $\theta_1, \theta_2, \dots, \theta_K$ is given by

$$\mathfrak{R} = \left[\hat{\theta}_1 \pm \hat{t} \times \sigma_1 \right] \times \left[\hat{\theta}_2 \pm \hat{t} \times \sigma_2 \right] \times \dots \times \left[\hat{\theta}_K \pm \hat{t} \times \sigma_K \right]$$

Algorithm 4 is similar to Algorithm 2 but computes for the coverage and average T_1, T_2 , and T_3 for the nonrank-based method.

Algorithm 4 Computation of Coverage Probability for Nonrank-based Method

For given values of $\theta_1, \theta_2, \dots, \theta_K$ and Σ

- 1: **for** replications = 1, 2, \dots , 5000 **do**
 - 2: Generate $\hat{\theta} \sim N_K(\theta, \Sigma)$
 - 3: Compute the rectangular confidence region \mathfrak{R} using Algorithm 3.
 - 4: Check if $(\theta_1, \theta_2, \dots, \theta_K) \in \mathfrak{R}$ and compute T_1, T_2 , and T_3 .
 - 5: **end for**
 - 6: Compute the proportion of times that the condition in step 4 is satisfied and the average of T_1, T_2 , and T_3 .
-

2.3 Results

For the simulation studies, α is fixed at 0.1, while the true standard deviations are varied ($sd = 2.0, 3.6, 6.0$) along with the number of items to be ranked ($K = 5, 10, 20, 30, 40, 51$). Table 1 shows that when the correlation is zero, the nonrank-based, independent, and Bonferroni CI methodology exhibit similar coverage values regardless of K and sd . In contrast, the parametric approach generally yields higher coverage for smaller sd while showing comparable variability across different K . It deviates the most from the nominal

coverage level.

Table 1: Simulation results for coverage probabilities when $\rho = 0$.

K	sd	Coverage			
		Parametric	Nonrank-based	Independent	Bonferroni
5	2.0	0.9198	0.8970	0.9000	0.9042
	3.6	0.8534	0.8970	0.9000	0.9042
	6.0	0.8034	0.8970	0.9000	0.9042
10	2.0	0.8900	0.8962	0.8984	0.9034
	3.6	0.8830	0.8962	0.8984	0.9034
	6.0	0.8212	0.8962	0.8984	0.9034
20	2.0	0.8842	0.9070	0.9096	0.9134
	3.6	0.8952	0.9070	0.9096	0.9134
	6.0	0.8264	0.9070	0.9096	0.9134
30	2.0	0.8786	0.9026	0.9048	0.9088
	3.6	0.8594	0.9026	0.9048	0.9088
	6.0	0.8458	0.9026	0.9048	0.9088
40	2.0	0.8820	0.8958	0.8972	0.9020
	3.6	0.8804	0.8958	0.8972	0.9020
	6.0	0.8474	0.8958	0.8972	0.9020
51	2.0	0.9442	0.9010	0.9008	0.9054
	3.6	0.9128	0.9010	0.9008	0.9054
	6.0	0.9124	0.9010	0.9008	0.9054

The case is different in terms of T_1 (See Table 2.) as it increases with decreasing sd and increasing K . The CIs are wider for the parametric approach compared to the remaining approaches whose T_1 only vary by a small margin, with nonrank-based method having the smallest T_1 and Bonferroni, the largest one. The same behavior is observed for T_2 and T_3 .

As the correlation increases, the coverage of both independent and Bonferroni CIs exceeds the nominal value while that of nonrank-based method remains close to it. This holds regardless of K and sd . See Table 3 for $sd = 2.0$; results for other sd values are omitted, as they are identical to those shown. This suggests that when items being ranked are correlated, the proposed method is preferable, as it maintains coverage close to the nominal level.

sd remains to be the quantity that affects T_1 as it only differs by a small amount with changes in ρ . This is shown in Table 4.

Table 2: Simulation results for average T_1 when $\rho = 0$.

K	sd	T_1			
		Parametric	Nonrank-based	Independent	Bonferroni
5	2.0	2.212960	2.127360	2.128560	2.130800
	3.6	1.983280	1.834720	1.835600	1.842240
	6.0	1.622000	1.462560	1.462560	1.465520
10	2.0	4.002280	3.243800	3.246320	3.259040
	3.6	2.710680	2.307480	2.308680	2.317680
	6.0	1.924080	1.731200	1.733320	1.736840
20	2.0	7.022060	5.333380	5.336680	5.361700
	3.6	4.207100	3.448120	3.451680	3.465240
	6.0	2.787040	2.453000	2.454920	2.462440
30	2.0	11.830987	9.538733	9.547507	9.591387
	3.6	7.653613	5.802093	5.806080	5.833933
	6.0	4.764387	3.778320	3.781573	3.797987
40	2.0	15.153140	12.100160	12.108990	12.160730
	3.6	10.392030	7.201310	7.205910	7.241320
	6.0	6.508180	4.483520	4.485920	4.506070
51	2.0	20.446533	15.607796	15.614745	15.685914
	3.6	13.206918	9.098996	9.103490	9.143977
	6.0	8.598722	5.786298	5.789153	5.814400

Table 3: Simulation results for coverage probabilities when $\rho \neq 0$.

corr	K	Coverage		
		Nonrank-based	Independent	Bonferroni
0.1	5	0.8984	0.9008	0.9046
	10	0.8996	0.9016	0.9060
	20	0.8988	0.9026	0.9082
	30	0.9000	0.9036	0.9088
	40	0.8916	0.8968	0.9012
	51	0.8944	0.8994	0.9048
0.5	5	0.9042	0.9218	0.9260
	10	0.9038	0.9322	0.9346
	20	0.9032	0.9378	0.9408
	30	0.8910	0.9312	0.9338
	40	0.8920	0.9328	0.9358
	51	0.9086	0.9492	0.9516
0.9	5	0.9032	0.9574	0.9586
	10	0.8962	0.9682	0.9690
	20	0.8980	0.9758	0.9766
	30	0.8960	0.9802	0.9806
	40	0.8996	0.9862	0.9870
	51	0.8928	0.9866	0.9868

Table 4: Simulation results for T_1 probabilities when $\rho \neq 0$.

K	sd	T_1								
		Nonrank-based			Independent			Bonferroni		
		$\rho = 0.1$	$\rho = 0.5$	$\rho = 0.9$	$\rho = 0.1$	$\rho = 0.5$	$\rho = 0.9$	$\rho = 0.1$	$\rho = 0.5$	$\rho = 0.9$
5	2.0	2.129280	2.140720	2.114400	2.130640	2.153280	2.170800	2.132640	2.155760	2.172320
	3.6	1.838480	1.830160	1.739120	1.839440	1.863040	1.889040	1.845760	1.869040	1.893840
	6.0	1.455040	1.420000	1.385040	1.456480	1.433200	1.400880	1.459920	1.436640	1.402000
10	2.0	3.254200	3.161880	2.883560	3.262520	3.249120	3.221600	3.274720	3.261680	3.233680
	3.6	2.297600	2.233440	1.980640	2.301520	2.305600	2.314720	2.311040	2.315960	2.327920
	6.0	1.728520	1.704800	1.634280	1.730840	1.733000	1.711920	1.735480	1.737160	1.716400
20	2.0	5.319420	5.109500	4.371980	5.332860	5.335500	5.360780	5.357940	5.359040	5.385320
	3.6	3.441220	3.321680	2.863180	3.448160	3.457860	3.488740	3.462300	3.473300	3.502700
	6.0	2.450240	2.384140	2.172600	2.455120	2.452100	2.441440	2.463000	2.460020	2.448520
30	2.0	9.525240	9.112560	7.639680	9.549013	9.576253	9.623440	9.592120	9.619173	9.664320
	3.6	5.784933	5.512867	4.555827	5.799840	5.813653	5.842280	5.828347	5.842120	5.870320
	6.0	3.770373	3.612987	3.087267	3.779547	3.787573	3.789267	3.795240	3.804000	3.804840
40	2.0	12.087970	11.537040	9.602120	12.123520	12.153500	12.224780	12.175670	12.203740	12.273560
	3.6	7.184540	6.756920	5.430030	7.206670	7.204860	7.226330	7.242580	7.242400	7.265960
	6.0	4.476240	4.256020	3.539500	4.488620	4.491630	4.503040	4.508860	4.511780	4.523070
51	2.0	15.563663	14.706651	11.878298	15.608400	15.641286	15.662024	15.679569	15.712047	15.736000
	3.6	9.071851	8.561145	6.969490	9.096541	9.099663	9.117435	9.138267	9.140047	9.159812
	6.0	5.772494	5.465592	4.432910	5.788596	5.800847	5.826855	5.814674	5.826659	5.853412

3 Introduction

3.1 Background of the Study

3.2 Statement of the Problem

3.3 Objective of the Study

3.4 Study Hypothesis

3.5 Significance of the Study

3.6 Scope and Limitation

3.7 Definition of Terms

THIS IS Rizzo (2008) and Klein et al. (2020)

References

Klein, M., Wright, T., & Wieczorek, J. (2020). *A joint confidence region for an overall ranking of populations.*

Rizzo, M. (2008). *Statistical computing with r.*

Appendices

Codes for algorithm 1

```
get_independent_ci <- function(theta_hat,  
                                S,  
                                alpha){  
  K <- length(theta_hat)  
  gamma = 1-(1-alpha)^(1/K)
```

```

z = qnorm(1-gamma/2)
ci_lower <- theta_hat - z*S
ci_upper <- theta_hat + z*S
return(list(
  ci_lower = ci_lower,
  ci_upper = ci_upper
))
}

```

```

get_bonferroni_ci <- function(theta_hat,
                               S,
                               alpha){
  K <- length(theta_hat)
  z = qnorm(1-(alpha/K)/2)
  ci_lower <- theta_hat - z*S
  ci_upper <- theta_hat + z*S
  return(list(
    ci_lower = ci_lower,
    ci_upper = ci_upper
  ))
}

```

```

get_parametric_ci <- function(B,
                               theta_hat,
                               S,
                               alpha) {
  K <- length(theta_hat)
  # step 1a =====
  thetahat_star <- sapply(seq_len(K), function(i) {

```

```

    rnorm(B, mean = theta_hat[i], sd = S[i])
  })
colnames(thetahat_star) <- paste0("thetahat_star",
                                   sprintf("%02d", 1:K))
sorted_thetahat_star <- t(apply(thetahat_star, 1, sort))
colnames(sorted_thetahat_star) <- paste0("sorted_thetahat_star",
                                           sprintf("%02d", 1:K))

# step 1b =====
variance_vector <- S^2
minuend <- thetahat_star^2 + rep(
  variance_vector, each = nrow(thetahat_star))
sigma_hat_star <- sqrt(
  t(apply(minuend, 1, sort)) - sorted_thetahat_star^2)

# step 1c =====
sorted_theta_hat <- sort(theta_hat)
t_star <- apply(
  abs(
    (
      sorted_thetahat_star - rep(
        sorted_theta_hat,
        each = nrow(sorted_thetahat_star)
      )
    )/sigma_hat_star
  ),
  1,
  max)

# step 2 =====
t_hat <- quantile(t_star, probs = 1 - alpha)

# step 3 =====

```

```

sigma_hat <- sqrt(
  sort(theta_hat^2 + variance_vector) - sorted_theta_hat^2)
# step 6 =====
ci_lower <- sorted_theta_hat - t_hat*sigma_hat
ci_upper <- sorted_theta_hat + t_hat*sigma_hat
return(list(
  ci_lower = ci_lower,
  ci_upper = ci_upper
))
}

```

```

get_nonrankbased_ci <- function(B,
                                theta_hat,
                                alpha,
                                varcovar_matrix) {
  K <- length(theta_hat)
  # step 1a =====
  generate_data <- function(){MASS::mvrnorm(n = 1,
                                             mu = theta_hat,
                                             Sigma = varcovar_matrix)}
  thetahat_star <- t(replicate(B, generate_data()))
  # step 1b =====
  t_star <- apply(thetahat_star,
                 1,
                 function(x) max(abs((x - theta_hat) / sqrt(
                   diag(varcovar_matrix))))))
  # step 2 =====
  t_hat <- quantile(t_star, probs = 1 - alpha)
  # step 3 =====

```

```

ci_lower <- theta_hat - t_hat*sqrt(diag(varcovar_matrix))
ci_upper <- theta_hat + t_hat*sqrt(diag(varcovar_matrix))
return(list(
  ci_lower = ci_lower,
  ci_upper = ci_upper
))
}

```

Codes for algorithm 2

```

source("../R/compute_ci.R")
library("doRNG")

get_ranks <- function(k, tuple_list){
  Lambda_lk <- which(
    tuple_list[,2]<=tuple_list[k,1])
  Lambda_lk <- Lambda_lk[Lambda_lk != k]
  Lambda_Ok <- which(
    tuple_list[,2]>tuple_list[k,1] & tuple_list[k,2] > tuple_list[,1])
  Lambda_Ok <- Lambda_Ok[Lambda_Ok != k]
  ranks <- seq(
    length(unique(Lambda_lk)) + 1,
    length(unique(Lambda_lk)) + length(unique(Lambda_Ok)) + 1,
    1
  )
  return(list(
    ranks = ranks,
    Lambda_Ok = Lambda_Ok
  ))
}

```



```
}
```

```
get_t1 <- function(v) mean(v)
```

```
get_t2 <- function(v) prod(v)^(1/length(v))
```

```
get_t3 <- function(v) {  
  1 - ((length(v)+sum(v))/(length(v)^2))  
}
```

```
get_coverage <- function(ci_lower,  
                          ci_upper,  
                          true_theta) {  
  return(all(ci_lower<=true_theta) & all(true_theta<=ci_upper))  
}
```

```
algo2_nonrankbased <- function(  
  true_theta,  
  K,  
  reps = 5, # step 4  
  B=100,  
  alpha= 0.10,  
  varcovar_matrix){  
  foreach(iter = 1:reps,  
    .combine = rbind,  
    .packages = c("foreach", "arrow", "MASS"),  
    .export = c("get_nonrankbased_ci", "get_independent_ci",  
                "get_bonferroni_ci", "get_ranks", "get_coverage",  
                "get_t1", "get_t2", "get_t3"))
```

```

) %dorning% {

# step 1 =====
theta_hat <- mvnrm(n = 1,
                  mu = true_theta,
                  Sigma = varcovar_matrix)

# step 2 =====
S <- sqrt(diag(varcovar_matrix))

ci_methods <- list(
  nonrankbased = function() get_nonrankbased_ci(B, theta_hat, alpha,
                                                varcovar_matrix),
  independent = function() get_independent_ci(theta_hat, S, alpha),
  bonferroni = function() get_bonferroni_ci(theta_hat, S, alpha)
)

ci_results <- lapply(ci_methods, function(f) f())

coverages <- lapply(ci_results, function(res) {
  get_coverage(
    ci_lower = res$ci_lower,
    ci_upper = res$ci_upper,
    true_theta = true_theta
  )
})

process_ci_result <- function(result, K) {
  tuple_list <- t(apply(

```

```

data.frame(
  ci_lower = result$ci_lower,
  ci_upper = result$ci_upper
),
1,
function(row) as.numeric(row)
))

rank_range_length <- sapply(1:K, function(x)
  length(get_ranks(x, tuple_list)$ranks)
)

list(
  t1 = get_t1(rank_range_length),
  t2 = get_t2(rank_range_length),
  t3 = get_t3(rank_range_length)
)
}

processed <- lapply(ci_results, process_ci_result, K = K)

data.frame(
  t1_nonrankbased = processed$nonrankbased$t1,
  t2_nonrankbased = processed$nonrankbased$t2,
  t3_nonrankbased = processed$nonrankbased$t3,
  coverage_nonrankbased = coverages$nonrankbased,
  t1_independent = processed$independent$t1,
  t2_independent = processed$independent$t2,
  t3_independent = processed$independent$t3,

```

```

coverage_independent = coverages$independent,
t1_bonferroni = processed$bonferroni$t1,
t2_bonferroni = processed$bonferroni$t2,
t3_bonferroni = processed$bonferroni$t3,
coverage_bonferroni = coverages$bonferroni
)
}
}

```

```

algo2_parametric <- function(
  true_theta,
  K,
  reps = 5, # step 4
  B=100,
  alpha= 0.10,
  S){
  foreach(iter = 1:reps,
    .combine = rbind,
    .packages = c("foreach", "arrow", "MASS"),
    .export = c("get_parametric_ci", "get_ranks", "get_coverage",
      "get_t1", "get_t2", "get_t3")
  ) %dornrg% {

    # step 1 =====
    theta_hat <- rnorm(
      n    = K,
      mean = true_theta,
      sd   = S
    )
  }
}

```

```

)

# step 2 =====
result <- get_parametric_ci(B,
                           theta_hat,
                           S,
                           alpha)

# step 3 =====
sorted_true_theta <- sort(true_theta)
coverage <- get_coverage(ci_lower = result$ci_lower,
                        ci_upper = result$ci_upper,
                        true_theta = sorted_true_theta)

tuple_list <- t(apply(
  data.frame(ci_lower = result$ci_lower,
            ci_upper = result$ci_upper), 1, function(row) as.numeric(row)))
rank_range_length <- sapply(1:K, function(x) length(
  get_ranks(x, tuple_list)$ranks))
t1 <- get_t1(rank_range_length)
t2 <- get_t2(rank_range_length)
t3 <- get_t3(rank_range_length)

data.frame(
  t1_parametric = t1,
  t2_parametric = t2,
  t3_parametric = t3,
  coverage_parametric = coverage
)

```

```
}  
}
```

Codes for simulation

```
#3:37PM  
source("../R/implement_algo2.R")  
  
mean <- 23.8  
df <- readRDS("../data/mean_travel_time_ranking_2011.rds")  
cl=parallel::makeCluster(15)  
registerDoParallel(cl)  
  
sds <- c(2, 3.6, 6)  
Ks <- c(51, 40, 30, 20, 10, 5)  
corrs <- c(0.1,0.5,0.9)  
alphas <- c(0.1)#c(0.05, 0.1, 0.15, 0.2)  
  
for (sd in sds) {  
  for (K in Ks) {  
    set.seed(123974)  
    true_theta <- rnorm(K, mean, sd)  
    true_sds <- df[[1:K]]  
  
    for (alpha in alphas) {  
  
      tic("Running parametric...")  
      coverage_parametric_df <- algo2_parametric(true_theta,
```

```

        K,
        reps = 5000,
        B=500,
        alpha= alpha,
        S=true_sds)

toc()

saveRDS(coverage_parametric_df, paste0("output/coverage_parametric_",
                                         K, "_", sd, "_", alpha, ".rds"))

for (corr in corrs) {
  corr_matrix <- (1 - corr) * diag(K) + corr * matrix(1, K, K)
  variance_vector <- true_sds^2
  delta <- diag(variance_vector)
  varcovar_matrix <- delta^(1/2) %*% corr_matrix %*% delta^(1/2)

  tic("Running nonrankbased...")
  coverage_output_df <- algo2_nonrankbased(
    true_theta,
    K,
    reps = 5000,
    B = 500,
    alpha=alpha,
    varcovar_matrix = varcovar_matrix)
  toc()

  saveRDS(coverage_output_df, paste0("output/coverage_probability_",
                                       K, "_", sd, "_", corr, "_",
                                       alpha, ".rds"))
}
}

```

```
}
}
```

```
stopCluster(cl)
```

```
param_grid <- expand.grid(K = Ks, sd = sds, corr = corrs, alpha = alphas)
```

```
results <- do.call(rbind, lapply(seq_len(nrow(param_grid)), function(i) {
```

```
  K <- param_grid$K[i]
```

```
  sd <- param_grid$sd[i]
```

```
  corr <- param_grid$corr[i]
```

```
  alpha <- param_grid$alpha[i]
```

```
  a <- readRDS(paste0("output/coverage_probability_",
                      K, "_", sd, "_", corr, "_", alpha, ".rds"))
```

```
data.frame(
```

```
  K = K, sd = sd, corr = corr, alpha = alpha,
```

```
  Cov_nonrankbased = mean(a$coverage_nonrankbased),
```

```
  Cov_independent = mean(a$coverage_independent),
```

```
  Cov_bonferroni = mean(a$coverage_bonferroni),
```

```
  T1_nonrankbased = mean(a$t1_nonrankbased),
```

```
  T1_independent = mean(a$t1_independent),
```

```
  T1_bonferroni = mean(a$t1_bonferroni),
```

```
  T2_nonrank = mean(a$t2_nonrankbased),
```

```
  T2_independent = mean(a$t2_independent),
```

```
  T2_bonferroni = mean(a$t2_bonferroni),
```

```
  T3_independent = mean(a$t3_independent),
```

```
  T3_nonrankbased = mean(a$t3_nonrankbased),
```



```

    T3_bonferroni = mean(a$t3_bonferroni)
  )
}))

param_grid <- expand.grid(K = Ks, sd = sds, alpha = alphas)

results1 <- do.call(rbind, lapply(seq_len(nrow(param_grid)), function(i) {
  K <- param_grid$K[i]
  sd <- param_grid$sd[i]
  alpha <- param_grid$alpha[i]

  a <- readRDS(paste0("output/coverage_parametric_",
                      K, "_", sd, "_", alpha, ".rds"))

  data.frame(
    K = K,
    sd = sd,
    alpha = alpha,
    Cov_parametric = mean(a$coverage_parametric),
    T1_parametric = mean(a$t1_parametric),
    T2_parametric = mean(a$t2_parametric),
    T3_parametric = mean(a$t3_parametric)
  )
}))

save(results, results1, file = "simulation_results.RData")

```