When the Evaluator Decides the Result: Measuring Faithfulness in Retrieval-Augmented Generation

Anonymous ACL submission

Abstract

Retrieval-augmented generation systems are often guarded by a faithfulness score that decides whether an answer is supported by the retrieved documents. Such scores usually come from natural language inference or trained alignment models, and prior work ranks them by how well they agree with human hallucination labels. Those pairs are built by editing reference text, so they cannot show whether a scorer treats answers from different generators alike, or whether a faithfulness comparison reflects the systems or the evaluator measuring them. We hold 24,000 answers fixed, from four embedding models, two question answering datasets and three generators, and score all of them with three evaluators. Into 200 answers per system, dataset and generator we then inject a known error, replacing one grounded value with one absent from the retrieved context. Under the most widely used entailment evaluator, a fixed threshold catches 5.1

1 Introduction

A document question answering system is given a set of uploaded files and must answer from them. If an invoice records a project budget of $1,000, an answer stating $1,500 fails in a specific way: fluent, on topic, citing the right document, wrong in the one place that matters. Such systems are typically guarded by a faithfulness score, which measures whether the retrieved text supports the answer (Maynez et al., 2020). The same scores are used to compare systems (Es et al., 2024; Tamber et al., 2025), so they decide both what users see and what papers conclude.

Many scorers ask a natural language inference model whether the retrieved context entails the answer, often taking the maximum over retrieved chunks. Others use a trained alignment model (AlignScore; Zha et al., 2023) or a language model as judge (Saad-Falcon et al., 2024; Tamber et al., 2025). Scorers are mostly evaluated against human hallucination labels (Honovich et al., 2022; Tang et al., 2023; Niu et al., 2024; Bao et al., 2025), or with minimal pairs in which a reference summary is edited to contain one error (Ma et al., 2023).

Neither kind of evaluation tells us whether a scorer can separate the systems someone is actually comparing, and pairs built from reference text cannot reveal whether a scorer treats answers from different generators the same way. A faithfulness result also rests on choices that are easy to leave unstated, such as how scores are aggregated, which answers enter the average, and what margin counts as equivalent.

This paper asks what such a score measures. We do not propose a new evaluator. We take 24,000 answers from a fixed grid of four embedding models, two datasets, Natural Questions (Kwiatkowski et al., 2019) and HotpotQA (Yang et al., 2018), and three generators, score every answer with three evaluators (NLI-max, claim-min and AlignScore), and ask whether the verdict on embedding choice survives a change of evaluator. The grid is only a testbed; its retrieval systems span 4.4 and 11.9 NDCG@5 points on the two datasets while generation stays fixed. Our hypothesis is that a score that rates a whole answer at once reacts less to one wrong value when more claims surround it, so its sensitivity would depend on the generator.

Our main findings are:

- Whether a comparison of four embedding systems returns a difference or a null depends on which evaluator scored it, in two of six dataset–generator cells after Holm correction. The evaluators are not shown to rank the systems differently; they differ in how sharply they resolve the same pattern (Section 7).
- In a falsification probe that swaps one grounded number for a value absent from the

context, NLI-max at a fixed threshold catches the edit in 5–14% of the most verbose generator's answers and 57–71% of the tersest's (Section 5).

- Making one model more verbose by prompt alone cuts that detection from 35.1% to 10.4% on Natural Questions, and detection falls under all three evaluators. The same prompt line also lowers the refusal rate and raises the score an unrelated document receives, so it does not vary answer length alone. Answer structure accounts for most of the gap between generators, though not all of it (Section 5.3).

- Averaging in refusals, or picking a different equivalence margin, can also change the conclusion (Sections 6 and 8).

Sections 2 to 4 cover related work and setup, Sections T to V report secondary analyses, and Section 9 gives recommendations for reporting faithfulness and choosing an evaluator.

2 Related Work

2.1 Retrieval quality and downstream outcome

Salemi and Zamani (2024) find that document-level relevance labels correlate only weakly with how a retrieval-augmented system actually performs, whether those labels come from human annotators or from an LLM. They propose eRAG, which labels each retrieved document by what the system's own generator produces from that document alone.

Three details decide how we sit against them. Their strongest baseline is answer-containment labelling, which our qrels also use, and it holds a moderate correlation of 0.31 to 0.40 Kendall's tau on the question-answering datasets. Their correlations fall as k grows, and they measure at k = 50 where we retrieve 5. Their downstream measure is correctness throughout, produced by a fine-tuned 60M reader that cannot decline to answer.

We start downstream of that. We take it as given that retrieval metrics do not predict generation quality directly, and ask a different question: what can a given measurement instrument resolve at all? We target faithfulness, not correctness, and our generators are prompted models that can refuse.

2.2 Faithfulness measurement

Most faithfulness scores work by entailment: an inference model is asked whether the retrieved context entails the generated answer. RAGAS (Es et al., 2024) packages that alongside context and answer relevance. AlignScore (Zha et al., 2023) replaces the general-purpose inference model with an alignment function trained across several factual-consistency tasks. FaithJudge (Tamber et al., 2025) hands the decision to a language model. This paper adds nothing to that list. It takes three such scorers, gives each of them the same known error, and reports what the differences between them do to the conclusions people draw.

2.3 Meta-evaluation of faithfulness detectors

A separate line of work evaluates the detectors themselves. TRUE (Honovich et al., 2022), AGGREFACT (Tang et al., 2023), RAGTruth (Niu et al., 2024) and FaithBench (Bao et al., 2025) assemble annotated corpora and score detectors against them; MiniCheck (Tang et al., 2024) trains compact fact-checkers on unified grounding datasets. Two of their findings bear on ours: no single metric is best in all settings or for all error types, and on summaries where current detectors disagree, detection falls to about 50%.

Those studies score detectors against human hallucination labels and report accuracy. Section 5 is a meta-evaluation as well, though its labels are constructed rather than annotated: we falsify one value in an otherwise identical answer, so the error is known by construction and every evaluator sees the same minimal pair. From Section 6 onward there are no labels at all. We hold the grid, the queries and the answers fixed, swap the evaluator, and watch whether the ranking of the systems survives.

Two recent papers separate faithfulness from correctness in ways that bear on what we measure. Wallat et al. (2025) distinguish whether a cited document supports a statement from whether the model actually relied on it, and show a citation can be correct while the reliance is post-hoc rationalisation. Xu et al. (2025) reward the faithfulness of intermediate reasoning steps rather than the final answer alone. Both concern whether a generator is faithful. We take the generator as given and ask what the scorer can resolve, which is the prior question in either case: a reward signal or a

citation audit is only as good as the faithfulness measurement underneath it.

These are different questions. A detector that scores well on a labelled corpus need not resolve differences between the systems a practitioner is actually choosing between, and it is that second property which decides whether a published comparison describes the systems or the instrument. Xiao et al. (2023) make the general case for treating generation metrics as measurement instruments with stated reliability and validity.

2.4 Hallucination and grounding analysis

ReDeEP (Sun et al., 2025) localises hallucination to attention heads and feed-forward components. A preprint by Sinha (2025) reports that embedding-based detection separates constructed hallucinations almost perfectly and naturally occurring ones not at all, the hard cases being those that stay semantically close to a faithful response; we return to it in the Limitations, because our probe constructs its errors. Chen et al. (2025) vary and then combine embedding models for mathematics question answering, having observed that different embedders succeed on different queries. We do not probe model internals. What we report here is behavioural.

3 Definitions

3.1 Faithfulness

For a generated answer a and retrieved context R = {d1, ..., dk}, the standard aggregate is:

$$F_{\max}(a, R) = \max_{d \in R} \mathrm{NLI}(d \models a) \qquad (1)$$

We also evaluate a claim-level aggregate. Writing C(a) for the assertions in a:

$$F_{\mathrm{claim}}(a, R) = \min_{c \in C(a)} \max_{d \in R} \mathrm{NLI}(d \models c) \qquad (2)$$

Taking the maximum over chunks makes sense, since any one retrieved document may support a claim. Taking it over claims, which (1) does implicitly, does not. An answer is only as supported as its weakest assertion, and one unsupported claim should not sit hidden behind several supported ones. Throughout, faithfulness is measured against the generated answer and the retrieved context. The gold answer never enters it.

An earlier version of this work subtracted faithfulness from NDCG@5 and reported the gap. We have retired that metric, for three reasons. The two terms share no unit. On Natural Questions the difference comes out negative for every model, because faithfulness (0.85) runs above retrieval quality (0.79), so the metric presumes a loss of fidelity that does not occur. And any metric of the form 1 - F/RQ reproduces the retrieval ranking whenever F is near-constant across systems, which it is here. We report absolute faithfulness instead, which has the further advantage of keeping the both-low case visible; a difference cannot tell it apart from both-high.

3.2 Correctness and retrieval hit

Correctness is measured against the gold answer, never against the context. Keeping the two apart is what lets a grounded wrong answer and an ungrounded right answer stay distinguishable. A retrieval hit means the gold answer string appears somewhere in the retrieved context. That is a strong definition of retrieval success, and Limitations sets out what it misses.

4 Experimental Setup

Two datasets are used, Natural Questions (Kwiatkowski et al., 2019) and HotpotQA (Yang et al., 2018), at 1,000 queries each. Four embedding models index each corpus, retrieval takes the top five chunks of 256 tokens with 32-token overlap, and three generators answer from a byte-identical prompt at temperature 0: two proprietary (Claude Haiku 4.5, GPT-4o-mini) and one open-weight run locally (Qwen2.5-7B-Instruct). That gives 4 x 2 x 3 x 1,000 = 24,000 answers, each re-scored by every evaluator. The four systems — all-mpnet-base-v2 (contrastive), BGE-M3 (multilingual), E5-large-instruct (instruction-tuned) and text-embedding-3-small (proprietary) — reach NDCG@5 of 0.786, 0.794, 0.806 and 0.830 on Natural Questions and 0.705, 0.809, 0.824 and 0.767 on HotpotQA, a spread of 4.4 and 11.9 points, and they do not rank the same way on the two datasets (Appendix A). A single prompt builder enforces parity, one user turn and no system message, since a prompt difference would confound every cross-generator comparison below.

Four further arms run off the same grid, in Sections S to V. A fifth embedding model, jina-embeddings-v3, was run over both datasets and all three generators. It serves as a control on the com-

parison and is not a member of the matched set. A third dataset, QASPER (Dasigi et al., 2021), was run at 819 questions over all five embedding models and all three generators. The floor, ceiling and context-arrangement conditions and the geometric and re-ranking analyses were run on the Claude arm. Their scope is stated where they appear and again in the Limitations.

Three evaluators are compared, on identical inputs. NLI-max is (1) with a DeBERTa-v3-large (He et al., 2023) inference model, the common choice. It uses the entailment probability alone. Steen et al. (2023) show that an NLI scorer predicts faithfulness better when it also uses the contradiction probability, and better again with task-adapted training and Monte-Carlo dropout. We deliberately score the configuration people deploy rather than the best one available, since the question here is what published comparisons rest on; a better-configured entailment scorer would be a fourth instrument to characterise, not a reason to expect the three we ran to agree. Claim-min is (2) with the same model and sentence-level claim segmentation, chosen so no second generator enters the measurement loop. AlignScore (Zha et al., 2023) is an independently trained alignment model.

The answers are byte-identical across evaluators. The premises are not, and that difference is part of what the comparison measures, since premise construction follows each evaluator's intended interface: the entailment scorer sees each of the five chunks separately plus their concatenation, truncated to the scorer's own 512-token window, and takes the maximum; the claim-level scorer applies the same construction per extracted claim; AlignScore takes the concatenated context as one premise and splits it internally. Some of the difference in Section 5 is therefore premise granularity rather than evaluator sensitivity; the Limitations section bounds that share by re-scoring the same cases on the concatenated premise alone. The hypothesis is normalised identically for all three, with markdown emphasis, headings and list markers stripped before scoring. That matters because one generator emits markdown in 76.0% of its attempted answers against 1.3% and 0.3% for the other two, and the entailment model responds to it (Section Q).

One refusal rule is used throughout, from a single shared implementation, so every section below describes the same population. An answer counts as a refusal when, after SQuAD-style normalisation, it begins with one of a fixed list of declining phrases. The rule excludes 5,776 of the 24,000 answers (24.1%), from 11.8% on NQ/Qwen to 30.2% on HotpotQA/GPT-4o-mini. All three generators prepend a "Based on the provided context," preamble to everything, refusals included, so the rule strips it before the anchored test; without that step 107 refusals, all Claude's, would count as attempts.

5 How Sensitive Are These Evaluators to a Known Error?

5.1 A controlled falsification

A faithfulness score is only useful if it responds when an answer stops being faithful, so we construct that condition directly. For each answer containing a numeric value that appears in the retrieved context, we replace the value with one that does not appear there, preserve the surface format, and re-score against the same chunks. Two eligibility rules carry the design: the original value must be present, or the answer was never grounded, and the replacement must be absent, or the altered answer is accidentally supported and a low score is correct behaviour.

Cases are taken deterministically, in dataset order rather than by random sampling: the first 200 eligible answers per system, dataset and generator. The scored set is therefore a prefix of an already filtered population: 4,784 cases against 7,609 eligible, from a near-census on GPT-4o-mini (800 of 882 on NQ) to two fifths on Claude (800 of 1,946).

Two controls accompany it: an entity substitution, which makes a comparable edit to a named entity instead of a value, and the untouched answer scored against another query's context, which gives the floor of each evaluator's scale. Cases are rebuilt deterministically, so all three evaluators see identical inputs.

On Claude's Natural Questions answers, NLI-max leaves the falsified answer at 0.852 against a floor of 0.474. That clears the fixed 0.5 gate and does not clear the floor-anchored gate for that cell, which sits at the 95th percentile of the floor distribution, 0.985. The same edit on GPT-4o-mini's answers lands at 0.436, essentially at that generator's floor of 0.506, and the open-weight generator falls between at 0.574 against a floor of 0.470. Evaluator, context and perturbation code are identical. Only the generator that wrote the answer differs.

		Claude Haiku 4.5			Qwen2.5-7B			GPT-4o-mini		
Dataset	**Evaluator**	Orig	Fals.	Det.	Orig	Fals.	Det.	Orig	Fals.	Det.
NQ	NLI-max	0.906	0.852	**5.1%**	0.836	0.574	35.1%	0.887	0.436	**56.6%**
	Claim-min	0.679	0.514	**25.1%**	0.693	0.397	48.1%	0.863	0.390	**61.0%**
	AlignScore	0.866	0.619	**24.1%**	0.863	0.428	51.8%	0.912	0.272	**75.4%**
HotpotQA	NLI-max	0.702	0.618	**13.9%**	0.547	0.277	54.8%	0.577	0.186	**70.5%**
	Claim-min	0.370	0.255	**34.3%**	0.424	0.160	66.8%	0.571	0.182	**70.6%**
	AlignScore	0.786	0.454	**48.9%**	0.749	0.255	74.5%	0.780	0.119	**89.4%**

Table 1: Response of three evaluators to a falsified value, on identical inputs, pooled over the four embedding systems (n = 800 per cell, 784 on HotpotQA/GPT-4o-mini). "Det." is the share of answers passing a fixed 0.5 threshold before falsification and failing it after. Bold marks the detection columns for the two extreme generators: the same falsification, scored by the same evaluator on the same retrieved context, is caught between 5.1% and 48.9% of the time on the most verbose generator and between 56.6% and 89.4% on the tersest. Scale floors, the floor-anchored gate and Wilson 95% intervals on every rate are in Appendix B.

We predicted that intermediate position before the arm was run, from its assertion count alone (Section 5.2), and it holds in both datasets under all three evaluators. The evaluator ordering is stable across these six cells too: AlignScore responds most, claim-min next, NLI-max least. Generators differ in how far apart the evaluators are, not in which responds most. That stability is a property of this grid and not of the evaluators: on a third dataset where retrieval fails under every system the ordering inverts for two of the three generators (Section V), so the ranking holds where retrieval works and stops holding where it does not.

The evaluators do not share a floor, so detection rates only become comparable once the scale is normalised, and we report two gates. On Claude's NQ cell an untouched answer scored against an unrelated context averages 0.474 under NLI-max and 0.245 under claim-min, and the distribution is heavy-tailed: its 95th percentile is 0.985 under NLI-max, so an unrelated document clears a fixed 0.5 gate nearly half the time. Our second gate, which we call floor-anchored because it sits relative to each evaluator's own floor rather than at a shared constant, is placed at that percentile, where "detected" means the falsified answer is no longer better supported than an unrelated document, which means the same thing on every scale. Read that way NLI-max detects 50.2% of falsifications rather than 5.1%, and its gap to GPT-4o-mini narrows from roughly elevenfold to under twofold. The ordering holds at either gate. The floor-anchored gate is a comparison device, not an operating point: it sits above the mean untouched answer.

Counterfactual substitution is also used to build training data. Ju et al. (2026) construct 99,094 examples by replacing answer-bearing entities in SQuAD and TriviaQA with type-consistent alternatives, so that following the context can be distinguished from agreeing with it by coincidence. The construction is close to ours and the purpose is not: they manufacture conflicts to train a generator toward the context, and we manufacture them to ask what a scorer does when the conflict is already there. Their scale also shows what ours is not, since our probe is 200 cases per system, dataset and generator, chosen for having a gold-standard error rather than for covering the space of errors.

5.2 Answers with more assertions are scored less sensitively

Segmenting each answer into sentence-level assertions and grouping by count gives a declining relationship in all three generators. It is not strictly monotone: the tail buckets are thin and each generator reverses direction once inside them (Appendix C).

The three generators average 3.08, 1.77 and 1.25 assertions per attempted answer here, with median lengths of 55, 25 and 15 words. That accounts for most of the cross-generator difference in Table 1. A falsified value is a smaller and smaller edit to the hypothesis as correct surrounding text accumulates, and the remainder dominates the entailment judgement. It does not account for all of it: within the single-assertion bucket the generators still differ, +0.102 against +0.409 and +0.485. As a check on the claim-level implementation, every single-assertion answer scores identically under both aggregates (n = 2,472, largest absolute difference 1.7e-05, which is batch-padding

noise). That check is what surfaced the normalisation defect in Section Q, where it failed on all 131 formatted answers by as much as 0.729.

Claim-level aggregation is a partial remedy. As a fraction of the distance to the random-context floor, the median response on Claude's answers moves from 0.01 to 0.03, and the minimum moves the right way in 55% of cases; when the falsified assertion is not already the weakest, the minimum does not move at all. A second dilution survives inside assertions, since the three generators still differ at matched assertion count and their single-assertion answers average 23.9, 19.5 and 16.1 words.

The third generator makes that residual legible. It sits between the other two in aggregate and does not once assertion count is held fixed: at one assertion it is +0.409, against +0.485 for GPT-4o-mini and +0.102 for Claude. Its intermediate aggregate comes from its assertion *distribution*, not from intermediate per-assertion sensitivity. So the remaining gap belongs to one generator, not to a smooth verbosity axis. Two generators cannot tell those apart; three can.

5.3 Verbosity, varied within one model

The gradient in Section 5.2 runs across three generators, and those generators differ in more than answer length. Two are proprietary chat models from different labs and one is open-weight; assertion count is confounded with everything else that distinguishes them. A fourth model would add a fourth confounded point. Varying the prompt on one model does not.

We ran Qwen2.5-7B a second time over the same queries, the same retrieved contexts and the same weights, adding one line to the prompt asking for a fuller answer. The grounding instruction and the refusal sentence are byte-identical to the standard template, so the refusal rule still matches and faithfulness is still measured against the same constraint. The arm carries its own label throughout.

The manipulation is large. Assertions per attempted answer go from 1.77 to 4.90 on Natural Questions and 1.54 to 4.99 on HotpotQA; attempted answers go from 34 and 26 words to 108 and 110. That overshoots the most verbose generator in the main grid, which averages 3.08, so the arm extends the axis rather than interpolating on it.

Sensitivity falls in all six cells (Table 2), and no confidence interval overlaps its own baseline. Under the entailment aggregate detection goes from 35.1% to 10.4% on Natural Questions and 54.8% to 17.4% on HotpotQA. The effect is not specific to the evaluator: AlignScore falls furthest in proportional terms, from 74.5% to 18.5% on HotpotQA, and its mean response to a falsified value drops from 0.494 to 0.127. The instrument Section 5.1 measures as most responsive is not exempt; it had been reading shorter answers.

Claim-min degrades least, retaining 28.9% and 43.6% where the others fall to between 10% and 19%. That is the behaviour its construction predicts and it is here demonstrated by manipulation rather than inferred across models. Its absolute scores, though, collapse: mean 0.693 to 0.234 on Natural Questions and 0.424 to 0.076 on HotpotQA. A minimum over five assertions sits near zero whatever the answer says, so claim-min keeps its sensitivity at this verbosity while ceasing to be usable against a fixed threshold. Resisting the structural bias and remaining thresholdable are separate properties.

What this does not show. We predicted, before running it, that an arm at 4.9 assertions would fall below the 5.1% detection of the main grid's most verbose generator at 3.08. It does not: 10.4% against 5.1%, on more assertions. Answer structure is therefore causal and accounts for most of the distance between the two, but not all of it, and what remains is a property of the generator that verbosity does not capture. Section 5.2 reaches the same conclusion from the opposite direction, by conditioning on assertion count and finding one generator still separated from the other two. On HotpotQA the residual is small enough to disappear: 0.088 here against 0.085 there.

Two effects that are not the one we manipulated. Refusals fall, from 11.8% to 9.8% and 29.6% to 23.8%, so the answered population is not identical between arms; the probe runs on attempted answers, but the two arms attempt slightly different questions. And the scale floor rises steeply. An untouched answer scored against an unrelated document averages 0.470 under the entailment aggregate on Natural Questions for the standard arm and 0.581 for the verbose one; on HotpotQA it goes from 0.245 to **0.509**. A five-assertion answer gives an unrelated context more chances to support something, and the aggregate takes the maximum. On HotpotQA that puts the unrelated-document baseline above the fixed 0.5

Evaluator	Arm	Δ	Det.	95% CI
Natural Questions				
NLI-max	standard	0.261	35.1%	[31.7, 38.8]
	verbose	0.072	**10.4%**	[8.2, 13.0]
Claim-min	standard	0.297	48.1%	[44.0, 52.2]
	verbose	0.054	**28.9%**	[22.4, 36.4]
AlignScore	standard	0.436	51.8%	[48.2, 55.4]
	verbose	0.149	**16.0%**	[13.5, 18.8]
HotpotQA				
NLI-max	standard	0.270	54.8%	[50.1, 59.5]
	verbose	0.088	**17.4%**	[14.3, 20.9]
Claim-min	standard	0.263	66.8%	[61.6, 71.6]
	verbose	0.025	**43.6%**	[31.4, 56.7]
AlignScore	standard	0.494	74.5%	[71.1, 77.7]
	verbose	0.127	**18.5%**	[15.8, 21.4]

Table 2: One model, one prompt line. Response to a falsified numeric value under the standard prompt (1.77 and 1.54 assertions per answer) and a verbose one (4.90 and 4.99), on the same queries, weights and retrieved contexts, pooled over the four matched embedding systems, $n = 800$ per row. Detection is at the fixed 0.5 gate over cases scoring above it before falsification. Every cell falls and no interval overlaps its baseline.

HotpotQA	refusal rate	pooled		answered	mean NLI-max	
	worst-best	spread	ρ	spread	refusals	attempts
Claude	0.393-0.224	0.085	+0.99	0.018	0.27-0.35	0.69-0.71
Qwen	0.378-0.241	0.053	-0.98	0.003	0.85-0.90	0.57
GPT-4o-mini	0.398-0.232	0.072	-0.92	0.029	0.91-0.94	0.62-0.65

Table 3: Pooling refusals into the faithfulness average gives a column that tracks retrieval quality in every generator (ρ = Spearman against NDCG@5 over the four systems) — in opposite directions. Excluding them collapses the spread and the ordering follows retrieval quality in none of the three.

gate entirely, which is the argument of Section 5.1 for a floor-anchored gate, arrived at here by manipulation: verbosity degrades a fixed threshold twice over, by moving the falsified answer up and the floor up with it.

6 The Evaluation Population Can Manufacture a Relationship

All three generators refuse a substantial share of queries, and they refuse more often when retrieval is worse. On HotpotQA the weakest retriever draws 0.378 to 0.398 refusals and the strongest 0.224 to 0.241. A refusal is not an attempt at a grounded answer, so averaging it in carries a retrieval effect into a faithfulness number without looking as though it does.

The amount carried is large: pooled spreads run 0.053 to 0.085, and excluding refusals leaves 0.003 to 0.029. The direction has nothing to do with refusing. It depends on how the evaluator scores the sentence each generator refuses in. Claude's refusals score far below its attempts, so pooling drags the weakest retriever down and the pooled column rises with NDCG@5. Qwen's and GPT-4o-mini's score far above theirs, so pooling lifts the weakest retriever and the same column falls. One experiment supports both readings and neither is about faithfulness. The pooled column is close to a monotone function of the refusal rate with a sign set by boilerplate, so anyone defending it cannot fall back on a consistent direction of bias. All faithfulness results here exclude refusals and are paired on the queries every system answered.

7 The Verdict Depends on the Evaluator's Acuity

We compare the four retrieval systems on faithfulness, refusals excluded, paired on a common query subset, with a paired bootstrap of 10,000 resamples.

The result of this section is narrower than it first appears, and we state the narrow version here so the table is read correctly. Which evaluator is used decides whether a comparison of these systems returns a difference or a null. It does not follow that the evaluators rank the systems differently, and a direct test finds no evidence that they do (Appendix I). What separates them is acuity: on identical answers AlignScore resolves a larger difference relative to its own noise in five of six cells (Appendix H.1) and needs a smaller effect to reach significance (Appendix H). The consequence for a published comparison is the same either way, which is why the distinction is easy to miss and worth stating.

The statistic is the spread, the difference in mean faithfulness between the best and worst of the four systems, with a p-value from a paired bootstrap over that pair re-centred at zero (Dror et al., 2018). It is what a practitioner is exposed to, since they adopt one embedding model and stand to lose the distance to the best alternative. It also summarises two systems chosen for being the extremes, so its p-value is not adjusted for that selection and the intermediate systems never enter it. We treat it as descriptive and give the direction across all four in Section R. An omnibus test would be stricter; we do not run one.

Under the common evaluator no cell of the six shows a detectable difference; under the evaluator

		Claude Haiku 4.5		Qwen2.5-7B		GPT-4o-mini	
Dataset	**Evaluator**	Spread	p (Holm)	Spread	p (Holm)	Spread	p (Holm)
NQ	NLI-max	0.0107	1.000	0.0055	1.000	0.0130	0.978
	Claim-min	0.0216	0.978	0.0076	1.000	0.0151	0.823
	AlignScore	0.0114	0.122	0.0072	1.000	0.0080	0.978
HotpotQA	NLI-max	0.0232	1.000	0.0123	1.000	0.0267	0.823
	Claim-min	0.0345	0.739	0.0181	1.000	0.0378	0.112
	AlignScore	0.0164	0.823	**0.0406**	**0.0187**	**0.0461**	**0.0090**

Table 4: The same comparison under three evaluators, Holm-corrected over the eighteen comparisons in the table. Two of six cells change verdict at alpha = 0.05 and survive correction, both under AlignScore and both on HotpotQA. Queries, answers, refusal handling and test are identical throughout. Paired n is 784, 790 and 628 on NQ and 517, 499 and 510 on HotpotQA. With 10,000 resamples the smallest attainable non-zero p is 1e-4, so the cell at p = 0.0005 uncorrected is 5 extreme resamples of 10,000, not a clamped floor.

Section 5 measures as most responsive to known errors, two do. Both surviving cells are on HotpotQA and all three Natural Questions cells are null, which may be a property of how that sample is drawn rather than of the evaluators: it retains only queries whose annotated answer falls inside the retained context window, leaving a constrained single-hop task with less for an embedding model to get wrong. We cannot separate that from the two datasets differing in hop structure. Appendix H reports what each cell could have detected: the minimum detectable effect at 80% power is 0.012 to 0.060, above the observed spread in 16 of 18 cells, and it is lowest under AlignScore in all six. Part of the difference between evaluators here is resolving power at fixed n, not only response to a known error. Appendix H.1 separates the two: dividing each spread by its own paired standard deviation removes the variance term, and AlignScore's standardised effect is still the largest in five of six cells. The verdict therefore does not change merely because one instrument is quieter. A result reported only under the first would describe the resolution of the instrument, not a property of the systems. Both surviving cells are on HotpotQA, which has the wider retrieval spread, and neither is on Claude, whose answers the entailment aggregate resolves least well.

Adding a third generator made the correction stricter, eighteen comparisons rather than twelve, and the count rose anyway. The design does not guarantee that. It also produced the sharpest result here: under AlignScore on HotpotQA all three generators rank the four systems identically (all-mpnet $<$ text-embedding-3-small $<$ BGE-M3 $<$ E5-instruct), while under NLI-max no two agree. Read it carefully. The generators are independent of each other but answer from the *same* retrieved contexts, so this is three generators agreeing about a property of the shared retrieval, not three replications. What it establishes is that one evaluator resolves that property consistently across generators and another does not, on identical inputs.

The count of two is not invariant to the correction either. Two comparisons sit either side of alpha = 0.05 depending on which are treated as one family. NQ/Claude under AlignScore is p = 0.0081 uncorrected, adjusted to 0.122 over the eighteen in the table, 0.032 over the six sharing an evaluator, 0.024 over the three in its own cell. HotpotQA/GPT-4o-mini under claim-min is p = 0.0070, adjusted to 0.112, 0.042 and 0.014. Either smaller family makes the count four. Correcting within evaluator is defensible, since the six NLI tests establish which cells are null and so precede the question rather than competing with it. We still report the eighteen-comparison family, because it is the most conservative and was fixed before the correction was applied, and choosing a smaller one after seeing that it restores cells is a selection we could not account for. We give the alternative as well as the choice, because a count that moves with the multiplicity family depends on an analysis decision in the same way this paper reports for the choice of evaluator.

The statistic moves it too, and in the less comfortable direction. Appendix I replaces the paired test on the extreme pair with a permutation test that re-selects the extremes in every resample, so the cost of choosing them is paid: one cell survives Holm rather than two. A rank-based omnibus over the same four systems leaves none. The two counts answer different questions — a practitioner comparing their adopted model against the

best alternative is exposed to the extreme pair, and the omnibus asks whether the four differ at all — but the paired figure is the most permissive of the three and we report all of them. The same appendix tests whether the evaluators disagree about the four systems, rather than merely returning different verdicts about them, and finds no detectable interaction in any of the six cells. Read with Appendix H.1, the defensible claim is that these evaluators resolve a common pattern with different acuity rather than seeing different patterns, which leaves the consequence for a published comparison unchanged and the mechanism narrower than evaluator disagreement.

8 What an Equivalence Claim Requires

Four of the six cells in Table 4 show no detectable difference under any evaluator. Read that as a statement about resolution, not about the systems: Appendix H puts the minimum detectable effect above the observed spread in 16 of the 18 cells, so an effect the size of the one we measured would usually not have been detected. A null here is not evidence of equivalence, so we test for equivalence directly with two one-sided tests (Schuirmann, 1987). TOST turns on the margin, and the margin is a judgement about what difference would matter, and not a fact the data supplies. We sweep it from ± 0.01 to ± 0.10 and report the curve (Appendix E).

The curve is steep. On NQ/Claude under NLI-max no pair is equivalent at ± 0.01, four of six are at ± 0.02 and all six at ± 0.03; on HotpotQA nothing is equivalent below ± 0.05 in any cell. Stating equivalence means choosing a column, and the choice does most of the work.

Section 5 gives a way to choose it. Falsifying one grounded value moves NLI-max by 0.049 to 0.095 on Claude's answers, so ± 0.05 on that evaluator is about the size of one fabricated fact, and equivalence at that margin says the systems differ by less than one fabrication. The anchor is evaluator-specific and so is the verdict: the same falsification moves claim-min by 0.165 and AlignScore by 0.247 on those answers, and at ± 0.03 on NQ/Claude, NLI-max calls all six pairs equivalent while claim-min calls two. An equivalence claim has to name its evaluator, and say what the margin is worth on that evaluator's scale.

The anchor fixes the units, not the tolerance. Saying ± 0.05 is about one fabricated fact on this evaluator does not establish that one fabricated fact is the right bar, and nothing in our data can establish that. A system summarising product reviews and a system reading a drug label have different tolerances for the same measured difference, and the second may want a margin an order of magnitude tighter. What the anchor removes is the case where a margin is chosen because it is conventional and its magnitude on the chosen evaluator's scale is never checked. Reporting the curve leaves the choice with the reader, who knows the application.

9 Discussion

For work reporting RAG faithfulness:

- Name the evaluator. "Faithfulness did not differ" is incomplete: in two of our six cells the same data returns a difference under one evaluator and a null under another. That is a statement about which instrument was used, not about the systems — the evaluators are not shown to rank them differently — and it is the instrument the reader needs in order to know what the null is worth.

- Report the evaluation population, and whether membership depends on the system being compared. Pooling refusals here produced a column tracking retrieval quality in all three generators, in opposite directions (Table 3). Established frameworks often separate refusals already, so this is a caution about aggregate reporting rather than a defect in those frameworks. It reached our own results through a shared helper whose two implementations disagreed on 365 rows, which is the more realistic failure: the rule exists, and two parts of the pipeline apply different versions of it.

- Prefer claim-level aggregation to a maximum over the whole answer, most of all where answers carry several assertions. Treat it as a partial remedy. It roughly quadruples detection on the verbose generator's NQ cell, 5.1% to 25.1%, and 25.1% is still a minority of known fabrications, against 61.0% for the tersest generator under the same aggregate. The gap between generators narrows and does not close, so claim-min reduces the structural bias rather than removing it.

Per-assertion thresholding, or weighting assertions by how much of the answer's content they carry, are the obvious next steps and we did not test them.

- For symbolic content, put a deterministic check in front of the evaluator. Requiring every value in an answer to appear in the retrieved context flags every falsification we constructed. That part is circular and we state it as such: our second eligibility rule defines the substituted value as absent from the retrieved context, so a containment test must catch it. The informative comparison is the other direction. A trained evaluator tested on the same cases reaches 89.4% at best and 5.1% at worst, so these edits are not hard to catch — they are hard for an entailment aggregate to catch, and the check is indifferent to answer length where the aggregates are not. What the probe does measure about the check is its false-positive rate, 0.8% to 5.2% on untouched answers, and that rate is not circular.

- Calibrate the margin against a measured effect before claiming equivalence. A falsification experiment of this kind costs nothing beyond re-scoring.

For a document question answering system, the practical reading of Table 1 is that a grounding threshold on a verbose generator catches a minority of falsified values: 5.1% under the common evaluator, 25.1% under the most responsive one tested. That is the case for the deterministic check above, and two qualifications on it matter. Numbers that assert nothing about the world, such as chunk indices and ordered-list markers, are not expected in the retrieved text, and counting them raises that rate on Claude's HotpotQA answers to about 39%. The rest are quantities the answer derives instead of copying, which a literal check also flags, so it complements an entailment score rather than replacing one.

Checking symbolic content against the source is an old idea (Goodrich et al., 2019; Nan et al., 2021; Zhao et al., 2020), and that numbers are a weak point is documented at the level of the representations too (Wallace et al., 2019). We claim no novelty for it. We do claim the measurement that makes the case for it here, against three current evaluators on identical inputs, and note that a practitioner choosing an instrument is served by knowing which one works rather than which one is new. Entailment is separately a loose proxy for attribution: the AIS framework (Rashkin et al., 2023) separates support by an identified source from general plausibility.

What this paper adds is narrower than the check: the controlled minimal pair. One numeric value is replaced in an otherwise byte-identical generation and the same case goes to all three evaluators, so what is measured is each evaluator's response to a known error on identical input, not its agreement with a human label on some other corpus. That covers numeric values, three generators and two datasets.

10 Conclusion

Holding a 24,000-answer generation grid fixed and varying only the faithfulness evaluator changes the conclusion about whether embedding choice affects faithfulness in two of six dataset-generator cells, or one of six under a test that pays for selecting the pair compared. The evaluators are not shown to disagree about the systems; they resolve the same differences with different acuity, and that is sufficient to move a published verdict. The differences between evaluators are directly measurable: a falsified grounded value moves the common entailment aggregate by 0.054 on one generator, 0.262 on a second and 0.451 on a third, and how many assertions an answer contains accounts for most of that gap. A faithfulness result that does not name its evaluator, population, aggregation and equivalence margin is not reproducible in the sense that matters: another group making different standard choices on the same generations would reach a different conclusion.

Code and Data Availability

The pipeline, the three evaluator interfaces, the falsification probe, the refusal rule and every analysis script behind the tables in this paper are available at `https://github.com/Shakhriyorbek/rag-faithfulness`. The repository includes a map from each method claim in this paper to the function that implements it, and scripts that regenerate each table from stored checkpoints. This matters for a paper whose central recommendation is to re-run the probe on oneś own outputs: the probe is roughly 200 cases per cell and needs no API access once generations exist. The generated answers and

their scores are retained and can be shared on request; we do not redistribute the source datasets, which are publicly available.

Limitations

What we can claim is bounded by the grid we measured on, and by the graders that decide who belongs to each population.

- Four embedding models, two English datasets, three generators. Two things this bounds should be separated, because our controls move one and not the other. The *axis* the mechanism in Section 5.2 runs along is assertions per answer, The three generators as prompted span 1.17 to 2.77 assertions per attempted answer, and the prompt-varied arm of Section 5.3 carries one of them to 4.90 and 4.99 on the two datasets, where the effect continues in the direction the mechanism predicts. The span of the axis we have measured is therefore roughly twice the span of the generators themselves. The *population* of models is three, and no control here changes that. Varying a prompt holds the weights fixed, which is what makes it a clean test of the confound between length and model identity and equally what stops it saying anything about models trained differently. Two of the three are instruction-tuned chat models from broadly similar recipes, the residual that answer structure fails to explain is measured on one generator, and whether any of this holds for a much larger model, a much smaller one, or a different training regime is untested.

- Correctness is graded by a judge model rather than by string overlap. Exact match is 0.000 across all 24,000 answers because the generators do not emit bare answer spans. String containment is the obvious fallback, and it bounds accuracy in neither direction. Measured against the judge it understates accuracy by 5 to 15 points in twelve cells, and overstates it by 3 to 7 points in the four HotpotQA cells under Claude, where a long answer mentions a reference string while asserting something else. The judge is itself a language model reading model output, and we have not checked it against a human annotator on this data.

- Retrieval hit is defined as the gold answer string appearing in the retrieved context. This is a strong definition, and it does not separate retrieval failure from failures of composition, entity resolution or inference once the evidence is present.

- The Natural Questions sample retains only queries whose annotated answer falls inside the retained context window. This makes the retrieval task more constrained than open-domain RAG, where evidence may be distributed, partial or implicit. It may also be why the three Natural Questions cells are null under every evaluator while both surviving cells are on HotpotQA: a constrained single-hop task leaves less for an embedding model to get wrong, so the systems have less to differ about. We cannot separate that from the datasets differing in hop structure, and do not claim to.

- Pairing on the queries every system answered removes exactly those queries where retrieval quality determined whether an answer was produced, so the comparison is conditional on a subset selected partly by the systems being compared. Substituting each system's own answered rows moves the spread by at most 0.022 and reorders the systems in three of six cells under NLI-max, but leaves the ordering unchanged in every cell that survives correction, including the one where all three generators agree. The pairing cannot explain disagreement between evaluators in any case, because it is identical across them.

- Where we do detect a difference it is small: 0.046 and 0.041, against retrieval spreads of 4.4 and 11.9 NDCG@5 points. They are detectable, but they are not large.

- The three evaluators receive byte-identical answers but not identical premises. The entailment scorer is given each of the five retrieved chunks separately, plus their concatenation truncated to the model's window, and the maximum is taken; the claim-level scorer applies that construction per extracted claim; AlignScore is given the concatenated context as one premise and performs its own splitting. Each scorer is used as its authors intend, but that means some of the difference

reported in Section 5 comes from premise granularity and not from evaluator sensitivity. We bound that share by re-scoring the same cases with the same entailment model on the concatenated premise alone. As a fraction of the NLI-max-to-AlignScore gap it runs from -0.55 to +0.20 across the six cells, and it is negative in four of them, meaning the concatenated premise makes the entailment model *less* responsive to a falsified value, not more. So premise granularity does not account for AlignScore's advantage. In most cells it works against it. The hypothesis is normalised identically for all three scorers (Section Q). It was not in an earlier version, and that difference alone decided one cell.

- Which answers count as refusals is fixed by a rule rather than given by the data, and that rule sets the evaluation population for every result from Section 5 onward. It is a researcher degree of freedom as much as a finding. Swapping one defensible detector for another moves the rows nearest the boundary between refusing and attempting, and carries the uncorrected p-value across the conventional threshold in two of eight cells (Section O). Neither of those two survives correction for multiple comparisons, but the population every reported number rests on still depends on the choice. The rule used here strips the generators' standard preamble before matching; without that step 107 refusals, all from one generator, would be graded as attempts. Appendix J reports the headline count under each of the three defensible rules available to us: all three select the same two cells, so the uncorrected p-values move with the rule while the corrected count does not.

- The falsification cases are the first 200 eligible answers in dataset order for each system, dataset and generator, rather than a random sample of the eligible answers: 4,784 cases scored against 7,609 eligible across the grid. Eligibility requires a grounded numeric value in the answer together with a replacement value absent from the context, so the scored set is a prefix of an already filtered population. Cells whose eligible count is near 200 are close to a census; the largest cells are sampled at about two fifths. Appendix K tests whether that prefix is exchangeable with the eligible set by regressing detection on position within it; no cell shows a trend that survives correction over the six tests.

- The repository configures seven embedding models. Four carry the matched comparison — all-mpnet-base-v2 (contrastive), BGE-M3 (multilingual), E5-large-instruct (instruction-tuned) and text-embedding-3-small (proprietary) — chosen to span pretraining paradigms and to include one closed-source arm. A fifth, jina-embeddings-v3 (Sturua et al., 2024), was run over both datasets and all three generators and is reported in Section S as a control on the matched set, not a member of it, because it fails the matched-quality precondition on Natural Questions. GTE-large and Instructor-XL remain unrun: each additional model is a further generation pass over every dataset and generator, and the grid is a testbed for the evaluator comparison rather than a survey of embedding models.

- The floor, ceiling and context-arrangement conditions of Section T were run on the Claude arm only, and the geometric analysis and re-ranking of Section U on one embedding system. Neither set of conclusions has been shown to hold across generators, and the re-ranking result in particular is a single operating point ($\lambda = 0.6$) on a single system, so it bounds what that intervention achieved here. It says nothing about what such interventions can achieve in general.

- The oracle condition supplies answer-bearing chunks only. That is narrower context than top-five retrieval, so it ceilings evidence selection and not accuracy, and retrieval exceeds it on Natural Questions. Defining the ceiling as gold passages in full would raise it, at the cost of comparability with what retrieval actually produces.

- QASPER is reported as a boundary condition rather than a third dataset. Retrieval fails on it under every system tested, so the population it yields cannot test a claim about systems at matched retrieval quality, and the inverted evaluator ordering we observe there is measured on answers produced largely without supporting evidence.

- All three datasets are English, and the two that carry the main grid are built on Wikipedia. The no-retrieval condition shows 32.2% of Natural Questions is answerable from parametric memory alone, so the Wikipedia dependence is measured rather than hypothetical.

- The two-detector comparison in Section O and the contingency decomposition were computed on the two proprietary arms, and cover eight of the twenty-four cells; graded correctness itself covers all twenty-four. Nothing in Sections 5, 7 or 8 depends on that grading.

- The detection rates here bear on deployment. A system that gates answers on a fixed grounding threshold, using the common entailment aggregate on a verbose generator, would pass 94.9% of the answers in which we falsified a grounded value on Natural Questions. Anyone operating such a gate in a setting where a wrong number matters – an invoice, a dosage, a contract term – should measure its detection rate on their own generator's output before relying on it, because the rate is a property of that pairing and not of the threshold. We did not test deployment-scale traffic, and our probe injects errors rather than observing natural ones. That distinction may matter a great deal: Sinha (2025) report embedding-based detection separating constructed hallucinations at a 0% false-positive rate and naturally occurring ones at 100%, on the grounds that real hallucinations stay semantically closer to a faithful answer than constructed ones do. If that holds for the evaluators we test, every detection rate in this paper is an upper bound on what the same gate would catch in deployment, and the verbose-generator figures are already low. The result is from an unrefereed preprint and we have not replicated it; we report it because it bounds our own method in the direction that matters.

- The correct-versus-incorrect faithfulness comparison rests on 44 to 134 attempted wrong answers per cell. Excluding refusals and grading correctness with a judge both reduce that population, and the resulting confidence intervals are 0.064 to 0.129 wide. The tests reported in Section P bear on the general claim and do not resolve individual systems.

References

F. S. Bao, M. Li, R. Qu, G. Luo, E. Wan, Y. Tang, W. Fan, M. S. Tamber, S. Kazi, V. Sourabh, M. Qi, R. Tu, C. Xu, M. Gonzales, O. Mendelevitch, and A. Ahmad. 2025. FaithBench: A diverse hallucination benchmark for summarization by modern LLMs. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Short Papers)*, pages 448–461.

S. Chen, Z. Zhao, and J. Chen. 2025. Confident RAG: Enhancing the performance of LLMs for mathematics question answering through multi-embedding and confidence scoring. *arXiv preprint arXiv:2507.17442*.

Pradeep Dasigi, Kyle Lo, Iz Beltagy, Arman Cohan, Noah A. Smith, and Matt Gardner. 2021. A dataset of information-seeking questions and answers anchored in research papers. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4599–4610, Online. Association for Computational Linguistics.

R. Dror, G. Baumer, S. Shlomov, and R. Reichart. 2018. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, pages 1383–1392.

S. Es, J. James, L. Espinosa-Anke, and S. Schockaert. 2024. RAGAS: Automated evaluation of retrieval augmented generation. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics: System Demonstrations*, pages 150–158.

B. Goodrich, V. Rao, P. J. Liu, and M. Saleh. 2019. Assessing the factual accuracy of generated text. In *Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 166–175. ArXiv:1905.13322.

P. He, J. Gao, and W. Chen. 2023. DeBERTaV3: Improving DeBERTa using ELECTRA-style pretraining with gradient-disentangled embedding sharing. In *Proceedings of the International Conference on Learning Representations*. ArXiv:2111.09543.

O. Honovich, R. Aharoni, J. Herzig, H. Taitelbaum, D. Kukliansy, V. Cohen, T. Scialom, I. Szpektor, A. Hassidim, and Y. Matias. 2022. TRUE: Re-evaluating factual consistency evaluation. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3905–3920. ArXiv:2204.04991.

Li Ju, Junzhe Wang, and Qi Zhang. 2026. Faithfulness-qa: A counterfactual entity substitution dataset for training context-faithful RAG models. *arXiv preprint arXiv:2604.25313*.

T. Kwiatkowski et al. 2019. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:453–466.

Liang Ma, Shuyang Cao, Robert L Logan IV, Di Lu, Shihao Ran, Ke Zhang, Joel Tetreault, and Alejandro Jaimes. 2023. BUMP: A benchmark of unfaithful minimal pairs for meta-evaluation of faithfulness metrics. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12788–12812, Toronto, Canada. Association for Computational Linguistics.

Joshua Maynez, Shashi Narayan, Bernd Bohnet, and Ryan McDonald. 2020. On faithfulness and factuality in abstractive summarization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1906–1919, Online. Association for Computational Linguistics.

Keerthana Murugaraj, Salima Lamsiyah, and Martin Theobald. 2026. RAGVUE: A diagnostic view for explainable and automated evaluation of retrieval-augmented generation. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, Rabat, Morocco. Association for Computational Linguistics.

F. Nan, R. Nallapati, Z. Wang, C. N. dos Santos, H. Zhu, D. Zhang, K. McKeown, and B. Xiang. 2021. Entity-level factual consistency of abstractive text summarization. In *Proceedings of the Conference of the European Chapter of the Association for Computational Linguistics*, pages 2727–2733. ArXiv:2102.09130.

C. Niu, Y. Wu, J. Zhu, S. Xu, K. Shum, R. Zhong, J. Song, and T. Zhang. 2024. RAGTruth: A hallucination corpus for developing trustworthy retrieval-augmented language models. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, pages 10862–10878.

H. Rashkin, V. Nikolaev, M. Lamm, L. Aroyo, M. Collins, D. Das, S. Petrov, G. S. Tomar, I. Turc, and D. Reitter. 2023. Measuring attribution in natural language generation models. *Computational Linguistics*, 49(4):777–840. ArXiv:2112.12870.

Jon Saad-Falcon, Omar Khattab, Christopher Potts, and Matei Zaharia. 2024. ARES: An automated evaluation framework for retrieval-augmented generation systems. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*. Association for Computational Linguistics.

A. Salemi and H. Zamani. 2024. Evaluating retrieval quality in retrieval-augmented generation. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2395–2400. ArXiv:2404.13781.

D. J. Schuirmann. 1987. A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability. *Journal of Pharmacokinetics and Biopharmaceutics*, 15(6):657–680.

Debu Sinha. 2025. The semantic illusion: Certified limits of embedding-based hallucination detection in RAG systems. *arXiv preprint arXiv:2512.15068*.

Julius Steen, Juri Opitz, Anette Frank, and Katja Markert. 2023. With a little push, NLI models can robustly and efficiently predict faithfulness. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 914–924, Toronto, Canada. Association for Computational Linguistics.

S. Sturua, I. Mohr, M. K. Akram, M. Gunther, B. Wang, M. Krimmel, F. Wang, G. Mastrapas, A. Koukounas, N. Wang, and H. Xiao. 2024. jina-embeddings-v3: Multilingual embeddings with task LoRA. *arXiv preprint arXiv:2409.10173*.

Z. Sun, X. Zang, K. Zheng, J. Xu, X. Zhang, W. Yu, Y. Song, and H. Li. 2025. ReDeEP: Detecting hallucination in retrieval-augmented generation via mechanistic interpretability. In *Proceedings of the International Conference on Learning Representations*. ArXiv:2410.11414.

M. S. Tamber, S. Kazi, V. Sourabh, and J. Lin. 2025. Benchmarking LLM faithfulness in RAG with evolving leaderboards. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 799–811. ArXiv:2505.04847.

L. Tang, T. Goyal, A. R. Fabbri, P. Laban, J. Xu, S. Yavuz, W. Kryscinski, J. F. Rousseau, and G. Durrett. 2023. Understanding factual errors in summarization: Errors, summarizers, datasets, error detectors. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, pages 11626–11644.

L. Tang, P. Laban, and G. Durrett. 2024. MiniCheck: Efficient fact-checking of LLMs on grounding documents. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 8818–8847. ArXiv:2404.10774.

E. Wallace, Y. Wang, S. Li, S. Singh, and M. Gardner. 2019. Do NLP models know numbers? probing numeracy in embeddings. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing and the International Joint Conference on Natural Language Processing*, pages 5307–5315. ArXiv:1909.07940.

Embedding model	Paradigm	NDCG@5 (NQ)	NDCG@5 (HotpotQA)
all-mpnet-base-v2	contrastive	0.786	0.705
BGE-M3	multilingual	0.794	0.809
E5-large-instruct	instruction-tuned	0.806	0.824
text-embedding-3-small	proprietary	0.830	0.767
spread, matched four		*4.4 pts*	*11.9 pts*
jina-embeddings-v3	distilled	0.685	0.772
spread, all five		*14.5 pts*	*11.9 pts*

Table 5: Retrieval quality of every system run. The four above the rule carry the matched comparison; their ranking differs between datasets and their spread is far larger on HotpotQA. jina-embeddings-v3 is reported separately (Section S): it sits inside the band on HotpotQA but is the weakest system by ten points on Natural Questions, where it triples the spread and fails TOST equivalence against all four at ± 0.02.

Jonas Wallat, Maria Heuss, Maarten de Rijke, and Avishek Anand. 2025. Correctness is not faithfulness in retrieval augmented generation attributions. In *Proceedings of the 2025 International ACM SIGIR Conference on Innovative Concepts and Theories in Information Retrieval (ICTIR)*. Association for Computing Machinery.

Z. Xiao, S. Zhang, V. Lai, and Q. V. Liao. 2023. Evaluating evaluation metrics: A framework for analyzing NLG evaluation metrics using measurement theory. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 10967–10982.

Zhichao Xu, Zongyu Wu, Yun Zhou, Aosong Feng, Kang Zhou, Sangmin Woo, Kiran Ramnath, Yijun Tian, Xuan Qi, Weikang Qiu, Lin Lee Cheong, and Haibo Ding. 2025. Beyond correctness: Rewarding faithful reasoning in retrieval-augmented generation. In *Findings of the Association for Computational Linguistics: EMNLP 2025*.

Z. Yang, P. Qi, S. Zhang, Y. Bengio, W. W. Cohen, R. Salakhutdinov, and C. D. Manning. 2018. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 2369–2380.

Y. Zha, Y. Yang, R. Li, and Z. Yu. 2023. AlignScore: Evaluating factual consistency with a unified alignment function. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, pages 11328–11348.

Z. Zhao, S. B. Cohen, and B. Webber. 2020. Reducing quantity hallucinations in abstractive summarization. In *Findings of the Association for Computational Linguistics: EMNLP*, pages 2237–2249. ArXiv:2009.13312.

A Retrieval quality of every system run

B Falsification response in full

C Response to falsification by assertion count

D Correlation between retrieval quality and faithfulness

Spearman correlation between NDCG@5 and mean faithfulness over the four retrieval systems, in every generator-evaluator combination. With four systems these coefficients carry no significance individually; the pattern across them is what Section R reads. The one non-canonical value, +0.63, arises from a tie between two systems.

E Equivalence across margins

Two one-sided tests on per-query faithfulness, over the six pairs of retrieval systems in each cell, across five margins. A claim of equivalence is a claim about one column of this table and one row of it.

F Verbatim overlap and the response to falsification

Overlap is the fraction of answer word 5-grams occurring in the retrieved context as a contiguous token sequence, on tokens with punctuation mapped to spaces, so it is unaffected by the markdown normalisation of Section Q. Answers under five tokens are excluded rather than scored zero, since one generator writes far more of them and scoring them zero would manufacture the difference the control tests for. Grouping the 4,784 cases into four overlap bands leaves the mean response to falsification at +0.052 to +0.085 for Claude, +0.202 to +0.364 for Qwen and +0.326 to +0.507 for GPT-4o-mini. The ordering is the same in all four bands, including the band above 0.3 where all three generators reuse a substantial part of the retrieved wording, and Claude is separated from GPT-4o-mini by at least fourfold throughout. The 95% confidence intervals on the three correlations are -0.004 to +0.096, +0.127 to +0.229 and +0.118 to +0.212.

G Retrieval success against correctness

H What the comparison could have detected

Four of the six cells in Table 4 are null under every evaluator, and Section S shows the procedure

Dataset / generator	Evaluator	Orig	Falsified	Floor	Detected @0.5	Detected @floor gate
NQ / Claude Haiku 4.5	NLI-max	0.906	0.852	0.474	5.1% [3.8-7.0]	50.2% [45.7-54.7]
	Claim-min	0.679	0.514	0.245	25.1% [21.7-28.9]	58.3% [53.3-63.1]
	AlignScore	0.866	0.619	0.331	24.1% [21.3-27.3]	77.9% [74.4-81.1]
NQ / Qwen2.5-7B	NLI-max	0.836	0.574	0.470	35.1% [31.7-38.8]	71.0% [66.1-75.4]
	Claim-min	0.693	0.397	0.378	48.1% [44.0-52.2]	79.0% [74.6-82.8]
	AlignScore	0.863	0.428	0.240	51.8% [48.2-55.4]	75.5% [72.1-78.7]
NQ / GPT-4o-mini	NLI-max	0.887	0.436	0.506	56.6% [52.9-60.1]	85.2% [81.9-88.1]
	Claim-min	0.863	0.390	0.490	61.0% [57.4-64.6]	91.0% [88.1-93.2]
	AlignScore	0.912	0.272	0.160	75.4% [72.2-78.4]	82.1% [79.2-84.7]
HotpotQA / Claude	NLI-max	0.702	0.618	0.427	13.9% [11.3-17.0]	49.7% [42.3-57.2]
	Claim-min	0.370	0.255	0.161	34.3% [29.0-40.0]	48.9% [41.8-56.1]
	AlignScore	0.786	0.454	0.475	48.9% [45.2-52.5]	93.7% [90.7-95.8]
HotpotQA / Qwen2.5-7B	NLI-max	0.547	0.277	0.245	54.8% [50.1-59.5]	69.6% [64.0-74.7]
	Claim-min	0.424	0.160	0.178	66.8% [61.6-71.6]	76.9% [71.3-81.7]
	AlignScore	0.749	0.255	0.304	74.5% [71.1-77.7]	96.6% [94.4-98.0]
HotpotQA / GPT-4o-mini	NLI-max	0.577	0.186	0.201	70.5% [66.2-74.6]	83.8% [79.7-87.2]
	Claim-min	0.571	0.182	0.204	70.6% [66.2-74.6]	84.2% [80.1-87.6]
	AlignScore	0.780	0.119	0.234	89.4% [86.8-91.6]	97.5% [95.8-98.5]

Table 6: Table 1 with the scale floors, the floor-anchored gate and Wilson 95% intervals. "Floor" is the mean score of an untouched answer against an unrelated query's context; the floor gate is the 95th percentile of that distribution, per cell and evaluator.

	Claude Haiku 4.5			Qwen2.5-7B			GPT-4o-mini		
Assertions	**n**	**NLI-max**	**Claim-min**	**n**	**NLI-max**	**Claim-min**	**n**	**NLI-max**	**Claim-min**
1	91	+0.102	+0.102	413	+0.409	+0.409	680	+0.485	+0.485
2	300	+0.076	+0.151	205	+0.152	+0.219	77	+0.360	+0.467
3	194	+0.032	+0.229	103	+0.051	+0.150	26	+0.041	+0.401
4	103	+0.024	+0.162	40	+0.024	+0.076	10	+0.204	+0.192
5 or more	112	+0.024	+0.146	39	+0.072	+0.126	7	+0.032	+0.002

Table 7: Drop in score when one grounded value is falsified, by number of assertions in the answer, on Natural Questions. Under NLI-max the response decays as answers accumulate assertions; under claim-level aggregation it does not. The GPT-4o-mini rows beyond two assertions rest on 26, 10 and 7 cases and should be read as such. In the single-assertion row the two aggregates coincide exactly, which is the degenerate case they must reduce to.

separates systems that genuinely differ. Neither of those says what size of effect it would have caught. Table 11 gives the minimum detectable effect at 80% power for a two-sided paired test at $\alpha = 0.05$, computed from the observed standard deviation of the paired per-query differences between the best and worst system in each cell.

Two things follow, and the first is a caution about our own null results. The minimum detectable effect runs from 0.012 to 0.060 with a median of 0.034, and in 16 of the 18 cells it exceeds the spread actually observed. Where we report no detectable difference, an effect the size of the one we measured would usually not have been detected. The nulls bound what a practitioner would notice at this sample size; they are not evidence that the systems are identical, which is why Section 8 tests equivalence separately instead of reading the nulls as equivalence. Both cells that do reach significance have a spread above their own minimum detectable effect (0.0461 against 0.0368, and 0.0406 against 0.0350).

The second is about the evaluators, and it qualifies how Section 7 should be read. AlignScore has the lowest minimum detectable effect in all six cells, 0.012 to 0.037, against 0.021 to 0.060 for the entailment aggregate. Some of that is a variance property: the standard deviation of the paired per-query difference is 0.12 to 0.30 under AlignScore and 0.20 to 0.48 under NLI-max, on identical answers. So part of why the verdict changes with the evaluator is that the evaluators differ in resolving power at fixed n, and not only in how they respond to a known error. Appendix H.1 separates the two by dividing each spread by its own paired standard deviation, and AlignScore's standardised effect remains the larger in five of six cells — so the variance difference does not account for all of

Generator	Evaluator	Natural Questions	HotpotQA
Claude	NLI-max	-1.00	+0.20
	Claim-min	-0.60	+0.60
	AlignScore	-0.20	+1.00
Qwen	NLI-max	-0.80	+0.60
	Claim-min	+0.63	-0.40
	AlignScore	-0.40	+1.00
GPT-4o-mini	NLI-max	-0.80	+0.80
	Claim-min	-0.80	+0.80
	AlignScore	0.00	+1.00

Table 8: With four systems these coefficients cannot carry significance individually. Under NLI-max and AlignScore the pattern is clean in all twelve combinations: every HotpotQA coefficient is positive and every Natural Questions coefficient is zero or negative. Under claim-min it fails in two of six, both on the open-weight generator. The one non-canonical value, +0.63, arises from a tie between two systems.

it.

H.1 Separating resolving power from response

The minimum detectable effects above confound two things. AlignScore may break cells because it responds more to whatever differs between the systems, or because its per-query differences are quieter and the same difference clears significance sooner. The first is a claim about what the instrument resolves; the second is a claim about its variance. Both would produce the pattern in Table 4.

Dividing each cell's spread by the standard deviation of its own paired per-query differences removes the variance term and leaves a standardised effect, comparable across evaluators that do not share a scale (Table 12).

AlignScore's standardised effect exceeds the entailment aggregate's in five of six cells, by factors of 1.3 to 5.6. So the difference between these evaluators is not only that one is quieter. On the same answers, AlignScore resolves a larger difference between the retrieval systems relative to its own noise, which is a statement about what it measures rather than about its variance.

Two qualifications. The exception matters: on NQ/GPT-4o-mini the two are indistinguishable and the ordering reverses, which is the cell with the tersest generator and the narrowest retrieval spread. And this analysis separates variance from response without identifying what AlignScore is responding to. It is consistent with AlignScore tracking a property of the retrieved context that the entailment aggregate discards when it takes a maximum over chunks, and we do not test that.

I An omnibus test, and the system by evaluator interaction

The spread in Table 4 is a maximum minus a minimum over four systems, so the two systems entering it are chosen for being extreme and its p-value is not adjusted for that choice. Two further tests remove that objection, and they qualify the headline.

An omnibus that re-selects the extremes. Permuting system labels independently within each query and recomputing the range makes the selection part of the null, since the extremes are chosen afresh in every resample. Over 10,000 resamples, and Holm-corrected across the eighteen comparisons, **one cell survives** rather than two: HotpotQA/GPT-4o-mini under AlignScore, at permutation $p = 0.0008$. HotpotQA/Qwen under AlignScore is $p = 0.0090$ uncorrected and does not survive. A Friedman test over the same four systems, which asks the same question by ranks, leaves **no cell** significant after the same correction; its smallest uncorrected values are 0.0092 and 0.0101, on two cells the paired test does not pick out.

So the count is 2 under a paired test on the extreme pair, 1 under a permutation test that pays for selecting that pair, and 0 under a rank-based omnibus. The paired figure is not wrong — it is the test a practitioner comparing their adopted model against the best alternative would run — but it is the most permissive of the three, and a reader should see all of them.

Do the evaluators disagree about the systems? A verdict changing is not the same as two instruments ranking four systems differently. We test the second directly. Scores are standardised within evaluator, since the three share neither scale nor variance, and fitted as `z ~ system * evaluator` with a random intercept per query, by maximum likelihood so that the fixed-effects likelihood ratio is valid.

The interaction is undetectable in all six cells, p from 0.31 to 0.95. Taken with Appendix H.1, where AlignScore's standardised effect is the larger in five of six cells, the coherent reading is that the three evaluators see much the same thing about these four systems and resolve it with different clarity, rather than disagreeing about it. A study using the common entailment aggre-

Dataset / generator	Evaluator	±0.01	±0.02	±0.03	±0.05	±0.10
NQ / Claude	NLI-max	0/6	4/6	6/6	6/6	6/6
	Claim-min	0/6	0/6	2/6	6/6	6/6
	AlignScore	3/6	6/6	6/6	6/6	6/6
NQ / Qwen	NLI-max	0/6	3/6	6/6	6/6	6/6
	Claim-min	0/6	0/6	6/6	6/6	6/6
	AlignScore	1/6	6/6	6/6	6/6	6/6
NQ / GPT-4o-mini	NLI-max	0/6	3/6	6/6	6/6	6/6
	Claim-min	0/6	3/6	6/6	6/6	6/6
	AlignScore	1/6	6/6	6/6	6/6	6/6
HotpotQA / Claude	NLI-max	0/6	0/6	0/6	5/6	6/6
	Claim-min	0/6	0/6	0/6	3/6	6/6
	AlignScore	0/6	2/6	5/6	6/6	6/6
HotpotQA / Qwen	NLI-max	0/6	0/6	0/6	6/6	6/6
	Claim-min	0/6	0/6	0/6	6/6	6/6
	AlignScore	0/6	0/6	0/6	4/6	6/6
HotpotQA / GPT-4o-mini	NLI-max	0/6	0/6	1/6	4/6	6/6
	Claim-min	0/6	0/6	1/6	4/6	6/6
	AlignScore	0/6	0/6	0/6	4/6	6/6

Table 9: System pairs judged equivalent, of six tested, across margins. A claim of equivalence is a claim about a particular column — and about a particular row: at ±0.03 on NQ/Claude, NLI-max calls all six pairs equivalent and claim-min two, on the same answers.

Retrieval hit and answer incorrect	Claude, NQ	Claude, HQA	GPT, NQ	GPT, HQA
Share of all queries	17.4%	34.0%	31.7%	36.3%
Of that cell, refusals	69.3%	86.8%	79.0%	78.1%
Attempted and wrong	5.4%	4.5%	6.7%	7.9%

Table 10: Correctness from graded judgement. The raw cell is 17 to 36 per cent of queries; the share that is a grounded, committed, wrong answer is 4.5 to 7.9 per cent.

gate then reports no difference and a study using AlignScore reports one, and both are reading the same underlying pattern through instruments of different acuity.

That is a narrower claim than evaluator disagreement and it has the same practical consequence: the published verdict depends on the evaluator. It is also the more defensible one at this sample size, and we state it in preference to the stronger reading. What we cannot do is rule out disagreement, since an interaction test on four systems at these spreads inherits the resolution limits of Appendix H; absence of a detectable interaction is not evidence that none exists.

J The headline count under each refusal rule

Every result from Section 5 onward is computed on the answers a rule calls attempts, and that rule is a researcher degree of freedom. Since this paper's argument is that such choices move conclusions, the count is reported under each defensible rule rather than only under the one we adopted (Table 14).

Three rules are available. The adopted rule strips a leading "Based on …," preamble before an anchored phrase test, because both generators prepend one to refusals as well as to answers. The rule before that change is the same test without the stripping; it grades 107 genuine refusals as attempts, all from one generator. The third hands the decision to the judge model used for correctness.

All three rules give two of six, and they agree on which two. No cell breaks under one rule and not another. The Limitations note that swapping detectors carries an *uncorrected* p-value across the conventional threshold in two of eight cells still holds, and the two statements are compatible: the uncorrected values move, and the corrected count does not. That the headline survives all three is a result about this grid and not a general guarantee, since all three rules are variations on anchored phrase matching and a rule built on different principles might not agree.

K Is the probe's prefix exchangeable?

Cases are the first 200 eligible answers in dataset order rather than a random 200, so the Wilson intervals beside each detection rate assume a sampling scheme we did not use. If detection does not vary with position inside the prefix, the prefix behaves like a random draw from the eligible set on the quantity being reported.

Detection by quartile of position under the en-

Generator	Evaluator	n	spread	MDE
Natural Questions				
Claude	NLI-max	784	0.011	0.021
	Claim-min	784	0.022	0.038
	AlignScore	784	0.011	0.012
Qwen	NLI-max	790	0.006	0.025
	Claim-min	790	0.008	0.032
	AlignScore	790	0.007	0.016
GPT-4o-mini	NLI-max	628	0.013	0.022
	Claim-min	628	0.015	0.024
	AlignScore	628	0.008	0.015
HotpotQA				
Claude	NLI-max	517	0.023	0.046
	Claim-min	517	0.035	0.050
	AlignScore	517	0.016	0.025
Qwen	NLI-max	499	0.012	0.060
	Claim-min	499	0.018	0.049
	AlignScore	499	**0.041**	0.035
GPT-4o-mini	NLI-max	510	0.027	0.041
	Claim-min	510	0.038	0.040
	AlignScore	510	**0.046**	0.037

Table 11: Minimum detectable effect at 80% power, two-sided paired test at $\alpha = 0.05$, against the spread observed in each cell. Bold marks the two cells that reach significance in Table 4; both have a spread exceeding their own MDE. AlignScore has the lowest MDE in every cell.

Generator	NLI-max	Claim-min	Align
Natural Questions			
Claude	0.051	0.057	**0.094**
Qwen	0.022	0.024	**0.045**
GPT-4o-mini	**0.066**	0.071	0.062
HotpotQA			
Claude	0.062	0.085	**0.082**
Qwen	0.026	0.046	**0.145**
GPT-4o-mini	0.081	0.116	**0.155**

Table 12: Spread in units of each evaluator's own paired per-query standard deviation, which removes the variance difference Table 11 reports. Bold marks the larger of NLI-max and AlignScore, the comparison at issue: AlignScore is larger in five of six cells, the exception being NQ/GPT-4o-mini (0.062 against 0.066). Claim-min is shown for completeness and is in fact the largest of the three in two cells, HotpotQA/Claude and NQ/GPT-4o-mini.

Dataset	Generator	n	LR χ^2_6	p
NQ	Claude	9,408	6.57	0.36
	Qwen	9,480	1.63	0.95
	GPT-4o-mini	7,536	2.42	0.88
HotpotQA	Claude	6,204	3.18	0.79
	Qwen	5,988	7.08	0.31
	GPT-4o-mini	6,120	3.77	0.71

Table 13: Interaction between embedding system and evaluator, on scores standardised within evaluator, with a random intercept per query. A Wald test on the same six terms agrees to two decimal places in every row. No cell shows a detectable interaction.

tailment aggregate, pooled over the four embedding systems: on Natural Questions 3.2, 3.1, 7.9 and 6.7% for Claude, 40.4, 33.1, 30.7 and 36.2% for Qwen, and 63.5, 55.4, 44.0 and 63.5% for GPT-4o-mini; on HotpotQA 12.8, 13.7, 18.4 and 10.9%, then 55.0, 58.3, 44.4 and 61.0%, then 68.8, 71.2, 65.1 and 78.8%. A Spearman test of per-case detection against position reaches $\alpha = 0.05$ in one of the six cells (NQ/Qwen, $\rho = -0.076$, $p = 0.048$), which does not survive correction over the six tests ($p \approx 0.29$) and corresponds to almost no relationship in any case. The quartile figures fluctuate without a direction.

We therefore treat the prefix as exchangeable with the eligible set for the detection rates reported, which is what the intervals require. This checks position only. It does not rule out some other ordering effect in the datasets that happens not to show up as a monotone trend in detection.

L The markdown normalisation defect

Sizing the defect before the fix, on 300 answers per cell, stripping markdown lowers Claude's whole-answer entailment score by 0.005 to 0.012 on Natural Questions and 0.021 to 0.043 on HotpotQA, moving it by more than 0.05 on 4.7 to 9.7% and 17.7 to 19.3% of answers respectively. The single-assertion identity is the diagnostic: with one claim and no markdown the whole-answer and claim-level aggregates must be numerically equal, and they were, to 1.7e-05. With markdown they differed on every one of the 131 formatted answers then in the grid, by up to 0.729 on a pair of asterisks. After stripping in both places the formatted group behaves like the unformatted one: 7 of 140 cases differ at all, by at most 1.5e-05, which is batch-padding noise. Over the present grid the check covers 2,472 single-assertion answers with a largest absolute difference of 1.66e-05.

M The same probe with entities instead of numbers

A numeric substitution is one error type, and the pattern above could be specific to it. The same construction runs on named entities: take a grounded entity in the answer, replace it with a donor entity that the context does not contain, hold everything else fixed. Cases are built once and every evaluator

Rule	Cell	spread	p_{holm}
adopted: anchored test, preamble stripped			
	HotpotQA/Qwen	0.0406	0.0187
	HotpotQA/GPT	0.0461	0.0090
bare: no preamble stripping			
	HotpotQA/Qwen	0.0413	0.0187
	HotpotQA/GPT	0.0461	0.0090
judge decides the refusal			
	HotpotQA/Qwen	0.0433	0.0108
	HotpotQA/GPT	0.0432	0.0119

Table 14: Cells breaking at $\alpha = 0.05$ after Holm correction over the eighteen comparisons, under each refusal rule. All three rules select the same two cells and no other cell reaches significance under any of them. Paired n moves with the rule — 499, 507 and 467 on HotpotQA/Qwen — so the populations are not identical.

sees the same ones. Table 15 reports them.

The verbosity effect survives the change of error type. Under the entailment aggregate on Natural Questions a falsified entity moves the score by 0.082 for the most verbose generator and 0.403 for the tersest, against 0.054 and 0.451 for numbers. Detection at the fixed gate is 9.1% against 48.8%, against 5.1% and 56.6%. The gap narrows slightly and does not close.

Ordering by generator holds in five of the six dataset-evaluator combinations. The exception is claim-min on Natural Questions, where the verbose generator is scored *more* sensitively than the mid-length one (0.163 against 0.112, detection 25.9% against 17.9%). Assertion count predicts the ordering well but it does not fix it.

Entity and numeric substitution are not interchangeable, and neither is uniformly the harder case. Both agree closely for the tersest generator, within 0.05 in every cell. They diverge for the other two, and in opposite directions: on HotpotQA the entailment aggregate responds roughly twice as strongly to a falsified entity as to a falsified number for the verbose generator (0.178 against 0.085), while on Natural Questions the mid-length generator shows the reverse and by a wider factor (0.088 against 0.261). A claim that an evaluator does or does not catch fabrications is therefore a claim about a particular kind of fabrication, and the two error types we tested do not license extrapolation to each other, let alone to unsupported causal claims or contradicted negations, which we did not test.

N The effect is not verbatim copying

A natural explanation is that one generator quotes the retrieved text back, so the evaluator scores a copy of its own premise and one substituted value cannot move it. The data does not support it. Verbatim overlap with the retrieved context is 0.226 for Claude, 0.194 for Qwen and 0.235 for GPT-4o-mini, where the explanation needs overlap to run opposite to sensitivity, and the correlations between overlap and the response to falsification are +0.046, +0.178 and +0.166, where it needs all three to be negative. The separation also survives at matched overlap, in every band including the one above 0.3 (Appendix F).

O Membership Is Set by a Grader, and Graders Disagree

Excluding refusals means deciding which answers are refusals, and a rule decides it. We compare two: a string match against the refusal templates the prompt offers, and a judge model shown the question, the reference answers and the answer. They agree on most rows, the judge finding four to five more refusals per hundred in every system without reordering them. The detector comparison below was computed on the two proprietary arms, so it covers eight of the twenty-four cells; the graded-correctness results in the next subsection cover all of them.

A level shift that preserves the ordering is usually unremarkable. This one is not, because the rows it moves sit at the boundary between refusing and attempting. Swapping detectors moves nineteen rows on NQ/Claude and fifty-five on HotpotQA/Claude, and carries the uncorrected p across 0.05 in two of the eight cells it was run over: NQ/Claude under the entailment aggregate from 0.223 to 0.048, HotpotQA/Claude under AlignScore from 0.151 to 0.049. Both land within a thousandth of the threshold and neither survives correction. The number of cells whose verdict changes between evaluators is the same under either detector, but they are different cells, so we report the count and treat any single cell as undetermined.

P The Correctness Grader Admits Refusals to the Wrong Population

The same problem returns once faithfulness is conditioned on correctness. String containment marks an answer correct when a reference string occurs

		Claude Haiku 4.5		Qwen2.5-7B		GPT-4o-mini	
Dataset	**Evaluator**	Δ	Det.	Δ	Det.	Δ	Det.
NQ	NLI-max	0.082	9.1%	0.088	10.8%	0.403	48.8%
	Claim-min	0.163	25.9%	0.112	17.9%	0.431	53.4%
	AlignScore	0.232	21.9%	0.290	33.1%	0.673	77.5%
HotpotQA	NLI-max	0.178	28.6%	0.267	54.1%	0.412	75.1%
	Claim-min	0.132	38.2%	0.262	67.3%	0.412	75.9%
	AlignScore	0.321	47.6%	0.463	69.4%	0.668	90.6%

Table 15: Response to a falsified *entity*, on the same answers and the same fixed 0.5 gate as Table 1. Δ is the mean drop in score. n = 783, 740 and 725 on NQ and 800, 771 and 762 on HotpotQA; detection is computed over the cases scoring above the gate before falsification. The generator ordering of Table 1 is reproduced in five of six rows, the exception being claim-min on NQ.

in it, and a short reference string can occur inside a refusal; on a 200-answer calibration ten refusals were marked correct this way and the judge overturned nine. Each such row carries a near-floor score into the correct-answer average and lowers the baseline every correct-versus-incorrect comparison is measured against. Under graded judgement no refusal is correct in any of the twenty-four judged cells.

That is enough to change a sign. With containment, and a baseline excluding refusals from the incorrect side only, NQ/Claude answers looked more grounded when wrong than when right by 0.018 to 0.050. Excluding refusals from both sides gives -0.006 to +0.018; grading with the judge gives -0.051 to -0.113. Each step corrects a grader, not an answer, and all three move the quantity the same way. Tested directly over all twenty-four judged cells, a permutation test with Holm correction finds six significant, every one of them negative, and none of the four positive-signed cells has an interval excluding zero. E5-instruct on Natural Questions is negative under all three generators (-0.105, -0.115, -0.125) and survives correction in each. We report no evidence that answers are more grounded when wrong. Intervals are 0.064 to 0.129 wide on 44 to 134 wrong answered rows per cell, so this bears on the general claim rather than on individual systems.

The same accounting applies to the contingency between retrieval success and correctness (Appendix G). The cell where retrieval succeeded and the answer was still wrong bears on whether retrieval quality is sufficient, and 69 to 87 per cent of it was never attempted. Read whole it runs from 17 to 36 per cent of queries and would support the claim that good retrieval often fails to produce a correct answer. Most of what it counts is a system declining to answer, and refusal rates differ by more than twenty points across the systems compared. What is left is real, and 4.5 to 7.9 per cent.

Q A normalisation defect that produced a result

An earlier version of this analysis reported two of the four cells then in the design rather than one. The difference was a change of text normalisation, not of test, data or population: the entailment scorer read the answer as the generator wrote it while the claim-level scorer stripped markdown first, so the two aggregates were not reading the same hypothesis. Markdown is unevenly distributed, appearing in 76.0% of Claude's attempted answers against 1.3% and 0.3% for the other two, so one generator's formatting habits were entering a comparison between embedding systems. Stripping it for all three removed the significance of NQ/Claude under AlignScore, the cell Table 4 still places just outside the threshold; neither cell that survives correction is affected, both being on generators that emit almost no markdown.

How it was caught is the transferable part. The defect is invisible in every summary statistic and survives every significance test. What exposed it was an identity the two aggregates must satisfy exactly on single-assertion answers, which failed on all 131 formatted answers then in the grid by as much as 0.729 (Appendix L). Metrics that admit such an identity should be checked against it.

R Direction is dataset-dependent

Where a difference exists it does not point the same way. Correlating NDCG@5 with mean faithfulness across the four systems, in all eighteen generator-evaluator combinations (Appendix D),

splits the two datasets. Under NLI-max and AlignScore the split is exact: all six HotpotQA coefficients are positive, reaching +1.00 in each AlignScore cell, and all six Natural Questions coefficients are zero or negative, reaching -1.00 for Claude under NLI-max. Better retrieval accompanies more faithful answers on the multi-hop dataset and not on the single-hop one. Composing an answer out of several retrieved pieces plausibly makes grounding sensitive to how much of the evidence is present, where a single-fact answer is not. We do not test that. The experiment varies embedding model rather than manipulating retrieval quality, so none of this is an effect of NDCG@5 itself.

Claim-min breaks the split. Two of its six combinations go the wrong way, both on the open-weight generator and in opposite directions on the two datasets. With two evaluators, or two generators, this table would have shown a clean dataset effect. The third of each is what shows the direction is not a property of the dataset alone.

S A system the test should separate

Four of the six cells are null. A reader is entitled to ask whether the test detects anything at all, and the grid answers that without a new experiment.

We ran a fifth embedding model, jina-embeddings-v3 (Sturua et al., 2024), over both datasets and all three generators. On Natural Questions it retrieves badly. Its NDCG@5 is 0.685, where the other four sit between 0.786 and 0.830, and it widens the spread the comparison runs on from 4.4 points to 14.5. Paired TOST on per-query NDCG gives mean differences of 0.102 to 0.145 against the other four, at $p_{\mathrm{TOST}} = 1.0000$ each time. The test cannot place a system further from equivalence than that. HotpotQA is a different story. There jina falls inside the band, and its pair with text-embedding-3-small is the only pair in our grid that is both undifferentiated and TOST-equivalent at ± 0.02 (mean difference 0.0059, $p_{\mathrm{TOST}} = 0.0083$).

Rerun Table 4 over five systems instead of four, holding the test, the resampling and the correction fixed, and the count goes from two of six cells to six of six. Every cell differs under every evaluator.

We read that as the precondition failing. This section asks what happens to systems that retrieve about equally well, and a system retrieving ten points worse ought to come out differently. It does, under all three evaluators. So the four nulls do not come from an instrument that never fires. At these sample sizes the procedure separates systems that differ and declines to separate the matched four.

The control bounds our own framing too. Matched retrieval quality has to be checked rather than assumed from a plausible-looking set of models, and one of the five we ran fails the check on one of the two datasets.

T Floor, Ceiling and the Arrangement of Context

Everything above compares retrieval systems against each other. That comparison fixes neither endpoint, so we measured both. These conditions ran on the Claude arm only, at $n = 1000$ per dataset.

The floor. Given no retrieved context at all, the generator answers 32.2% of Natural Questions correctly and declines 15.5% of the time. Both benchmarks are built on Wikipedia, so roughly a third of the single-hop result is available without retrieval. HotpotQA behaves differently: 20.9% correct, with a 70.4% refusal rate. Asked to compose across documents it does not have, the model mostly declines. Any claim that retrieval produced a correct answer on Natural Questions sits on top of this floor.

The ceiling. Supplying the answer-bearing chunks and nothing else gives 77.0% on Natural Questions and 86.8% on HotpotQA. On HotpotQA that works as a ceiling, with the best of the four systems reaching 81.0% of it and the worst 60.8%. On Natural Questions three of the four exceed it, at 102.2%, 102.6% and 103.4%.

We report those unclipped, because the explanation is a design choice worth stating. Our oracle supplies answer-bearing chunks and nothing around them. That is less context than top-five retrieval, not more. Questions that need the surrounding material get refused under it, 12.9% of the time here. It therefore ceilings evidence selection and not accuracy. On a single-hop dataset the extra material retrieval drags in pays for the extra noise. Where composition is the difficulty it stops paying.

Arrangement. We vary how the gold evidence is presented, over 300 queries per condition (Table 16).

Order is inert. Reversing or shuffling the evidence moves accuracy by at most 1.7 points on

	NQ		HotpotQA	
condition	acc.	ref.	acc.	ref.
all gold	.790	.127	.877	.073
reversed	.773	.123	.890	.063
shuffled	.790	.123	.880	.070
one gold only	.770	.170	**.517**	**.757**
one gold, first	.753	.137	.530	.693
one gold, middle	.757	.163	.503	.683
one gold, last	.727	.153	.510	.723
distractors only	**.090**	.667	**.150**	.913

Table 16: Accuracy and refusal rate when the gold evidence is rearranged, $n = 300$ per condition, Claude. The last four conditions hold context length at five chunks. Order is inert. Losing half a multi-hop chain is not, and it converts into refusals instead of errors.

either dataset. Holding length at five chunks and moving a single gold chunk between the first, middle and last position spans 0.727 to 0.757 on Natural Questions and 0.503 to 0.530 on HotpotQA. At $k = 5$ we see no position effect.

Subset is not inert, and it bites only where composition does. Cutting the context to one gold chunk costs Natural Questions two points and HotpotQA thirty-six. The refusal column explains the gap: HotpotQA refusals go from 7.3% to 75.7%. Handed half of a multi-hop chain, the model declines instead of completing it from memory. This is the same refusal machinery that Section 6 shows will distort a faithfulness average if those answers are left in it, and retrieval quality is what triggers it here.

Distractors alone give a second floor and it is not zero: 9.0% and 15.0% correct. That is consistent with the no-retrieval numbers above.

U Geometric Analysis and Re-ranking

One obvious response to any of this is to re-rank retrieved chunks by how well they support an answer. Whether that can work depends on a usable signal existing before the answer does. We tested for one.

Two correlations are relevant and they are not interchangeable. Correlating a chunk's similarity to the query with its entailment of the *gold* answer measures a static property of the embedding space. Correlating it with entailment of the *query* measures what a re-ranker could condition on. We compute both, at $n = 200$ per system and dataset.

Natural Questions gives a weak positive signal on both, and the two track each other: 0.146 to 0.217 for the gold-answer version, 0.131 to 0.226 for the query version, significant at $\alpha = 0.05$ in three of four systems each. HotpotQA gives nothing. The gold-answer correlation there is negative in all four systems (-0.086 to -0.115), and the query correlation sits between 0.037 and 0.077 with no p below 0.27.

Re-ranking behaves accordingly. Taking the top twenty for one system, re-ranking by entailment of the query at $\lambda = 0.6$ and regenerating, faithfulness on attempted answers moves $+0.008$ on Natural Questions (95% CI $[-0.007, +0.023]$) and -0.008 on HotpotQA ($[-0.029, +0.012]$). Both intervals contain zero. The refusal rate does move, from 15.4% to 19.0% on Natural Questions. Re-ranking takes away context the generator had been using, and it declines instead of answering from less.

Faithfulness-aware re-ranking is often proposed on the strength of a correlation like the one we find on Natural Questions. A correlation of 0.13 to 0.23 is not enough to convert into a gain. On HotpotQA there is no correlation to convert.

V When Retrieval Collapses

Both benchmarks above are Wikipedia, and both are ones these retrieval systems handle well. QASPER (Dasigi et al., 2021) is neither. We ran the same grid over 819 questions about NLP papers with all five embedding systems, and retrieval collapsed: NDCG@5 between 0.062 and 0.122, against 0.705 to 0.830 on the other two datasets, with Recall@5 of 8% to 18%.

The cause is structural. QASPER is single-document question answering. Pooling 819 papers into one corpus of 13,876 chunks leaves a question like "which multilingual approaches do they compare with?" carrying no signal about which paper it belongs to. We would not offer this as a fair test of the retrievers.

Refusals rise, to 27.8%, 35.4% and 45.0% across the three generators, and between 2,254 and 2,955 answers per generator survive. On those answers, two orderings from the main grid invert.

The generators swap places. GPT-4o-mini is the most faithful here under all three evaluators and Claude the least, reversing Section 7. The evaluators swap as well, and that matters more. Across all six cells of the main grid the three order identically, AlignScore above claim-min above NLI-max. On QASPER that survives for GPT-4o-mini alone. Claude reads NLI-max 0.712, AlignScore 0.629, claim-min 0.240.

The 0.240 carries the information. Claim-min reports the least supported assertion in an answer, so a value that low says Claude is producing multi-assertion answers whose weakest component the context does not support. That is what we would expect when the context usually lacks the evidence and the generator answers anyway. NLI-max takes a maximum over chunks, finds something to entail, and reports 0.712 on the same answers.

We keep this out of the main grid, and these numbers are not comparable to the ones above. A population where retrieval failed cannot test a claim about systems at matched retrieval quality. The inversion also has a competing explanation we cannot rule out: with Recall@5 between 8% and 18%, scores are compressed toward the bottom of each evaluator's range, and orderings among compressed scores can reverse through floor effects and distribution shift without any change in what the evaluators are sensitive to. Read this as one boundary observation, not as evidence that evaluator orderings are generally unstable across domains. What it establishes is narrower: the ordering held in every cell we measured where retrieval worked, and it stopped holding in the one regime we measured where retrieval did not.

W Does this reach past entailment scorers?

Two of the three evaluators we test are built on the same entailment model, which invites the reading that we have diagnosed NLI rather than faithfulness measurement. Other paradigms exist. ARES (Saad-Falcon et al., 2024) fine-tunes lightweight judges on synthetic data and calibrates them against a few hundred human annotations with prediction-powered inference. RAGVUE (Murugaraj et al., 2026) decomposes a RAG system into retrieval quality, answer relevance, claim-level faithfulness and judge calibration, and attaches an explanation to each. We ran neither, so what follows is an argument about what our measurements imply for them, not a test of them.

Three of our results do not depend on entailment. AlignScore is not an NLI model — it is an alignment function trained across factual-consistency tasks — and in the verbosity control it loses more than either entailment aggregate, falling from 74.5% to 18.5% on HotpotQA with its mean response to a falsified value dropping 0.494 to 0.127 (Section 5.3). The structural bias therefore attaches to scalar aggregation over a multi-assertion answer, not to the entailment model underneath. Any scorer that returns one number for a five-assertion answer inherits it, including a fine-tuned judge.

Claim-level decomposition is the obvious response and is what RAGVUE prescribes. We measure it. Claim-min is the most length-robust of the three, giving up 36 detection points between the extreme generators against 54 and 46 for the others, and it holds 43.6% detection where the others fall below 19%. It is also the aggregate whose absolute scores collapse at that verbosity, to means of 0.234 and 0.076, so decomposition buys sensitivity and costs thresholdability. That trade is a property of taking a minimum, not of the model taking it, and it will appear in any claim-decomposed metric.

Calibration is a different axis from the one we measure, which is why ARES is complementary rather than an answer. Prediction-powered inference corrects a judge's bias against a human-labelled sample: it makes the reported number closer to what annotators would say on that distribution. Our two failure modes survive that correction. A judge can be unbiased on average and still fail to separate two systems at the sample sizes people use, which is resolving power (Appendix H), and it can be unbiased on average and still move by 0.054 when a grounded value is replaced with a false one, which is sensitivity to a known error. Neither is a calibration error, and neither would be visible in agreement with annotators on unperturbed answers.

What would test this properly is running these frameworks through the same probe. We expect the verbosity effect to reproduce for any scalar aggregate and the calibration machinery to be orthogonal to it, and we have not shown either.

X What to do with a verbose generator

The detection rates above are low enough to raise a practical question the recommendations so far do not answer: given a generator that writes several assertions per answer, what should a system actually run? Our measurements support four steps, in order of how much they buy.

Put a deterministic check in front, for anything symbolic. That it flags every falsification we constructed is a consequence of how the probe defines them, not a measurement of the check. The

measurement is what it costs — 0.8 to 5.2% of untouched answers flagged — and what the learned scorers do on the same cases, which is 5.1% to 89.4%. A check indifferent to answer length is worth having where the aggregates are not, and it cannot see unsupported prose, so it is a pre-filter and not a gate.

Do not put a fixed threshold on a long answer. The scale floor moves with verbosity. Under the entailment aggregate, an untouched answer scored against an *unrelated* document averages 0.245 for our terse arm on HotpotQA and 0.509 for the verbose one (Section 5.3), so a 0.5 gate sits below the unrelated-document baseline for the verbose arm. Anchoring the gate to that floor costs one extra scoring pass over random contexts and makes the number mean the same thing across generators.

If you control the generator, constrain the answer. This is the largest single lever we measured, and it is free. One added prompt line moved Qwen from 1.77 to 4.90 assertions and detection from 35.1% to 10.4%; the same lever is available in the other direction. Shortening answers buys more detection than switching evaluators does.

Choose the evaluator against the failure you care about. Table 17 gives the properties. For separating two systems at a few hundred queries the binding constraint is resolving power, where AlignScore needs the smallest effect. For scoring a single verbose answer it is length robustness, where claim-min gives up the least — with the caveat that its absolute scores fall near zero at five assertions, so it resists the bias without remaining thresholdable.

None of this is a general recipe. Every rate above is a property of a particular generator, evaluator and dataset, and the point of the paper is that those properties are not transferable. What does transfer is the procedure: falsify a value in your own outputs, score the floor against random contexts, and read the detection rate you actually have rather than the one the evaluator's benchmark reports.

Y Choosing among the three

The recommendations above say how to report a faithfulness result. They do not say which evaluator to run, and nothing in this paper supports a single answer to that, since the three differ on properties that matter different amounts in different applications. Table 17 collects what we measured into the form that decision needs. Every entry comes from a table earlier in the paper; none of it is new evidence.

Read it against the deployment, not in the abstract. If answers are short and the question is whether a fabricated value gets caught, the deterministic check dominates and the choice of entailment scorer barely matters. If answers are long, no evaluator here catches most fabrications and the gap between the best and worst of them, 24.1% against 5.1% on the verbose generator's NQ cell, is the difference between a weak gate and no gate. If the evaluation population cannot be guaranteed free of refusals, AlignScore is the only one of the three that scores refusals below attempted answers for every generator we ran; under the other two, refusals score above real answers for two generators and far below for the third, so pooling them moves the average in a generator-dependent direction. If systems are being compared and the expected difference is small, the relevant property is resolving power, where AlignScore needs 0.012 to 0.037 against 0.021 to 0.060 for the entailment aggregate at the same sample size.

Those criteria do not agree, and we are not proposing a weighting for them. The point of stating them together is that a choice is being made whenever a faithfulness number is reported, and it is usually made by default.

	NLI-max	Claim-min	AlignScore	Value check
Detects a falsified value, terse generator	57–71%	61–71%	75–89%	**100%**
. . . verbose generator	5–14%	25–34%	24–49%	**100%**
Sensitivity to answer length (gap above)	54 pts	**36 pts**	46 pts	none
Resolving power, minimum detectable effect at 80%	.021–.060	.024–.050	**.012–.037**	—
Scores a refusal above a real answer?	2 of 3 gens	2 of 3 gens	**never**	—
Error types covered	any	any	any	symbolic only
False-positive rate	—	—	—	0.8–5.2%

Table 17: What we measured about each instrument, arranged for choosing one. Detection is against a falsified numeric value at the fixed gate (Table 1); the entity probe gives the same ordering (Table 15). MDE is from Appendix H. Refusal behaviour is the mean refusal score against the mean attempted-answer score, per generator. The sensitivity row is the detection gap between the two generators, averaged over the two datasets; claim-min is the least length-sensitive of the three and still gives up 36 points. The deterministic value check covers only symbolic content, which is why it supplements an evaluator instead of replacing one. One column of this table is dataset-conditional: the evaluator ordering it summarises holds on the two datasets where retrieval works and inverts where retrieval fails (Section V), so these properties are measured on a working retrieval regime and should not be read as intrinsic. Its two numbers are not the same quantity, and only one is a measurement: the 100% follows by construction, since the probe defines the substituted value as absent from the context and a containment test must therefore flag it, while 0.8–5.2% is the measured rate at which values in untouched answers are flagged — chunk indices and list markers if those are counted, and otherwise quantities the answer derives rather than copies.