

Option 1: Apache Web Server (CentOS/RHEL)

apache_setup.yml

```
  yaml
---
  - name: Install and configure Apache Web Server
    hosts: webservers
    become: true
  tasks:
    - name: Install Apache
      yum:
        name: httpd
        state: present

    - name: Start and enable Apache
      service:
        name: httpd
        state: started
        enabled: yes

    - name: Create a custom index.html page
      copy:
        dest: /var/www/html/index.html
        content: |
          <html>
          <head><title>Apache Server</title></head>
```

```
<body><h1>Hello from Apache on {{ inventory_hostname }}</h1></body>
</html>
```

Option 2: Nginx Web Server (Ubuntu/Debian)

nginx_setup.yml

```
    yaml
---
- name: Install and configure Nginx Web Server
  hosts: webservers
  become: true
  tasks:
    - name: Update apt cache
      apt:
        update_cache: yes

    - name: Install Nginx
      apt:
        name: nginx
        state: present

    - name: Start and enable Nginx
      service:
        name: nginx
        state: started
```

enabled: yes

- name: Create a custom index.html page

copy:

dest: /var/www/html/index.html

content: |

<html>

<head><title>Nginx Server</title></head>

<body><h1>Hello from Nginx on {{ inventory_hostname }}</h1></body>

</html>

Inventory File (inventory.ini)

ini

[webservers]

localhost ansible_connection=local

If you're targeting a remote server (e.g., a cloud VM), use:

ini

[webservers]

192.168.1.100 ansible_user=ubuntu ansible_ssh_private_key_file=~/.ssh/your_key.pem

Run the Playbook

Choose either `apache_setup.yml` or `nginx_setup.yml` depending on your OS and desired server, then run:

```
bash
```

```
ansible-playbook -i inventory.ini apache_setup.yml
```

or

```
bash
```

```
ansible-playbook -i inventory.ini nginx_setup.yml
```

After Running

- Visit <http://localhost> or your server's IP in a browser.
- You should see the custom message in your web page.