

INST0072 Lecture 9: Logic, Prolog, and Clark Completion

1. In the Last Lecture
2. Prolog and Resolution
3. Reminder: Resolution Proof By Contradiction
4. Example Resolution Proof By Contradiction
5. An Example Prolog Proof
6. Transforming Programs Into CNF Theories
7. An Example Resolution Proof
8. Comparing Resolution and Prolog Proofs
9. The Meaning of Prolog Programs with Negation-as-Failure
10. A Prolog Search Tree with Negation-as-Failure
11. Models of $\{soft \leftarrow (\neg new \wedge red), red\}$
12. Clark Completion for Propositional Programs
13. Clark Completion: Propositional Examples
14. Clark Completion: Another Example
15. Prolog Soundness and Completeness
16. Clark Completion for Predicate Prolog Programs
17. Safe and Unsafe Prolog Programs
18. A Prolog Program, Its General Form and Its Completion
19. Example Completion with Equality Theory
20. Summary
21. Further Reading for Technical Details

1. In the Last Lecture

In the last lecture we saw that

- ▶ A Prolog program can include *meta-level* clauses about itself.
- ▶ Three commonly used predefined meta-level predicates are 'clause/2', 'assertz/1' and 'retract/1'.
- ▶ The 'clause/2' predicate can be used in *meta-interpreters* that refine or adapt Prolog's search strategy for specific problems.
- ▶ The meaning of Prolog programs in terms of classical logic is not always straightforward, partly because Prolog includes *Uniqueness-of-names* and *Closed World Assumptions*.

2. Prolog and Resolution

For a Prolog program in which all the predicates have arity 0 (i.e. no arguments) and that does not use negation-by-failure, a successful branch in the search tree of a query is equivalent to a propositional calculus proof by contradiction using resolution.

Reminder: the general resolution inference rule is:

$$\frac{(L_1 \vee \dots \vee L_i \vee p \vee L_{i+1} \vee \dots \vee L_m), (L'_1 \vee \dots \vee L'_j \vee \neg p \vee L'_{j+1} \vee \dots \vee L'_n)}{(L_1 \vee \dots \vee L_m \vee L'_1 \vee \dots \vee L'_n)}$$

For example:

$$\frac{(big \vee soft \vee \neg red), (\neg soft \vee \neg new)}{(big \vee \neg red \vee \neg new)} \qquad \frac{(soft), (\neg soft)}{\perp}$$

3. Reminder: Resolution Proof By Contradiction

The general theorem (from Lecture 3, Slide 12):

Resolution Calculus Soundness and Completeness

For any CNF knowledge base KB and formula F

$$KB \models F \text{ if and only if } KB \cup \text{cnfset}[\neg F] \vdash_{res} \perp$$

... and a special (simpler) case if F is a single proposition p :

For any CNF knowledge base KB and proposition p

$$KB \models p \text{ if and only if } KB \cup \{\neg p\} \vdash_{res} \perp$$

For example: $\{(\neg \text{raining} \vee \text{wet}), (\text{raining})\} \models \text{wet}$ if and only if $\{(\neg \text{raining} \vee \text{wet}), (\text{raining}), (\neg \text{wet})\} \vdash_{res} \perp$

4. Example Resolution Proof By Contradiction

- Finish the following proof of

$$\{(\neg \textit{raining} \vee \textit{wet}), (\textit{raining}), (\neg \textit{wet})\} \vdash_{res} \perp$$

by adding the final two steps (4) and (5):

- | | | |
|-----|---|-------------------------|
| (1) | $(\neg \textit{raining} \vee \textit{wet})$ | by assumption |
| (2) | $(\textit{raining})$ | by assumption |
| (3) | (\textit{wet}) | by (1), (2), resolution |

4. Example Resolution Proof By Contradiction

- Finish the following proof of

$$\{(\neg \textit{raining} \vee \textit{wet}), (\textit{raining}), (\neg \textit{wet})\} \vdash_{\textit{res}} \perp$$

by adding the final two steps (4) and (5):

- | | | |
|-----|---|-------------------------|
| (1) | $(\neg \textit{raining} \vee \textit{wet})$ | by assumption |
| (2) | $(\textit{raining})$ | by assumption |
| (3) | (\textit{wet}) | by (1), (2), resolution |
| (4) | $(\neg \textit{wet})$ | by assumption |
| (5) | \perp | by (3), (4), resolution |

so by resolution soundness and completeness this shows that:

$$\{(\neg \textit{raining} \vee \textit{wet}), (\textit{raining})\} \models \textit{wet}$$

5. An Example Prolog Proof


Prolog program:

```
big :- soft, red.  
soft :- new.  
new.  
red.
```

Query:

```
?- big.
```

Search tree:



6. Transforming Programs Into CNF Theories

Prolog program:

```
big :- soft, red.  
soft :- new.  
new.  
red.
```

In logic:

```
 $big \leftarrow (soft \wedge red)$   
 $soft \leftarrow new$   
 $new$   
 $red$ 
```

In CNF:

```
 $(big \vee \neg soft \vee \neg red)$   
 $(soft \vee \neg new)$   
 $(new)$   
 $(red)$ 
```

```
 $big \leftarrow (soft \wedge red)$ 
```

```
 $\equiv big \vee \neg (soft \wedge red)$ 
```

```
 $\equiv big \vee (\neg soft \vee \neg red)$ 
```

```
 $\equiv (big \vee \neg soft \vee \neg red)$ 
```

[implication]

[De Morgan]

[\vee associativity]

7. An Example Resolution Proof

CNF Knowledge Base KB :

- (1) $(big \vee \neg soft \vee \neg red)$
- (2) $(soft \vee \neg new)$
- (3) (new)
- (4) (red)

Proposition to prove:

big

Resolution proof:

- (5) $(\neg big)$ [assumption]
- (6) $(\neg soft \vee \neg red)$ [by (1),(5)]
- (7) $(\neg new \vee \neg red)$ [by (2),(6)]
- (8) $(\neg red)$ [by (3),(7)]
- (9) \perp [by (4),(8)]

So by resolution soundness:

$KB \models big$

8. Comparing Resolution and Prolog Proofs

Resolution proof (from Slide 7):

(5) $(\neg big)$


(6) $(\neg soft \vee \neg red)$

(7) $(\neg new \vee \neg red)$

(8) $(\neg red)$

(9) \perp

Prolog search tree (from Slide 5):



9. The Meaning of Prolog Programs with Negation-as-Failure

Negation-as-failure (“\+”) cannot be directly translated as classical logic negation (“ \neg ”). A simple example shows why:

Prolog program:

```
:- dynamic new/0, soft/0, red/0.
```

```
soft :- \+ new, red.  
red.
```

Query:

```
?- soft.  
true.
```

Equivalent knowledge base
KB?

```
soft  $\leftarrow (\neg new \wedge red).$   
red.
```

No equivalent entailment:

$$KB \not\models soft$$

10. A Prolog Search Tree with Negation-as-Failure


Prolog program:

```
:- dynamic new/0, soft/0, red/0.
```

```
soft :- \+ new, red.  
red.
```

Query:

```
?- soft.  
true.
```



11. Models of $\{soft \leftarrow (\neg new \wedge red), red\}$

Reminders:

- ▶ In propositional logic, the models of a formula are the lines in the formula's truth table that make the formula true.
- ▶ If F and G are formulas, then " $F \models G$ " means "every model of F is also a model of G ".

$soft$	new	red	$(soft \leftarrow (\neg new \wedge red)) \wedge red$									
t	t	t	t	t	f	t	f	f	t	t	f	
t	t	f	t	t	f	t	f	f	t	f	f	
t	f	t	t	t	t	f	t	t	t	t	f	
t	f	f	t	t	t	f	f	f	t	f	f	
\Rightarrow	f	t	t	t	f	t	f	f	t	t	f	\Leftarrow
f	t	f	t	t	f	t	f	f	t	f	f	
f	f	t	t	t	t	f	t	t	t	f	f	
f	f	f	t	t	t	f	f	f	t	f	f	

So, $\{soft \leftarrow (\neg new \wedge red), red\} \not\models soft$ because line 5 is not a model of $soft$.

12. Clark Completion for Propositional Programs

Given a proposition 'p' appearing in a propositional program PR :

1. If 'p' does not appear as a fact or as the head of a clause in PR then $\mathbf{COMP}(p, PR) = \neg p$.
2. If 'p' appears as a fact in PR then $\mathbf{COMP}(p, PR) = p$.
3. If 'p' does not appear as a fact in PR and has a definition

$$p \text{ :- Body}_1. \quad \dots \quad p \text{ :- Body}_n.$$

then $\mathbf{COMP}(p, PR) = [p \leftrightarrow (B_1 \vee \dots \vee B_n)]$, where each B_i is the same as 'Body_i' but with '+' replaced by '¬', and ',' replaced by '∧'.

Clark Completion:

$$\mathbf{COMP}(PR) = \{\mathbf{COMP}(p, PR) \mid p \text{ appears in } PR\}.$$

13. Clark Completion: Propositional Examples

PR

$COMP(PR)$

$soft :- \backslash+ new, red.$
 $red.$

$soft \leftrightarrow (\neg new \wedge red),$
 $red,$
 $\neg new$

$big :- soft, red.$
 $big :- \backslash+ new.$
 $red.$

$big \leftrightarrow ((soft \wedge red) \vee \neg new),$
 $red,$
 $\neg new,$
 $\neg soft$

$big :- soft.$

$big \leftrightarrow soft,$
 $\neg soft$

14. Clark Completion: Another Example

What is $\text{COMP}(PR)$ if PR is the following program?

```
happy :- on_holiday, has_money.  
happy :- work_done, \+ has_lectures.  
has_money :- \+ student.  
has_lectures :- term_time, student.  
work_done.
```


14. Clark Completion: Another Example

What is $\text{COMP}(PR)$ if PR is the following program?

```
happy :- on_holiday, has_money.  
happy :- work_done, \+ has_lectures.  
has_money :- \+ student.  
has_lectures :- term_time, student.  
work_done.
```

Answer: $\text{COMP}(PR)$ is:

```
happy  $\leftrightarrow ((on\_holiday \wedge has\_money) \vee (work\_done \wedge \neg has\_lectures))$ ,  
has_money  $\leftrightarrow \neg student$ ,  
has_lectures  $\leftrightarrow (term\_time \wedge student)$ ,  
work_done,  
 $\neg on\_holiday$ ,  
 $\neg student$ ,  
 $\neg term\_time$ 
```

15. Prolog Soundness and Completeness

Let 'p' be a proposition appearing in the propositional Prolog program PR .

Soundness:

If PR returns 'true' for the query '?- p' then $\mathbf{COMP}(PR) \models p$.

If PR returns 'false' for the query '?- p' then $\mathbf{COMP}(PR) \models \neg p$.

Completeness:

If $\mathbf{COMP}(PR) \models p$ and PR is *stratified* (i.e. does not contain loops) then PR will return 'true' for the query '?- p'.

If $\mathbf{COMP}(PR) \models \neg p$ and PR is *stratified* (i.e. does not contain loops) then PR will return 'false' for the query '?- p'.

16. Clark Completion for Predicate Prolog Programs

Clark completion can be applied to predicate Prolog programs as well, but extra steps and conditions must be applied:

- ▶ Programs must be safe – written in such a way that negative sub-goals (i.e. sub-goals with ‘\+’) are evaluated only after the variables in them have all been *ground* (i.e. substituted with terms containing no variables).
- ▶ Clauses must be re-written in general form, i.e. including quantifiers and with only universally quantified variables in their head, before the **COMP** procedure is applied.
- ▶ Clark equality theory must be added to the completion to ensure that the ‘=’ predicate corresponds to Prolog unification.

17. Safe and Unsafe Prolog Programs

An unsafe Prolog program:

```
happy(X) :-  
    \+ sad(X).  
sad(mani).  
hungry(nina).
```

Queries:

```
?- happy(X).  
false.  
?- happy(nina).  
true.
```

A safe Prolog program:

```
happy(X) :-  
    person(X),  
    \+ sad(X).  
sad(mani).  
hungry(nina).  
person(mani).  
person(nina).
```

Query:

```
?- happy(X).  
X=nina.
```

18. Example General Form and Completion

Prolog program PR :

```
likes(X, partner_of(X)).  
likes(nina, X) :- polite(X).  
polite(partner_of(mani)).
```

PR in general form:

$$\begin{aligned} &\forall x_1 \forall x_2. [likes(x_1, x_2) \leftarrow \exists x. (x_1 = x \wedge x_2 = partner_of(x))], \\ &\forall x_1 \forall x_2. [likes(x_1, x_2) \leftarrow \exists x. (x_1 = nina \wedge x_2 = x \wedge polite(x))], \\ &\forall x_1. [polite(x_1) \leftarrow x_1 = partner_of(mani)] \end{aligned}$$

COMP(PR):

$$\begin{aligned} &\forall x_1 \forall x_2. [likes(x_1, x_2) \leftrightarrow [\exists x. (x_1 = x \wedge x_2 = partner_of(x)) \vee \\ &\quad \exists x. (x_1 = nina \wedge x_2 = x \wedge polite(x))]], \\ &\forall x_1. [polite(x_1) \leftrightarrow x_1 = partner_of(mani)], \\ &- \text{plus the Clark equality theory for } PR. \end{aligned}$$

19. Example Completion with Equality Theory

Prolog program PR :

```
likes(X, partner_of(X)).  
likes(nina, X) :- polite(X).  
polite(partner_of(mani)).
```

COMP(PR):

$$\forall x_1 \forall x_2. [likes(x_1, x_2) \leftrightarrow [\exists x. (x_1 = x \wedge x_2 = partner_of(x)) \vee \\ \exists x. (x_1 = nina \wedge x_2 = x \wedge polite(x))]],$$
$$\forall x_1. [polite(x_1) \leftrightarrow x_1 = partner_of(mani)],$$

Clark equality theory for PR :

$$mani \neq nina \wedge \forall x. [partner_of(x) \neq mani \wedge partner_of(x) \neq nina],$$
$$\forall x_1 \forall x_2. [x_1 \neq x_2 \rightarrow partner_of(x_1) \neq partner_of(x_2)],$$

plus for any structured term $\tau[x]$ containing any variable x :

$$\tau[x] \neq x \quad [\text{e.g. } partner_of(partner_of(x)) \neq x]$$

20. Summary

- ▶ A query execution with a stratified (i.e. non-looping) propositional Prolog program without negation-as-failure corresponds to a search for a resolution proof by contradiction.
- ▶ For “sensibly written” (i.e. safe, stratified) Prolog programs with negation-as-failure, their logical meaning can be understood as their Clark completion.
- ▶ For predicate Prolog programs, the Clark completion must include Clark equality theory, because of the way Prolog unifies terms and variables.
- ▶ In A.I. terms, Clark completion is related to the “closed world assumption”, and Clark equality theories are examples of “uniqueness-of-names axioms”.

21. Further Reading for Technical Details

- ▶ Marek Sergot's notes on negation as failure are available at:
https://www.doc.ic.ac.uk/~mjs/teaching/KnowledgeRep491/NBF_491-2x1.pdf
(Marek Sergot is a professor in the Computer Science Department at Imperial College London.)
- ▶ Keith Clark's original paper "Negation as Failure", first published in: Logic and Data Bases, (eds Gallaire and Minker), 1978, can be found at:
<https://www.doc.ic.ac.uk/~klc/NegAsFailure.pdf>