Cloud and Fog Computing for IoT (CS4001)

CIA-1

Question 2: Smart Healthcare Remote Patient Monitoring Platform

Docker image: **https://hub.docker.com/r/shakthe1311/vitalwatch** (v1, latest)

GitHub repo link: **https://github.com/Shakthe/cfccia**

Submitted by **Shakthevell M 23011102092 IoT-B**

1. System Architecture Diagram

I named my system **VitalWatch**. The idea is simple: a patient wears a device that keeps measuring heart rate, blood pressure, oxygen level (SpO2) and body temperature. These readings go to the cloud, where my application checks them. If any reading crosses a danger limit, the system sends an alert straight back to the same wearable device, so the patient knows something is wrong right away.

I built the cloud side on **Amazon Web Services (AWS)**. The full path of the data, from the sensors to the alert on the patient's wrist, has five layers, shown below.




Figure 1.1 — VitalWatch architecture on AWS, from wearable sensors to the alert on the patient's wearable

How the data flows through each layer

Layer	What is there	What it does

1 — Edge / IoT	Sensors on the wearable: heart rate, blood pressure, SpO2, body temperature	Keeps measuring the patient's vital signs and sends them out
2 — AWS Ingestion	AWS IoT Core	Every wearable connects here over MQTT with its own certificate. An IoT Rule picks up the readings from the topic `vitalwatch/telemetry/<device_id>` and passes them on
3 — Processing & App	Amazon Kinesis + Amazon EKS running my container	Kinesis holds the incoming stream of readings. My Flask app (running on Kubernetes) checks each reading against the limits: heart rate above 120 or below 45 bpm, SpO2 below 90%, temperature above 38.5 °C, BP above 180/110 mmHg
4 — Alert Delivery	AWS IoT Core publish (main path) and Amazon SNS (extra path)	When a limit is crossed, the app publishes the alert to that patient's own topic `vitalwatch/alerts/<device_id>`, which the wearable listens to. SNS can also inform doctors/family by SMS or email
5 — Users	The patient's wearable, plus doctors and caregivers	The wearable vibrates and shows the alert to the patient. Doctors can watch everything on a live dashboard

For storage, DynamoDB would keep the patient list and old alerts, Timestream would keep the history of readings, and CloudWatch would watch the health of the system itself.

2. Creating the Docker Image

The application itself is a Python Flask service (`app/app.py`). Since I do not have real medical wearables, the app generates realistic readings for each registered patient (with occasional bad readings mixed in on purpose), checks every reading against the danger limits (`app/alerts.py`), and publishes an alert to the patient's wearable topic whenever a limit is crossed. If no real AWS IoT endpoint is given, the publish is written to the logs instead, so everything can be tested without an AWS account.

Step 1 — Write the Dockerfile

```
FROM python:3.12-slim

ENV PYTHONDONTWRITEBYTECODE=1 \
    PYTHONUNBUFFERED=1

WORKDIR /srv/vitalwatch

COPY requirements.txt .
RUN pip install --no-cache-dir -r requirements.txt

COPY app ./app

RUN useradd --create-home vitalwatch
USER vitalwatch

EXPOSE 5000

HEALTHCHECK --interval=30s --timeout=5s --retries=3 \
  CMD python -c "import urllib.request,sys; \
      sys.exit(0 if urllib.request.urlopen('http://localhost:5000/health').status==200 else
1)"

CMD ["gunicorn", "--workers", "2", "--bind", "0.0.0.0:5000", "app.app:app"]
```

Why I wrote it this way:

- I picked `python:3.12-slim` as the base because it is a much smaller download than the full Python image. My final image came to 213 MB, so Kubernetes can pull it quickly, and a smaller image also means fewer things inside it that could have security holes.
- The two ENV lines stop Python from writing `.pyc` files and make it print logs immediately, so I can see the alerts live with `docker logs` or `kubectl logs` .
- I copy `requirements.txt` and install packages *before* copying my code. Docker caches each step, so when I only change my code, it does not reinstall all the packages again — rebuilds finish in a few seconds.

- I made a normal user called `vitalwatch` and switched to it. The app never runs as root inside the container, which is safer.
- The HEALTHCHECK keeps calling my `/health` endpoint. If the app stops answering, Docker and Kubernetes can see the container is unhealthy and restart it on their own.
- I start the app with gunicorn (with 2 workers) and not with Flask's built-in server, because the built-in server is only meant for development and handles one request at a time.

Step 2 — Add a .dockerignore

I added a `.dockerignore` file so that tests, the git folder, the Kubernetes files, this report and cache files do not get copied into the image. The image only carries what the app actually needs.

Step 3 — Build the image

I built the image with two tags: `v1` (fixed version) and `latest` (always the newest). The final `.` tells Docker to use the current folder as the build context.

```
$ docker build -t shakthe1311/vitalwatch:v1 -t shakthe1311/vitalwatch:latest .
Step 1/11 : FROM python:3.12-slim
Step 2/11 : ENV PYTHONDONTWRITEBYTECODE=1     PYTHONUNBUFFERED=1
Step 3/11 : WORKDIR /srv/vitalwatch
Step 4/11 : COPY requirements.txt .
Step 5/11 : RUN pip install --no-cache-dir -r requirements.txt
Step 6/11 : COPY app ./app
Step 7/11 : RUN useradd --create-home vitalwatch
Step 8/11 : USER vitalwatch
Step 9/11 : EXPOSE 5000
Step 10/11 : HEALTHCHECK --interval=30s --timeout=5s --retries=3   CMD python -c "import
urllib.request,sys; sys.exit(0 if
urllib.request.urlopen('http://localhost:5000/health').status==200 else 1)"
Step 11/11 : CMD ["gunicorn", "--workers", "2", "--bind", "0.0.0.0:5000", "app.app:app"]
Successfully built 17f8a49fc9c5
Successfully tagged shakthe1311/vitalwatch:v1
Successfully tagged shakthe1311/vitalwatch:latest
```

Figure 2.1 — docker build finishing all 11 steps and tagging the image as v1 and latest

Step 4 — Verify locally

Before pushing anything, I ran the image on my machine. `-d` runs it in the background and `-p 5001:5000` connects port 5001 on my laptop to port 5000 inside the container.

```
$ docker run -d --name vitalwatch -p 5001:5000 shakthe1311/vitalwatch:v1
fe69d1942da62bd81af9da6d2be4de9e5dea7b065cae2b8334b189335228b33b

$ curl -s http://localhost:5001/health
{"monitor_interval_s":15,"patients":2,"status":"healthy"}


$ docker ps --filter name=vitalwatch --format "table {{.Names}} {{.Image}}      {{.Status}}
{{.Ports}}"
NAMES                     IMAGE                          STATUS                            PORTS
vitalwatch                shakthe1311/vitalwatch:v1      Up About a minute (healthy)
0.0.0.0:5001->5000/tcp
vitalwatch-control-plane  kindest/node:v1.36.1           Up 20 minutes
127.0.0.1:53055->6443/tcp
```

Figure 2.2 — the container running locally; /health answers "healthy" and docker ps shows the built-in healthcheck passing

I checked that `/health` answered properly, that I could register a new patient through the API, and that alerts were generated and sent to the wearable topic from inside the container.

Step 5 — Push to Docker Hub

```
docker login -u shakthe1311
docker buildx build --platform linux/amd64,linux/arm64 \
  -t shakthe1311/vitalwatch:v1 -t shakthe1311/vitalwatch:latest --push .
```

I pushed the image with buildx for two CPU types (amd64 and arm64), so the same image works on normal cloud servers as well as ARM machines. Anyone can now pull it with `docker pull shakthe1311/vitalwatch:v1` — no login needed, the repository is public.




Figure 2.3 — the public Docker Hub repository shakthe1311/vitalwatch




Figure 2.4 — the Tags page of the repository with the pull command

Step 6 — Deploy anywhere without modification

Nothing in the image is tied to my laptop. All settings (limits, intervals, AWS endpoint) come from environment variables. So the exact image from Docker Hub runs as-is under Kubernetes — `k8s/deployment.yaml` simply says `image: shakthe1311/vitalwatch:v1`, and the CI/CD pipeline (Section 4) deploys the same image into a cluster on every push.

3. Kubernetes Deployment Architecture

All the Kubernetes files are in the `k8s/` folder of the repo. They pull the same public image from Docker Hub and run it:

Resource	File	What it is for
Namespace	namespace.yaml	Puts everything of this project in its own space called `vitalwatch`, away from other apps in the cluster
ConfigMap	configmap.yaml	Holds the danger limits and the monitoring interval. I can change a limit and restart the pods — no need to rebuild the image
Secret	secret.yaml	Holds the AWS IoT endpoint and keys. In my demo these are empty, so the app just logs the wearable pushes instead of really sending them
Deployment	deployment.yaml	Runs 2 copies (replicas) of the container. Updates roll out one pod at a time so the service never goes fully down. Liveness and readiness probes keep hitting `/health`; a stuck pod gets restarted automatically
Service	service.yaml	Gives the pods one stable address. I used NodePort 30090 for my local cluster; on EKS this would just become type LoadBalancer
HPA	service.yaml	Autoscaler — if average CPU goes above 70%, it grows from 2 pods up to 6, and shrinks back later

I tested all of this on a local cluster made with kind. These are the commands I ran:

```
kind create cluster --name vitalwatch
kind load docker-image shakthe1311/vitalwatch:v1 --name vitalwatch
kubectl apply -f k8s/namespace.yaml
kubectl apply -f k8s/
kubectl rollout status deployment/vitalwatch -n vitalwatch
```

```
$ kubectl get all -n vitalwatch
NAME                              READY   STATUS        RESTARTS   AGE
pod/vitalwatch-5f7d85f98-qcqjb    1/1     Running       0          12s
pod/vitalwatch-5f7d85f98-wfsdg    1/1     Running       0          22s
pod/vitalwatch-86c4f469dd-4bpvq   1/1     Terminating   0          18m

NAME                 TYPE       CLUSTER-IP     EXTERNAL-IP   PORT(S)        AGE
service/vitalwatch   NodePort   10.96.21.170   <none>        80:30090/TCP   18m

NAME                          READY   UP-TO-DATE   AVAILABLE   AGE
deployment.apps/vitalwatch    2/2     2            2           18m

NAME                                    DESIRED   CURRENT   READY   AGE
replicaset.apps/vitalwatch-5f7d85f98    2         2         2       22s
replicaset.apps/vitalwatch-86c4f469dd   0         0         0       18m

NAME                                                  REFERENCE                TARGETS
MINPODS   MAXPODS   REPLICAS   AGE
horizontalpodautoscaler.autoscaling/vitalwatch   Deployment/vitalwatch   cpu: <unknown>/70%
2         6         2          18m
```

Figure 3.1 — kubectl get all: both pods Running, the NodePort service, the Deployment with 2/2 ready, and the autoscaler set for 2 to 6 pods

Checking that the deployed service really works

I forwarded the Service to port 8080 on my machine and called the API running inside the cluster:

```
$ curl -s http://localhost:8080/patients | python3 -m json.tool
[
    {
        "age": 67,
        "condition": "post-cardiac surgery",
        "device_id": "wearable-ak-01",
        "name": "Arun Kumar",
        "patient_id": "P-1001"
    },
    {
        "age": 54,
        "condition": "COPD",
        "device_id": "wearable-mn-02",
        "name": "Meera Nair",
        "patient_id": "P-1002"
    }
]
```

Figure 3.2 — GET /patients answered by the pods inside the cluster, listing the registered patients

```
$ curl -s -X POST http://localhost:8080/vitals/refresh | python3 -m json.tool
{
    "alerts": [
        {
            "category": "LOW SPO2 ALERT",
            "message": "Oxygen saturation 85% below 90%",
            "patient_id": "P-1001",
            "reading": {
                "diastolic": 76,
                "heart_rate": 73,
                "spo2": 85,
                "systolic": 109,
                "temperature": 36.6
            },
            "timestamp": "2026-08-22T10:12:55Z",
            "topic": "vitalwatch/alerts/wearable-ak-01"
        }
    ],
    "readings": [
        {
            "diastolic": 76,
            "heart_rate": 73,
            "patient_id": "P-1001",
            "spo2": 85,
            "systolic": 109,
            "temperature": 36.6,
            "timestamp": "2026-08-22T10:12:55Z"
        },
        {
            "diastolic": 83,
            "heart_rate": 92,
            "patient_id": "P-1002",
            "spo2": 96,
            "systolic": 127,
            "temperature": 36.9,
            "timestamp": "2026-08-22T10:12:55Z"
        }
    ]
}
```

Figure 3.3 — POST /vitals/refresh forces one monitoring round. Here the SpO2 came out at 85%, which is under the 90% limit, so a LOW SPO2 ALERT was created and sent to that patient's wearable topic




Figure 3.4 — the dashboard served from the cluster: patients, their latest vitals (bad values in red), and the last alerts that went to the wearables

The pod logs show the same thing from the inside — the moment a reading crosses a limit, an alert goes out to that exact patient's wearable topic. In my demo the MQTT publish is simulated and logged; if a real AWS IoT endpoint is put into the Secret, the very same code does the real publish.

```
$ kubectl logs vitalwatch-86c4f469dd-4bpvq -n vitalwatch
2026-08-22 10:12:23,057 WARNING vitalwatch.alerts WEARABLE PUSH (simulated MQTT) ->
vitalwatch/alerts/wearable-ak-01 [Arun Kumar] FEVER ALERT: Body temperature 40.1 degC exceeds
38.5 degC
2026-08-22 10:12:38,060 WARNING vitalwatch.alerts WEARABLE PUSH (simulated MQTT) ->
vitalwatch/alerts/wearable-ak-01 [Arun Kumar] FEVER ALERT: Body temperature 39.5 degC exceeds
38.5 degC
2026-08-22 10:12:53,146 WARNING vitalwatch.alerts WEARABLE PUSH (simulated MQTT) ->
vitalwatch/alerts/wearable-mn-02 [Meera Nair] TACHYCARDIA ALERT: Heart rate 151 bpm exceeds
120 bpm
2026-08-22 10:12:55,337 WARNING vitalwatch.alerts WEARABLE PUSH (simulated MQTT) ->
vitalwatch/alerts/wearable-ak-01 [Arun Kumar] LOW SPO2 ALERT: Oxygen saturation 85% below 90%
2026-08-22 10:12:55,373 WARNING vitalwatch.alerts WEARABLE PUSH (simulated MQTT) ->
vitalwatch/alerts/wearable-ak-01 [Arun Kumar] LOW SPO2 ALERT: Oxygen saturation 84% below 90%
```

Figure 3.5 — pod logs with FEVER, TACHYCARDIA and LOW SPO2 alerts going to each patient's own wearable topic

4. CI/CD Pipeline Workflow

The pipeline lives in `.github/workflows/ci-cd.yml`. GitHub Actions runs it by itself on every push (and pull request) to `main`. It has three jobs, and each one only starts if the one before it passed:

Job	What it does
Run Unit Tests	Installs the packages and runs my 8 pytest tests. If even one test fails, nothing else runs — a broken image can never get published.
Build and Push to Docker Hub	Logs in to Docker Hub with the repository secrets (`DOCKERHUB_USERNAME` , `DOCKERHUB_TOKEN`) and pushes the image with the tags `latest` , `v1` and the commit id, plus labels saying which commit it was built from.
Deploy to Kubernetes	Starts a fresh Kubernetes cluster right inside the GitHub runner (using kind), loads the newly built image, applies all my `k8s/` files, waits for the rollout to finish, and finally runs a small curl pod that calls `/health` through the cluster Service to prove the deployed app answers.

The two Docker Hub secrets are added in the repo under Settings → Secrets and variables → Actions. Below is a real run of the pipeline — all three jobs finished green in 1m 52s:




Figure 4.1 — GitHub Actions run #4 with all three jobs (tests, build & push, deploy) successful

5. Evaluation Report with Design Justification

Why I chose each technology

Choice	Reason
AWS	The main reason is AWS IoT Core. It gives every wearable its own certificate, handles MQTT at any scale, and most importantly it can publish *back down* to a device. That downlink is exactly how my alert reaches the patient's wearable, which is the core requirement of this question. Kinesis absorbs the flood of readings, EKS runs my container, and SNS covers the doctors/family messages.
Python + Flask	Small, quick to write, and easy for anyone to read. Perfect size for this kind of service.
gunicorn	A proper WSGI server that runs several workers, so more than one request can be served at a time. Flask's own server is only for development.
Docker (slim base)	A 213 MB image that pulls fast, runs as a non-root user and checks its own health. One image, same behaviour everywhere.
Kubernetes	For a patient monitor, downtime is not acceptable. Kubernetes restarts dead pods on its own, runs 2+ copies, updates them one by one with zero downtime, and keeps settings and secrets outside the image.
GitHub Actions	It is already part of GitHub, free for public repos, and the whole pipeline sits in one YAML file in the repo where anyone (including the evaluator) can read it.

Design decisions

- **The alert goes to the patient's own wearable.** Each device listens on its own topic `vitalwatch/alerts/<device_id>`, and the app publishes the alert exactly there. This is the requirement of Question 2, and it is the main path of the design, not an afterthought.
- **The checking code does not care where readings come from.** `alerts.evaluate()` just takes a reading and returns alerts. Today the readings come from my simulator; tomorrow they can come from real IoT Core telemetry, and the alert code does not change at all.
- **All settings are environment variables.** Limits, the monitor interval and the AWS endpoint come from the ConfigMap and Secret. The same image goes from my laptop to a real cluster without being rebuilt. A hospital could even set stricter limits for a cardiac ward just by changing the ConfigMap.
- **The demo never breaks.** If the AWS endpoint is empty, the app logs the wearable push instead of crashing. Put a real endpoint in the Secret and the real MQTT publish happens — no code change.

- **2 replicas + autoscaler.** Two pods mean one can die and patients are still being monitored. The HPA adds pods when load grows, for example when many more patients are added.
- **The limits are medically sensible.** Heart rate above 120 (tachycardia) or below 45 (bradycardia), SpO2 below 90% (low oxygen), temperature above 38.5 °C (fever) and BP above 180/110 (hypertensive crisis) are standard warning levels, so the alerts mean something and do not spam the patient.

Limitations

- Patients and alert history live in the app's memory, so they are lost when a pod restarts. A real deployment would keep them in DynamoDB and the readings in Timestream.
- The wearable push is simulated (logged) in my demo instead of a real AWS IoT Core publish.
- The vital signs come from a simulator, not from real sensors.
- Everything runs in one region; there is no failover to a second region yet.

6. Conclusion and Future Enhancements

Conclusion

VitalWatch covers the complete journey asked for in Question 2. Vital signs (heart rate, blood pressure, SpO2, body temperature) are collected non-stop for every registered patient, each reading is checked against clear medical limits, and the moment something is wrong the alert is pushed to that patient's own wearable device, with doctors and family covered through SNS as a second channel. The app is packed into a Docker image that anyone can pull from Docker Hub (`shakthe1311/vitalwatch:v1`), it runs on Kubernetes with health probes, two replicas, autoscaling and zero-downtime updates, and every push to GitHub is tested, built, published and deployed automatically by the Actions pipeline. Since the design sits on managed AWS services (IoT Core, Kinesis, EKS, SNS, DynamoDB), the same architecture would carry over to a real hospital deployment.

Future enhancements

- **Real wearables** — connect actual BLE devices through a small gateway to AWS IoT Core instead of the simulator.
- **Proper storage** — DynamoDB for patients and alert history, Timestream for the reading history and trends.
- **Smarter alerts** — use anomaly detection on the trend of a patient's vitals to warn *before* a hard limit is crossed, and tune limits per patient.
- **Fog layer at home** — run the limit checks on a small box in the patient's house (AWS IoT Greengrass) so alerts still work even when the internet is down.
- **Escalation** — if the patient does not acknowledge the alert on the wearable, automatically inform the doctor or emergency services; connect to hospital record systems (FHIR).
- **Security and privacy** — encryption end to end, audit logs, and handling patient data as per healthcare rules like HIPAA.
- **Monitoring the monitor** — Prometheus and Grafana dashboards plus CloudWatch alarms on the system itself.
- **Two regions** — run the cluster in a second region with automatic failover so even a region outage does not stop patient monitoring.