

C:\ Select Command Prompt - mysql -u root -p

```
mysql> use database2;
```

Database changed

```
mysql> show tables;
```

Empty set (0.01 sec)

```
mysql> create table persons(personID int,firstname varchar(20),lastname varchar(20),age int);
```

Query OK, 0 rows affected (0.05 sec)

```
mysql> select*from persons;
```

Empty set (0.01 sec)

```
mysql> insert into persons values('001','ABC','Pune','Pune','411001','MH','100000');
```

ERROR 1136 (21S01): Column count doesn't match value count at row 1

```
mysql> insert into persons values('001','ABC','XYZ','29');
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into persons values('002','XYZ','ABC','31');
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into persons values('003','PQR','LMN','33');
```

Query OK, 1 row affected (0.01 sec)

```
mysql> select*from persons;
```

personID	firstname	lastname	age
1	ABC	XYZ	29
2	XYZ	ABC	31
3	PQR	LMN	33

3 rows in set (0.00 sec)

```
mysql>
```

```
mysql> alter table persons add middlename varchar(20);
```

```
Query OK, 0 rows affected (0.04 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> select*from persons;
```

personID	firstname	lastname	age	middlename
1	ABC	XYZ	29	NULL
2	XYZ	ABC	31	NULL
3	PQR	LMN	33	NULL

```
3 rows in set (0.00 sec)
```

```
mysql> alter table persons drop middlename;
```

```
Query OK, 0 rows affected (0.09 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> select*from persons;
```

personID	firstname	lastname	age
1	ABC	XYZ	29
2	XYZ	ABC	31
3	PQR	LMN	33

```
3 rows in set (0.00 sec)
```

```
mysql>
```

```

C:\ Select Command Prompt - mysql -u root -p
mysql> create table customer1(id int,name varchar(20),city varchar(20),sal int
);
Query OK, 0 rows affected (0.03 sec)

mysql> select*from customer;
Empty set (0.00 sec)

mysql> insert into customer values('1','a','Pune','10000');
Query OK, 1 row affected (0.01 sec)

mysql> insert into customer values('2','b','Mumbai','9000');
Query OK, 1 row affected (0.01 sec)

mysql> insert into customer values('3','c','Nashik','9500');
Query OK, 1 row affected (0.01 sec)

mysql> select*from customer;
+-----+-----+-----+-----+
| id    | name  | city   | sal    |
+-----+-----+-----+-----+
| 1     | a     | Pune   | 10000  |
| 2     | b     | Mumbai | 9000   |
| 3     | c     | Nashik | 9500   |
+-----+-----+-----+-----+
3 rows in set (0.01 sec)

mysql> update customer set city='Mumbai';
Query OK, 2 rows affected (0.01 sec)
Rows matched: 3  Changed: 2  Warnings: 0

mysql> update customer set name='BSIOTR';
Query OK, 3 rows affected (0.01 sec)
Rows matched: 3  Changed: 3  Warnings: 0

mysql> select*from customer;
+-----+-----+-----+-----+
| id    | name   | city   | sal    |
+-----+-----+-----+-----+
| 1     | BSIOTR | Mumbai | 10000  |

```

C:\> Select Command Prompt - mysql -u root -p

mysql> select\*from customer;

id	name	city	sal
1	a	Pune	10000
2	b	Mumbai	9000
3	c	Nashik	9500

3 rows in set (0.01 sec)

mysql> update customer set city='Mumbai';

Query OK, 2 rows affected (0.01 sec)

Rows matched: 3 Changed: 2 Warnings: 0

mysql> update customer set name='BSIOTR';

Query OK, 3 rows affected (0.01 sec)

Rows matched: 3 Changed: 3 Warnings: 0

mysql> select\*from customer;

id	name	city	sal
1	BSIOTR	Mumbai	10000
2	BSIOTR	Mumbai	9000
3	BSIOTR	Mumbai	9500

3 rows in set (0.00 sec)

mysql> desc customer;

Field	Type	Null	Key	Default	Extra
id	int	YES		NULL	
name	varchar(20)	YES		NULL	
city	varchar(20)	YES		NULL	
sal	int	YES		NULL	

4 rows in set (0.01 sec)