Project 1: Tender RAG 2.0
Stage-by-stage plan and reference

German public-tender documents · private · measured · reliable

Upgrade of the existing multilingual-tender-rag repository

Weeks 1 to 12 (5 Nov 2026 to 27 Jan 2027) · about 52 of 76 project hours

Target roles: AI / GenAI Engineer, RAG and Document-AI Engineer

Prepared for: Shalin Vachheta

Status: plan v1.2. Part 1 describes the code as READ, not as run. Nothing in the stages has been built or measured yet. Targets marked TBD are set from the baseline measurement. Companion: Project 2 plan (separate PDF).

Version 1.2 · 4 November 2026 · repository branch chore/repo-cleanup

Contents

1. Summary and status 3

2. Problem, users and scope 4

3. The data 5

4. The system today 5

5. Known defects (22) 8

6. Job targeting for this project 10

7. Lessons from the reference projects 12

8. Interview-question map 12

9. Stage overview and schedule 14

10. Stage S0: Baseline and safety 15

11. Stage S1: Retrieval fixes 16

12. Stage S2: Evaluation 17

13. Stage S3: Reliability, scale and access control 18

14. Stage S4: Polish and deploy 18

15. Evaluation protocol 19

16. Experiments 21

17. Reliability, scaling, observability and security 21

18. Mandatory, stretch, risks and cut order 23

19. Deliverables, evidence and interview stories 23

20. Interface to Project 2 24

21. Decision log and next steps 25

22. Sources and verification status 25

23. Glossary 26

Appendix: decision record template 26

PART 1 · OVERVIEW AND CURRENT STATE

What the project is, the data, the system as it is today, and what is wrong with it

1. Summary and status

Decision. Upgrade the existing German tender RAG system in place into a measured, reliable, production-style service. The order is fixed: **evaluation first, reliability second, scaling third**. Every change has a reason, a test and a before/after number. This project takes about 52.5 of the 75.5 hours planned for both projects (weeks 1 to 7 and 9 to 11) plus a share of the polish week.

Item	Value
Repository	multilingual-tender-rag (this repository, upgraded in place; its git remote still uses the old name ragbot-core, which GitHub redirects)
What it is	Private question answering over 112 German public tenders, with page-level citations, in German and English
Roles it targets	AI Engineer, GenAI Engineer, RAG / Document-AI Engineer (junior to 3 years); evidence also useful for Forward Deployed Engineer roles
Core evidence	Before/after retrieval metrics, citation precision, refusal and false-refusal rate, failure analysis per stage, p95 latency at 1/5/20 users
Stack	Python, FastAPI, Qdrant, Jina embeddings v3, BM25, BGE reranker, Ollama, pytest, Docker, GitHub Actions, Langfuse or Phoenix
Hours	S0 12 · S1 18.5 · S2 13 · S3 9 = 52.5 h, plus a shared 6 h polish week
Machine	RTX 4060 Laptop GPU with 8 GB; Python 3.14 installed (project needs a 3.12 environment); Docker installed but stopped; Ollama not installed

Honest status. Everything about the current system comes from reading the source code. Qdrant and Ollama are not running on this machine, so nothing has been executed and no quality number exists. The old 30.6 % “retrieval quality” in evaluation/EVALUATION_REPORT.md came from heuristic manual scoring; it is not a Recall@k. All targets here are marked TBD until the baseline is measured.

What is new in version 1.2

- **Separate documents:** this project and the future agent project are now two PDFs; docs/TENDER_RAG_REFERENCE.md holds this project's content as Markdown. The older plan files were merged into it.
- **From the review:** read-only or isolated baseline; test questions sampled by held-out tender and sealed with a hash; code fixes (Type A) and corpus changes (Type B) measured separately; manual citation checks; supersession needs evidence; failure-analysis table; mandatory versus stretch split.
- **From the interview question sets:** false-refusal rate; aggregation questions through the metadata route; a cross-language experiment; re-indexing into a new collection with an alias; version tags in every trace; an injection test document; a CI evaluation gate; a passages-per-answer sweep; a contextual chunk header (stretch); an access-control filter promoted to mandatory.
- **From the jamwithai course repository:** factories and dependency injection (they also fix the reranker and embedder reloads), a test layout of unit, api and integration, Makefile, ruff and pre-commit, a git tag per stage, a ready Langfuse compose template, a cache key from all request parameters, and two stretch experiments (BM25 inside Qdrant, chunk-size sweep).
- **Hours:** 72 became 75.5 (about 6.3 h per week). Section 18 shows what to drop to get back to exactly 6 h per week.

2. Problem, users and scope

Business problem. Companies that bid for public contracts in Germany receive “Vergabeunterlagen”: a zip with 10 to 100 files per tender (scanned PDFs, plans, Word forms, GAEB bills of quantities). A bid manager must find the deadline, the issuing authority, the required declarations (for example Formblatt 124 Eigenerklärung), the work package and the risks for every tender. This takes hours.

Why RAG and not only an LLM. The answers live in these specific documents, not in a model's training data. Retrieval brings the right passages, generation writes the answer from them. Answers must be traceable to a file and a page, because people make bidding decisions on them. Tenders change daily: updating an index is cheap, retraining a model is not.

Why local. Qdrant, Ollama and the embedding model all run on one machine, so no question or passage leaves the computer. German postings and a 2026 trend article describe the same preference for local pipelines.

The general problem behind it. Organisations hold large, messy, multi-format, multi-language collections and need answers that are complete, correct, traceable and honest when evidence is missing or contradictory, and that stay that way as the collection and the number of users grow. Recent research shows this is not solved:

Study	Finding	What it means for us
HERB, Salesforce, EMNLP 2025 Industry (39,190 enterprise artifacts)	Best agentic RAG method averaged 32.96; retrieval was the main bottleneck	Measure retrieval completeness, not only answer fluency
EnterpriseRAG, arXiv 2608.11584 (983 cases, 13 LLMs)	Best model 83.8 % on single constraints but 26.8 % on all together; flagged contradictions in under 45 % of cases; refused correctly at most 42.7 %	Test conflicts and refusals explicitly
From BM25 to Corrective RAG, arXiv 2604.01733 (23,088 questions)	Hybrid retrieval plus reranking was best (Recall@5 0.816); BM25 beat dense retrieval on financial text and tables	Compare BM25, dense, hybrid and reranked on our own questions
EnterpriseRAG-Bench, arXiv 2605.05253	About 500,000 documents, 500 questions; English text only, no PDFs or scans	Optional later; it cannot test OCR or layout

Users and tasks

- **Exact lookup:** “Show tender 20046645”: deterministic, no LLM, must never hallucinate.
- **Question answering** over one or several tenders, German or English, with file and page citations, or an honest refusal.
- **Aggregation and listing:** “How many tenders in region X in 2023?”: answered from the metadata table, not by RAG.
- **Comparison** of two to four tenders on deadline, authority and required declarations (the basis for Project 2).
- **Primary user:** a bid manager screening tenders. **Secondary:** a reviewer who checks the sources.

Scope

In scope (mandatory, section 18)	Not in scope
Safe reproducible pipeline; baseline; retrieval fixes; 48-question evaluation set with sealed test split; retrieval and answer comparison; claim-level citation checks; failure analysis; access-control filter; injection test; load test at 1/5/20 users; Docker; CI; one AWS workflow	Fine-tuning models; Kubernetes; multi-region deployment; a public web service; corpus growth beyond the 112 tenders; agents (Project 2)

3. The data


Item	Verified fact (checked on disk, 4 Nov 2026)
Tenders	112 folders in data/raw, one zip each, from DTAD (April 2023 packages), plus one metadata spreadsheet (VUDb_Data_2025-07-13)
Zip health	105 zips are valid; 7 are truncated downloads (20044887, 20046902, 20046916, 20046935, 20046979, 20046996, 20047346), kept as real broken-input test fixtures
Unzipped content	1,781 files in data/extract: 1,488 PDF, 103 DOCX, 107 GAEB (62 x83, 33 d83, 12 p83), 41 nested zips, 13 XLSX, a few other types
Size	about 1.4 GB raw, 1.8 GB extracted
Path collisions	Measured from the zips by CRC: 101 file paths occur in more than one tender; for 66 the content differs (159 file versions overwritten), 35 are byte-identical. Nested zips not counted
Metadata	Excel columns include DTAD ID, title, date, region, issuing authority, source URL (cleaned into data/metadata/cleaned_metadata.xlsx)
Back-up	**data/raw is the only copy of the tenders.** The legacy prototype code is archived outside the repository at D:/Projects/_archive/legacy_rag_prototypes_2025.zip

4. The system today


Architecture at a glance

The **offline** half runs once or when documents change and turns files into a searchable index. The **online** half runs on every question. Red outlines mark steps with known defects (section 5).

Offline: files to index



Online: question to answer



Entry points

Command	File	What it does
docker compose up -d	docker-compose.yml	Starts Qdrant 1.9.2 on port 6333
python scripts/data_processing/ingest.py	scripts/data_processing/ingest.py	Unzips, logs, cleans the Excel, triggers indexing. **Default mode is fresh (destructive)**
python scripts/data_processing/embed.py --mode MODE	scripts/data_processing/embed.py	Chunks, embeds and upserts PDFs. MODE is fresh, append or ocr-only; **default fresh deletes the collection**
python scripts/deployment/build_bm25_index.py	scripts/deployment/build_bm25_index.py	Reads all chunks from Qdrant and writes data/state/bm25_index.pkl
uvicorn src.api.main:app --port 8000	src/api/main.py	REST API: /health, /api/v1/search, /api/v1/chat
streamlit run ui/streamlit/app.py	ui/streamlit/app.py	Chat UI (uses core.qa directly, not the API)
pytest tests/	tests/ (7 files)	Caching, API, ID lookup, multilingual tests (pass status not yet verified)

Module map

Path	Role
src/core/config.py	Settings (pydantic-settings); every field can be overridden by an environment variable with prefix RAGBOT_
src/core/io.py	ZipIngestor (extract, hash, log), ExcelCleaner, PDFLoader (PyMuPDF + Tesseract OCR), ExcelMetadataJoiner
src/core/index.py	PageAwareChunker and Indexer (Jina v3, Qdrant upsert, collection handling)
src/core/search.py	Dense search, RRF, hybrid search, query embedding cache, tender ID detection
src/core/hybrid_search.py	BM25Index (rank_bm25, German tokenizer, pickle save and load)
src/core/qa.py	retrieve_candidates (language routing, fusion, reranking) and answer_query (prompt and Ollama call)
src/core/domain.py, logger.py	DocumentPage and DocumentChunk data classes; pipeline logger
src/api/	FastAPI app, X-API-Key check, 60 requests per minute limit, search and chat routes, request and response models
scripts/	data_processing (ingest, embed, unified processor), deployment (BM25 build, deploy script), evaluation (hybrid validation)
ui/streamlit/app.py	Streamlit chat, metadata route, sources panel
evaluation/	Manual and RAGAS evaluation scripts, query lists, old results, EVALUATION_REPORT.md
docs/	This reference, the two stage PDFs, planning images, architecture diagram (docs/references is local only)

Settings that matter (src/core/config.py)

Setting	Current value	Note
llm_model	qwen2.5:1.5b	Small; compared with a 3B model in E5
embed_model / embed_dim	jinaai/jina-embeddings-v3 / 1024	Revision pinned in code; called without the retrieval task (defect 7)
chunk_size / chunk_overlap	1000 / 400 characters	40 % overlap roughly doubles the chunk count
topk_candidate / final_k	100 / 16	topk_candidate is never used online (defect 22)
use_hybrid / dual_query	True / True	Dual query translates non-German questions to German with the LLM (E6)
use_rerank / reranker_model	True / BAAI/bge-reranker-v2-m3	rerank_keep 24, rerank_weight 0.8
qdrant_collection	tender_docs_jina-v3_d1024_fresh	Override with RAGBOT_QDRANT_COLLECTION for isolated runs
API key	RAGBOT_API_KEY, default dev-key-12345	Defect 4

Pipeline step by step

Step	What the code does	Why it exists
Ingest (io.py)	Hashes each zip (SHA-256) and skips known ones; extracts members, nested zips recursively; labels each file (type, size, language) in data/logs/ingest_YYYY-MM.csv; cleans the metadata Excel	Zips cannot be searched; hashing makes re-runs cheap; the log is an audit trail
Load PDF	PyMuPDF text layer; a page with fewer than 50 characters is rendered at 300 dpi and read by Tesseract (German + English)	Many tender pages are stamped, signed scans
Chunk (index.py)	Cuts the text of one PDF into 1,000-character pieces with 400 overlap; remembers first and last page	Embedding models have input limits; small chunks give precise matches and citations; overlap saves facts cut at a boundary
Metadata join	Finds the tender ID in the chunk or in the digits of the file name, merges the Excel row (title, date, region, authority)	Filter by tender, region or date; show titles
Embed and store	Jina v3 at a pinned revision, GPU fp16, normalised, 1,024-D; point ID = UUID5(file hash + chunk index) so re-indexing overwrites instead of duplicating; payload keeps path, pages, metadata and the first 1,500 characters	Multilingual, long input, local. Qdrant gives fast vector search with payload filters
BM25 file	Reads every chunk back from Qdrant, tokenises with a German stop-word list, builds BM25Okapi, saves data/state/bm25_index.pkl (7.8 MB)	Exact words, IDs and form numbers: vectors are weak on these
Route (UI)	A 7 to 8 digit number looks up that tender in the Excel; a year or region lists matching tenders; no LLM involved	Fast, cannot hallucinate
Hybrid search	Dense and BM25 each return only as many results as the final count (16 in the UI; the API's top_k, default 5, in /chat), not the configured pool of 100. Merged with Reciprocal Rank Fusion (1 / (60 + rank)); non-German questions are also translated to German with the LLM and searched again	Meaning plus exact terms
Rerank	BGE cross-encoder reads question and passage together, blends 0.8 x rerank + 0.2 x earlier score; keeps up to 24, final cut 16 (it only ever sees the small pool above)	Much better ordering, too slow for the whole corpus
Answer	Prompt with numbered sources (UI: English prompt; API: German prompt), Ollama, sources shown with page numbers	Grounded answer with citations

One question traced end to end

Question: “Welche Eigenerklärungen muss der Bieter für Tender 20046645 abgeben?” (Which self-declarations must the bidder submit for tender 20046645?)

Step	What happens today	Consequence
UI metadata route	Finds “20046645” (8 digits), looks it up in the Excel, returns title, date, region, authority and stops	The actual question (which declarations?) is never answered
Dense search	detect_tender_id finds the ID, filters on payload field id, which does not exist, so 0 results, then falls back to an unfiltered search	Results from any tender
BM25	Tokens: welche, eigenerklärungen, bieter, tender, 20046645, abgeben. The ID is in no chunk text; “eigenerklärungen” does not match “eigenerklärung”	Generic form text from many tenders
RRF	Fuses the dense result with BM25 results in scrambled order, from a pool of only 16	Fusion is partly random
Rerank	Loads the BGE model from disk, re-orders the small pool	Slow; best passages may belong to another tender
Answer	Context cut to 3,000 characters, qwen2.5 1.5B answers	Plausible text that may describe the wrong tender, with citations that look right

Why each component exists

Component	Why it is there	Alternative	What decides it
SHA-256 manifest	Do not reprocess unchanged zips	Re-run everything	Keep; extend to per-file versions
PyMuPDF text layer	Fast, exact text for digital PDFs	Docling, Unstructured, MinerU	E4 (stretch challenger)
Tesseract OCR fallback	Scanned pages would be empty	PaddleOCR, Docling OCR	E4: character error rate
Character chunker 1000/400	Simple, keeps page numbers	Section-aware chunks, tables as units, contextual header	E7 (stretch)
Jina v3 embeddings	Multilingual, long input, local	bge-m3 (dense + sparse)	E2, then only if a problem remains
Qdrant	Vector search with filters, local, native hybrid queries	pgvector, OpenSearch	Keep
BM25 (rank_bm25 + pickle)	Exact IDs and terms	Qdrant sparse vectors	E1; pickle files are a code-execution risk if untrusted
RRF fusion	Combines rankings without score calibration	Weighted score fusion	E1
Dual query with LLM translation	English question finds German text	Rely on multilingual embeddings only	E6
BGE reranker v2-m3	Better relevance ordering	None	E1: quality gain against added latency
Metadata route (Excel)	Exact facts and counts without an LLM	—	Keep; fix the ID regex; add counts
Ollama qwen2.5 1.5B	Private, free, fits an 8 GB GPU	3B or 7B local; one hosted model as a labelled comparison	E5
FastAPI + key + rate limit	Programmatic access, basic protection	—	Keep; remove the default key
Streamlit	Quick demo UI	—	Keep; later behind the API
LRU caches	Repeat questions return fast	Version-aware cache	Add the index version to the key (S3)

5. Known defects (22)

Found by reading the code line by line. Each defect gets a test when it is fixed. **Rule: measure the baseline first, then fix one defect at a time and record the effect of each.** The old evaluation ran with defects 1, 6, 7, 8 and 10 all active, so it says little about what a corrected system can do.

#	Defect	Effect	Fix	Pri	Test to write
1	Extraction writes every file to one shared folder, not per tender: 101 paths shared, 66 with differing content (159 versions overwritten), 35 identical	Tender-specific documents vanish; every chunk loses its tender link	S1 B	P0	Two tenders with the same member name both exist under their tender folder
2	Zip path traversal (io.py line 135); no zip-bomb or nesting limit	A crafted zip can write outside the data folder	S0	P0	A zip with a ../ member is rejected, nothing written outside
3	ingest.py and embed.py default to mode fresh, which deletes the Qdrant collection	One wrong command destroys the index	S0	P0	Default mode leaves an existing collection intact
4	Fallback API key dev-key-12345	Anyone can call the API	S0	P0	App refuses to start without RAGBOT_API_KEY
5	Chat text rendered as raw HTML in Streamlit	Script injection	S0	P0	A message containing a script tag is shown escaped
6	Only PDFs are indexed: 103 DOCX, 107 GAEB, 13 XLSX ignored	Forms and bills of quantities cannot be found	S1 B	P1	A DOCX fixture is indexed and retrieved

#	Defect	Effect	Fix	Pri	Test to write
7	Jina v3 called without its retrieval task; code adds nomic-style prefixes. Probable; to be tested	Retrieval adapters unused; lower recall possible	S1 A (E2)	P1	Dense recall with task versus with prefix on the dev set
8	Exact-ID filter uses payload field id, chunks store dtad_id	Filter returns nothing and silently falls back	S1 B	P1	An ID question returns only chunks of that tender
9	Metadata join needs the ID in the file name; extracted names are like 124.pdf	Most chunks have no tender metadata	S1 B	P1	100 % of chunks of a sample tender carry dtad_id
10	BM25 hits fetched with retrieve(), which does not keep their order	RRF fuses scrambled ranks	S1 A	P1	A known BM25 ranking survives fusion
11	Reranker model loaded on every question; errors swallowed	Seconds of delay; silent failure	S1 A	P1	Constructed once across three calls; error is raised
12	/chat retrieves twice and ignores top_k for the answer	Double cost; wrong evidence count	S1 A	P1	One retrieval per request; top_k respected
13	Context cut to 3,000 characters	Only 2 to 3 of 16 passages reach the LLM	S1 A	P1	All selected passages fit a token budget and are present
14	Scores on different scales mixed (cosine, BM25, RRF, rerank) and compared with fixed thresholds	A threshold such as 0.35 means nothing	S1 A / S2	P1	Refusal decided by the evidence check, not a raw score
15	Any 7 to 8 digit number is treated as a tender ID	A CPV code question answers “not in the tender data”	S1 A	P1	A CPV code question is not routed as an ID
16	Two online pipelines (UI and API) with different prompts and refusal texts	Same question, different answers	S1 A	P1	UI and API return the same refusal text and answer
22	Candidate pool equals the final count: qa.py:116 passes its final limit to both searches, so topk_candidate = 100 is never used online	Dense and BM25 see 5 to 16 results each; RRF and reranker have little to choose from; recall is capped	S1 A	P1	A pool of 100 reaches the reranker; the final count is respected
17	A second copy of the embedding model is loaded at import (qa.py)	Slow start, wasted GPU memory	S1 A	P2	One embedder instance per process
18	Caches ignore the index version	Stale results after re-indexing	S3	P2	Changing the index version changes the cache key
19	BM25 has no German compound splitting or stemming	Baustelleneinrichtung does not match Baustelle	stretch	P2	Compound term matches its parts
20	pyproject.toml packages core instead of src; fastapi, uvicorn, rank_bm25 missing; UI import shim points to ui/	Install fails; UI may not start	S0	P2	pip install -e . works; all modules import
21	Garbled import line 3 in qa.py	Runs only because half the line is a comment	S0	P2	Module imports cleanly

PART 2 · TARGETS AND LESSONS

Which jobs this project answers, what the reference projects taught, which interview questions it covers

6. Job targeting for this project

Market signals

Source	Finding	Caveat
DEV Community, 390 AI-engineer postings (Jul 2026)	LLMs 63 %, Python 59 %, evaluation 56 %, agents 50 %; evaluation outranked every classical ML framework	Small, self-published sample
Simpleapply 2026 report	Generative AI, LLM and RAG each appear in 14 to 18 % of AI/ML postings; Python 77 %	Different method and geography
Lightcast data via Second Talent (Stanford AI Index 2026)	Agentic-AI skills grew from 0.06 % to 0.23 % of US postings, 2024 to 2025	Small share, fast growth; US data
Open Telekom Cloud case; tech-insider.org (2026)	Tender-document AI hosted in Germany is a real use case; German companies are moving to local RAG pipelines	Vendor and trend articles

Verified postings (examples, not a survey)

Posting (opened and read)	Level / place	Requires	Nice to have
Accenture, (Junior) Generative AI Engineer	Early career, Hamburg	Python and FastAPI backends, practical AI or data apps, LLMs + RAG + tool calling + agents, testing, Git, SQL, AI coding tools (Claude Code, Copilot), German and English	LangChain, vector databases, knowledge graphs, LLM evaluation, Docker/Kubernetes, MLOps, MCP servers, TypeScript/React; Azure and Databricks named
Capco, Mid Level AI Engineer	2 to 3 years, Orlando USA (hybrid)	LLM apps (OpenAI, Anthropic, open source), Python REST and microservices, RAG with a vector DB (Qdrant named), Git/CI/CD/testing, one cloud	Multi-agent frameworks (LangGraph named), MCP, LangSmith / Langfuse / Arize, Docker/Kubernetes
RightShip, AI Engineer	3+ years, London	Python engineering, LangGraph agents and RAG with tool use, state management, structured outputs	Evaluation datasets and LLM-as-judge, hybrid retrieval, Azure, Databricks/MLflow, document understanding, public portfolio

Not verified: the European Dynamics and Titan AI pages returned only a title; Neurawork, ALGEBRA, zeroG, HTGF, MTR Legal and PER Intelligence were not opened or could not be found. Only one of the three verified postings is in Germany. These are examples, not a market survey.

Roles and what to emphasise

Role title (typical)	Level	Emphasise	Main evidence
(Junior) Generative AI Engineer / AI Engineer	0 to 2 years	Python, FastAPI, RAG, testing, SQL, evaluation	Reports, tests, API
RAG Engineer / Document-AI Engineer	0 to 3 years	OCR, hybrid retrieval, reranking, citations, evaluation, failure analysis	Comparison, OCR and failure-analysis reports
Forward Deployed Engineer / AI Consultant	Junior to mid	Business framing, messy data, privacy, demo, accuracy gap story	Problem statement, local-first design, baseline-to-fix story, demo video
MLOps / LLMOps Engineer	Junior to mid	CI/CD, monitoring, load tests, versioned releases	CI gate, traces, load test, alias rollback; your existing MLOps repositories

Requirement to proof

Employers ask for	Seen in	Proof in this project
Python, FastAPI, testing, Git, CI	All three postings	Refactored API, pytest suite, GitHub Actions (S0, S3)
RAG with a vector database (Qdrant named)	All three	Qdrant hybrid retrieval with measured quality (S1, S2)
Evaluation datasets, LLM-as-judge, regression tests	Capco, RightShip, Accenture (nice-to-have); 56 % in the 390-post sample	48-question set, sealed test split, comparison report, failure analysis, CI gate (S2, S3)
Tracing and observability	Capco; widely named	Structured traces with version tags; Langfuse or Phoenix (S1)
Hybrid retrieval; document understanding	RightShip	E1 and E4 reports
Docker, one cloud (AWS, Azure or GCP)	All three	Docker Compose, Actions, one AWS workflow; know the Azure equivalents (S3 = Blob Storage, ECR = Container Registry)
Security and access control	Common in descriptions	Safe ingestion, no default key, access-control filter, injection test (S0, S3)
German and English; AI coding tools	Accenture	English README with German summary; describe how you use Claude Code and how tests verify its output
Public portfolio	RightShip	Public repository with reports and decision records

Keywords for the CV and README (only those you can demonstrate): RAG · hybrid search · BM25 · Qdrant · embeddings · reranking · OCR · document AI · German NLP · citations · evaluation datasets · failure analysis · Langfuse or Phoenix · FastAPI · Pydantic · pytest · Docker · GitHub Actions · AWS · access control · prompt-injection testing · local LLM (Ollama) · GDPR-friendly design

7. Lessons from the reference projects

Reference	What it is	What we take	What we leave
Clinical-RAG (German gynecology guidelines)	Local German RAG on Ollama, hybrid search, reranker, refuses without evidence	Frozen results in reports/; recall with and without the reranker (0.50 to 0.83 there); refusal on trap questions; one exact refusal sentence	Only 3 gold questions; ChromaDB
8hr-MARATHON (sourangshupal; the notes doc points to the d-hackmt original)	Enterprise agentic RAG with guardrails, gateway, tracing, RAGAS, CI, AWS	Folder layout; tests for auth, rate limit, retry, health; ruff + pytest CI; Locust load test; /metrics	All-cloud stack conflicts with local-first
ATLAS Enterprise AI	Bedrock + Pinecone + LangGraph learning project	Permission filter inside the vector query; tables for document versions, audit, feedback; guard, retrieve, no-evidence or generate, validate	AWS lock-in; its README says it is not production-secure
Enterprise IT-Support Copilot	Corrective RAG with LangGraph	Grade the evidence, rewrite once, refuse honestly; return the decision trace	Web-search fallback (wrong for private data)
pdichone production course	About 40 standalone lesson files	Patterns for error handling, security, testing	Not an architecture
jamwithai production-agentic-rag-course (arXiv Paper Curator; MIT; about 10k stars; the original of your fork)	Seven-week course: Docker infrastructure, Airflow ingestion with Docling, BM25 in OpenSearch, chunking and hybrid search, RAG with Ollama, Langfuse tracing with a Redis cache, LangGraph agentic RAG and a Telegram bot	BM25 first, then hybrid (our E1 order); factories and dependency injection; tests split into unit, api and integration with mocked clients; Makefile, ruff, pre-commit; a git tag per stage; the six Langfuse services for a compose file; an exact-match cache key built from all request parameters; a word chunker with a minimum size and boosted title fields; the graph guardrail, retrieve, grade, rewrite (max 2), generate	OpenSearch and Airflow (overkill for 112 static tenders); Telegram and Gradio; its cloud embedding API; an LLM guardrail call on every request (extra latency on an 8 GB GPU; measure first)
Codebasics AI System Design guide	13-page guide with 11 production blocks	Numbers before boxes; route to the cheapest approach; version-aware caches; fallback; pre-launch checklist	Support-chatbot specifics
Galileo Mastering RAG (ebook)	Enterprise RAG guide	Only the cover was viewed; not reviewed	—

Shared lesson: none of these projects handles messy, scanned, multi-format German documents. They use clean markdown or a handful of PDFs. Ingestion, OCR, GAEB files and tender identity are our hard part, and the part these projects skip. A limited repository search found no open-source RAG project for German public tenders. That is not proof that none exists, so present this as a specific technical and domain-focused contribution, not a first-of-its-kind claim.

Tools surveyed (stars on GitHub, 4 Nov 2026)

Group	Projects	Use here
RAG platforms (study, do not copy)	dify 160k · ragflow 93k · onyx 33k · haystack 27k · kotaemon 26k · Verba 7.7k · cognita 4.4k (quiet since Mar 2026)	RAGFlow for document-aware chunking ideas; kotaemon for citation highlighting; Onyx for document-level permissions
Parsing and OCR	docling 70k · PaddleOCR 92k · MinerU 83k · unstructured 16k	E4 challenger (stretch); DOCX and XLSX coverage
Evaluation and tracing	langfuse 37k · deepeval 19k · ragas 16k (last push Feb 2026) · phoenix 12k	Langfuse or Phoenix; RAGAS names for the metrics
Benchmarks (optional)	EnterpriseRAG-Bench (English text only); OmniDocBench (English and Chinese, no German)	Stretch; our own questions are the main benchmark

8. Interview-question map

From the seven Krish Naik interview sets (350 questions; questions read, answers not). This table shows where this project answers a question with its own evidence. RAG = RAG set, EV = Evals and Guardrails, OP = LLMOps, FDE = Forward Deployed Engineer.

Question	Where this project answers it
RAG Q18: the answer exists but the retriever never returns it	Failure labels (ingestion, OCR, retrieval, ranking); defects 1, 6, 22
RAG Q19: right chunks, wrong answer	Generation label; E5 passages sweep and evidence check
RAG Q7, Q8, Q20: hybrid search, reranking, RRF	E1; defect 10 (rank order); defect 22 (candidate pool)
RAG Q9: top-k and lost in the middle	E5: 3 / 5 / 8 passages sent to the LLM
RAG Q10: metadata and filters; Q47: aggregation questions	Metadata route; two aggregation questions in the set; access-control filter
RAG Q13, Q25, Q26: evaluation and datasets	Section 15: 48 questions, sealed split, failure analysis
RAG Q22: contextual retrieval	E7 contextual chunk header (stretch)
RAG Q23: tables	Table / GAEB category; E3
RAG Q27: outdated answers	Alias re-index, version-aware cache, stale-chunk removal
RAG Q28: multilingual retrieval	E6: translated query against direct multilingual retrieval
RAG Q32: conflicting sources	Versions and amendments category; supersession needs evidence
RAG Q37: permission-aware retrieval; Q49: privacy	S3 access-control filter; local-only design; deletion of stale chunks
RAG Q41: hidden instructions in a document	S3 injection test document
RAG Q45: switching embedding or chunking lowers quality	One change at a time; new collection plus alias; per-fix reports
RAG Q46: monitoring; Q50: “accuracy is bad, you have two weeks”	Traces with version tags; the whole S0 to S2 method
EV Q5, Q6, Q41: golden set, error analysis, Goodhart	Sealed test split; failure-analysis table
EV Q17, Q19: trust a judge, statistics	Optional calibrated judge; counts and confidence intervals on a small set
EV Q28: over-refusal	False-refusal rate on answerable questions
EV Q39, Q50: compliance evidence, launch readiness	reports/ folder; pre-launch checklist
OP Q3, Q14: what to version	Version tags in every trace; pinned Jina revision and Ollama model digest
OP Q16: CI with evaluation gates	S3 CI gate on dev Recall@5
OP Q17, Q18: canary and rollback	New collection plus alias switch; old collection kept
OP Q7, Q28, Q29: SLOs, load test, capacity	S3 load test, memory arithmetic for 8 GB, SLOs set from measurements
FDE Q17, Q18: messy data, 70 % against 95 % expected	Corpus inventory, baseline, failure analysis, per-fix gains
FDE Q20: security blocks external LLM APIs	Local-first design
FDE Q39, Q48: procurement assistant; take-home over 50 documents	This project and its README structure

PART 3 · STAGES

S0 to S4: tasks, technical notes, tests, outputs, exit gates


9. Stage overview and schedule

Stage	Weeks	Hours	Goal	Exit gate
S0 Baseline and safety	1 to 2	12	Safe start, first honest score	Backup verified; baseline and failure labels committed; P0 tests pass; nothing real modified
S1 Retrieval fixes	3 to 5	18.5	Remove defects that corrupt retrieval, one at a time	Each fix tested and measured; full re-index; no wrong-tender answers on dev questions
S2 Evaluation	6 to 7	13	Frozen, fair comparison	Final setup justified on dev, confirmed once on the sealed test split; CI gate threshold set
S3 Reliability, scale, access	9 to 11	9	Behaviour under load, no silent failures, who may see what	SLOs from measurements; ACL and injection tests pass; failed request diagnosable
S4 Polish and deploy	12	6 (shared)	A stranger can run and read it	README, diagrams, demo, one AWS workflow

Tag every stage exit in git (s0-baseline, s1-retrieval-fixes, s2-evaluation, s3-reliability), as the course tags week1.0 to week7.0, and cite the tag in the matching report so every number can be reproduced from its commit.

Week by week (both projects)

Week	Starts	Hours	Project 1: Tender RAG 2.0	Project 2: MultiDoc Evidence Agent
W1	5 Nov	6	S0: backup, snapshot, environment, corpus inventory	—
W2	12 Nov	6	S0: read-only baseline, sampling rule and seed, 32 dev questions, P0 security fixes	—
W3	19 Nov	6	S1 Type A: candidate pool, BM25 order, reranker loaded once, one retrieval, context budget	—
W4	26 Nov	6	S1 Type A: one answer pipeline, ID detection, Jina task re-embedding into a new collection with alias, trace logs	—
W5	3 Dec	6.5	S1 Type B: per-tender extraction, ID filter, metadata join, DOCX and XLSX, re-index; seal 16 test questions	—
W6	10 Dec	6.5	S2: E1 search methods, E6 cross-language, E2 and E3 results	—
W7	17 Dec	6.5	S2: E5 answers, E4 OCR baseline, sealed test run, citation checks, failure analysis, reports	—
W8	24 Dec	5	— (holiday week)	P2-1: plain-Python agent drill, LangGraph toy graph (5 h)
W9	31 Dec	6	S3: injection test fixture (1 h)	P2-2: contract generator, single agent (5 h)
W10	7 Jan	7	S3: access-control filter, load test, cache key, timeouts and degraded mode (6 h)	P2-3: MCP server (1 h)
W11	14 Jan	7	S3: Docker, CI gate, capacity note (2 h)	P2-3 finish, P2-4 LangSmith, P2-5 safety tests (5 h)
W12	21 Jan	7	S4: README, diagrams, demo, one AWS workflow (6 h, shared)	P2-5 finish (1 h)
Total		**75.5**	**52.5 h** in S0 to S3 plus the shared polish	**17 h**



Hours are my estimates (not measured). Weeks 8 and 9 fall over Christmas and New Year, so they hold flexible learning work instead of benchmarks that need long machine runs.

10. Stage S0: Baseline and safety

S0 · weeks 1 to 2 · 12 h	
Goal	A safe starting point and a first honest score, without touching the only copy of anything.
Entry	Branch chore/repo-cleanup in use; data/raw present (112 folders); RTX 4060 8 GB.
Tasks	1. Back up data/raw to external storage and verify the SHA-256 of every zip (0.5 h). 2. If an old Qdrant Docker volume exists, snapshot it or copy the volume before any run (0.25 h). 3. Start Docker Desktop (docker compose up -d); install Ollama and pull a 3B model; create a uv environment with Python 3.12; fix pyproject.toml and the requirements (defects 20, 21); add a Makefile (start, stop, test, lint, format), ruff and pre-commit; arrange tests as unit, api and integration with integration tests marked so CI can skip them (2 h). 4. Corpus inventory script: files per tender, types, scanned-page share, path collisions by CRC; commit reports/corpus_inventory.md (1 h). 5. **Baseline, option A (preferred): evaluate the existing index read-only** (no ingest, no index). Option B if the collection is gone: rebuild into an isolated copy, with RAGBOT_QDRANT_COLLECTION=baseline_v0 and the extract, state, logs and metadata folders redirected through RAGBOT_* variables (1.25 h plus machine time). 6. Write the sampling rule and the tender split: fixed seed, stratified so scanned documents, tables and non-PDF files are represented; hold out about one third of the tenders; commit seed and split before drafting any question (0.5 h). 7. Draft and review 32 dev questions across the 8 categories, including 2 aggregation questions; tag each with the corpus level it needs (L0, L1, L2). I can draft candidates; you verify each against its source page (3.5 h). 8. Run the baseline; label each failed question with exactly one failure stage; write reports/baseline_v0.md (1 h). 9. Fix defects 2 to 5, each with a test, only after the baseline is recorded (2 h).
Technical notes	Never run ingest.py or embed.py in their default mode: both default to fresh. Use append plus an isolated collection name. Qdrant snapshot: POST /collections/NAME/snapshots. config.py reads RAGBOT_* variables (RAGBOT_QDRANT_COLLECTION, RAGBOT_EXTRACT_DIR, RAGBOT_STATE_DIR, RAGBOT_LOGS_DIR, RAGBOT_METADATA_DIR). Keep the code unchanged until the baseline is recorded.
Tests	Four P0 tests (zip traversal, non-destructive default, no default key, escaped chat text); seed reproduces the same tender split.
Outputs	reports/corpus_inventory.md · reports/baseline_v0.md (retrieval hit rate, answer check, refusal, latency, failure labels) · evaluation/gold/dev.jsonl (32) · evaluation/gold/split.json (seed, split) · backup log · four tests.
Exit gate	Backup verified; baseline numbers and failure labels committed; the four P0 tests pass; no real data folder or collection was modified. Tag the commit s0-baseline.
Questions covered	RAG Q18, Q50; EV Q5, Q6, Q41; FDE Q18.

11. Stage S1: Retrieval fixes

S1 · weeks 3 to 5 · 18.5 h	
Goal	Remove the defects that corrupt retrieval, one at a time, and measure each.
Entry	S0 exit gate met; baseline numbers exist.
Tasks: Type A	**Code and algorithm fixes on the baseline corpus; measure after each.** 1. Candidate pool of 100 into RRF and the reranker, final cut to the requested count (defect 22) (1.5 h). 2. Keep BM25 order when fetching points; fuse by rank (10) (1 h). 3. Create the embedder, reranker, Qdrant and Ollama clients once at start-up in a factory and inject them (the course's pattern); this fixes 11 and 17 together; raise errors instead of swallowing them (1 h). 4. One retrieval per request; honour top_k; replace the 3,000-character cut with a token budget (12, 13) (1.5 h). 5. One answer pipeline and one refusal sentence for UI and API (16); ID detection only for ID-shaped questions (15) (1 h). 6. Jina retrieval task: embed the same chunks with task retrieval.passage and queries with retrieval.query into a new collection (7, E2) (1.5 h).
Tasks: Type B	**Corpus changes; measure separately, after Type A.** 7. Extract into one folder per tender, put the tender ID in every payload, fix the ID filter field and the metadata join (1, 8, 9); re-index into a new collection (3.5 h). 8. Index DOCX and XLSX (6); GAEB as text only if time allows (1.5 h).
Tasks: hygiene	9. Each re-index writes a new collection; switch with a Qdrant alias; keep the old collection for rollback; never change the embedding call and the chunking in the same step (0.5 h). 10. Structured trace logs for every request with version tags: prompt version, LLM tag and digest, embedder revision and task, chunk settings, collection name (1 h). 11. Try Langfuse (time-box 1.5 h): copy the six Langfuse services (web, worker, Postgres, Redis, ClickHouse, MinIO) from the course's compose file into docker-compose.langfuse.yml and start it only when needed; otherwise Phoenix (1.5 h). 12. Write the 16 sealed test questions from the held-out tenders; commit them with a content hash; do not run them (2 h). 13. Decision records and regression tests for each fix (1 h).
Technical notes	Jina v3 with sentence-transformers: model.encode(texts, task='retrieval.passage', prompt_name='retrieval.passage') for chunks and task='retrieval.query' for questions (model card, trust_remote_code=True). Qdrant alias: update_collection_aliases (delete and create alias in one request). Qdrant search with limit 100, then rerank, then cut. Langfuse needs Web, Worker, Postgres, Redis, ClickHouse and S3-compatible storage; Phoenix is one container or pip with SQLite.
Tests	One test per defect listed in section 5 for defects 1, 6 to 13, 15, 16, 17, 22.
Outputs	reports/fixes.md: one before/after row per change, tagged Type A or B and by corpus level · decision records · traces of failed requests · updated failure labels · evaluation/gold/test.jsonl (sealed, with hash).
Exit gate	Every fix has a test and a measured effect; full re-index finished; no dev question is answered from the wrong tender. Tag the commit s1-retrieval-fixes.
Questions covered	RAG Q18, Q20, Q27, Q45; OP Q3, Q14, Q17, Q18; FDE Q18.

12. Stage S2: Evaluation

S2 · weeks 6 to 7 · 13 h	
Goal	A frozen, fair comparison of search methods and answer settings.
Entry	S1 exit gate met; sealed test file committed with its hash.
Tasks	1. E1 search methods on the dev questions: BM25 only, dense only, hybrid, hybrid + rerank (2.5 h). 2. E6 cross-language: translated query (dual query) against direct multilingual retrieval (0.5 h). 3. Compile E2 (Jina task) and E3 (coverage) results from S1 (1 h). 4. E5 answer pipeline: grounded prompt with numbered sources; 3 / 5 / 8 passages sent to the LLM; evidence check; refusal rule; measure the false-refusal rate on answerable questions (2.5 h). 5. Choose the final candidates on the dev set; run the sealed test questions once (1 h). 6. Manual claim-level citation check: all test answers in the scanned, table, paraphrase and conflict categories; 20 % spot check of the rest (1 h). 7. E4 OCR baseline: transcribe 10 scanned pages by hand and measure Tesseract character and word error rates (2 h). 8. Failure-analysis table, before and after (1 h). 9. Reports and decision records (1.5 h).
Technical notes	Compare variants on the same questions with paired bootstrap differences. Report counts (for example 11 of 16) as well as percentages. An LLM judge is optional and only used after it agrees with human labels on at least 20 answers; otherwise use exact match and a hand rubric.
Tests	Evaluation harness runs end to end on a tiny fixture; scores are reproducible for a fixed seed; CI gate script fails when dev Recall@5 drops below the stored baseline minus the margin.
Outputs	reports/retrieval_comparison.md · reports/answers_and_citations.md · reports/failure_analysis.md · reports/ocr_baseline.md · decision records for retrieval method, reranker, embedding call, cross-language handling.
Exit gate	The chosen retrieval setup is justified by numbers on the dev set and confirmed once on the sealed test set; the CI gate margin is decided. Tag the commit s2-evaluation.
Questions covered	RAG Q7, Q8, Q9, Q13, Q20, Q25, Q26, Q28, Q32; EV Q6, Q19, Q28, Q41.

13. Stage S3: Reliability, scale and access control

S3 · weeks 9 to 11 · 9 h	
Goal	Know how the service behaves under load, keep it from failing silently, and enforce who may see what.
Entry	S2 exit gate met; retrieval setup chosen.
Tasks	1. Injection test document: a tender PDF with a hidden instruction; the answer must ignore it; delimit context in the prompt (1 h, week 9). 2. Access-control filter: allowed tender IDs (or groups) stored in the payload and injected server-side from the API key; two tests: user A never sees tender B, and a missing filter returns nothing (2 h, week 10). 3. Load test with Locust: 1, 5 and 20 concurrent users, a realistic question mix, search-only and full answer, cold and warm cache reported separately (2 h). 4. Version-aware cache key: all request parameters as in the course's key, plus the index version and the prompt version (0.5 h); timeouts and retries with backoff; degraded mode that returns ranked sources when the LLM is down (1.5 h). 5. Docker Compose for Qdrant and the API; GitHub Actions with ruff, pytest and the evaluation smoke gate (1.5 h). 6. Capacity note: memory arithmetic for the 8 GB GPU (weights, KV cache) checked against nvidia-smi under load (0.5 h).
Technical notes	Expect search to scale well and answer generation on one 8 GB GPU to queue; the LLM saturation point is the result to report. Service-level targets (p95 for exact lookup, search, first token, full answer) are TBD and set from these measurements. Phoenix and Langfuse both accept OpenTelemetry traces.
Tests	Injection fixture ignored; ACL test A/B; no-filter-no-results; degraded mode returns sources; cache key changes with index version.
Outputs	reports/load_test.md (operating envelope: users x hardware) · docker-compose.yml · .github/workflows · capacity note · SLO table.
Exit gate	Service-level targets set from measurements; a failed request is diagnosable from its trace; access-control and injection tests pass. Tag the commit s3-reliability.
Questions covered	RAG Q37, Q41, Q46; OP Q7, Q16, Q25, Q28, Q29; EV Q29.

14. Stage S4: Polish and deploy

S4 · week 12 · 6 h (shared with Project 2)	
Goal	A stranger can clone, run, test and read the results in 15 minutes.
Tasks	README in English with a short German summary; architecture diagram; results tables copied from reports/; decision-record index; 3-minute demo video; one demonstrated AWS workflow (image pushed to ECR through an IAM role with no long-lived keys; backup to S3); repository clean-up.
Outputs	Public repository with README, diagrams, reports, decision records, demo video link.
Exit gate	Fresh clone passes tests; README results match reports/ exactly.

PART 4 · METHOD

Evaluation protocol, experiments, reliability, scaling, observability, security

15. Evaluation protocol

Evaluation comes first because every later claim depends on it. The question set is called **G-DE**: 48 questions (mandatory), 32 for development and 16 sealed for testing; grow toward 64 as a stretch.

Category	Questions	What it tests	Failure it exposes
Exact ID, metadata and aggregation (2 of the 6 are counts or lists)	6	Deterministic route, no LLM	Wrong tender, ID filter, ID detection
Single-document fact	10	Right passage, right page	Chunking, retrieval, citation
Paraphrase, including English question on German text	8	Meaning, not keywords	Embedding call, language handling
Multi-document comparison	6	All required tenders retrieved	Incomplete evidence
Scanned-page fact	4	OCR quality	Lost or garbled text
Table / GAEB quantity	3	Table fidelity	Lost structure, missing GAEB
Versions, amendments and conflicts	3	Explicit supersession applied; ambiguous precedence flagged, not decided	Outdated or contradictory answers
Not answerable (traps)	8	Refuse honestly	Hallucination
Total	**48**	32 dev (S0) + 16 sealed test (S1)	

Rules

- **Sampling rule, written down before any question is drafted:** choose the tenders with a fixed random seed, stratified so scanned documents, tables and non-PDF files are represented; hold out about one third of the tenders for the test split. Commit the seed and the split first.
- **The test questions are sealed:** written in weeks 3 to 5 from the held-out tenders, committed with a content hash, never used to choose a setting, run once per final candidate in S2.
- **Corpus-level tag:** every question records the minimum corpus it needs (L0 = existing index, L1 = per-tender extraction, L2 = plus DOCX and XLSX). Results are reported per level.
- **Type A and Type B changes are separate:** Type A = code and algorithm changes on the same corpus; Type B = corpus changes (extraction, DOCX/XLSX coverage). Measure and record one at a time.
- **Citations are checked by hand** for scanned pages, tables, paraphrased answers and conflicts; text matching is trusted only for exact-text answers.
- **Supersession needs evidence:** a newer date alone does not make a document win. The newer text must say it replaces or changes the earlier clause, or the contract must define an order of precedence; otherwise the answer reports an unresolved conflict for a human.
- Compare variants on the same questions and report differences with confidence intervals. “No clear difference” is a valid result.
- Record for every report: code commit, models and versions, hardware, configuration, command, results, limitations.
- With 48 questions, and only 16 in the test split, only large differences mean anything. Report counts, not only percentages, and say so instead of ranking by decimals.

Metrics

Layer	Metric	How measured
Retrieval	Recall@5, Recall@10, MRR@10, nDCG@10; **complete-evidence recall** for multi-document questions (all required tenders found)	Own harness: gold tender, file and page per question
Answer	Correctness against the gold answer; unsupported-claim rate	Exact match for facts, hand rubric for prose; judge optional and calibrated
Citation	Citation precision: the cited page really contains the claim	Manual claim-level check for scanned, table, paraphrased and conflict answers (all of them on the test set); text match only for exact-text answers, plus a 20 % spot check
Abstention	Refusal rate on traps; false-answer rate; **false-refusal rate on answerable questions**	Trap category plus all answerable questions; one fixed refusal sentence
Aggregation	Exact match of counts and lists	Metadata route against the Excel
OCR	Character error rate, word error rate	10 hand-transcribed German pages (20 as a stretch)
Speed and cost	p50 and p95 latency (first token, full answer), error rate, GPU-seconds per answer	Traces and Locust

Failure-analysis table

Every failed question gets exactly one primary label, found by walking back through the pipeline. The reports show the count per stage before and after each change, so you can explain why the system improved. One table or chart in reports/, not a web dashboard.

Label	Meaning
Ingestion	File missing, overwritten or never indexed
OCR	Text or table wrongly extracted
Retrieval	Correct evidence not found
Ranking	Evidence found but ranked too low
Generation	Answer contradicts or goes beyond the evidence
Citation	Claim linked to the wrong file or page
Abstention	Answered without enough evidence, or refused although evidence existed

16. Experiments

Exp	Decision	Baseline	Challenger	Measured by
E1	Search method	BM25 only	Dense only; hybrid (RRF); hybrid + BGE rerank	Recall@k, MRR, exact-ID recall, latency added by reranking
E2	How Jina v3 is called	Current nomic-style prefixes	Task retrieval.query / retrieval.passage	Dense Recall@k on G-DE (needs re-embedding into a new collection)
E3	Indexing coverage	PDF only	+ DOCX, + XLSX (+ GAEB text if time)	Recall on questions whose answer is in a non-PDF file; a Type B change
E4	OCR engine	Tesseract (measured: mandatory)	One challenger (PaddleOCR or Docling OCR): stretch	CER and WER on hand-transcribed pages; seconds per page
E5	Answer pipeline	Plain retrieve then generate, 16 passages	Evidence check and refusal; 3 / 5 / 8 passages; shared refusal sentence	Correctness, unsupported claims, refusal and false-refusal rate
E6	Cross-language handling	Dual query with LLM translation (current)	Direct multilingual retrieval, no translation	Recall on English questions against German text; latency
E7 (stretch)	Contextual chunk header	Chunk text only	Tender title and document type prepended before embedding, and also stored as keyword fields with a boost (the course boosts chunk_text 3, title 2, abstract 1)	Recall, especially for form text that is identical across tenders (35 identical paths)
E8 (stretch)	Where BM25 lives	Pickle file next to Qdrant	BM25 as Qdrant sparse vectors: no pickle, no rebuild step, no rank-order defect	Exact-ID and term recall; rebuild time; code removed
E9 (stretch)	Chunk size and overlap	1000 characters, 400 overlap	Larger chunks with less overlap (for example 1500/200 and 2500/300)	Recall@k, citation precision, chunk count; needs re-embedding

Optional only if time remains: a subset of EnterpriseRAG-Bench for generality (English text only), OmniDocBench for parsing (no German), corpus growth beyond the 112 tenders (needs synthetic distractors), GraphRAG, A2A.

17. Reliability, scaling, observability and security

Reliability measures

Measure	Why	Stage
Safe ingestion: path check, size and depth limits, quarantine of broken zips (the 7 truncated zips are the test set)	A bad input must fail safely	S0
Non-destructive indexing; stable IDs; chunks of deleted or changed files removed	No data loss, no stale duplicates	S0, S1
New collection plus alias for every re-index; old collection kept	Zero-downtime switch and rollback	S1
One shared refusal path and one answer pipeline	Same question, same answer	S1
Reranker and embedder loaded once; one retrieval per request	Predictable latency	S1
Version-aware cache key	No stale results after re-indexing	S3
Timeouts, retries with backoff, degraded mode (ranked sources when the LLM is down)	Fail visibly, not silently	S3

Scaling plan

- **Users:** 1, 5 and 20 concurrent users with Locust on the same question mix. Search-only and full answer reported separately, cold and warm cache separately.
- **Expectation (to be tested):** search should scale well; answer generation on one 8 GB GPU will queue, so the saturation point of the LLM is the result to report, not a failure.
- **Targets:** service-level targets are TBD and set from the S0 baseline and S3 measurements. Latency is not expected to stay identical as load grows; the goal is to meet stated targets inside a tested operating envelope.
- **Capacity arithmetic (estimates, to be measured):** embedder and reranker about 1 GB each in fp16, a 3B model at 4-bit about 2 GB, a 7B model at 4-bit about 4.5 GB; the KV cache grows with context length and

concurrent users. Check against nvidia-smi.

- **Corpus growth** beyond 112 tenders is optional and needs synthetic distractor documents; it is not promised.

Observability

Structured trace logs are mandatory: request ID, per-stage timing, retrieval hits, tokens, document text redacted, and **version tags** (prompt version, LLM tag and digest, embedder revision and task, chunk settings, collection name). Viewer: Langfuse self-hosted if its Docker stack (Web, Worker, Postgres, Redis, ClickHouse, S3-compatible storage; the docs call Compose a local-testing setup) runs comfortably next to Qdrant and Ollama within a 1.5 h time-box; otherwise Phoenix (one container or pip, SQLite by default, Elastic License 2.0).

Security and guardrails

Topic	Plan
Authentication	No default API key; key read from the environment and required at start-up; rate limit kept
Access control	Allowed tender IDs (or groups) in the payload, injected server-side from the API key into every Qdrant query; two tests (S3)
Prompt injection	Tender text is untrusted: context delimited in the prompt; one test document with a hidden instruction must not change the answer (S3)
Output checks	Every cited source must exist and contain the claim; refuse when evidence is weak; shared refusal sentence
Secrets and supply chain	.env never committed; dependency pinning; pip-audit in CI; pickle files treated as trusted internal artifacts only

PART 5 · SCOPE, OUTPUTS AND DECISIONS

Mandatory and stretch, risks, deliverables, the interface to Project 2, decisions, sources

18. Mandatory, stretch, risks and cut order

	Mandatory (must exist by the end of week 12)	Stretch (only if time allows)
Pipeline and data	Per-tender extraction; P0 fixes; baseline; retrieval fixes; DOCX and XLSX indexed	GAEB text and completeness; German compound splitting; corpus growth beyond 112 tenders
Evaluation	48 questions with a sealed test split; E1, E2, E3, E5, E6; Tesseract OCR baseline on 10 pages; claim-level citation checks; failure analysis	Questions 49 to 64; E4 challenger engine; E7 contextual header; E8 BM25 in Qdrant; E9 chunk-size sweep; calibrated LLM judge
Reliability and security	Access-control filter; injection test; load test at 1/5/20 users; alias re-index; version-aware cache; CI gate; Docker; structured traces	Langfuse self-hosting (if Phoenix was used); Kubernetes; large-scale load tests
Operations	One demonstrated AWS workflow; GitHub Actions; README, diagrams, demo video	Full EC2 or container deployment

Risks

Risk	Mitigation
About 76 hours is slightly above 6 h per week	Cut list below; baseline and question set are protected
Christmas and New Year in weeks 8 and 9	Those weeks hold flexible Project 2 learning work; benchmarks run in weeks 6 to 7 and 10
Docker or Ollama problems on this machine	Do the setup first in S0; keep a CPU-only fallback for tests
The Qdrant collection may be gone; a full re-index takes hours	Treat re-indexing as machine time; it is needed anyway after fixing defect 1
Small local LLM (1.5B) gives weak answers	Compare 3B in E5; judge retrieval separately from generation
Data terms: may the tenders be shown publicly?	Check the DTAD terms; publish scripts, questions and a small sample, not the corpus
data/raw is the only copy of the tenders	Copy to external storage before any further cleanup or re-indexing

Cut in this order if you fall behind

- 1. 3 / 5 / 8 passages sweep in E5 (0.5 h)
- 2. E6 cross-language experiment (0.5 h)
- 3. Injection test document in Project 1 (1 h)
- 4. Capacity note (0.5 h). Items 1 to 4 return 2.5 h; a lighter load-test mix (1 h less) brings the total to 72 h, exactly 6 h per week
- 5. Questions beyond 48; the OCR challenger engine
- 6. Full cloud deployment (keep one demonstrated AWS workflow)
- 7. GAEB text indexing
- 8. German compound splitting
- **Never cut:** the baseline, the 48-question set with its sealed test split, the P0 security fixes, per-tender extraction, the access-control filter.

19. Deliverables, evidence and interview stories

- Upgraded repository with a clean layout, a working API and UI, and a pytest suite including the security, regression and access-control tests.
- **reports/**: corpus_inventory, baseline_v0, fixes, retrieval_comparison, answers_and_citations, failure_analysis, ocr_baseline, load_test. Every number comes from a run.

- 48-question evaluation set (64 as a stretch) with a sealed test split, the sampling rule and seed, and the harness that scores it.
- Decision records for the main choices (retrieval method, Jina call, reranker, OCR, caching, access control).
- Docker Compose stack, GitHub Actions pipeline with the evaluation gate, traces, architecture diagram, 3-minute demo video, README in English with a German summary.

README outline

1 Problem and who it is for · 2 Results at a glance (table from reports/) · 3 Architecture diagram · 4 How to run (3 commands) · 5 Evaluation method (question set, sealed split, failure analysis) · 6 What failed and how it was fixed (the per-fix table) · 7 Limits and honest caveats · 8 Decision records · 9 German summary.

Evidence table (fill from the reports; no values yet)

Question an employer asks	Number you will be able to show	Source
Did retrieval actually improve?	Recall@5 and MRR: baseline vs hybrid vs hybrid + rerank = TBD	reports/retrieval_comparison.md
Why did it improve?	Failures per stage, before and after = TBD	reports/failure_analysis.md
Are the citations correct?	Citation precision = TBD	reports/answers_and_citations.md
Does it admit when it does not know, and not refuse too much?	Refusal rate on 8 traps and false-refusal rate on answerable questions = TBD	reports/answers_and_citations.md
How good is the OCR?	CER and WER, Tesseract on 10 pages = TBD	reports/ocr_baseline.md
What happens under load?	p95 at 1 / 5 / 20 users, search-only and full answer = TBD	reports/load_test.md
Is it safe?	Access-control tests, injection test, P0 tests = pass or fail	tests/

Interview stories (fill the numbers from reports/; do not invent them)

Story	Structure	Evidence needed
“The system answered from the wrong tender”	Situation: wrong-tender answers; task: find the cause; action: traces showed the shared extract folder and the missing ID; result: per-tender extraction, effect measured	reports/fixes.md, a trace
“Did hybrid search help, or not?”	Four methods on the same 48 questions; what won; what it cost in latency	reports/retrieval_comparison.md
“I made it refuse instead of guess, without refusing everything”	Trap questions, one refusal rule, false-refusal rate	reports/answers_and_citations.md
“Accuracy is bad: what do you do in two weeks?”	Baseline, failure labels, one fix at a time, sealed test	baseline_v0, failure_analysis
“What happens at 20 users?”	Where it saturates and why	reports/load_test.md

20. Interface to Project 2

Project 2's agents call this project through an MCP server, so retrieval quality is proven once, here. The contract below is version v1; S3 builds the access-control and trace behaviour it relies on, and Project 2 week 10 wraps it.

Tool	Input	Output
search_documents	query, top_k (default 8), mode (hybrid), optional tender_ids	List of hits: chunk_id, tender_id, file, page_start, page_end, text, score
get_document	tender_id, file	Metadata: title, pages, document type, language, ingestion version
read_pages	tender_id, file, first page, last page	Page text (with an OCR flag per page)
list_tenders	optional filters (region, year, authority)	Rows from the metadata table (counts and lists, no LLM)

Every call carries an API key; the access scope is injected server-side and never supplied by the agent; every response carries a trace ID; rate limits apply.

21. Decision log and next steps

Date	Decision	Status
4 Nov 2026	Portfolio is 2 MLOps projects (existing) and 2 RAG projects; the fraud-detection project was dropped	Decided
4 Nov 2026	Project 1 is built in this repository; Project 2 gets a new repository	Decided
4 Nov 2026	Hours: 6 per week assumed from your answer; this plan needs about 6.3 on average (75.5 total)	Please confirm
4 Nov 2026	Langfuse in Project 1 (time-boxed 1.5 h, Phoenix as fallback); LangSmith in Project 2	Langfuse and LangSmith agreed; time-box is new
4 Nov 2026	Jina v3 stays the default embedding model; bge-m3 only as a challenger if E2 shows a problem	Decided
4 Nov 2026	Access-control filter promoted to mandatory (you asked to implement all the additions)	Assumed; please confirm
4 Nov 2026	Older plan files merged into this reference; two stage PDFs replace the single PDF	Done

Open decisions

- [ ] Back-up location for data/raw (the only copy of the tenders)
- [ ] May I install Ollama (winget install Ollama.Ollama)? Start Docker Desktop.
- [ ] DTAD terms: may the tenders and a sample be published?
- [ ] Project names (“TenderLens” was suggested; no exact match found, similar tender-AI products exist)
- [ ] Push branch chore/repo-cleanup and merge into main

Week 1 checklist

- [ ] Copy data/raw to external storage and verify checksums; snapshot or copy any existing Qdrant volume
- [ ] Start Docker Desktop; confirm Qdrant starts and whether the old collection still exists
- [ ] Install Ollama and a 3B model; create the uv Python 3.12 environment; fix packaging (defects 20, 21)
- [ ] Run the corpus inventory; commit reports/corpus_inventory.md
- [ ] Baseline in isolation: evaluate the existing index read-only, or rebuild into baseline_v0 folders; never the default fresh mode on a real collection
- [ ] Fix the sampling rule, seed and tender split, then draft and review 32 dev questions
- [ ] Record reports/baseline_v0.md before changing behaviour
- [ ] Fix defects 2 to 5, each with a test

22. Sources and verification status

Verified means the page or repository was opened or checked by search or API in November 2026.

Group	Source	Status
Code	This repository (branch chore/repo-cleanup), read file by file	Read, not run
Model usage	Jina embeddings v3 model card and config_sentence_transformers.json (tasks retrieval.query and retrieval.passage)	Verified
Research	HERB arXiv 2506.23139 · EnterpriseRAG arXiv 2608.11584 · EnterpriseRAG-Bench arXiv 2605.05253 · From BM25 to Corrective RAG arXiv 2604.01733 · OmniDocBench (CVPR 2025)	Verified to exist; findings from abstracts and summaries
Postings	Accenture R00368889 (Hamburg) · Capco 8178266 · RightShip 4982444101	Opened and read
Postings	European Dynamics D53EAA65D5 · Titan AI (Applied AI Engineer)	Title only; skills not verified
Market	DEV Community 390-posting analysis · Simpleapply · Second Talent (Lightcast) · ODSC · 365 Data Science · Axial Search	Read via search; small or commercial samples

Group	Source	Status
Reference repos	Clinical-RAG, 8hr-MARATHON, ATLAS, IT-Support Copilot, pdichone course; stars and activity of 18 tools checked through the GitHub API on 4 Nov 2026	Verified
Reference course	jamwithai/production-agentic-rag-course: README, file tree, compose.yml, agent graph, nodes, cache and tracer files read; 10,032 stars, MIT, last push 5 Jun 2026. Your fork (ShalinVachheta017/production-agentic-rag-course) last pushed 5 Apr 2026	Verified via the GitHub API
Interview sets	Krish Naik interview prep: 7 sets of 50 questions (agentic AI, FDE, system design, RAG, LLMOps, evals and guardrails, LLM fundamentals); questions read, answers not	Questions verified
Guides	Codebasics AI System Design (13 pages, read); Galileo Mastering RAG (cover only)	Partly read
Corpus	Zip-member comparison across the 105 valid zips by CRC: 101 shared paths, 66 with differing content (159 versions overwritten), 35 identical; nested zips not counted	Measured 4 Nov 2026
Tracing tools	Langfuse self-hosting docs (Web, Worker, Postgres, Redis, ClickHouse, S3-compatible storage; Compose for local testing); Arize Phoenix Docker docs (single container, SQLite default, Elastic License 2.0)	Verified via docs and search
Name check	TenderLens: web search found no exact match	Not a trademark check

23. Glossary

Term	Meaning
RAG	Retrieval-Augmented Generation: find passages first, then write the answer from them
Chunk	A piece of text (here 1,000 characters) that is embedded and searched
Embedding	A list of numbers (here 1,024) that represents the meaning of a text
BM25	Keyword scoring by exact word overlap; strong for IDs and rare terms
Hybrid search / RRF	Combine vector and keyword results; Reciprocal Rank Fusion adds 1 / (60 + rank) from each list
Reranker (cross-encoder)	A model that reads question and passage together and re-orders the best candidates
Recall@k, MRR, nDCG	Retrieval metrics: is a correct result in the top k; how high is the first correct one; ranking quality
False-refusal rate	Share of answerable questions the system refused to answer
p95 latency	The time under which 95 % of requests finish
Trace	A recorded step-by-step history of one request
Qdrant alias	A name that points to a collection; switching the alias switches the live index without downtime
Type A / Type B change	Code change on the same corpus / change to the corpus itself
Sealed test set	Questions committed with a hash and never used for tuning
MCP	Model Context Protocol: a standard way for an agent to call tools

Appendix: decision record template

1 Business	2 Options	3 Choice	4 Evidence	5 Trade-off	6 Reference
What problem does this solve?	What alternatives were tried?	Why this one?	Which metric or test supports it?	What did it cost (latency, privacy, effort)?	Where are the code, report and record?