Architecture invariants

These are the properties the architecture must preserve. Each names the test that currently enforces it, or says `not yet` when the invariant is adopted but its enforcement test has not landed. The kernel boundary tests live in `development/scale/tests.fs` under `Kernel boundary`.

No.	Invariant	Enforcement
1	The kernel runs without the Prelude loaded	`The kernel abstraction runs without Prelude state`
2	The Prelude is swappable data	`an image swap changes the entry result; scale_image imports a replacement image`
3	The kernel state has no Prelude state	`The kernel assembly contains no Prelude state, errors, or portable IR`
4	The kernel source contains no Prelude logic	`The kernel assembly references no Prelude assembly`
5	Removing a feature requires no kernel change	Removing per-feature test not yet
6	Adding a feature requires no kernel change	Adding image units are data; per-feature test not yet

No.	Invariant	Enforcement
7	Partial failures are attributed to the raising layer	Partial: `a kernel failure carries its named reason`; `a primitive failure carries its named reason`
8	Upcalls are real	Upcalls; kernel image execution currently resolves image units, not Prelude policy upcalls
9	The exported ABI version is the header version; an unsupported image schema is refused; the adapter's guard compiles and `just kernel-aot` runs the C conformance harness against the NativeAOT kernel in alpha (D180) is enforced at load time	`the exported ABI version is the header version`; `an unsupported image schema is refused`;

A change that breaks an enforced invariant is a kernel-boundary change and must update this file, the affected decision record, and the test in the same change. `not yet` is a visible gap, not a silent pass.