From	Kind	To	Rationale
`expression-logic`	`embeds`	`pattern-logic`	PatternMatch clauses carry PatternLogic patterns.
`expression-logic`	`lowers-to`	`lowered-abstraction`	EvaluatorLowering maps the expression subset to instructions.
`package-logic`	`contains`	`expression-logic`	A PackageUnit root is an ExpressionLogic node.
`expression-logic`	`serializes-to`	`portable-documents`	ExpressionPortable writes the canonical expression document.
`pattern-logic`	`serializes-to`	`portable-documents`	PatternPortable writes the canonical pattern document.
`package-logic`	`serializes-to`	`portable-documents`	PackagePortable writes the canonical package document.
`expression-logic`	`inferred-by`	`type-retrieval`	TypeInference elaborates against the signature table.
`lowered-abstraction`	`executes-on`	`image-values`	The VM reads and writes the image store.
`symbolic-abstraction`	`executes-on`	`image-values`	The interpreter reads and writes the image store.
`domain-expression`	`projects-to`	`image-values`	Verification expressions project into the image value model.

```
expression-logic -> pattern-logic : embeds
expression-logic -> lowered-abstraction : lowers-to
package-logic -> expression-logic : contains
expression-logic -> portable-documents : serializes-to
pattern-logic -> portable-documents : serializes-to
package-logic -> portable-documents : serializes-to
expression-logic -> type-retrieval : inferred-by
lowered-abstraction -> image-values : executes-on
symbolic-abstraction -> image-values : executes-on
domain-expression -> image-values : projects-to
```