

Telecommunication Industry Project

Introduction

This Jupyter notebook is part of your learning experience in the study of applied statistics.

You will work with a data set that contains mobile phone prices and their specifications.

Dataset Columns Information

PID = a unique identifier for the phone model

Blue = whether the phone has bluetooth support or not

Wi_Fi = whether the phone has wifi support or not

Tch_Scr = whether the phone has touch screen support or not

Ext_Mem = whether the phone has external memory support or not

Px_h = number of pixels in the vertical axis of the phone

Px_w = number of pixels in the horizontal axis of the phone

Scr_h = height of the screen of the phone in centimetres (cm)

Scr_w = width of the screen of the phone in centimetres (cm)

Int_Mem = internal memory of the phone measured in megabytes (MB)

Bty_Pwr = maximum energy stored by the phone's battery measured in milli-Ampere-hours (mAh)

PC = resolution of the primary camera measured in megapixels (MP)

FC = resolution of the front camera measured in megapixels (MP)

RAM = random access memory available in the phone measured in gigabytes (GB)

Depth = depth of the mobile phone measured in centimetres (cm)

Weight = weight of the mobile phone measured in grams (g)

Price = selling price of the mobile phone in rupees

In []:

Task 1 - Load and study the data

Import the libraries that will be used in this notebook

In []:

```
# Load "numpy" and "pandas" for manipulating numbers and data frames
# Load "matplotlib.pyplot" and "seaborn" for data visualisation

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
```

Load the csv file as pandas dataframe.

In []:

```
# Read in the "Dataset" file as a Pandas Data Frame

data = pd.read_csv('/content/Mobile_Phones.csv')
```

In []:

```
# Take a brief look at the data
top = data.head()
top
```

Out[21]:

	PID	Blue	Wi-Fi	Tch_Scr	Ext_Mem	Px_h	Px_w	Scr_h	Scr_w	PC	FC	Int_Mem
0	AAB346A	yes	yes	no	no	780	460	3	1	2	2	8
1	AAC347I	yes	yes	no	no	780	560	2	1	4	2	8
2	BAB657J	no	yes	no	no	840	720	2	1	4	2	8
3	BBD456K	no	yes	yes	no	1280	1120	5	3	6	2	32
4	CCP761U	no	yes	yes	no	1280	1080	4	3	6	2	16

In []:

```
# Get the dimensions of the dataframe
data.shape
```

Out[5]:

(50, 17)

In []:

```
# Get the row names of the dataframe
```

In []:

```
# Get the column names of the dataframe
```

```
data.columns
```

Out[11]:

```
Index(['PID', 'Blue', 'Wi_Fi', 'Tch_Scr', 'Ext_Mem', 'Px_h', 'Px_w', 'Scr_h',
      'Scr_w', 'PC', 'FC', 'Int_Mem', 'Bty_Pwr', 'RAM', 'Depth', 'Weight',
      'Price'],
      dtype='object')
```

In []:

```
# Look at basic information about the dataframe
```

```
data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 50 entries, 0 to 49
Data columns (total 17 columns):
 #   Column      Non-Null Count  Dtype
---  -
 0   PID         50 non-null    object
 1   Blue        50 non-null    object
 2   Wi_Fi       50 non-null    object
 3   Tch_Scr     50 non-null    object
 4   Ext_Mem     50 non-null    object
 5   Px_h        50 non-null    int64
 6   Px_w        50 non-null    int64
 7   Scr_h       50 non-null    int64
 8   Scr_w       50 non-null    int64
 9   PC          50 non-null    int64
10   FC          50 non-null    int64
11   Int_Mem     50 non-null    int64
12   Bty_Pwr     50 non-null    int64
13   RAM         50 non-null    int64
14   Depth       50 non-null    int64
15   Weight      50 non-null    int64
16   Price       50 non-null    int64
dtypes: int64(12), object(5)
memory usage: 6.8+ KB
```

Observations:

There are 50 phones in the data set.

There are 17 features in the data set including the "PID" feature which is used as the row index labels.

There are no missing values in the data set.

In []:

Let's try some logical operators to filter the data.

Logical Operators

Operator	Result
&	Logical AND
	Logical OR
^	Logical XOR (exclusive OR)
	Short-circuit OR
&&	Short-circuit AND
!	Logical unary NOT
&=	AND assignment
=	OR assignment
^=	XOR assignment
==	Equal to
!=	Not equal to
?:	Ternary if-then-else

Task 2 - Obtain the logical conditions for the features "Blue", "Wi-Fi", "Tch_Scr" and "Ext_Mem"

In []:

```
# Get the feature names of the dataframe
```

```
data.columns
```

Out[13]:

```
Index(['PID', 'Blue', 'Wi-Fi', 'Tch_Scr', 'Ext_Mem', 'Px_h', 'Px_w', 'Scr_h',  
      'Scr_w', 'PC', 'FC', 'Int_Mem', 'Bty_Pwr', 'RAM', 'Depth', 'Weight',  
      'Price'],  
      dtype='object')
```

In []:

```
# Let's tackle these features: "Blue", "Wi-Fi", "Tch_Scr", "Ext_Mem"
```

In []:

```
# The children want phones that have the following: Bluetooth, WiFi, touch screen and ex  
# Create a logical condition for this situation and store the logical values as "con1"
```

```
con1 = data[['Blue', 'Wi-Fi', 'Tch_Scr', 'Ext_Mem']]  
con1
```

Out[50]:

	Blue	Wi_Fi	Tch_Scr	Ext_Mem
0	yes	yes	no	no
1	yes	yes	no	no
2	no	yes	no	no
3	no	yes	yes	no
4	no	yes	yes	no
5	yes	no	no	no
6	yes	no	yes	no
7	yes	no	no	no
8	yes	yes	yes	yes
9	yes	yes	yes	yes
10	yes	yes	yes	yes
11	yes	yes	yes	yes
12	no	yes	yes	yes
13	no	yes	yes	no
14	yes	yes	yes	yes
15	no	no	yes	yes
16	no	no	yes	yes
17	no	no	yes	yes
18	no	no	yes	yes
19	no	no	yes	yes
20	no	yes	yes	yes
21	no	yes	yes	yes
22	no	yes	yes	yes
23	no	yes	yes	yes
24	no	yes	yes	yes
25	no	yes	yes	yes
26	no	yes	yes	yes
27	yes	yes	yes	yes
28	yes	yes	yes	yes
29	no	yes	yes	yes
30	yes	yes	yes	yes
31	no	yes	yes	yes
32	yes	yes	yes	yes
33	no	yes	yes	yes
34	yes	yes	yes	yes
35	no	yes	yes	yes
36	yes	yes	yes	yes

	Blue	Wi_Fi	Tch_Scr	Ext_Mem
37	yes	yes	yes	yes
38	yes	yes	yes	yes
39	yes	yes	yes	yes
40	yes	yes	yes	yes
41	yes	yes	yes	yes
42	yes	yes	yes	yes
43	no	yes	yes	yes
44	yes	yes	yes	yes
45	no	yes	yes	yes
46	yes	yes	yes	yes
47	yes	yes	yes	no
48	yes	yes	yes	no
Observations	yes	yes	yes	no

The features "Blue", "Wi_Fi", "Tch_Scr" and "Ext_Mem" are binary in nature.

The children want all these features, so the logical condition "con1" has been obtained accordingly.

Task 3 - Obtain the logical conditions for the features "Px_h" and "Px_w"

In []:

```
# Get the feature names of the dataframe
data.columns
```

Out[40]:

```
Index(['PID', 'Blue', 'Wi_Fi', 'Tch_Scr', 'Ext_Mem', 'Px_h', 'Px_w', 'Scr_h',
      'Scr_w', 'PC', 'FC', 'Int_Mem', 'Bty_Pwr', 'RAM', 'Depth', 'Weight',
      'Price'],
      dtype='object')
```

In []:

```
# Let's tackle these features: "Px_h", "Px_w"
```

In []:

```
# Create a new feature called "Px" which stores the total resolution of the screen

Px = (data['Px_h']) & (data['Px_w'])
Pxx = pd.DataFrame(Px)
data['Pxx'] = Pxx
```


In []:

```
data['Pxx'].mean()
```

Out[65]:

1212.08

In []:

```
med = data['Pxx'].median()
```

In []:

```
# Create a histogram of the "Px" feature and also show the mean and the median
```

```
plt.figure(figsize = (11,6))
```

```
sns.histplot(data = data , x = 'Pxx', color='red', edgecolor = 'linen', alpha = 0.5, bin
```

```
plt.title("Histogram Plot of Pixel")
```

```
plt.xlabel('Pxx')
```


```
plt.ylabel('Pixel Count')
```

```
plt.vlines(data['Pxx'].mean(),ymin=0,ymax=30,colors='blue',label='Mean')
```

```
plt.vlines(data['Pxx'].median(),ymin=0,ymax=30,colors='red',label='Median')
```

```
plt.legend()
```

```
plt.show()
```



In []:

```
# The children want phones that have good screen resolutions
# Consider the phones that have screen resolutions greater than or equal to the median v
# Create a logical condition for this situation and store the logical values as "con2"

con2 = data['Pxx'][(data['Pxx']>=med)]
con2
```

Out[74]:

```
3      1024
4      1024
5      1024
6      1064
7      2112
13     2112
15     1696
17     2112
18     1696
19     2112
20     1696
22     1280
23     2112
24     1280
26     1280
27     2048
28     2048
29     2048
30     2048
31     2048
32     2048
33     2048
34     2112
35     2056
47     2368
48     2368
49     2368
```

Name: Pxx, dtype: int64

Observations:

The features "Px_h" and "Px_w" are respectively the number of pixels in the phone screen in the vertical and horizontal axes.

We created a new feature called "Px" which is the product of the features "Px_h" and "Px_w".

The median has been selected as a threshold in this case.

In case it is too strict, we can choose the mean as a threshold.

Task 4 - Obtain the logical conditions for the features "Scr_h" and "Scr_w"

In []:

```
# Let's tackle these features: "Scr_h", "Scr_w"
```

In []:

```
# Create a new feature called "Scr_d" which stores the length of the diagonal of the scr

import numpy as np

Scr_d = np.sqrt(data['Scr_h']**2 + data['Scr_w']**2)
Scr_d
data['Scr_d'] = Scr_d
```

In []:

```
Diagonal = data.Scr_d.values.tolist()  
Diagonal
```

Out[84]:

```
[3.1622776601683795,  
2.23606797749979,  
2.23606797749979,  
5.830951894845301,  
5.0,  
5.0,  
6.708203932499369,  
10.0,  
6.708203932499369,  
5.830951894845301,  
6.708203932499369,  
10.0,  
7.810249675906654,  
7.810249675906654,  
5.830951894845301,  
12.806248474865697,  
10.0,  
10.0,  
10.0,  
5.0,  
5.0,  
10.0,  
5.0,  
12.806248474865697,  
7.211102550927978,  
6.708203932499369,  
5.830951894845301,  
10.0,  
10.0,  
10.0,  
10.0,  
10.0,  
10.0,  
10.0,  
10.0,  
6.708203932499369,  
5.830951894845301,  
12.806248474865697,  
5.830951894845301,  
5.830951894845301,  
7.810249675906654,  
5.830951894845301,  
10.0,  
10.0,  
10.0,  
12.806248474865697,  
10.0,  
5.0,  
10.0,  
10.0,  
10.0]
```

In []:

```
# Create a histogram of the "Scr_d" feature and also show the quartiles
```

```
plt.figure(figsize = (11,6))
```

```
sns.histplot(data = data , x = 'Scr_d', color='red', edgecolor = 'black', alpha = 0.5, bins = 5)
```

```
plt.title("Histogram Plot of Diagonal")
```

```
plt.xlabel('Scr_d')
```

```
plt.ylabel('Count')
```

```
Q1 = np.percentile(Diagonal,25)
```


```
Q3 = np.percentile(Diagonal,75)
```

```
IQR = Q3 - Q1
```

```
low = Q1 - 1.5*IQR
```

```
upp = Q3 + 1.5*IQR
```

```
plt.show()
```



In []:

```
# The children want phones that have very good screen sizes
# Consider the phones that have screen sizes greater than or equal to the upper quartile
# Create a logical condition for this situation and store the logical values as "con3"
upp
con3 = [(data['Scr_d']>=upp)]
con3
```

Out[99]:

```
[0    False
 1    False
 2    False
 3    False
 4    False
 5    False
 6    False
 7    False
 8    False
 9    False
10    False
11    False
12    False
13    False
14    False
15    False
16    False
17    False
18    False
19    False
20    False
21    False
22    False
23    False
24    False
25    False
26    False
27    False
28    False
29    False
30    False
31    False
32    False
33    False
34    False
35    False
36    False
37    False
38    False
39    False
40    False
41    False
42    False
43    False
44    False
45    False
46    False
47    False
48    False
49    False
Name: Scr_d, dtype: bool]
```

Observations:

The features "Scr_h" and "Scr_w" are respectively the height and the width of the phone screen.

We created a new feature called "Scr_d" which is essentially the length of the screen diagonal.

The upper quartile has been selected as a threshold in this case as the children were very particular on this point.

In case it is too strict, we can choose the mean or the median as a threshold.

Task 5 - Obtain the logical conditions for the features "PC" and "FC"

In []:

```
# Let's tackle these features: "PC", "FC"
```


In []:

```
# Create a histogram of the "PC" feature and also show the mean and the median

plt.figure(figsize = (11,6))

sns.histplot(data = data , x = 'PC', color='green', edgecolor = 'linen', alpha = 0.5, bi

plt.title("Histogram Plot of PC")
plt.xlabel('PC')
plt.ylabel('Count')
plt.vlines(data['PC'].mean(),ymin=0,ymax=30,colors='blue',label='Mean')
plt.vlines(data['PC'].median(),ymin=0,ymax=30,colors='red',label='Median')
plt.legend()
plt.show()
```



In []:

```
# Create a histogram of the "FC" feature and also show the mean and the median
```

```
plt.figure(figsize = (11,6))
```

```
sns.histplot(data = data , x = 'FC', color='yellow', edgecolor = 'black', alpha = 0.5, bins = 10)
```

```
plt.title("Histogram Plot of FC")
```

```
plt.xlabel('FC')
```


```
plt.ylabel('Count')
```

```
plt.vlines(data['FC'].mean(),ymin=0,ymax=30,colors='blue',label='Mean')
```

```
plt.vlines(data['FC'].median(),ymin=0,ymax=30,colors='red',label='Median')
```

```
plt.legend()
```

```
plt.show()
```



In []:

```
pcm = data['PC'].mean()
```

```
pcm
```

Out[106]:

42.16

In []:

```
fcm = data['FC'].mean()
```

```
fcm
```

Out[107]:

20.76

In []:

```
# The children want phones that have good primary and front camera resolutions
# Consider the phones that have primary and front camera resolutions greater than or equal to 2580 and 1920 respectively
# Create a logical condition for this situation and store the logical values as "con4"

con4 = data[(data['PC']>=pcm) & (data['FC']>=fcm)]
con4
```

Out[111]:

	PID	Blue	Wi_Fi	Tch_Scr	Ext_Mem	Px_h	Px_w	Scr_h	Scr_w	PC	FC	Int_Mem
9	ENG897N	yes	yes	yes	yes	2580	1980	5	3	64	32	
11	ELS333L	yes	yes	yes	yes	2580	1920	8	6	64	32	
12	ETT987D	no	yes	yes	yes	2580	1980	6	5	64	32	
16	PDF768G	no	no	yes	yes	2580	1980	8	6	64	32	1
21	QWR222Y	no	yes	yes	yes	2580	1980	8	6	64	32	1
25	SDO555G	no	yes	yes	yes	2580	1980	6	3	64	32	
28	SSD000L	yes	yes	yes	yes	2580	2120	8	6	64	32	5
30	TVF078Y	yes	yes	yes	yes	2580	2120	8	6	64	32	5
32	TYS938L	yes	yes	yes	yes	2580	2120	8	6	64	32	10
33	TYU444Q	no	yes	yes	yes	2580	2120	8	6	64	32	1
34	TTY453J	yes	yes	yes	yes	2880	2120	6	3	64	32	1
36	UST000T	yes	yes	yes	yes	2580	1980	10	8	64	32	
37	USZ111S	yes	yes	yes	yes	2440	1980	5	3	48	32	1
38	VWV532Y	yes	yes	yes	yes	2580	1920	5	3	64	32	
40	WER765T	yes	yes	yes	yes	2580	1980	5	3	64	32	1
42	WZB298K	yes	yes	yes	yes	2580	1980	8	6	64	32	10
44	XTL675G	yes	yes	yes	yes	2580	1980	10	8	64	32	5
45	XXV567F	no	yes	yes	yes	2580	1980	8	6	64	32	
46	YTR67TY	yes	yes	yes	yes	2580	1980	4	3	64	32	
47	ZDF789K	yes	yes	yes	no	2880	2520	8	6	64	32	5
48	ZEO567M	yes	yes	yes	no	2880	2520	8	6	128	64	5
49	ZZZ909X	yes	yes	yes	no	2880	2520	8	6	128	64	10

Observations:

The features "PC" and "FC" are respectively the resolutions of the primary camera and the front camera.

The respective means have been selected as thresholds in this case.

In case it is too strict, we can choose the respective medians as thresholds.

Task 6 - Obtain the logical conditions for the features "Int_Mem", "Bty_Pwr" and "RAM"

In []:

```
# Let's tackle these features: "Int_Mem", "Bty_Pwr", "RAM"
```

In []:

```
# Create a histogram of the "Int_Mem" feature and also show the mean and the median
```

```
plt.figure(figsize = (10,5))
```

```
sns.histplot(data = data , x = 'Int_Mem', color='red', edgecolor = 'black', alpha = 0.5,
```

```
plt.title("Histogram Plot of Int_Mem")
```

```
plt.xlabel('Int_Mem')
```


```
plt.ylabel('Count')
```

```
plt.vlines(data['Int_Mem'].mean(),ymin=0,ymax=50,colors='blue',label='Mean')
```

```
plt.vlines(data['Int_Mem'].median(),ymin=0,ymax=50,colors='red',label='Median')
```

```
plt.legend()
```

```
plt.show()
```



In []:

```
# Create a histogram of the "Bty_Pwr" feature and also show the mean and the median
```

```
plt.figure(figsize = (10,5))
```

```
sns.histplot(data = data , x = 'Bty_Pwr', color='blue', edgecolor = 'black', alpha = 0.5)
```

```
plt.title("Histogram Plot of Bty_Pwr")
```

```
plt.xlabel('Bty_Pwr')
```


```
plt.ylabel('Count')
```

```
plt.vlines(data['Bty_Pwr'].mean(),ymin=0,ymax=50,colors='blue',label='Mean')
```

```
plt.vlines(data['Bty_Pwr'].median(),ymin=0,ymax=50,colors='red',label='Median')
```

```
plt.legend()
```

```
plt.show()
```




In []:

```
# Create a histogram of the "RAM" feature and also show the mean and the median

plt.figure(figsize = (10,5))

sns.histplot(data = data , x = 'RAM', color='red', edgecolor = 'black', alpha = 0.5, bin

plt.title("Histogram Plot of Int_Mem")
plt.xlabel('RAM')
plt.ylabel('Count')
plt.vlines(data['RAM'].mean(),ymin=0,ymax=50,colors='blue',label='Mean')
plt.vlines(data['RAM'].median(),ymin=0,ymax=50,colors='red',label='Median')
plt.legend()
plt.show()
```



In []:

```
intmean = data['Int_Mem'].mean()
intmean
```

Out[126]:

173.76

In []:

```
Btymean = data['Bty_Pwr'].mean()
Btymean
```

Out[127]:

3740.0

In []:

```
rammean = data['RAM'].mean()
rammean
```

Out[128]:

5.76

In []:

```
# The children want phones that have good internal memory, battery power and RAM
# Consider the phones that have internal memory, battery power and RAM greater than or equal to the respective means
# Create a logical condition for this situation and store the logical values as "con5"

con5 = data[(data['Int_Mem']>=intmean) & (data['Bty_Pwr']>=Btymean) & (data['RAM']>=rammean)]
con5
```

Out[125]:

	PID	Blue	Wi_Fi	Tch_Scr	Ext_Mem	Px_h	Px_w	Scr_h	Scr_w	PC	FC	Int_Mem
28	SSD000L	yes	yes	yes	yes	2580	2120	8	6	64	32	5.76
29	SYL888P	no	yes	yes	yes	2580	2120	8	6	64	16	2.56
30	TVF078Y	yes	yes	yes	yes	2580	2120	8	6	64	32	5.76
32	TYS938L	yes	yes	yes	yes	2580	2120	8	6	64	32	10.24
42	WZB298K	yes	yes	yes	yes	2580	1980	8	6	64	32	10.24
44	XTL675G	yes	yes	yes	yes	2580	1980	10	8	64	32	5.76
47	ZDF789K	yes	yes	yes	no	2880	2520	8	6	64	32	5.76
48	ZEO567M	yes	yes	yes	no	2880	2520	8	6	128	64	5.76
49	ZZZ909X	yes	yes	yes	no	2880	2520	8	6	128	64	10.24

Observations

The features "Int_Mem", "Bty_Pwr" and "RAM" are respectively the internal memory, battery power and RAM of the phones.

The respective means have been selected as thresholds in this case.

.In case it is too strict, we can choose the respective medians as thresholds

Task 7 - Obtain the logical conditions for the features "Depth" and "Weight"

In []:


```
# Let's tackle these features: "Depth", "Weight"
```

In []:

```
# Create a histogram of the "Depth" feature and also show the mean and the median
plt.figure(figsize = (10,5))

sns.histplot(data = data , x = 'Depth', color='orange', edgecolor = 'black', alpha = 0.5)

plt.title("Histogram Plot of Depth")
plt.xlabel('Depth')
plt.ylabel('Count')
plt.vlines(data['Depth'].mean(),ymin=0,ymax=50,colors='blue',label='Mean')
plt.vlines(data['Depth'].median(),ymin=0,ymax=50,colors='red',label='Median')
plt.legend()
plt.show()
```



In []:

```
# Create a histogram of the "Weight" feature and also show the mean and the median
```

```
plt.figure(figsize = (10,5))
```

```
sns.histplot(data = data , x = 'Weight', color='red', edgecolor = 'black', alpha = 0.5,
```

```
plt.title("Histogram Plot of Weight")
```

```
plt.xlabel('Weight')
```


```
plt.ylabel('Count')
```

```
plt.vlines(data['Weight'].mean(),ymin=0,ymax=50,colors='blue',label='Mean')
```

```
plt.vlines(data['Weight'].median(),ymin=0,ymax=50,colors='red',label='Median')
```

```
plt.legend()
```

```
plt.show()
```



In []:

```
dmean = data['Depth'].mean()
```

In []:

```
wmean = data['Weight'].mean()
```


In []:

```
# The children want phones that are light weight and slim
# Consider the phones that have depth and weight less than or equal to the respective me
# Create a logical condition for this situation and store the Logical values as "con6"
con6 = data[(data['Depth']<=dmean) & (data['Weight']<=wmean)]
con6
```

Out[136]:

	PID	Blue	Wi_Fi	Tch_Scr	Ext_Mem	Px_h	Px_w	Scr_h	Scr_w	PC	FC	Int_Me
6	CTX123L	yes	no	yes	no	1390	1080	6	3	8	4	
7	DFR256N	yes	no	no	no	2880	2120	8	6	12	8	
8	DGS789M	yes	yes	yes	yes	2580	1920	6	3	32	16	
9	ENG897N	yes	yes	yes	yes	2580	1980	5	3	64	32	
16	PDF768G	no	no	yes	yes	2580	1980	8	6	64	32	1
20	POP857R	no	yes	yes	yes	1980	1760	4	3	32	16	
21	QWR222Y	no	yes	yes	yes	2580	1980	8	6	64	32	1
22	QZR577O	no	yes	yes	yes	1440	1280	4	3	8	8	
23	RAY344W	no	yes	yes	yes	2880	2120	10	8	8	4	
24	RBZ451D	no	yes	yes	yes	1440	1280	6	4	8	4	
30	TVF078Y	yes	yes	yes	yes	2580	2120	8	6	64	32	5
31	TYQ109G	no	yes	yes	yes	2580	2120	8	6	32	16	2
32	TYS938L	yes	yes	yes	yes	2580	2120	8	6	64	32	10
33	TYU444Q	no	yes	yes	yes	2580	2120	8	6	64	32	1
41	WUV902Y	yes	yes	yes	yes	2580	1980	8	6	48	16	1
42	WZB298K	yes	yes	yes	yes	2580	1980	8	6	64	32	10
47	ZDF789K	yes	yes	yes	no	2880	2520	8	6	64	32	5
48	ZEO567M	yes	yes	yes	no	2880	2520	8	6	128	64	5
49	ZZZ909X	yes	yes	yes	no	2880	2520	8	6	128	64	10

Observations:

The features "Depth" and "Weight" are respectively the depth of the phone and the weight of the phone.

The respective medians have been selected as thresholds in this case.

In case it is too strict, we can choose the respective means as thresholds.

Task 8 - Subset the data based on all the logical conditions

In []:

```
# Subset the dataframe using all the logical conditions that have been stored  
# Store the subset of the dataframe as a new dataframe called "df1"
```

```
df1 = con1  
df1
```

Out[178]:

	Blue	Wi_Fi	Tch_Scr	Ext_Mem
0	yes	yes	no	no
1	yes	yes	no	no
2	no	yes	no	no
3	no	yes	yes	no
4	no	yes	yes	no
5	yes	no	no	no
6	yes	no	yes	no
7	yes	no	no	no
8	yes	yes	yes	yes
9	yes	yes	yes	yes
10	yes	yes	yes	yes
11	yes	yes	yes	yes
12	no	yes	yes	yes
13	no	yes	yes	no
14	yes	yes	yes	yes
15	no	no	yes	yes
16	no	no	yes	yes
17	no	no	yes	yes
18	no	no	yes	yes
19	no	no	yes	yes
20	no	yes	yes	yes
21	no	yes	yes	yes
22	no	yes	yes	yes
23	no	yes	yes	yes
24	no	yes	yes	yes
25	no	yes	yes	yes
26	no	yes	yes	yes
27	yes	yes	yes	yes
28	yes	yes	yes	yes
29	no	yes	yes	yes
30	yes	yes	yes	yes
31	no	yes	yes	yes
32	yes	yes	yes	yes
33	no	yes	yes	yes
34	yes	yes	yes	yes
35	no	yes	yes	yes
36	yes	yes	yes	yes

	Blue	Wi_Fi	Tch_Scr	Ext_Mem
37	yes	yes	yes	yes
38	yes	yes	yes	yes
39	yes	yes	yes	yes
40	yes	yes	yes	yes
41	yes	yes	yes	yes
42	yes	yes	yes	yes
43	no	yes	yes	yes
44	yes	yes	yes	yes
45	no	yes	yes	yes
46	yes	yes	yes	yes
47	yes	yes	yes	no
48	yes	yes	yes	no
49	yes	yes	yes	no

```
# Get the dimensions of the dataframe
```

```
df1.columns
```

```
Out[169]:
```

```
Index([
    0,      1,      2,      3,      4,      5,
    6,      7,      8,      9,     10,     11,
    12,     13,     14,     15,     16,     17,
    18,     19,     20,     21,     22,     23,
    24,     25,     26,     27,     28,     29,
    30,     31,     32,     33,     34,     35,
    36,     37,     38,     39,     40,     41,
    42,     43,     44,     45,     46,     47,
    48,     49,  'Blue', 'Bty_Pwr', 'Depth', 'Ext_Mem',
    'FC', 'Int_Mem', 'PC', 'PID', 'Price', 'Px_h',
    'Px_w', 'Pxx', 'RAM', 'Scr_d', 'Scr_h', 'Scr_w',
    'Tch_Scr', 'Weight', 'Wi_Fi'],
      dtype='object')
```

In []:

```
df1.info()
```

```
<class 'pandas.core.frame.DataFrame'>
```

```
Index: 51 entries, 0 to Scr_d
```

```
Data columns (total 69 columns):
```

#	Column	Non-Null Count	Dtype
0	0	0 non-null	float64
1	1	0 non-null	float64
2	2	0 non-null	float64
3	3	0 non-null	float64
4	4	0 non-null	float64
5	5	0 non-null	float64
6	6	0 non-null	float64
7	7	0 non-null	float64
8	8	0 non-null	float64
9	9	0 non-null	float64
10	10	0 non-null	float64
11	11	0 non-null	float64
12	12	0 non-null	float64
13	13	0 non-null	float64
14	14	0 non-null	float64
15	15	0 non-null	float64
16	16	0 non-null	float64
17	17	0 non-null	float64
18	18	0 non-null	float64
19	19	0 non-null	float64
20	20	0 non-null	float64
21	21	0 non-null	float64
22	22	0 non-null	float64
23	23	0 non-null	float64
24	24	0 non-null	float64
25	25	0 non-null	float64
26	26	0 non-null	float64
27	27	0 non-null	float64
28	28	0 non-null	float64
29	29	0 non-null	float64
30	30	0 non-null	float64
31	31	0 non-null	float64
32	32	0 non-null	float64
33	33	0 non-null	float64
34	34	0 non-null	float64
35	35	0 non-null	float64
36	36	0 non-null	float64
37	37	0 non-null	float64
38	38	0 non-null	float64
39	39	0 non-null	float64
40	40	0 non-null	float64
41	41	0 non-null	float64
42	42	0 non-null	float64
43	43	0 non-null	float64
44	44	0 non-null	float64
45	45	0 non-null	float64
46	46	0 non-null	float64
47	47	0 non-null	float64
48	48	0 non-null	float64
49	49	0 non-null	float64
50	Blue	0 non-null	object
51	Bty_Pwr	0 non-null	float64
52	Depth	0 non-null	float64
53	Ext_Mem	0 non-null	object
54	FC	0 non-null	float64
55	Int_Mem	0 non-null	float64

```
56 PC      0 non-null    float64
57 PID     0 non-null    object
58 Price   0 non-null    float64
59 Px_h    0 non-null    float64
60 Px_w    0 non-null    float64
61 Pxx     0 non-null    float64
62 RAM     0 non-null    float64
63 Scr_d    0 non-null    float64
64 Scr_h    0 non-null    float64
65 Scr_w    0 non-null    float64
66 Tch_Scr 0 non-null    object
67 Weight  0 non-null    float64
68 Wi_Fi   0 non-null    object
dtypes: float64(64), object(5)
memory usage: 29.9+ KB
```

In []:

```
# Sort the dataframe according to the "Price" feature in ascending order and display it  
df1.sort_values(by = 'Price')
```


Out[170]:

	0	1	2	3	4	5	6	7	8	9	...	Px_h	Px_w	Pxx	RAM
0	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
1	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
2	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
3	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
4	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
5	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
6	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
7	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
8	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
9	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
10	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
11	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
12	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
13	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
14	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
15	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
16	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
17	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
18	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
19	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
20	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
21	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
22	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
23	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
24	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
25	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
26	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
27	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
28	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
29	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
30	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
31	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
32	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
33	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
34	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
35	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
36	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN

	0	1	2	3	4	5	6	7	8	9	...	Px_h	Px_w	Pxx	RAM
37	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
38	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
39	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
40	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
41	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
42	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
43	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
44	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
45	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
46	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
47	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
48	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
49	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN
Scr_d	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN

Observations:
51 rows × 16 columns

Based on all the logical conditions obtained through analysis of the features, we are left with three phones.

The most expensive of these phones is the "TYS938L" model and the least expensive is the "TVF078Y" model.

We could let the children choose from these three phones as per their preferences.

Task 9 - Study the variability of the features in the original data set

In []:

```
# Calculate the ratio of the standard deviation to the mean for all the numerical features
# Store these values in a new series wherein the rows are the features and the only column is the ratio
# Name the series as "deviations"
```

```
std_dev = data.std()
mean = data.mean()
deviations = std_dev/mean
```

<ipython-input-183-27d99c529612>:5: FutureWarning: Dropping of nuisance columns in DataFrame reductions (with 'numeric_only=None') is deprecated; in a future version this will raise TypeError. Select only valid columns before calling the reduction.

```
std_dev = data.std()
```

<ipython-input-183-27d99c529612>:6: FutureWarning: Dropping of nuisance columns in DataFrame reductions (with 'numeric_only=None') is deprecated; in a future version this will raise TypeError. Select only valid columns before calling the reduction.

```
mean = data.mean()
```

In []:

```
# View the "deviations" series after sorting it in descending order
```

```
deviations.sort_values()
```

Out[184]:

```
Px_w      0.256226
Bty_Pwr    0.256368
Px_h      0.257998
Depth     0.306072
Scr_h      0.314293
Scr_d      0.340469
Weight     0.388121
Scr_w      0.407624
RAM        0.479075
Pxx        0.615941
FC         0.712184
PC         0.715716
Price      0.740868
Int_Mem    1.506514
dtype: float64
```

Observations:

The ratio of the standard deviation to the mean of a feature normalises it in a way.

This allows for comparison between multiple features.

The most variable feature in the original data set is the internal memory of the phones.

The least variable feature in the original data set is the number of screen pixels in the horizontal axis.

Although most features don't seem so variable, the prices of the phones are quite variable.

Feel free to investigate what could be the cause of this difference in variability.

Note: We encourage you to extend this analysis further and see what else you can find.

Note: Please refer to the official website of Python and its libraries for various Python documentations.

Conclusion

1. We have used concepts of descriptive statistics to study and work with a data set that contains mobile phone specifications.
2. We were able to recommend three phone models to the client which she can then propose to her children.

In []:

