

Fluxiflow — Database Table & Model Specification

Complete architectural schema reference covering all database models, fields, types, constraints, foreign key relationships, and tenant boundary designs.

Target System: Fluxiflow Multi-Tenant Agency ERP	Custom Models: 29 Models	Total Fields: 350 Fields across 7 Modules
--	--------------------------	---

Authentication & Organization Multi-Tenancy (accounts)

Organization (DB Table: accounts_organization)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
active_users	ForeignKey	FK, Nullable	→ Relates to CustomUser
memberships	ForeignKey	FK, Nullable	→ Relates to Membership
invitations	ForeignKey	FK, Nullable	→ Relates to Invitation
projects	ForeignKey	FK, Nullable	→ Relates to Project
task_types	ForeignKey	FK, Nullable	→ Relates to TaskType
tasks	ForeignKey	FK, Nullable	→ Relates to Task
activities	ForeignKey	FK, Nullable	→ Relates to ActivityLog
notifications	ForeignKey	FK, Nullable	→ Relates to Notification
keep_items	ForeignKey	FK, Nullable	→ Relates to KeepItem
keepauditlog	ForeignKey	FK, Nullable	→ Relates to KeepAuditLog
clients	ForeignKey	FK, Nullable	→ Relates to Client
client_brand_asset_folders	ForeignKey	FK, Nullable	→ Relates to ClientBrandAssetFolder
client_brand_assets	ForeignKey	FK, Nullable	→ Relates to ClientBrandAsset
id	UUIDField	PK, Unique, Required	-
name	CharField	Required	-
display_name	CharField	Nullable, Blankable	-
slug	CharField	Unique, Nullable, Blankable	-
logo	FileField	Nullable, Blankable	-
description	TextField	Required, Blankable, Default=	-
enable_task_types	BooleanField	Required, Default=True	-
weekly_capacity_hours	IntegerField	Required, Default=40	-
is_active	BooleanField	Required, Default=True	-
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

CustomUser (DB Table: accounts_customuser)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
logentry	ForeignKey	FK, Nullable	→ Relates to LogEntry
memberships	ForeignKey	FK, Nullable	→ Relates to Membership
sent_invitations	ForeignKey	FK, Nullable	→ Relates to Invitation
sessions	ForeignKey	FK, Nullable	→ Relates to Session
created_projects	ForeignKey	FK, Nullable	→ Relates to Project
created_tasks	ForeignKey	FK, Nullable	→ Relates to Task
completed_tasks	ForeignKey	FK, Nullable	→ Relates to Task
task_time_logs	ForeignKey	FK, Nullable	→ Relates to TaskTimeLog
task_assignments	ForeignKey	FK, Nullable	→ Relates to TaskAssignee
completed_subtasks	ForeignKey	FK, Nullable	→ Relates to SubTask
subtask_assignments	ForeignKey	FK, Nullable	→ Relates to SubTaskAssignee
task_assignment_histories	ForeignKey	FK, Nullable	→ Relates to TaskAssignmentHistory
task_comments	ForeignKey	FK, Nullable	→ Relates to TaskComment
uploaded_attachments	ForeignKey	FK, Nullable	→ Relates to TaskAttachment
activities	ForeignKey	FK, Nullable	→ Relates to ActivityLog
notifications	ForeignKey	FK, Nullable	→ Relates to Notification
related_notifications	ForeignKey	FK, Nullable	→ Relates to Notification
owned_keep_items	ForeignKey	FK, Nullable	→ Relates to KeepItem
imported_keep_items	ForeignKey	FK, Nullable	→ Relates to KeepItem
created_keep_items	ForeignKey	FK, Nullable	→ Relates to KeepItem
updated_keep_items	ForeignKey	FK, Nullable	→ Relates to KeepItem
keep_pins	ForeignKey	FK, Nullable	→ Relates to KeepUserPin
keep_recents	ForeignKey	FK, Nullable	→ Relates to KeepRecentItem
keep_permissions	ForeignKey	FK, Nullable	→ Relates to KeepPermission
keepsharelink	ForeignKey	FK, Nullable	→ Relates to KeepShareLink
keepversionhistory	ForeignKey	FK, Nullable	→ Relates to KeepVersionHistory
keepauditlog	ForeignKey	FK, Nullable	→ Relates to KeepAuditLog
created_clients	ForeignKey	FK, Nullable	→ Relates to Client
updated_clients	ForeignKey	FK, Nullable	→ Relates to Client
created_brand_asset_folders	ForeignKey	FK, Nullable	→ Relates to ClientBrandAssetFolder
uploaded_brand_assets	ForeignKey	FK, Nullable	→ Relates to ClientBrandAsset
password	CharField	Required	-
last_login	DateTimeField	Nullable, Blankable	-

is_superuser	BooleanField	Required, Default=False	Designates that this user has all permissions without explicitly assigning them.
username	CharField	Unique, Required	Required. 150 characters or fewer. Letters, digits and @/./+/-/_ only.
first_name	CharField	Required, Blankable	-
last_name	CharField	Required, Blankable	-
is_staff	BooleanField	Required, Default=False	Designates whether the user can log into this admin site.
is_active	BooleanField	Required, Default=True	Designates whether this user should be treated as active. Unselect this instead of deleting accounts.
date_joined	DateTimeField	Required	-
id	UUIDField	PK , Unique, Required	-
email	CharField	Unique, Required	-
name	CharField	Required	-
role	CharField	Required, Default=MEMBER	Choices: [ADMIN, MEMBER]
status	CharField	Required, Default=INVITED	Choices: [INVITED, ACTIVE, INACTIVE]
active_organization	ForeignKey	FK , Nullable, Blankable, Indexed	→ Relates to Organization on_delete=SET_NULL
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-
deactivated_at	DateTimeField	Nullable, Blankable	-
groups	ManyToManyField	FK , Required, Blankable	→ Relates to Group The groups this user belongs to. A user will get all permissions granted to each of their groups.
user_permissions	ManyToManyField	FK , Required, Blankable	→ Relates to Permission Specific permissions for this user.

Membership (DB Table: accounts_membership)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK , Unique, Required	-
organization	ForeignKey	FK , Required, Indexed	→ Relates to Organization on_delete=CASCADE
user	ForeignKey	FK , Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
role	CharField	Required, Default=MEMBER	Choices: [ORG_ADMIN, ADMIN, MEMBER]
is_active	BooleanField	Required, Default=True	-
joined_at	DateTimeField	Required	-
created_at	DateTimeField	Required, Blankable	-

Profile (DB Table: accounts_profile)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
user	OneToOneField	FK, Unique, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
avatar	FileField	Nullable, Blankable	-

Invitation (DB Table: accounts_invitation)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
organization	ForeignKey	FK, Required, Indexed	→ Relates to Organization on_delete=CASCADE
email	CharField	Required	-
name	CharField	Required	-
role	CharField	Required, Default=MEMBER	Choices: [ORG_ADMIN, ADMIN, MEMBER]
token	UUIDField	Required	-
status	CharField	Required, Default=PENDING	Choices: [PENDING, ACCEPTED, EXPIRED]
invited_by	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
created_at	DateTimeField	Required, Blankable	-
expires_at	DateTimeField	Required	-
accepted_at	DateTimeField	Nullable, Blankable	-

OTPVerification (DB Table: accounts_otpverification)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
email	CharField	Required	-
purpose	CharField	Required, Default=LOGIN	-
hashed_otp	CharField	Required	-
expires_at	DateTimeField	Required	-
attempt_count	IntegerField	Required, Default=0	-
verified_at	DateTimeField	Nullable, Blankable	-
created_at	DateTimeField	Required, Blankable	-

Session (DB Table: accounts_session)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
refresh_token_hash	CharField	Required	-
created_at	DateTimeField	Required, Blankable	-
expires_at	DateTimeField	Required	-
revoked_at	DateTimeField	Nullable, Blankable	-
last_used_at	DateTimeField	Required, Blankable	-

Project Management (projects)

Project (DB Table: projects_project)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
tasks	ForeignKey	FK, Nullable	→ Relates to Task
notifications	ForeignKey	FK, Nullable	→ Relates to Notification
id	UUIDField	PK, Unique, Required	-
name	CharField	Required	-
description	TextField	Nullable, Blankable	-
organization	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Organization on_delete=CASCADE
client	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Client on_delete=SET_NULL
created_by	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
client_name	CharField	Nullable, Blankable	-
start_date	DateField	Nullable, Blankable	-
due_date	DateField	Nullable, Blankable	-
project_date	DateField	Nullable, Blankable	-
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

Task Management & Subtasks (tasks)

TaskType (DB Table: tasks_tasktype)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
tasks	ForeignKey	FK, Nullable	→ Relates to Task
id	UUIDField	PK, Unique, Required	-
organization	ForeignKey	FK, Required, Indexed	→ Relates to Organization on_delete=CASCADE
name	CharField	Required	-
description	TextField	Nullable, Blankable	-
allocated_seconds	IntegerField	Required, Default=3600	-
is_active	BooleanField	Required, Default=True	-
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

Task (DB Table: tasks_task)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
time_logs	ForeignKey	FK, Nullable	→ Relates to TaskTimeLog
assignee_relationships	ForeignKey	FK, Nullable	→ Relates to TaskAssignee
subtasks	ForeignKey	FK, Nullable	→ Relates to SubTask
assignment_histories	ForeignKey	FK, Nullable	→ Relates to TaskAssignmentHistory
comments	ForeignKey	FK, Nullable	→ Relates to TaskComment
attachments	ForeignKey	FK, Nullable	→ Relates to TaskAttachment
notifications	ForeignKey	FK, Nullable	→ Relates to Notification
id	UUIDField	PK, Unique, Required	-
project	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Project on_delete=CASCADE
organization	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Organization on_delete=CASCADE
task_type	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to TaskType on_delete=SET_NULL
name	CharField	Required	-
description	TextField	Nullable, Blankable	-
due_date	DateField	Nullable, Blankable	-
due_time	TimeField	Nullable, Blankable	-
priority	CharField	Nullable, Blankable, Default=MEDIUM	Choices: [LOW, MEDIUM, HIGH]
status	CharField	Required, Default=PENDING	Choices: [PENDING, COMPLETED]
created_by	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
completed_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
completed_at	DateTimeField	Nullable, Blankable	-
allocated_seconds	IntegerField	Nullable, Blankable	-
elapsed_seconds	IntegerField	Required, Default=0	-
timer_started_at	DateTimeField	Nullable, Blankable	-
timer_status	CharField	Required, Default=NOT_STARTED	Choices: [NOT_STARTED, RUNNING, PAUSED, COMPLETED]
actual_duration_seconds	IntegerField	Nullable, Blankable	-
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

TaskTimeLog (DB Table: tasks_tasktimelog)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
task	ForeignKey	FK, Required, Indexed	→ Relates to Task on_delete=CASCADE
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
started_at	DateTimeField	Required	-
paused_at	DateTimeField	Nullable, Blankable	-
duration_seconds	IntegerField	Required, Default=0	-
created_at	DateTimeField	Required, Blankable	-

TaskAssignee (DB Table: tasks_taskassignee)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
task	ForeignKey	FK, Required, Indexed	→ Relates to Task on_delete=CASCADE
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
completed	BooleanField	Required, Default=False	-
completed_at	DateTimeField	Nullable, Blankable	-

SubTask (DB Table: tasks_subtask)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
assignee_relationships	ForeignKey	FK, Nullable	→ Relates to SubTaskAssignee
assignment_histories	ForeignKey	FK, Nullable	→ Relates to TaskAssignmentHistory
comments	ForeignKey	FK, Nullable	→ Relates to TaskComment
attachments	ForeignKey	FK, Nullable	→ Relates to TaskAttachment
id	UUIDField	PK, Unique, Required	-
task	ForeignKey	FK, Required, Indexed	→ Relates to Task on_delete=CASCADE
name	CharField	Required	-
status	CharField	Required, Default=PENDING	Choices: [PENDING, COMPLETED]
due_date	DateField	Nullable, Blankable	-
due_time	TimeField	Nullable, Blankable	-
completed_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
completed_at	DateTimeField	Nullable, Blankable	-
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

SubTaskAssignee (DB Table: tasks_subtaskassignee)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
subtask	ForeignKey	FK, Required, Indexed	→ Relates to SubTask on_delete=CASCADE
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
completed	BooleanField	Required, Default=False	-
completed_at	DateTimeField	Nullable, Blankable	-

TaskAssignmentHistory (DB Table: tasks_taskassignmenthistory)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
task	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Task on_delete=CASCADE
subtask	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to SubTask on_delete=CASCADE
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
assigned_at	DateTimeField	Required	-
unassigned_at	DateTimeField	Nullable, Blankable	-
completed	BooleanField	Required, Default=False	-
completed_at	DateTimeField	Nullable, Blankable	-

TaskComment (DB Table: tasks_taskcomment)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
task	ForeignKey	FK, Required, Indexed	→ Relates to Task on_delete=CASCADE
subtask	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to SubTask on_delete=CASCADE
author	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
content	TextField	Required	-
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

TaskAttachment (DB Table: tasks_taskattachment)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
task	ForeignKey	FK, Required, Indexed	→ Relates to Task on_delete=CASCADE
subtask	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to SubTask on_delete=CASCADE
file	FileField	Required	-
original_name	CharField	Required	-
mime_type	CharField	Required	-
size	BigIntegerField	Required	-
uploaded_by	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

Activity Logs & Audit Trail (activity)

ActivityLog (DB Table: activity_activitylog)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
organization	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Organization on_delete=CASCADE
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
action	CharField	Required	Choices: [TASK_CREATED, TASK_UPDATED, TASK_DELETED, TASK_ASSIGNED, TASK_COMPLETED...]
entity_type	CharField	Required	-
entity_id	UUIDField	Nullable, Blankable	-
description	TextField	Required	-
created_at	DateTimeField	Required, Blankable	-

Notification System (notifications)

Notification (DB Table: notifications_notification)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
organization	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Organization on_delete=CASCADE
recipient	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
type	CharField	Required	Choices: [TASK_ASSIGNED, TASK_UNASSIGNED, TASK_REASSIGNED, TASK_DUE_TODAY, TASK_DUE_SOON...]
title	CharField	Required	-
message	TextField	Required	-
related_task	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Task on_delete=SET_NULL
related_project	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Project on_delete=SET_NULL
related_user	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
is_read	BooleanField	Required, Default=False	-
created_at	DateTimeField	Required, Blankable	-
read_at	DateTimeField	Nullable, Blankable	-

Keep Notes, Checklists & Documents (keep)

KeepItem (DB Table: keep_keepitem)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
children	ForeignKey	FK, Nullable	→ Relates to KeepItem
user_pins	ForeignKey	FK, Nullable	→ Relates to KeepUserPin
user_recents	ForeignKey	FK, Nullable	→ Relates to KeepRecentItem
permissions	ForeignKey	FK, Nullable	→ Relates to KeepPermission
share_links	ForeignKey	FK, Nullable	→ Relates to KeepShareLink
versions	ForeignKey	FK, Nullable	→ Relates to KeepVersionHistory
audit_logs	ForeignKey	FK, Nullable	→ Relates to KeepAuditLog
id	UUIDField	PK, Unique, Required	-
item_type	CharField	Required	Choices: [FOLDER, DOCUMENT, NOTE, SPREADSHEET, FILE]
name	CharField	Required	-
version	PositiveIntegerField	Required, Default=1	-
owner	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
organization	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Organization on_delete=CASCADE
parent_folder	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to KeepItem on_delete=SET_NULL
document_content	TextField	Required, Blankable, Default=	-
spreadsheet_data	JSONField	Required, Blankable	-
file	FileField	Nullable, Blankable	-
file_size	BigIntegerField	Nullable, Blankable	-
file_type	CharField	Nullable, Blankable	-
original_filename	CharField	Nullable, Blankable	-
original_import_filename	CharField	Nullable, Blankable	-
original_import_format	CharField	Nullable, Blankable	-
imported_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
imported_at	DateTimeField	Nullable, Blankable	-
import_warnings	JSONField	Required, Blankable	-
is_deleted	BooleanField	Required, Default=False	-
deleted_at	DateTimeField	Nullable, Blankable	-
created_by	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
updated_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
created_at	DateTimeField	Required, Blankable	-

updated_at	DateTimeField	Required, Blankable	-
-------------------	----------------------	---------------------	---

KeepUserPin (DB Table: keep_keepuserpin)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	BigAutoField	PK, Unique, Required, Blankable	-
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
item	ForeignKey	FK, Required, Indexed	→ Relates to KeepItem on_delete=CASCADE
created_at	DateTimeField	Required, Blankable	-

KeepRecentItem (DB Table: keep_keeprecentitem)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	BigAutoField	PK, Unique, Required, Blankable	-
user	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
item	ForeignKey	FK, Required, Indexed	→ Relates to KeepItem on_delete=CASCADE
last_opened_at	DateTimeField	Required, Blankable	-

KeepPermission (DB Table: keep_keeppermission)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	BigAutoField	PK, Unique, Required, Blankable	-
item	ForeignKey	FK, Required, Indexed	→ Relates to KeepItem on_delete=CASCADE
user	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=CASCADE
access_level	CharField	Required, Default=ONLY_ME	Choices: [ONLY_ME, YOU_AND_ADMINS, EVERYONE, SPECIFIC]
role	CharField	Required, Default=VIEW	Choices: [VIEW, EDIT]
created_at	DateTimeField	Required, Blankable	-

KeepShareLink (DB Table: keep_keepsharelink)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	BigAutoField	PK, Unique, Required, Blankable	-
item	ForeignKey	FK, Required, Indexed	→ Relates to KeepItem on_delete=CASCADE
token	CharField	Unique, Required, Indexed	-
permission	CharField	Required, Default=VIEW	Choices: [VIEW, EDIT]
is_active	BooleanField	Required, Default=True	-
expires_at	DateTimeField	Nullable, Blankable	-
created_by	ForeignKey	FK, Required, Indexed	→ Relates to CustomUser on_delete=CASCADE
created_at	DateTimeField	Required, Blankable	-
revoked_at	DateTimeField	Nullable, Blankable	-

KeepVersionHistory (DB Table: keep_keepversionhistory)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	BigAutoField	PK, Unique, Required, Blankable	-
item	ForeignKey	FK, Required, Indexed	→ Relates to KeepItem on_delete=CASCADE
author	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
version_number	PositiveIntegerField	Required	-
content_snapshot	TextField	Required, Blankable, Default=	-
spreadsheet_snapshot	JSONField	Required, Blankable	-
created_at	DateTimeField	Required, Blankable	-

KeepAuditLog (DB Table: keep_keepauditlog)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	BigAutoField	PK, Unique, Required, Blankable	-
item	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to KeepItem on_delete=SET_NULL
organization	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Organization on_delete=CASCADE
user	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
action	CharField	Required	-
description	CharField	Required	-
timestamp	DateTimeField	Required, Blankable	-

Client Management & Brand Assets (clients)

Client (DB Table: clients_client)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
projects	ForeignKey	FK, Nullable	→ Relates to Project
brand_asset_folders	ForeignKey	FK, Nullable	→ Relates to ClientBrandAssetFolder
brand_assets	ForeignKey	FK, Nullable	→ Relates to ClientBrandAsset
id	UUIDField	PK, Unique, Required	-
organization	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to Organization on_delete=CASCADE
name	CharField	Required	-
company_name	CharField	Nullable, Blankable	-
email	CharField	Nullable, Blankable	-
phone	CharField	Nullable, Blankable	-
website	CharField	Nullable, Blankable	-
address	TextField	Nullable, Blankable	-
city	CharField	Nullable, Blankable	-
state	CharField	Nullable, Blankable	-
country	CharField	Nullable, Blankable	-
description	TextField	Nullable, Blankable	-
notes	TextField	Nullable, Blankable	-
status	CharField	Required, Default=ACTIVE	Choices: [ACTIVE, INACTIVE]
created_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
updated_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

ClientBrandAssetFolder (DB Table: clients_clientbrandassetfolder)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
children	ForeignKey	FK, Nullable	→ Relates to ClientBrandAssetFolder
assets	ForeignKey	FK, Nullable	→ Relates to ClientBrandAsset
id	UUIDField	PK, Unique, Required	-
client	ForeignKey	FK, Required, Indexed	→ Relates to Client on_delete=CASCADE
organization	ForeignKey	FK, Required, Indexed	→ Relates to Organization on_delete=CASCADE
name	CharField	Required	-
parent	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to ClientBrandAssetFolder on_delete=CASCADE
created_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-

ClientBrandAsset (DB Table: clients_clientbrandasset)

Field Name	Type / Class	Constraints / Attributes	Details / Target Relation
id	UUIDField	PK, Unique, Required	-
client	ForeignKey	FK, Required, Indexed	→ Relates to Client on_delete=CASCADE
organization	ForeignKey	FK, Required, Indexed	→ Relates to Organization on_delete=CASCADE
folder	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to ClientBrandAssetFolder on_delete=SET_NULL
name	CharField	Required	-
file	FileField	Required	-
asset_type	CharField	Required, Default=OTHER	Choices: [BRAND_GUIDELINES, LOGO, LOGO_VARIATION, TYPOGRAPHY, COLOR_GUIDELINES...]
description	TextField	Nullable, Blankable	-
file_size	BigIntegerField	Required, Default=0	-
file_type	CharField	Nullable, Blankable	-
uploaded_by	ForeignKey	FK, Nullable, Blankable, Indexed	→ Relates to CustomUser on_delete=SET_NULL
created_at	DateTimeField	Required, Blankable	-
updated_at	DateTimeField	Required, Blankable	-