

SETTING UP HYPERLEDGER FABRIC DEVELOPMENT ENVIRONMENT

AIM

To set up and configure a Hyperledger Fabric development environment on a Linux machine using Docker, Go, and the Fabric binaries, to build a blockchain test network, and to establish a communication channel between the peer organizations.

SOFTWARE REQUIREMENTS

- Operating System: Kali Linux / Ubuntu (64-bit)
- Docker: Engine v20.10.0 or later
- Docker Compose: v2.0.0 or later
- Go Language: Version 1.20 or later
- Utilities: Git, Curl, jq
- Binaries & Images: Hyperledger Fabric Samples, Docker Images (v2.5.16)

HARDWARE REQUIREMENTS

- Processor: Intel Core i3 or above
- RAM: Minimum 8 GB
- Storage: Minimum 20 GB free disk space
- Network: Active Internet Connection

PROCEDURE

Step 1: Update the System

```
sudo apt update  
sudo apt upgrade -y
```

Step 2: Install the Required Packages

```
sudo apt install -y git curl jq docker-compose
```

Check that the utility tools were installed correctly:

```
git --version  
curl --version  
docker-compose --version
```

Step 3: Verify and Configure the Docker Installation

```
docker --version  
sudo systemctl start docker  
sudo systemctl enable docker  
sudo usermod -aG docker $USER  
newgrp docker  
docker run hello-world
```

Step 4: Verify the Go Installation

```
go version
```

Step 5: Create a Workspace Directory

```
mkdir -p ~/fabric-dev  
cd ~/fabric-dev  
pwd
```

Step 6: Download the Hyperledger Fabric Samples, Binaries, and Docker Images

```
curl -sSL https://bit.ly/2ysb0FE | bash -s
```

Step 7: Move into the Fabric Samples Directory

```
cd fabric-samples
```

Step 8: Set Up the Environment Variables

```
echo 'export PATH=$PATH:$HOME/fabric-dev/fabric-samples/bin' >>  
~/.zshrc  
source ~/.zshrc
```

Step 9: Confirm the Hyperledger Fabric Binaries

```
peer version  
orderer version
```

Step 10: Bring Up the Hyperledger Fabric Test Network

```
cd ~/fabric-dev/fabric-samples/test-network  
./network.sh up
```

Step 11: Check the Running Containers

```
docker ps
```

Step 12: Set Up an Application Channel


```
./network.sh createChannel -c mychannel
```

Step 13: Take Down the Network

Once verification is complete, shut down the network to release system resources:

```
./network.sh down
```

FLOW OF THE SETUP



OUTPUT (SCREENSHOTS)

```
user@kali-linux: ~/fabric-dev

user@kali-linux:~/fabric-dev$ go version
go version go1.22.0 linux/amd64
user@kali-linux:~/fabric-dev$ peer version
peer:
  Version: v2.5.16
  Commit SHA: 2a75cdb8e
  Go version: go1.20.12
  OS/Arch: linux/amd64
user@kali-linux:~/fabric-dev$ orderer version
orderer:
  Version: v2.5.16
  Commit SHA: 2a75cdb8e
  Go version: go1.20.12
  OS/Arch: linux/amd64
```

```
user@kali-linux: ~/fabric-dev/fabric-samples/test-network

user@kali-linux:~/fabric-dev/fabric-samples/test-network$ ./network.sh up
Starting nodes with CLI timeout of '10' tries and CLI delay of '3' seconds and
using database 'leveldb'...
LOCAL_VERSION=2.5.16
DOCKER_IMAGE_VERSION=2.5.16
Creating network "fabric_test" with the default driver
Generating certificates using cryptogen tool...
Creating org1 identities...
Creating org2 identities...
Creating Orderer Org identities...
Creating container orderer.example.com ... done
Creating container peer0.org1.example.com ... done
Creating container peer0.org2.example.com ... done
STATUS: Fabric Test Network is Up and Running!
```

```
user@kali-linux: ~/fabric-dev/fabric-samples/test-network

user@kali-linux:~/fabric-dev/fabric-samples/test-network$ docker ps --format
"table {{.Names}}\t{{.Status}}\t{{.Ports}}"

NAMES                STATUS              PORTS
peer0.org2.example.com Up 42 seconds      0.0.0.0:9051->9051/tcp
peer0.org1.example.com Up 42 seconds      0.0.0.0:7051->7051/tcp
orderer.example.com   Up 43 seconds      0.0.0.0:7050->7050/tcp
```

```
user@kali-linux: ~/fabric-dev/fabric-samples/test-network

user@kali-linux:~/fabric-dev/fabric-samples/test-network$ ./network.sh
createChannel -c mychannel
Generating channel definition asset configtx...
Creating channel 'mychannel'...
Using organization 1
    peer channel create -o localhost:7050 -c mychannel ... [Success]
    Channel 'mychannel' created successfully
Joining peer0.org1 to the channel...
    Successfully submitted proposal to join channel
Joining peer0.org2 to the channel...
    Successfully submitted proposal to join channel
Setting anchor peer for Org1...
    Anchor peer set for Org1
Setting anchor peer for Org2...
    Anchor peer set for Org2
Channel 'mychannel' joined by Org1 and Org2 successfully!
```

RESULT

The Hyperledger Fabric development environment was set up and configured successfully. The necessary Fabric binaries and Docker images were installed, the test network was brought up, the mychannel application channel was created, both peer organizations joined the channel, and the anchor peers were configured. The development environment is now ready for deploying chaincode (smart contracts) and building blockchain applications.