

Ex. No.: 6d

NAME:SHAMRUDHA VARSHINI.P

Date: 26.03.2025

ROLLNO:231901048

ROUND ROBIN SCHEDULING

Aim:

To implement the Round Robin (RR) scheduling technique using C programming.

Algorithm:

1. Start.
2. Get the number of processes and the time quantum from the user.
3. Read the process burst time (arrival time is assumed 0 for simplicity).
4. Initialize an array rem_bt[] (remaining burst time) as a copy of burst time.
5. Initialize an array wt[] (waiting time) as 0 for all processes.
6. Set current time t = 0.
7. Repeat while all processes are not completed:
 - o For each process i:
 - If rem_bt[i] > 0:
 - If rem_bt[i] > quantum:
 - t += quantum ▪ rem_bt[i] -= quantum
 - Else:
 - t += rem_bt[i]
 - wt[i] = t - bt[i]
 - rem_bt[i] = 0
8. Calculate Turnaround Time for each process as: $tat[i] = bt[i] + wt[i]$
9. Compute Average Waiting Time and Average Turnaround Time.
10. Display the process-wise result.
11. End.

Program Code (C):

```
#include <stdio.h>
```

```

int main() {    int i, n, time = 0,
quantum;    int bt[20], rem_bt[20],
wt[20], tat[20];    float avg_wt = 0,
avg_tat = 0;

    printf("Enter total number of processes: ");
scanf("%d", &n);

    printf("Enter burst time for each process:\n");
    for (i = 0; i < n; i++)
    {
        printf("P[%d]: ",
i + 1);    scanf("%d",
&bt[i]);    rem_bt[i]
= bt[i];    wt[i] = 0;
    }

    printf("Enter Time Quantum: ");
scanf("%d", &quantum);

    int done;

    do {        done = 1;        for
(i = 0; i < n; i++) {            if
(rem_bt[i] > 0) {
done = 0;                if
(rem_bt[i] > quantum) {
time += quantum;
rem_bt[i] -= quantum;
                } else {

```

```

        time += rem_bt[i];
wt[i] = time - bt[i];
rem_bt[i] = 0;

    }
}
}
} while (!done);

printf("\nProcess\tBurst Time\tWaiting Time\tTurnaround Time\n");
for (i = 0; i < n; i++) {    tat[i] = bt[i] + wt[i];
avg_wt += wt[i];    avg_tat += tat[i];
printf("P[%d]\t%d\t%d\t%d\n", i + 1, bt[i], wt[i],
tat[i]);
}

avg_wt /= n;
avg_tat /= n;

printf("\nAverage Waiting Time = %.2f", avg_wt);
printf("\nAverage Turnaround Time = %.2f\n", avg_tat);

return 0;
}

```

Sample Output:

Enter total number of processes: 4

Enter burst time for each process:

P[1]: 5

P[2]: 15

P[3]: 4

P[4]: 3

Enter Time Quantum: 5

Process	Burst Time	Waiting Time	Turnaround Time
P[1]	5	0	5
P[2]	15	12	27
P[3]	4	5	9
P[4]	3	9	12

Average Waiting Time = 6.50

Average Turnaround Time = 13.25

Result:

The Round Robin Scheduling algorithm was successfully implemented and tested. It correctly calculated the waiting and turnaround times based on the given time quantum.