Silsila

Plan once. Show up daily.

Architecture of a single-owner execution system: modules, data, flows, deployment, security and the trade-offs behind them. Written from the repository as it stands.

usesilsila.me · release 3.0.0 + Unreleased (WI-120 to WI-145) · 2026-11-03

Contents

1. Overview 4
- Product purpose 4
- Architecture classification 4
- Technology stack 4
- Design principles visible in the code 5
- Evolution 5
- Current limitations 5

2. C4 model 6
- System context 6
- Containers 6
- Components (feature modules) 7

3. Module architecture 8

4. Database architecture 10
- Planning and execution 10
- Review, notes and Google Calendar 11
- Practice 11
- Roadmap and learning 12
- Jobs and interview preparation 13
- Rumi and AI 14
- Sign-in, notifications and platform 14
- Constraints that carry the rules 15
- Historical records and consistency 15
- Time 15

5. Data flows 16
- Level 0 16
- Level 1 16

6. User flows 18
- Sign-in 19
- Today 20
- Plan 20
- Roadmap 12
- Practice 11
- Jobs 22

Weekly review 22
Settings 23
Ask Rumi 23
7. Sequences 24
Sign-in and sessions 24
Planning and executing a block 25
Recording a practice attempt 26
An interview round and its result 27
Google Calendar sync 28
Reminders, Rumi's lines and push 29
Weekly review 22
Ask Rumi 23
8. Deployment 32
9. Security architecture 34
10. Reliability and operations 35
11. Performance 36
12. Decisions and trade-offs 37
13. Interview preparation 38
30-second introduction 38
2-minute architecture explanation 38
5–10-minute technical walkthrough 38
Key engineering challenges 39
Likely follow-up questions 39
Known limitations to state honestly 39
Appendix: inventory (2026-11-02) 40

The architecture of Silsila as it exists on 2026-11-02 (`main` at WI-144, release 3.0.0 plus the Unreleased items WI-120 to WI-145). Every statement here is drawn from the repository; where something is configured outside it (hosting dashboards, schedulers), that is said. The diagrams are generated from the editable sources in `diagrams/` and are repeated in this file so it reads on GitHub; the PDF is built from this file by `node scripts/architecture-pdf.mjs`.

1. Overview

Product purpose

Silsila is a private, single-owner execution system for a person preparing for software engineering interviews. It answers one question every day: what did I plan, and what actually happened? Weekly routines become dated plans; sessions record real time; DSA practice runs on a revision ladder; job applications carry their interview rounds; each week closes with a review. Rumi, an assistant inside the app, reads the owner's records, makes small changes with Undo and proposes bigger ones as cards.

Live at https://usesilsila.me since 2026-10-20. One owner, by design: the sign-in refuses a second account and a database that already belongs to someone else.

Architecture classification

A modular monolith with a layered core, deployed as one Next.js container over one PostgreSQL database (ADR-001).

- *Monolith*: one deployable, one database, one transaction boundary. There are no services, queues or workers; scheduled work is two HTTP endpoints called by external schedulers.
- *Modular*: 31 feature folders under `src/features/`, each with pure rules (`domain.ts`), owner-scoped reads and locked writes (`service.ts`), Server Actions (`actions.ts`), loaders (`page-data.ts`) and its components.
- *Layered*: pages and route handlers call feature services; features call a small **kernel** (`src/lib`, `src/server/lock.ts`, `src/server/action.ts`) that never imports a feature. A test (`tests/boundaries.test.ts`) enforces the kernel rule, that pages never query the database, that Zod stays off client components outside a fixed list, that feature dependencies only shrink, and that every exported Server Action hands its errors to the shared runner.

It is not a strict hexagonal or clean architecture: services call Prisma directly, and 13 pairs of features still import each other (listed in the boundaries test; the list may only shrink).

Technology stack

Layer	Choice
Runtime	Node.js 24 in a Docker image (`node:24-bookworm-slim`), `next start`
Framework	Next.js 16.4.3 App Router, React 19, Server Components by default, Server Actions for forms, webpack build
Language	TypeScript, strict; Zod 4 for every input
Data	PostgreSQL 17 through Prisma 7 and `@prisma/adapter-pg`; 43 models, 29 enums, 35 versioned SQL migrations
Styling	Tailwind 4 on Silsila's tokens for new UI, hand-written `app.css` in the components layer, three CSS Modules
Time	date-fns and date-fns-tz; owner's IANA zone (America/Toronto)
Tests	Vitest (161 files, about 900 tests, database suites on a disposable PostgreSQL), Playwright with axe (21 journeys)

Layer	Choice
Hosting	Render (app), Supabase (database), cron-job.org and GitHub Actions (schedulers), Better Stack (monitor)
Integrations	Google OIDC, Google Calendar API, OpenRouter (Claude Haiku 5.5 on Vertex, zero data retention), Web Push, browser speech

Design principles visible in the code

1. **Planned and actual are different records.** `RoutineBlock` → `DailyPlan` → `TimeBlock` → `ActualSession`; nothing derives one from another (ADR-002).
2. **The owner comes from the server session only.** `owner()` in `src/server/db.ts` resolves the cookie; no id from the browser is ever trusted.
3. **Writes are serialised per owner.** Multi-row changes run in a transaction that first locks the owner's `User` row (`locked()` in `src/server/lock.ts`), and idempotency comes from unique keys.
4. **Calendar days are labels, instants are UTC.** SQL `DATE` for days, `timestamptz` for moments, every session pinned to `TimeZone=UTC` (ADR-003, ADR-009).
5. **History is append-only.** Attempts, activities, job activities and stage history are never edited.
6. **Undo over confirmation.** Server Actions return an Undo payload that `src/features/undo/service.ts` replays, checked against its own schema and the owner.
7. **AI reads through the same services and never sees private fields.** Rumi's tools are owner-scoped reads; notes, reflections, compensation and contacts are never read (ADR-024).

Evolution


Period	Work items	What changed in the architecture
2026-09-23 to 2026-10-20	WI-001 to WI-026 (1.0.0)	Monolith on PostgreSQL, planned vs actual, UTC sessions and the legacy repair, Google Calendar sync, sign-in and Web Push, Heroku then Render + Supabase, live
2026-10-25 to 2026-10-31	WI-027 to WI-098 (2.0.0)	Today as an agenda, Focus, Close the Day, the roadmap and curriculum, the revision ladder, the AI engine with a pinned provider, Rumi 1
2026-10-31 to 2026-11-01	WI-099 to WI-119 (3.0.0)	Rumi 2 and 3: memory, lines, small writes with Undo, cards, voice, streaming answers
2026-11-02	WI-120 to WI-145 (Unreleased)	The audit's clean-up: one action runner, the kernel and boundaries, page loaders, service splits, retention, ops safety, Tailwind for new UI, Talk with Rumi, this audit

Current limitations

- One owner by design; scaling to many users would need tenancy, a shared rate limiter and a job runner.
- Free hosting tiers: a sleeping instance, 0.1 CPU, a 500 MB database, app (Ohio) and database (Canada Central) in different regions, so every statement is a cross-region round trip.
- Rate limits and the snapshot cache live in process memory; a second instance would not share them.
- Voice recognition is the browser's own (Google or Apple), outside the zero-retention AI path, behind consent.


2. C4 model

System context




The owner is the only person. Google provides identity and the one calendar Silsila creates; OpenRouter provides the language model; browsers' push services deliver notifications; two schedulers call the cron endpoints; monitors read the health endpoint.

Containers



There is one application container and one database. Inside the container, `src/proxy.ts` runs before every request: it resolves the session for private routes, sets a per-request CSP nonce, applies rate limits to public endpoints and checks the bearer secret on the two cron endpoints.

Components (feature modules)



3. Module architecture

Each feature folder follows the same recipe: `domain.ts` (pure functions and Zod schemas, unit-tested without a database), `service.ts` or split service modules (owner-scoped reads, writes inside `locked()`), `actions.ts` (`'use server'`, through `runAction`), `page-data.ts` (the page's loader) and components.

Module	Responsibility	Main code	Depends on
schedule	Routines, dated plans, blocks, generation today → Sunday, Prepare next week, block editing	`features/schedule/`	kernel, calendar (sync soon)
execution	Sessions: start, pause, resume, complete; Focus	`features/execution/`	schedule
close-day	Closing a day: each open block Done, Tomorrow or Let go; a check-in	`features/close-day/`	schedule, execution
today	Today's loader and sections, the launcher, facts, Needs attention	`features/today/`	schedule, execution, jobs, dsa, roadmap, noticed
dsa, drills	Practice: problems, append-only attempts, the 3/7/14 ladder, the pattern quiz	`features/dsa/`, `features/drills/`	kernel
roadmap, curriculum, goals	Roadmaps by week, items and their revision, the default curriculum, goals	`features/roadmap/` etc.	dsa (items follow Practice), learning
learning	Learn subjects and topics (reachable by URL only)	`features/learning/`	kernel
jobs, prep	Applications, stage history, rounds, the round's block, prep items, prep docs, invites, debriefs, mocks	`features/jobs/`, `features/prep/`	schedule, roadmap, ai
review, look-back, day-print	Weekly review, months of records, a print of a closed day	`features/review/` etc.	schedule, notifications
agent (Rumi)	Chat loop, tools, small writes, cards, memory, lines, voice, page context	`features/agent/`, `app/api/rumi/ask/`	ai, most features' services
ai, listen	Model calls, the ledger and the owner's monthly limit, the pinned provider check; Grill Me, Listen	`features/ai/`, `features/listen/`	kernel
notifications, nudges, push	The durable inbox, study nudges and Rumi's lines, Web Push delivery, retention	`features/notifications/` etc.	schedule, review, agent
calendar	Google Calendar OAuth, sync (lease, push, pull, conflicts), webhook, watch channels	`features/calendar/`	schedule
undo, deletes, notes, command	Undo kinds, deletes with Undo, quick notes, the ⌘K bar	`features/undo/` etc.	the features they act on
auth, settings, setup	Sign-in, sessions, Settings' loader and sections, first-run steps	`features/auth/`, `server/session.ts`	kernel


The kernel: `src/lib/time.ts` (`dayKey`, `localInstant`, `repeatedInstant`, `dayBounds`, `hhmm`), `src/lib/day.ts` (`checkDay`, `shiftDay`, `weekDays`, `weekOf`, `isSunday`), `src/lib/categories.ts`, `src/lib/copy.ts` (`BANNED_WORDS`, `plural`), `src/lib/cookie.ts`, `src/lib/action-state.ts`, `src/server/lock.ts` (`locked`), `src/server/action.ts` (`runAction`, `failure`).

4. Database architecture


PostgreSQL 17 holds everything durable. The schema has 43 models, drawn below in seven groups. Every owner row carries `userId` with `ON DELETE CASCADE` from `User`, so the owner's data lives and goes together; links between records use `SET NULL` so deleting one record never deletes another owner record by accident.

Every owner table also carries `userId` → `User` with `ON DELETE CASCADE`; to keep the diagrams readable, that link is drawn only in the last two, where it is the only one.


Planning and execution




Review, notes and Google Calendar




Practice




Roadmap and learning




Jobs and interview preparation



Rumi and AI



Sign-in, notifications and platform



Constraints that carry the rules

Rule	Where it is enforced
A routine is generated once per day	`TimeBlock @@unique([routineKey, occurrenceDate])`
One plan per owner per day	`DailyPlan @@unique([userId, date])`
At most one running session per owner	partial unique index `one_running_session_per_user` on `ActualSession(userId) WHERE endedAt IS NULL`
A block ends after it starts; COMPLETED ⇔ completedAt	`CHECK time_block_order`, `CHECK completion_consistency`
A round has at most one block	`TimeBlock.interviewRoundId @unique`
A retried attempt, activity or stage change is written once	`@@unique([userId, requestId])` on `DsaAttempt`, `LearningActivity`, `JobActivity`
A reminder is queued once	`NotificationLog.dedupeKey @unique`
An imported roadmap item is keyed by its slug	`RoadmapItem @@unique([roadmapId, slug])`
Valid ranges	`CHECK` on ratings, durations, revision stages, confidence vs independence, problem URLs
One weekly review per week	`WeeklyReview @@unique([userId, weekStart])`

Indexes follow the reads: a day's blocks by `(dailyPlanId, plannedStart)` (WI-140), revisions due by `(userId, nextRevisionAt)`, the inbox by `(userId, readAt, scheduledFor)`, history by `(…, occurredAt)` and `(…, attemptedAt)`, sessions by `(userId, startedAt)`.

Historical records and consistency


- `DsaAttempt`, `LearningActivity`, `JobActivity` and stage history are append-only; corrections are new rows.
- `TimeBlock` keeps its own copy of the routine's title and times (a snapshot); editing a dated block never touches its routine, and a routine edit reaches future days only through a previewed choice.
- A deleted block is cancelled with the reason `Deleted`, not removed, so the calendar sync can remove its Google event and Undo can bring it back.
- Every multi-row write runs in one transaction behind the owner lock. The calendar sync uses a lease on its connection row instead, because it calls Google between statements.
- Migrations are SQL files, never edited after they ship; CI checks drift with `prisma migrate diff --exit-code` and runs an upgrade test.

Time


Instants (`plannedStart`, `startedAt`, `scheduledFor`, `sentAt`) are `timestamptz`; days (`DailyPlan.date`, `occurrenceDate`, revision and review dates) are `DATE`. Every connection is pinned to `TimeZone=UTC` and startup refuses otherwise. Local times become instants through `localInstant` (refuses a time that does not exist on a spring-forward day, for times typed for one day) and `repeatedInstant` (for thresholds such as a reminder's time or a day's midnight: a time in the gap is reached when the clock jumps; WI-145). A routine whose time falls in the gap is left out of that one day, never shifted (ADR-003). A legacy audit and a guarded one-time repair exist for data written before WI-005.1.

5. Data flows

Level 0



Level 1




Trust boundaries. (1) The public internet to `proxy.ts`: everything is untrusted until a session cookie's hash matches a live `Session`, or a cron request carries the bearer secret, or a webhook matches its channel id and token hash. (2) Server code to the database: every query is scoped by the owner id from the session. (3) The server to third parties: Google gets only the dedicated calendar's events; OpenRouter gets the question and owner-scoped reads stripped of private fields; push services get an encrypted payload with generic text.


Sensitive flows. Calendar refresh tokens are encrypted with AES-256-GCM before they are stored. Session tokens are stored only as SHA-256 hashes. Notes, reflections, compensation, contacts and job-description text never reach the model and never reach logs. Backups leave the database only as age-encrypted artifacts.

6. User flows


Sign-in


Any private page
no session
/login?next=...
Continue with Google
Verified email is OWNER_EMAIL and no other owner exists?
yes
no
Session row + 30-day cookie
/login with a plain error
Back to next (same-origin only)
Settings → Sessions: sign out other devices
Sign out: session revoked, cookie cleared


Today


Today: greeting, date, clock, one quotation
Facts: yesterday's and the week's counts
Needs attention: interviews, follow-ups, revisions, reminders, Rumi noticed
Rumi's line card: Start, Move, Let go, Ask Rumi, Reply
Add a block for this day
Launcher state
earlier blocks undecided
day over
quiet yesterday
block next
block running
Update earlier blocks: Done / Skip / Move
Close the day: each block Done, Tomorrow or Let go; one line
Let go of yesterday's blocks (Undo)
Start session
Focus: pause, resume, complete


Plan


Plan (/calendar): the week as one list
‹ › weeks around it
Routines panel: add, edit (preview of future days), disable
A block: edit for this day only, move, delete (Undo)
Prepare next week (generates next week's days)
Google Calendar: Sync now, connection state
edit
Apply to planned days?
preview accepted
Future occurrences change; past and edited stay


Roadmap




Practice




Jobs




Weekly review



Settings




Ask Rumi




7. Sequences


Sign-in and sessions




Planning and executing a block




Recording a practice attempt




An interview round and its result




Google Calendar sync




Reminders, Rumi's lines and push




Weekly review



Ask Rumi


Owner
Rumi drawer (client)
POST /api/rumi/ask
agent service
ai engine (ledger)
OpenRouter
PostgreSQL
question (typed or Talk)
JSON {conversationId, text, voice, page}
same-origin check, owner(), Zod, 4,000 chars max
askRumi (stream lines as they happen)
history window, memory lines, page record as data
loop
[at most MAX_ROUNDS]
reserve cost under the owner lock (monthly limit if the owner set one)
chat + tools (pinned provider, zdr, cached system prompt)
text or tool calls
settle AiUsage (tokens, micros)
alt
[read tool]
owner-scoped read · ids remembered
{"read":"get_today"}
[small write (note, block, rest day)]
lock owner · write through the feature service · action + Undo
{"write":"add_note"}
[bigger change]
card stored on the answer · the owner presses Apply later
store the answer with actions, cards, seen ids
{"done": answer} then {"kept": memories}
A model failure after a write still stores the answer with its Undo (WI-145)

8. Deployment



Concern	How it works	Verified from
Runtime	Render free web service, Docker image from this repository, Ohio, `next start`; deploys `main` only after the Quality workflow passes	`Dockerfile`, `docs/engineering/deployment.md`, ADR-014
Database	Supabase free PostgreSQL 17, Canada Central, session pooler, TLS with `DATABASE_SSL=no-verify`	`.env.example`, deployment guide
Domain and HTTPS	`usesilsila.me`; HSTS and a nonce CSP from `src/server/security.ts`	code; a public GET of `/privacy` on 2026-11-02
Configuration	Environment variables validated at startup by `src/lib/env.ts`; production refuses to start with a missing or invalid value and never prints values	code
Scheduled work	cron-job.org: `/api/notifications/process` every minute, `/api/calendar/sync` every 5–15 minutes; a GitHub Actions caller every 15 minutes as a second caller	`docs/engineering/operations.md`, `.github/workflows/scheduler.yml`
Health	`/api/health`: database, session time zone, schema version, jobs fresh or stale; Render's health check and Better Stack read it	code; dashboards are outside the repository

Concern	How it works	Verified from
Backups	Daily GitHub Actions dump, restore-checked, encrypted with age to the owner's public key; the owner's monthly recovery drill (`scripts/restore-drill.sh`)	`.github/workflows/backup.yml`, `docs/engineering/backup-restore.md`
Migrations	Applied from the workstation to Supabase before the merge, after a verified backup	operations runbook

The Render and Supabase dashboards, cron-job.org and Better Stack are configured outside the repository; their settings above come from the runbooks, not from inspection of those dashboards.

9. Security architecture

- **Authentication.** Google OIDC with PKCE (S256), state and nonce in an AES-256-GCM encrypted, path-scoped, 10-minute cookie; `openid email` scope only; the verified email must equal `OWNER_EMAIL`; a database with another owner refuses sign-in.
- **Sessions.** A random token in an httpOnly, SameSite=Lax, Secure (over HTTPS) cookie for 30 days; only its SHA-256 hash is stored; sign-out revokes the row; Settings signs out other devices; resolved sessions are cached for 60 seconds.
- **Authorisation.** One owner: every page, action and private API calls `owner()`, and every query filters by that id. Owner-scoping tests run per area (`*-security.test.ts`), including Rumi's tools, cards and undo payloads.
- **Request protection.** `proxy.ts` gates private routes (redirect to `/login`, 401 for APIs); Server Actions keep Next's same-origin check; the Rumi stream checks `Origin` against `Host`; a nonce-based CSP with `strict-dynamic`; HSTS; rate limits on sign-in, the callback, the webhook and the health check.
- **Integrations.** Calendar refresh tokens encrypted with AES-256-GCM (`CALENDAR_TOKEN_ENCRYPTION_KEY`, 16-byte tag enforced); only the app-created calendar is read or written; the webhook checks channel id and a token hash; push subscriptions must point at a known browser push service; the AI provider is pinned and its zero-retention listing is checked daily.
- **Secrets.** Environment only, validated without printing; nothing `NEXT_PUBLIC_`; cron endpoints need `Authorization: Bearer $CRON_SECRET`; backups encrypted to a public key so the repository holds no private key.
- **Logs.** A fixed vocabulary (`docs/engineering/security.md`): error classes, codes, counts and short references, never tokens, personal text or contacts.

10. Reliability and operations

- **Idempotency.** Unique keys make generation, attempts, activities, stage changes and reminders safe to retry; both cron endpoints are safe to call twice or concurrently.
- **Concurrency.** The owner row lock serialises an owner's writes; the calendar uses a lease; the one-running-session index stops two sessions even under a race.
- **Partial failure.** A Rumi answer that fails after a change still stores the change with its Undo (WI-145). Each daily job beside the reminders runs on its own (WI-145). Push failures never remove inbox rows. A follow-up after a committed action (a calendar sync) never turns the action into a failure.
- **Timeouts.** The pool cancels a statement after 15 seconds; each Google request attempt times out after 10 seconds; the model call has its own timeout.
- **Detection.** `/api/health` reports `jobs: ok | stale` from `JobRun` freshness; a calendar run where every connection failed now counts as a failure, so it turns stale (WI-145). Server errors are logged with the reference the error page shows.
- **Recovery.** Daily encrypted backups with a restore check; the owner's monthly drill (`scripts/restore-drill.sh`), first run on 2026-11-02: 3 s to a verified restore; up to a day of writes can be lost (Supabase Free keeps no provider backups).

11. Performance

- Every statement is a cross-region round trip (Ohio to Canada Central), so pages are designed by statement count: `currentSession` is request-cached, read-only snapshots go through a three-minute in-process cache (`src/server/memo.ts`) dropped by every write, Today's Needs attention streams behind its own Suspense boundary, links prefetch only on intent.
- Generation is skipped with one count query when the week is already planned.
- The model's system prompt and tools are sent as cached blocks (WI-143).
- Zod is kept out of client bundles except on seven form pages; the shell, `/privacy` and Today ship without it.

12. Decisions and trade-offs

Decision	Chosen	Alternatives	Why
Shape (ADR-001)	Modular monolith on PostgreSQL	Services, a BaaS	One owner, one transaction boundary, simplest operations
Planned vs actual (ADR-002)	Separate templates, dated snapshots and sessions	One "task" with a done flag	The gap between plan and record is the product
Time (ADR-003, ADR-009)	DATE labels, UTC instants, UTC sessions	Store local times, or everything as timestamps	DST and day boundaries stay correct; a legacy repair existed once
Concurrency (ADR-004)	Owner row lock + unique keys	Optimistic retries, a queue	Few writers, so serialising is cheap and simple
Access (ADR-005, ADR-012)	Google OIDC, one allowlisted owner, server sessions	Passwords, JWT sessions	No password storage; revocable sessions
Calendar (ADR-010)	Only an app-created calendar, dated blocks only	Two-way sync with the main calendar	Never touch the owner's other events
Cache (ADR-017)	Three-minute in-process snapshots dropped on writes	Redis, no cache	Free tier, one instance, round trips dominate
Hosting (ADR-013, ADR-014)	Docker on Render + Supabase free	Heroku (credit pending), a VPS	Zero cost, portable image
AI (ADR-021, ADR-022, ADR-024, ADR-030)	One pinned model with zero data retention; reads first, small writes with Undo, bigger ones as cards; a monthly limit the owner sets	Free models that may train on prompts, autonomous writes	Privacy and reversibility over autonomy
Styling (WI-135, WI-137)	Tailwind for new UI, the old stylesheet below it	A big rewrite	Change pages when they are next touched

13. Interview preparation

30-second introduction

Silsila is a full-stack app I built and run in production at usesilsila.me. It is a personal execution system for interview preparation: it turns weekly routines into dated plans, records what actually happened, runs DSA practice on spaced revision, tracks job applications and interview rounds, and closes each week with a review. It is Next.js 16 with React Server Components and Server Actions on PostgreSQL through Prisma, deployed as a Docker image on Render with Supabase, with Google sign-in, Google Calendar sync, Web Push, and an AI assistant that reads my records but cannot see private fields.

2-minute architecture explanation

It is a modular monolith: one container and one database. Every request goes through a proxy that resolves the session from a hashed token, sets a CSP nonce, and rate-limits public endpoints. Pages are Server Components that read through feature loaders; forms are Server Actions that run through one action runner, which resolves the owner, validates with Zod, writes inside a transaction that locks the owner's row, then invalidates a small in-process cache and returns an Undo. The core domain separates templates, dated plans, planned blocks and actual sessions, so planned and actual time never overwrite each other. Days are SQL DATEs and instants are UTC timestamps, and every database session is pinned to UTC. Scheduled work is two idempotent HTTP endpoints called by external schedulers: one builds the reminder inbox and delivers push, the other syncs a dedicated Google calendar with a lease. The assistant calls a pinned model with zero data retention; its tools are owner-scoped reads, small writes that carry an Undo, and cards for bigger changes the owner applies.

5–10-minute technical walkthrough

1. **The problem and the core model** (1 min). Routine → DailyPlan → TimeBlock → ActualSession. Generation is idempotent on `(routineKey, occurrenceDate)` and fills today to Sunday when Today or Plan is viewed; next week is prepared on purpose.
2. **Request path** (1 min). `proxy.ts` → Server Component → `page-data.ts` loader → services; Server Actions through `runAction` (owner, Zod, `locked()`, error classes, references, revalidation).
3. **Data integrity** (2 min). The owner lock, unique keys for retries, the partial unique index for one running session, CHECK constraints, append-only history, Undo payloads validated per kind and owner.
4. **Time** (1 min). DATE vs `timestamptz`, the UTC session pin, DST: a typed time that does not exist is refused, a routine in the gap is left out of that one day, and a reminder in the gap is due when the clock jumps.
5. **Integrations** (2 min). Google OIDC with PKCE; Calendar sync with a lease, etags, a sync token, conflicts recorded and only the dedicated calendar touched; Web Push as a channel over a durable inbox; the AI engine with a ledger, a pinned zero-retention provider checked daily, and a monthly limit the owner sets.
6. **Rumi** (1 min). A tool loop with a round cap, reads streamed as NDJSON, writes only on ids the conversation has read, two write classes (at once with Undo, or a card), memory kept only from the owner's own words.
7. **Operations and testing** (1 min). CI gate (lint, types, unit and database tests, build, e2e with axe, docs links), daily encrypted backups, health with job freshness, owner-scoping tests and a boundaries test that keeps the architecture honest.

Key engineering challenges

- **DST and day boundaries.** Solved with DATE labels, UTC sessions and two explicit conversions; tests cover both transitions.
- **Idempotent scheduling without a queue.** Unique dedupe keys and the owner lock make every cron run safe to repeat.
- **Two-way calendar sync without touching other events.** A dedicated calendar, private properties on events, a lease and etags.
- **An assistant that can change data safely.** Owner-scoped tools, a seen-id rule, write caps, Undo on every write, cards for anything bigger, and the change kept even if the model fails afterwards.

Likely follow-up questions

Why a monolith and not microservices? One owner and one database: a monolith gives one transaction boundary and no network between modules. Modularity is enforced in code instead (feature folders, a kernel, a boundaries test).

How do you stop two sessions running at once? A partial unique index on `ActualSession(userId) WHERE endedAt IS NULL`, so even a race loses at the database, plus the owner lock in the service.

How do retries not duplicate data? Each write that can be retried carries a request id or a natural key with a unique constraint (`requestId`, `dedupeKey`, `routineKey + occurrenceDate`).

How do you handle time zones? Days are DATE labels, instants are UTC, sessions are pinned to UTC, and the owner's zone converts between them at the edges. A spring-forward time typed for one day is refused; a routine in the gap is left out of that day, never shifted; a reminder in the gap is due when the clock jumps.

What does the AI see? Owner-scoped reads through the same services; never notes, reflections, compensation, contacts or job descriptions. The provider is pinned with zero data retention and checked daily; the owner sets the monthly limit.

What happens if Google or the model is down? Calendar errors are recorded on the connection with backoff; a run where all connections fail turns the job stale on the health check. A model failure after a change keeps the change and its Undo; without a change the owner sees a plain message.

How is it secured? OIDC with PKCE, an allowlisted owner, hashed server sessions, nonce CSP, HSTS, rate limits, encrypted tokens, bearer-protected cron, owner-scoping tests, a fixed log vocabulary.

How would it scale to many users? Add tenancy to every query (already owner-scoped), move rate limits and the cache to shared storage, move scheduled work to a job runner, and put the app and database in one region.

What would you change? Put the app and database in one region, move off free tiers, add error tracking, and keep shrinking the remaining feature cycles.

Known limitations to state honestly

Single owner; free-tier latency and limits; in-memory rate limits; browser-dependent voice; real-device checks (the owner's Android phone) are manual; the logo artwork is provisional.

Appendix: inventory (2026-11-02)

23 pages, 11 route handlers, 26 Server Action files with 120 exported actions, 90 client components, 31 feature folders, 43 models, 29 enums, 35 migrations (latest `20261107000000_time_block_plan_index`), 386 TypeScript files and about 68,700 lines in `src/` (with CSS), 161 Vitest files, 21 Playwright journeys.