```
In [2]: import seaborn as sns
         import matplotlib.pyplot as plt
 In [3]: from sklearn.datasets import make_blobs
 In [7]: data = make blobs(n samples = 200, n features = 2, centers = 4,
                           cluster std = 1.8, random state = 101)
 In [9]: data[0].shape
Out[9]: (200, 2)
In [15]: plt.scatter(data[0][:,0],data[0][:,1],c=data[1],cmap='rainbow')
Out[15]: <matplotlib.collections.PathCollection at 0x1a1aa71ba8>
           10
            0
           -5
          -10
                             -5
                                      ò
             -15
                     -10
In [16]: from sklearn.cluster import KMeans
In [17]: | kmeans = KMeans(n_clusters=4)
In [18]: kmeans.fit(data[0])
Out[18]: KMeans(algorithm='auto', copy_x=True, init='k-means++', max_iter=300,
                n_clusters=4, n_init=10, n_jobs=None, precompute_distances='auto',
                random state=None, tol=0.0001, verbose=0)
In [19]: kmeans.cluster_centers_
Out[19]: array([[-0.0123077 , 2.13407664],
                [-9.46941837, -6.56081545],
                [-4.13591321, 7.95389851],
                [ 3.71749226, 7.01388735]])
```

1 of 2 2019-08-11, 3:22 p.m.

In []:

```
In [21]:
         # will return most likely labels(KMeans)
         kmeans.labels_
Out[21]: array([2, 3, 0, 3, 3, 1, 3, 0, 3, 0, 2, 0, 3, 3, 2, 0, 3, 0, 1, 2, 1, 0,
                 0, 1, 2, 1, 1, 0, 3, 3, 2, 1, 3, 0, 0, 2, 1, 1,
                0, 3, 2, 0, 1, 0, 0, 2, 3, 0, 1, 2,
                                                     0, 0, 2, 3, 1, 3, 1, 2, 3, 0,
                1, 3, 3, 1, 3, 0, 1, 0, 1, 3, 3, 0, 2, 0, 0, 1, 3, 1, 0, 0, 0, 2,
                0, 1, 1, 1, 1, 0, 0, 1, 3, 2, 1, 3, 0, 1, 0, 0, 3, 0, 1, 3, 1, 1,
                3, 2, 2, 3, 1, 3, 2, 2, 3, 2, 0, 2, 0, 2, 0, 3, 2, 0, 1, 2, 2, 2,
                0, 1, 1, 2, 3, 2, 3, 0, 1, 3, 1, 2, 2, 3, 0, 1, 2, 2, 2, 2, 2, 0, 3,
                0, 2, 3, 3, 3, 0, 3, 0, 0, 2, 1, 2, 0, 3, 2, 0, 3, 0, 2, 3, 0, 2,
                3, 3, 1, 3, 2, 1, 1, 2, 1, 1, 1, 1, 1, 0, 1, 3, 3, 2, 1, 0, 3, 3,
                1, 0], dtype=int32)
In [22]: # now compare plots to see how acurate
         fig, (ax1,ax2) = plt.subplots(1,2, sharey=True, figsize=(10,6))
         ax1.set_title('K Means')
         ax1.scatter(data[0][:,0],data[0][:,1], c=kmeans.labels_,cmap='rainbow')
         ax2.set title('Original')
         ax2.scatter(data[0][:,0],data[0][:,1], c=data[1],cmap='rainbow')
Out[22]: <matplotlib.collections.PathCollection at 0x1a1bac7e48>
                          K Means
                                                                Original
           10
            5
            0
          -10
                   -io
                          -5
                                ò
                                                               -5
                                                                            Ś
                                                  -15
                                                         -10
                                                                      Ó
```

2 of 2 2019-08-11, 3:22 p.m.