Digital Image Processing

Chap 6: Color Image Processing

清華大學電機系林嘉文


cwlin@ee.nthu.edu.tw Tel: 03-5731152


Color Image Processing


- Color is a powerful descriptor
- Human can discern thousands of color shades.
- "color" is more pleasing than "black and white".
- Full Color: color from full-color sensor, i.e., CCD camera
- Pseudo color: assign a color to a particular monochromatic intensity.

2018/11/4

Digital Image Processing







Color Fundamentals


- The colors that humans perceive of an object are determined by the nature of the light reflected from the object.
- ullet Incident light (electromagnetic wave) ullet human eyes
- The light is visible to human eyes if its wavelength is between 380–780 (nm). Human eyes have the following sensitivity:
 - 1. Brightness: light intensity (energy)
 - 2. Color: different spectral composition.

2018/11/4

Digital Image Processing

Color Fundamentals

- Color Mixture
- light of any color can be synthesized by ar approximation mixture of three primary colors
- James Clerk Maxwell (1855) provided "colormetry"



Color Fundamentals

- **Tristimulus values** of a test color are the amounts of three primary colors required to give a match by additive mixture.
- Two rules of colorimetry:
 - Linearity
 - Additivity

2018/11/4

Digital Image Processing

Color Fundamentals

linearity:

If
$$S_1(\lambda) \xleftarrow{\text{color}} S_2(\lambda)$$
 then $aS_1(\lambda) \xleftarrow{\text{color}} aS_2(\lambda)$


• additivity:


$$\begin{array}{ccc} \text{If } S_1(\lambda) \xleftarrow{\text{color}} S_2(\lambda) & \text{and} & S_3(\lambda) \xleftarrow{\text{color}} S_4(\lambda) \\ \text{then} & S_{1(\lambda)} + S_3(\lambda) \xleftarrow{\text{color}} S_{2(\lambda)} + S_4(\lambda) \end{array}$$


• Color with negative tri-stimulus values:
$$\underbrace{color}_{color} \qquad aR(\lambda) - bG(\lambda) + cB(\lambda)$$


2018/11/4


Digital Image Processing











Color Matching Function

- Color matching function: the tristimulus values of the spectral color with unit intensity light of single wavelength.
- The primary colors are the spectral colors of wavelength (CIE 1931):

$$\begin{cases} 700.0 \ (R_0) \\ 546.1 \ (G_0) \\ 435.8 \ (B_0) \end{cases}$$


2018/11/4

Digital Image Processing

15

Color Matching Function

• CIE RGB and XYZ color matching functions: RGB is shown in dashed lines, and XYZ is shown in solid lines.



2018/11/4

Color Matching Function

• Any color $S(\lambda)$ can be derived as the color sensitivity summation as

$$S(\lambda)d\lambda = R_{s}(\lambda)d\lambda + G_{s}(\lambda)d\lambda + B_{s}(\lambda)d\lambda$$

$$R_s = \int_{\lambda} R_s(\lambda) d\lambda$$

$$G_s = \int_{\lambda} G_s(\lambda) d\lambda \quad R_s, G_s, B_s : \text{tristimul us values of components}$$

$$B_s = \int_{\lambda} B_s(\lambda) d\lambda$$

Using color matching function $r(\lambda)$, $g(\lambda)$, $b(\lambda)$

$$R_s = \int S(\lambda)r(\lambda)d\lambda, \quad G_s = \int S(\lambda)g(\lambda)d\lambda, \quad B_s = \int S(\lambda)b(\lambda)d\lambda$$

2018/11/4

Digital Image Processing

17

Color Matching Function

• Color matches between $S_1 \leftrightarrow S_2$

$$R_{1} = \int S_{1}(\lambda)r(\lambda)d\lambda = \int S_{2}(\lambda)r(\lambda)d\lambda = R_{2}$$

$$G_{1} = \int S_{1}(\lambda)g(\lambda)d\lambda = \int S_{2}(\lambda)g(\lambda)d\lambda = G_{2}$$

$$B_{1} = \int S_{1}(\lambda)b(\lambda)d\lambda = \int S_{2}(\lambda)b(\lambda)d\lambda = B_{2}$$

- Metamer: $S_1(\lambda) \neq S_2(\lambda), S_1(\lambda) \xleftarrow{\text{color}} S_2(\lambda)$
- Isomer: $S_1(\lambda) = S_2(\lambda)$: the same spectral distribution
- Color matching function are averaged for people with normal color vision
- Color matching normally depends on the conditions of observation and previous exposure of eyes

2018/11/4

Digital Image Processing

Color Matching Function

$$\begin{bmatrix} R \\ G \\ B \end{bmatrix} \xrightarrow{normalization} \begin{bmatrix} r \\ g \\ b \end{bmatrix} \qquad r+g+b=1$$

$$r = \frac{R}{R+G+B}$$
 $g = \frac{G}{R+G+B}$ $b = \frac{B}{R+G+B}$

Since r + g + b = 1, the 3-D color reduces to 2-D color information \rightarrow **chromaticity**

The 3rd information is the luminance

2018/11/4

Digital Image Processing

19

Color Matching

- Y (luminance) → The 3rd-dimension information
- Luminance (Brightness) sensor
- Different wavelengths contribute different brightness to the sensor
- The relative brightness response for the eye is termed "relative luminous efficiency" $y(\lambda)$
- $y(\lambda)$ is obtained by photometric matches (matching of brightness)

2018/11/4

Digital Image Processing

Color Matching

• The luminance of any spectral distribution $S(\lambda)$ is

$$Y = k_m \int S(\lambda) y(\lambda) d\lambda$$

where $k_m = 680 lumens/watt$ $1 lumen = candelas/m^2$

• Brightness match

$$\int S_1(\lambda) y(\lambda) d\lambda = \int S_2(\lambda) y(\lambda) d\lambda$$

$$S_1(\lambda) \neq S_2$$
 or $\int S_1(\lambda) d\lambda \neq \int S_2(\lambda) d\lambda$

2018/11/4

Digital Image Processing

21

Standard CIE Color System

- The tristimulus values for two color-matched colors are different for different observers.
- **Standard Observer**: by averaging the color matching data of a large number of color normal observers.
- 1931, CIE defined standard observer which consists of color matching functions for primary stimuli of wavelengths: 700 (R₀), 546.1 (G₀), 435.8 (B₀)
- Unit normalized ⇒ equal amount of three primaries are required to match the light from equal energy illumination energy.

2018/11/4

Digital Image Processing

Standard CIE Color System

• CIE also defines three new primaries : X, Y, Z

$$\begin{cases} X = 2.365R_0 - 0.515G_0 + 0.005B_0 \\ Y = -0.897R_0 + 1.426G_0 - 0.014B_0 \\ Z = -0.468R_0 + 0.089G_0 + 1.009B_0 \end{cases} \tag{a}$$

• By matrix inversion, we obtain

$$R_0 = 0.490 X + 0.177 Y$$

$$G_0 = 0.310 X + 0.813 Y + 0.01 Z$$

$$B_0 = 0.200 X + 0.010 Y + 0.990 Z$$
 (b)

• Y tristimulus value corresponds to the normalized luminance.

2018/11/4

Digital Image Processing

23

Standard CIE Color System

- The tristimulus values and color-matching function are always positive primaries; X, Y, Z are non-real (cannot be realized by actual color stimuli)
- Normalized tristimulus values:

$$x = \frac{X}{X + Y + Z}$$

$$y = \frac{Y}{X + Y + Z}$$

$$z = \frac{Z}{Y + Y + Z}$$
color { chromaticity x, y luminance Y luminance Y }

- x: red light \rightarrow orange, reddish-purple
- y: green light \rightarrow bluish-green, yellowish-green.
- small x, y: blue light \rightarrow violet or purple

2018/11/4


Digital Image Processing

Standard CIE Color System

- Chromaticity diagram: (r_0, g_0) and (x, y)
- Pure spectral colors are plotted on the elongated horseshoe-shaped curve called the spectral locus.
- line of purples: straight line consists of two extremes of the spectral locus
- chromaticity diagram ≠ color matching function


2018/11/4

Digital Image Processing



Typical Color Gamut

FIGURE 6.6 Illustrative color gamut of color monitors (triangle) and color printing devices (shaded region).



2018/11/4

Digital Image Processing

27

Color Mixtures

Grassman's Law:

- The tristimulus values of a color mixture are obtained by the vector addition of the tristimulus values of the components of the mixture
- If colors: $S_1=(X_1,Y_1,Z_1)$ and $S_2=(X_2,Y_2,Z_2)$ are mixed as S=(X,Y,Z) then $X=X_1+X_2$, $Y=Y_1+Y_2$, $Z=Z_1+Z_2$
- If colors: $S_1=(x_1,y_1,Y_1)$ and $S_2=(x_2,y_2,Y_2)$ are mixed as S=(x,y,Y) then

$$x_1, y_1$$

$$x = \frac{x_1(Y_1/y_1) + x_2(Y_2/y_2)}{(Y_1/y_1) + (Y_2/y_2)} \qquad y = \frac{Y_1 + Y_2}{(Y_1/y_1) + (Y_2/y_2)}$$


Digital Image Processing


Color Models

- The color model (color space or color system) is to facilitate the specification of colors in some standards.
- Color model is a specification of a coordinate system and a subspace within the system where a color is represented.
- RGB for color monitor.
- CMY (Cyan, Magenta, Yellow) for color printing.
- **HIS** (Hue, Intensity, Saturation): decouples the color and gray-scale information.

2018/11/4

Digital Image Processing







HSI Color Model

- Human describes a color in terms of Hue (色相、色調), Saturation (色度、飽和度) and Brightness (明度).
- **Hue**: describes the purity of color: pure yellow, orange, green or red.
- **Saturation** measures the degree to which a pure color is *diluted* by white light.
- **Brightness** is a subjective descriptor difficult to be measured.

2018/11/4

Digital Image Processing





HSI Color Model

• From RGB to HSI

$$H = \begin{cases} \theta & \text{if } B \le G \\ 360^{\circ} - \theta & \text{if } B > G \end{cases}$$
with
$$\theta = \cos^{-1} \left\{ \frac{1/2[(R-G) + (R-B)]}{[(R-G)^{2} + ((R-B)(G-B)]^{1/2}} \right\}$$


- $S = 1 [3 \cdot min(R,G,B) / (R+G+B)]$
- I = (R+G+B)/3

2018/11/4

Digital Image Processing

35

HSI Color Model



2018/11/4

Digital Image Processing

HSI Color Model

- From HSI to RGB
- R/G sector $(0^{\circ} \le H < 120^{\circ})$, min(R, G, B) = BB = I(1 - S) $R = I \left[1 + \frac{S \cos H}{\cos(60^\circ - H)} \right]$ G = 3I - (R + B)

2018/11/4

Digital Image Processing

37

HSI Color Model

G/B sector

$$(120^{\circ} \le H < 240^{\circ})$$
 $(240^{\circ} \le H < 360^{\circ})$

- $H = H 120^{\circ}$
- R = I (1 S)• G = I (1 S)• $G = I \left[1 + \frac{S \cos H}{\cos(60^\circ H)}\right]$ $B = I \left[1 + \frac{S \cos H}{\cos(60^\circ H)}\right]$
- B = 3I (R + G)

B/R sector


$$(240^{\circ} \le H < 360^{\circ})$$


- min(R, G, B) = R min(R, G, B) = G
 - $H = H 240^{\circ}$


 - R = 3I (G + B)


2018/11/4

Digital Image Processing









Pseudo Image Processing - Intensity Slicing

- Assigning colors to gray values based on a specified criterion.
- Intensity slicing: using a plane at $f(x, y) = l_i$ to slice the image function into two levels (Fig. 6.16).
- In general, we assume that P planes perpendicular to the intensity axis defined at level l_i l = 1, 2, ..., P.
- These P planes partition the gray level in to P + 1 intervals:


$$V_k, k = 1, 2, \dots, P+1$$
 and
$$f(x,y) = c_k \text{ if } f(x,y) \in V_k$$


where c_k is the color associated with the kth intensity interval V_k defined by the partition planes at l=k-1 and l=k.


• From Fig. 6.16; if more levels are used, the mapping function takes on a staircase form.


2018/11/4

Digital Image Processing









Intensity to Color Transformation


• Three independent transformation functions on the gray-level of each pixel.


Red, Green, Blue transform

- Piecewise linear function
- Smooth non-linear function


2018/11/4

Digital Image Processing









2018/11/4

Digital Image Processing

51

Intensity to Color Transformation

 Change the phase and frequency of each sinusoid can emphasize (in color) ranges in the gray scale.


Peak → constant color region.


Valley → rapid changed color region.

- A small change in the phase between the three transforms
 produces little change in pixels whose gray level corresponding
 to the peaks in the sinusoidal.
- Pixels with gray level values in the steep section of the sinusoids are assigned much strong color.

2018/11/4

Digital Image Processing





Intensity to Color Transformation





material ejected from the active volcano



2018/11/4

55

Full-Color Image Processing

- Color processing in two categories:
 - Process each component (R/G/B) individually and then form a composite processed color image from the components.
 - 2. Work with color pixels directly.


In RGB system, each color point can be interpreted as a vector, i.e., $\mathbf{c}(x,y) = [c_R(x,y), c_G(x,y), c_B(x,y)]$

2018/11/4

Digital Image Processing

Full-Color Image Processing

a b
FIGURE 6.27
Spatial
neighborhoods
for grayscale
and RGB color
images. Observe
in (b) that a single
pair of spatial
coordinates, (x, y),
addresses the
same spatial
location in all
three images.



2018/11/4

Digital Image Processing


57

Color Transformations

- Gray-level transformation: g(x, y) = T[f(x, y)]
- Color transformation: $s_i = T_i(r_1, r_2, \cdots, r_n) \ I = 1, 2, \cdots, n$ where r_i and s_i denote the **color component** of f(x, y) and g(x, y) at any point (x, y), i.e., R/G/B. n is the number of color components, (n = 3). $\{T_i\}$ is a set of transformation or color mapping functions.

2018/11/4

Digital Image Processing



Color Transformations

- To modify the **intensity** of the image $g(x,y) = kf(x,y) \ 0 < k < 1$
- HSI: $s_3 = kr_3$
- RGB: $s_i = kr_i$ i = 1, 2, 3
- CMY: $s_i = kr_i + (1-k) i = 1,2,3$

2018/11/4

Digital Image Processing

Color Transformations




FIGURE 6.29 Adjusting the intensity of an image using color transformations. (a) Original image. (b) Result of decreasing its intensity by 30% (i.e., letting k = 0.7). (c) The required RGB mapping function. (d)–(e) The required CMYK mapping functions. (f) The required CMY mapping function. (g)–(h) The required HSI mapping functions. (Original image courtesy of MedData Interactive.)

2018/11/4

Digital Image Processing


61


Color Complements

- The hues directly opposite one another on the color circle are called **complements** (互補色)
- Color complements are useful for enhancing detail that is embedded in **dark regions** of a color image.
- The saturation component of the complement of a color image cannot be computed from the saturation of the input image alone.
- In Fig. 6.30, the **saturation** component of the input image is unaltered.

2018/11/4

Digital Image Processing





Color Slicing

- **Highlighting** a specific range of colors in an image is useful for separating object from their surrounding.
- The simplest way to "slice" a color image is to map the colors outside some range of interest to a non-prominent neutral color, (R, G, B) = (0.5, 0.5, 0.5).
- If the colors of interest are enclosed by a **cube** (or hypercube for n > 3) of width W and centered at a average color with component $(a_1, a_2, ..., a_n)$, the necessary set of transformation is

$$s_{i} = \begin{cases} 0.5 & if \left[\left| r_{j} - a_{j} \right| > W / 2 \right]_{\text{any } 1 \le j \le n} \\ r_{i} & \text{otherwise} \end{cases}$$

2018/11/4

65

Color Slicing

• If a sphere is used to specify the colors of interest then

$$s_{i} = \begin{cases} 0.5 & \text{if } \sum_{j=1}^{n} (r-a)^{2} > R_{0}^{2} \\ r_{i} & \text{otherwise} \end{cases}$$

- Forcing all other colors to the mid-point of the reference color space.
- In RGB color space, the **neural color** is (0.5,0.5,0.5)

2018/11/4

Digital Image Processing

Color Slicing




FIGURE 6.32 Color-slicing transformations that detect (a) reds within an RGB cube of width W = 0.2549 centered at (0.6863, 0.1608, 0.1922), and (b) reds within an RGB sphere of radius 0.1765 centered at the same point. Pixels outside the cube and sphere were replaced by color (0.5, 0.5, 0.5).

2018/11/4

Digital Image Processing


67

Tone and Color Correction

- Digital Darkroom
- Effective transformation are developed to maintain a high degree of **color consistency** between the monitor used and the eventual output devices.
- Device independent color model: relate the color gamut (see Fig. 6.6) of the monitor and output devices as well as other devices to one another.

2018/11/4

Digital Image Processing



Tone and Color Correction

- The model of choice for many color management systems (CMS) is the CIE L*a*b* model called CIELAB.
- The $L^*a^*b^*$ color component is given as

$$L^* = 116 \cdot h(Y/Y_W) - 16$$

$$a^* = 500[h(X/X_W) - h(Y/Y_W)]$$

$$b^* = 200[h(Y/Y_W) - h(Z/Z_W)]$$

where

$$h(q) = \begin{cases} \sqrt[3]{q} & q > 0.008856 \\ 7.878q + 16/116 & q \le 0.008856 \end{cases}$$

2018/11/4

Digital Image Processing

Tone and Color Correction

- X_W , Y_W , Z_W are reference white tristimulus values.
- The L*a*b* color is colormetric (i.e., colors perceived as matching are encoded identically), perceptual uniform (i.e., color differences among various hues are perceived uniformly), and device independent.
- It is not a directly displayable format.
- The *gamut* of *L*a*b** encompasses the **entire visible spectrum** and can represent accurately the colors of any display, print, or input device.
- L*a*b* decouples intensity (L*) and color (a* and b*)

2018/11/4

Digital Image Processing


71


Tone and Color Correction

- Tonal and color imbalances are corrected interactively.
- Tonal correction and then color correction.
- The **tonal range** of an image (*key type*) refers to its general distribution of color intensity.
- High-key image: the color is concentrated at high (or light) intensity.
- Low-key image: the color is concentrated at low intensity.
- Middle-key image lies in between high-key and low-key images.
- It is desirable to distribute the intensities of a color image equally between the highlights and the shadows

2018/11/4

Digital Image Processing






Histogram Processing

- Equalizing the histogram of each component will results in erroneous color.
- Spread the color intensity (I) uniformly, leaving the color themselves (hues) unchanged.
- Equalizing the intensity histogram affects the relative appearance of colors in an image.
- Increasing the image's saturation component after the intensity histogram equalization.

2018/11/4

Digital Image Processing



Smoothing and Sharpening

• Let S_{xy} denote the set of coordinates defining a neighborhood centered at (x,y) in an RGB color space.

$$\overline{\mathbf{c}}(x,y) = \begin{bmatrix} \frac{1}{K} \sum_{(x,y) \in S_{xy}} R(x,y) \\ \frac{1}{K} \sum_{(x,y) \in S_{xy}} G(x,y) \\ \frac{1}{K} \sum_{(x,y) \in S_{xy}} B(x,y) \end{bmatrix}$$

2018/11/4

Digital Image Processing

77

Smoothing and Sharpening

a b c d
FIGURE 6.36
(a) RGB image.
(b) Red component image.
(c)Green component.
(d) Blue component.










2018/11/4

Digital Image Processing

Smoothing and Sharpening







a b c

FIGURE 6.37 HSI components of the RGB color image in Fig. 6.36(a). (a) Hue. (b) Saturation. (c) Intensity.

2018/11/4

Digital Image Processing

79

Smoothing and Sharpening







a b c

FIGURE 6.38 Image smoothing with a 5×5 averaging kernel. (a) Result of processing each RGB component image. (b) Result of processing the intensity component of the HSI image and converting to RGB. (c) Difference between the two results.

2018/11/4

Digital Image Processing

Smoothing and Sharpening

• Image sharpening using Laplacian

$$\nabla^2 \overline{\mathbf{c}}(x, y) = \begin{vmatrix} \nabla^2 R(x, y) \\ \nabla^2 G(x, y) \\ \nabla^2 B(x, y) \end{vmatrix}$$







a b c

 $\textbf{FIGURE 6.39} \ Image \ sharpening \ using \ the \ Laplacian. (a) \ Result \ of \ processing \ each \ RGB \ channel. (b) \ Result \ of \ processing \ the \ HSI \ intensity \ component \ and \ converting \ to \ RGB. (c) \ Difference \ between \ the \ two \ results.$

2018/11/4

Digital Image Processing


81

Color Segmentation

- Partition an image into regions.
- Segmentation in HSI color space.
- Saturation is used as a **masking image** to isolate further regions of interest in the **hue** image.
- The intensity image is used less frequently.

2018/11/4

Digital Image Processing



Color Segmentation in RGB

- Segmentation in RGB color space
- The measurement of color similarity is the Euclidean distance between two colors z, and a, (i.e., Fig. 6.41(a)),

$$D(\mathbf{z}, \mathbf{a}) = \|\mathbf{z} - \mathbf{a}\| = \left[(\mathbf{z} - \mathbf{a})^T (\mathbf{z} - \mathbf{a}) \right]^{1/2}$$

= $\left[(z_R - a_R)^2 + (z_G - a_G)^2 + (z_B - a_B)^2 \right]^{1/2}$


• A generalization of distance measure is


$$D(\mathbf{z}, \boldsymbol{a}) = \|\mathbf{z} - \mathbf{a}\| = \left[(\mathbf{z} - \mathbf{a})^T \mathbf{C}^{-1} (\mathbf{z} - \mathbf{a}) \right]^{1/2}$$

- Where C is the covariance matrix of the samples representative of the color we want to segment.
- Fig. 6.41(b) describes the solid elliptical body with the principal axes oriented in the direction of maximum data spread.

2018/11/4

Digital Image Processing






Color Edge Detection

- The gradient operators introduced is effective for scalar image.
- Computing the gradient on individual images and then using the results to form a color image will lead to erroneous results.

2018/11/4

Digital Image Processing



Color Edge Detection

 Let r, g, b be a unit vector along the R, G, B axis and define the unit vector as

$$\mathbf{u} = \frac{\partial R}{\partial x}\mathbf{r} + \frac{\partial G}{\partial x}\mathbf{g} + \frac{\partial B}{\partial x}\mathbf{b}$$

$$\mathbf{v} = \frac{\partial R}{\partial y} \mathbf{r} + \frac{\partial G}{\partial y} \mathbf{g} + \frac{\partial B}{\partial y} \mathbf{b}$$

- $g_{xx} = \mathbf{u} \cdot \mathbf{u} = |\partial R/\partial x|^2 + |\partial G/\partial x|^2 + |\partial B/\partial x|^2$
- $g_{yy} = \mathbf{v} \cdot \mathbf{v} = |\partial R/\partial y|^2 + |\partial G/\partial y|^2 + |\partial B/\partial y|^2$
- $g_{xy} = \mathbf{u} \cdot \mathbf{v} = (\partial R/\partial x)(\partial R/\partial y) + (\partial G/\partial x)(\partial G/\partial y) + (\partial B/\partial x)(\partial B/\partial y)$

2018/11/4

Digital Image Processing

89

Color Edge Detection

• The direction of maximum rate of change of the color pixel c(x,y) is given by the angle

$$\theta(x,y) = \frac{1}{2} \tan^{-1} \left[\frac{2g_{xy}}{\left(g_{xx} - g_{yy}\right)} \right]$$

- The value of the rate of change at (x, y) in the direction of θ is $F_{\theta}(x, y) = \left\{0.5(g_{xx} + g_{yy}) + (g_{xx} g_{yy})\cos 2\theta + 2g_{xy}\sin 2\theta\right\}^{1/2}$
- There are two solution θ_0 or $\theta_0+\pi/2$ in orthogonal directions.

$$F_{\theta}(x,y) = F_{\theta+\pi}(x,y)$$

• One generates maximum *F* and the other generates minimum *F*.

2018/11/4

Digital Image Processing



c d

FIGURE 6.44
(a) RGB image.
(b) Gradient
computed in RGB
color vector space.
(c) Gradient
image formed by
the elementwise
sum of three
individual
gradient images,
each computed
using the Sobel
operators.
(d) Difference
between (b) and
(c).



2018/11/4

Digital Image Processing

91

Color Edge Detection



a b c

FIGURE 6.45 Component gradient images of the color image in Fig. 6.44. (a) Red component, (b) green component, and (c) blue component. These three images were added and scaled to produce the image in Fig. 6.44(c).

2018/11/4

Digital Image Processing

Noise in Color Image

- The noise content of a color image has the same characteristics in each color channel.
- It is possible for color channels to be affected differently by noise.
- The fine grain noise (in Fig. 6.46) tends to be less visually noticeable in a color image than it is in a monochrome image.

2018/11/4

Digital Image Processing

93

Noise in Color Image











94

2018/11/4

Noise in Color Image







a b c

FIGURE 6.47 HSI components of the noisy color image in Fig. 6.46(d). (a) Hue. (b) Saturation. (c) Intensity.

2018/11/4

Digital Image Processing

95

Noise in Color Image











2018/11/4

Digital Image Processing

