

Programming Assignment #1: A Simple Shell

Due: Check My Courses

In this assignment you are required to create a C program that implements a shell interface that accepts user commands and executes each command in a separate process. Your shell program provides a command prompt, where the user inputs a line of command. The shell is responsible for executing the command. The shell program assumes that the first string of the line gives the name of the executable file. The rest of the strings in the line are considered as arguments for the command. Consider the following example.

```
sh > cat prog.c
```

The **cat** is the command that is executed with **prog.c** as its argument. Effectively, the user displays the contents of the file **prog.c** on the display terminal. If the file **prog.c** is not present, the **cat** program displays an appropriate error message. The shell is not responsible for such error checking.

One technique for implementing a shell interface is to have the parent process first read what the user enters on the command line (i.e., **cat prog.c**), and then create a separate child process that performs the command. Unless otherwise specified, the parent process waits for the child to exit before continuing. However, UNIX shells typically also allow the child process to run in the background – or concurrently – as well by specifying the ampersand (**&**) at the end of the command. By re-entering the above command as follows the parent and child processes can run concurrently.

```
sh > cat prog.c &
```

The separate child process is created using the **fork()** system call and the user's command is executed by using one of the system calls in the **exec()** family (see textbook or **man exec** for more information).

Simple Shell

A C program that provides the basic operations of a command line shell is supplied below. This program is composed of three functions: **main()**, **getcmd()**, and **freecmd()**. The **getcmd()** function reads in the user's next command, and then parses it into separate tokens that are used to fill the argument vector for the command to be executed. (If the command is to be run in the background, it will end with '**&**', and **getcmd()** will update the parameter background so the **main()** function can act accordingly. The program terminates when the user enters **<Control><D>**; **getcmd()** invokes **exit()**).

The **main()** invokes **getcmd()**, which waits for the user to enter a command. The contents of the command entered by the user are loaded into the **args** array. For example, if the user enters **ls -l** at the command prompt, **args[0]** becomes equal to the string **ls** and **args[1]** is set to the string to **-l**. (By "string," we mean a null-terminated, C-style string variable.)

This programming assignment is organized into three parts: (1) creating the child process and executing the command in the child, (2) modifying the shell to allow a history feature, and (3) additional commands.

Creating a Child Process

The first part of this programming assignment is to modify the **main()** function in the figure below so that upon returning from **getcmd()**, child process is forked and it executes the command specified by the user.

```
#include <stdio.h>
#include <unistd.h>
#include <string.h>
#include <stdlib.h>

int getcmd(char *prompt, char *args[], int *background)
{
    int length, i = 0;
    char *token, *loc;
    char *line;
    size_t linecap = 0;

    printf("%s", prompt);
    length = getline(&line, &linecap, stdin);

    if (length <= 0) {
        exit(-1);
    }

    // Check if background is specified..
    if ((loc = index(line, '&')) != NULL) {
        *background = 1;
        *loc = ' ';
    } else
        *background = 0;

    while ((token = strtok(&line, " \t\n")) != NULL) {
        for (int j = 0; j < strlen(token); j++)
            if (token[j] <= 32)
                token[j] = '\0';
        if (strlen(token) > 0)
            args[i++] = token;
    }

    return i;
}

int main(void)
{
    char *args[20];
    int bg;

    while(1) {
        bg = 0;
        int cnt = getcmd("\n>> ", args, &bg);

        /* the steps are:
        (1) fork a child process using fork()
        (2) the child process will invoke execvp()
        (3) if background == 0, the parent will wait,
            otherwise gets the next command... */

    }
}

freecmd()
{
    // you need to implement this one. Might need some modifications to
    // getcmd() provided with the assignment
}
```

```
}
```

As noted above, the `getcmd()` function loads the contents of the `args` array with the command line given by the user. This `args` array will be passed to the `execvp()` function, which has the following interface:

```
execvp(char *command, char *params[]);
```

Where `command` represents the file to be executed and `params` store the parameters to be supplied to this command. Be sure to check the value of `background` to determine if the parent process is to wait for the child to exit or not. You can use the `waitpid()` function to wait on the newly created child process. Check the man page for the actual usage of the `waitpid()` or similar functions that you can use.

Creating a History Feature

The next task is to modify the above program so that it provides a *history* feature that allows the user access up to the 10 most recently entered commands. These commands will be numbered starting at 1 and will continue to grow larger even past 10, e.g. if the user has entered 35 commands, the 10 most recent commands should be numbered 26 to 35. With this list, the user can run any of the previous 10 commands by entering just the number of the command. For example just typing 32 will execute the command that corresponds to entry 32. If there is no entry 32 in the history window, you print “no command found in history”. We assume no one is creating executable files with numeric filenames. Any command that is executed in this fashion should be echoed on the user’s screen and the command is also placed in the history buffer as the next command.

If the user attempts to use this history facility to run a command and the command is detected to be *erroneous*, an error message should be given to the user and the command not entered into the history list, and the `execvp()` function should not be called. (It would be nice to know about improperly formed commands that are handed off to `execvp()` that appear to look valid and are not, and not include them in the history as well, but that is beyond the capabilities of this simple shell program.) You could modify `getcmd()` as part of the history implementation.

Built-in Commands

The **history** command is a built-in command because the functionality is completely built into your shell. On the other hand, the process forking mechanism was used to execute outside commands. In addition to the **history** command, implement the **cd** (change directory), **pwd** (present working directory), and **exit** (leave shell) commands. The **cd** command could be implemented using the `chdir()` system call, the **pwd** could be implemented using the `getcwd()` library routine, and the **exit** command is necessary to quit the shell. Other built-in commands to be implemented include **fg** and **jobs**. The command **jobs** should list all the jobs that are running in the background at any given time. These are jobs that are put into the background by giving the command with **&** as the last one in the command line. Each line in the list provided by the jobs should have a number identifier that can be used by the **fg** command to bring the job to the foreground.

Simple Output Redirection

The last feature to implement is the output redirection. If you type

```
ls > out.txt
```

The output of the **ls** command should be sent to the **out.txt** file. See the class notes on how to implement this feature.

Turn-in and Marking Scheme

The programming assignment should be submitted via My Courses. Other submissions (including email) are not acceptable.

Useful Information for the Assignment

You need to know how process management is performed in Linux/Unix to complete this assignment. Here is a brief overview of the important actions.

- (a) Process creation: The **fork()** system call allows a process to create a new process (child of the creating process). The new process is an exact copy of the parent with a new process ID and its own process control block. The name “fork” comes from the idea that parent process is dividing to yield two copies of itself. The newly created child is initially running the exact same program as the parent – which is pretty useless. So we use the **execvp()** system call to change the program that is associated with the newly created child process.
- (b) The **exit()** system call terminates a process and makes all resources available for subsequent reallocation by the kernel. The **exit(status)** provides status as an integer to denote the exiting condition. The parent could use **waitpid()** system call to retrieve the status returned by the child and also wait for it.

```
#include <sys/wait.h>
```

```
pid_t waitpid(pid_t pid, int *status, int options);
```

Returns process ID of child, 0 (see text), or -1 on error

The return value and *status* arguments of *waitpid()* are the same as for *wait()*. (See Section 26.1.3 for an explanation of the value returned in *status*.) The *pid* argument enables the selection of the child to be waited for, as follows:

- If *pid* is greater than 0, wait for the child whose *process ID* equals *pid*.
- If *pid* equals 0, wait for any child in the *same process group as the caller* (parent). We describe process groups in Section 34.2.
- If *pid* is less than -1, wait for any child whose *process group* identifier equals the absolute value of *pid*.
- If *pid* equals -1, wait for *any* child. The call *wait(&status)* is equivalent to the call *waitpid(-1, &status, 0)*.