JSP-Java Server Page Tags

1.Scripting Elements -- To insert Java code in a JSP

Declaratives <%! ..... %>

Scriptlets <% ..... %>

Expression <%= ..... %>

2.Directives -- To pass directions to translator

page <%@page

autoFlush="true"

buffer="8kb"

contentType="text/html"

errorPage=" "

extends=" "

import=" "

info=" "

isELIgnored="false"

isErrorPage="false"

isThreadSafe="true"

language="java"

session="true"

deferredSyntaxAllowedAsLiteral="false"

pageEncoding=" "

trimDirectiveWhitespaces="false" %>

include <%@include file=" " %>

taglib <%@taglib uri=" " prefix=" " %>

3.Action Tags -- To communicate with Bean, Applet, Servlet, JSP, HTML

<!-- TO COMMUNICATE WITH SERVLET, JSP AND HTML -->

<jsp:forward page=" "> </jsp:forward>

<jsp:param name=" " value=" " />

<jsp:include page=" "> </jsp:include>

<!-- TO COMMUNICATE WITH BEAN CLASS -->

<jsp:useBean id=" " class=" " scope=" "> </jsp:useBean>

<jsp:setProperty property=" " name=" " />

<jsp:getProperty property=" " name=" " />

<!-- OTHER TAGS -->

<jsp:attribute name=" " trim="true"> </jsp:attribute>

<jsp:body>

</jsp:body>

<<jsp:element name=" "> </jsp:element>

<jsp:output> </jsp:output>

<jsp:params> </jsp:params>

<!-- TO COMMUNICATE WITH APPLETS -->

<jsp:fallback> </jsp:fallback>

<jsp:plugin code=" " codebase=" " type="bean"> </jsp:plugin>

JSTL (JSP Standard Tag Library)

<!-- CORE TAGS -->

<c:set   var=" "   value=" "/>

<c:out value=" "/>

<c:forEach var=" "   items=" ">

</c:forEach>

<c:forEach var=" " begin="1" end="10" step="2">   </c:forEach>

<c:if test=" ">   </c:if>

<c:choose>

<c:when test=" ">   </c:when>

<c:when test=" ">   </c:when>

<c:when test=" ">   </c:when>

<c:otherwise >

</c:otherwise>

</c:choose>

<c:import url=" ">   </c:import>

<c:forTokens items=" " delims=" ">   </c:forTokens>

<c:param name=" ">   </c:param>

<c:redirect>   </c:redirect>

<c:remove var=" "/>

<!-- SQL TAGS -->

<s:dateParam value=" " />

<s:param>   </s:param>

<s:query var=" ">   </s:query>

<s:setDataSource />

<s:transaction>   </s:transaction>

<s:update>   </s:update>

Expression language

Reserved Words

and eq gt true instanceof

or ne le false empty

not lt ge null div mod

Implicit Objects

pageScope

requestScope

sessionScope

applicationScope

param

paramValues

header

headerValues

cookie

initParam

pageContext

servletContext

session

request

response

Operators

Arithmetic: +, - (binary), *, / and div, % and mod, - (unary)

Logical: and, &&, or, ||, not, !

Relational: ==, eq, !=, ne, <, lt, >, gt, <=, ge, >=, le. Comparisons can be made against other values, or against boolean, string, integer, or floating point literals.

Empty: The empty operator is a prefix operation that can be used to determine whether a value is null or empty.

Conditional: A ? B : C. Evaluate B or C, depending on the result of the evaluation of A.

The precedence of operators highest to lowest, left to right is as follows:

[]

() - Used to change the precedence of operators.

- (unary) not ! empty

* / div % mod

+ - (binary)

< > <= >= lt gt le ge

== != eq ne

&& and

|| or

? :