No.	Status	Date
LNDE-RPT-01-037-DS-3-RV-101	Issued	2001-03-02

UT Thickness Data Sheet - 3-RV-101

Scope and Responsibilities

This data sheet provides the ultrasonic thickness measurements for the regenerator overhead line 3-RV-101 located within the ATU-100. The objective is to document wall loss and determine the remaining life of the asset based on the 5-year Class 1 survey requirements.

Grace Okafor, acting as the UT technician (SNT-TC-1A UT Level II) for Larkhall NDE Services Inc., performed the thickness measurements. The technician is responsible for the accurate acquisition of data and the identification of any readings falling below the minimum allowable thickness.

Technical Basis and Standards

All measurements were performed under the requirements of QSCP-NDT-001 Rev 0, the site NDE procedure issued for ATU-100 pre-startup and in-service NDE. The methodology for ultrasonic testing is conducted in accordance with ASTM E797.

The data presented herein supports the findings detailed in LNDE-RPT-01-037, the report covering the UT Thickness Survey for ATU-100 Class 1 and Rich Amine Piping.

Component Design Data

The subject line, 3-RV-101, is constructed from A106 Gr.B with a nominal outside diameter of 88.9 mm and a nominal wall thickness of 7.62 mm. The design pressure is 345 kPa(g) and the design temperature is 121 °C.

The minimum allowable thickness (t-min) for this line is 3.56 mm. Any measurement recorded below this threshold is subject to an NCR per site rules.

Thickness Evaluation

The evaluation of the 3-RV-101 wall thickness utilizes the larger of the long-term corrosion rate or the short-term rate calculated from readings at least 3 years apart. Remaining life is calculated as (t - t-min) / rate.

As a Class 1 line (sour gas, regenerator overhead), the maximum interval for thickness and external visual inspections is 5 years. The next measurement date is determined by half the remaining life or the class maximum.

Thickness readings, measured 2001-03-02

Line 6-SG-101 | Sour gas inlet | A106 Gr.B | t_nom 7.11 mm | t-min 3.56 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
6-SG-101-01	7.11	3.56	1996-03-08	7.12	6.82	0.060	0.060	>50	2006-03-02	
6-SG-101-02	7.11	3.56	1996-03-08	7.05	6.71	0.068	0.068	46.2	2006-03-02	
6-SG-101-03	7.11	3.56	1996-03-08	7.08	6.74	0.068	0.068	46.6	2006-03-02	
6-SG-101-04	7.11	3.56	1996-03-08	7.09	6.73	0.072	0.072	43.9	2006-03-02	
6-SG-101-05	7.11	3.56	1996-03-08	7.14	6.68	0.092	0.092	33.8	2006-03-02	
6-SG-101-06	7.11	3.56	1996-03-08	7.07	6.87	0.040	0.040	>50	2006-03-02	

Line 6-SG-102 | Sour gas inlet | A106 Gr.B | t_nom 7.11 mm | t-min 3.56 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
6-SG-102-01	7.11	3.56	1996-03-08	7.14	6.72	0.084	0.084	37.5	2006-03-02	
6-SG-102-02	7.11	3.56	1996-03-08	7.11	6.72	0.078	0.078	40.4	2006-03-02	
6-SG-102-03	7.11	3.56	1996-03-08	7.04	6.69	0.070	0.070	44.6	2006-03-02	
6-SG-102-04	7.11	3.56	1996-03-08	6.99	6.64	0.070	0.070	43.8	2006-03-02	
6-SG-102-05	7.11	3.56	1996-03-08	7.13	6.93	0.040	0.040	>50	2006-03-02	

Line 4-RA-101 | Rich amine | A106 Gr.B | t_nom 8.56 mm | t-min 3.81 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
4-RA-101-01	8.56	3.81	1996-03-08	8.52	8.39	0.026	0.026	>50	2011-03-02	
4-RA-101-02	8.56	3.81	1996-03-08	8.54	8.45	0.018	0.018	>50	2011-03-02	
4-RA-101-03	8.56	3.81	1996-03-08	8.61	8.42	0.038	0.038	>50	2011-03-02	
4-RA-101-04	8.56	3.81	1996-03-08	8.63	8.37	0.052	0.052	>50	2011-03-02	
4-RA-101-05	8.56	3.81	1996-03-08	8.60	8.42	0.036	0.036	>50	2011-03-02	
4-RA-101-07	8.56	3.81	1996-03-08	8.60	8.51	0.018	0.018	>50	2011-03-02	
4-RA-101-08	8.56	3.81	1996-03-08	8.68	8.30	0.076	0.076	>50	2011-03-02	
4-RA-101-09	8.56	3.81	1996-03-08	8.57	8.43	0.028	0.028	>50	2011-03-02	
4-RA-101-10	8.56	3.81	1996-03-08	8.67	8.48	0.038	0.038	>50	2011-03-02	
4-RA-101-11	8.56	3.81	1996-03-08	8.68	8.39	0.058	0.058	>50	2011-03-02	

Line 4-RA-102 | Rich amine | A106 Gr.B | t_nom 8.56 mm | t-min 3.81 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
4-RA-102-01	8.56	3.81	1996-03-08	8.54	8.48	0.012	0.012	>50	2011-03-02	
4-RA-102-02	8.56	3.81	1996-03-08	8.57	8.50	0.014	0.014	>50	2011-03-02	
4-RA-102-03	8.56	3.81	1996-03-08	8.56	8.37	0.038	0.038	>50	2011-03-02	
4-RA-102-04	8.56	3.81	1996-03-08	8.54	8.35	0.038	0.038	>50	2011-03-02	
4-RA-102-05	8.56	3.81	1996-03-08	8.55	8.36	0.038	0.038	>50	2011-03-02	
4-RA-102-06	8.56	3.81	1996-03-08	8.51	8.38	0.026	0.026	>50	2011-03-02	
4-RA-102-07	8.56	3.81	1996-03-08	8.58	8.49	0.018	0.018	>50	2011-03-02	
4-RA-102-08	8.56	3.81	1996-03-08	8.49	8.36	0.026	0.026	>50	2011-03-02	
4-RA-102-09	8.56	3.81	1996-03-08	8.55	8.35	0.040	0.040	>50	2011-03-02	

Line 6-RA-103 | Rich amine header | A106 Gr.B | t_nom 10.97 mm | t-min 4.57 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
6-RA-103-01	10.97	4.57	1996-03-08	11.00	10.82	0.036	0.036	>50	2011-03-02	
6-RA-103-02	10.97	4.57	1996-03-08	11.09	10.69	0.080	0.080	>50	2011-03-02	
6-RA-103-03	10.97	4.57	1996-03-08	10.99	10.84	0.030	0.030	>50	2011-03-02	
6-RA-103-04	10.97	4.57	1996-03-08	10.98	10.59	0.078	0.078	>50	2011-03-02	
6-RA-103-05	10.97	4.57	1996-03-08	10.95	10.61	0.068	0.068	>50	2011-03-02	
6-RA-103-06	10.97	4.57	1996-03-08	11.01	10.86	0.030	0.030	>50	2011-03-02	
6-RA-103-07	10.97	4.57	1996-03-08	10.99	10.79	0.040	0.040	>50	2011-03-02	
6-RA-103-08	10.97	4.57	1996-03-08	10.97	10.83	0.028	0.028	>50	2011-03-02	
6-RA-103-09	10.97	4.57	1996-03-08	11.01	10.85	0.032	0.032	>50	2011-03-02	
6-RA-103-10	10.97	4.57	1996-03-08	11.02	10.78	0.048	0.048	>50	2011-03-02	

Line 3-RV-101 | Regenerator overhead | A106 Gr.B | t_nom 7.62 mm | t-min 3.56 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
3-RV-101-01	7.62	3.56	1996-03-08	7.59	7.26	0.066	0.066	>50	2006-03-02	
3-RV-101-02	7.62	3.56	1996-03-08	7.57	7.31	0.052	0.052	>50	2006-03-02	
3-RV-101-03	7.62	3.56	1996-03-08	7.52	7.15	0.074	0.074	48.3	2006-03-02	
3-RV-101-04	7.62	3.56	1996-03-08	7.59	7.18	0.082	0.082	44.0	2006-03-02	
3-RV-101-05	7.62	3.56	1996-03-08	7.67	7.25	0.084	0.084	43.8	2006-03-02	
3-RV-101-06	7.62	3.56	1996-03-08	7.59	7.20	0.078	0.078	46.5	2006-03-02	

Line 2-RV-102 | Regenerator overhead | A106 Gr.B | t_nom 5.54 mm | t-min 2.79 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
2-RV-102-01	5.54	2.79	1996-03-08	5.53	5.29	0.048	0.048	>50	2006-03-02	
2-RV-102-02	5.54	2.79	1996-03-08	5.59	5.12	0.094	0.094	24.7	2006-03-02	
2-RV-102-03	5.54	2.79	1996-03-08	5.48	5.24	0.048	0.048	>50	2006-03-02	
2-RV-102-04	5.54	2.79	1996-03-08	5.58	5.33	0.050	0.050	>50	2006-03-02	

Line 4-RA-104 | L/R exchanger, rich side | A106 Gr.B | t_nom 8.56 mm | t-min 3.81 mm

CML	t_nom (mm)	t-min (mm)	Prev. date	Prev. (mm)	Current (mm)	CR LT (mm/y)	CR ST (mm/y)	RL (y)	Next due	Remark
4-RA-104-01	8.56	3.81	1996-03-08	8.51	8.40	0.022	0.022	>50	2011-03-02	
4-RA-104-02	8.56	3.81	1996-03-08	8.55	8.41	0.028	0.028	>50	2011-03-02	
4-RA-104-03	8.56	3.81	1996-03-08	8.54	8.46	0.016	0.016	>50	2011-03-02	
4-RA-104-04	8.56	3.81	1996-03-08	8.59	8.35	0.048	0.048	>50	2011-03-02	
4-RA-104-05	8.56	3.81	1996-03-08	8.60	8.29	0.062	0.062	>50	2011-03-02	
4-RA-104-06	8.56	3.81	1996-03-08	8.59	8.39	0.040	0.040	>50	2011-03-02	
4-RA-104-07	8.56	3.81	1996-03-08	8.59	8.29	0.060	0.060	>50	2011-03-02	

Sign-off	Name	Function	Date	Signature
Prepared	Grace Okafor	UT technician, SNT-TC-1A UT Level II	2001-03-02	_____