

Recap from
CS 228 : Logic in Computer Science

Krishna. S

edited by: Sayan Mukherjee

Finite State Machines

A deterministic finite state automaton (DFA) $A = (Q, \Sigma, \delta, q_0, F)$

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet
- ▶ $\delta : Q \times \Sigma \rightarrow Q$ is the transition function
- ▶ $q_0 \in Q$ is the initial state
- ▶ $F \subseteq Q$ is the set of final states
- ▶ $L(A)$ = all words leading from q_0 to some $q_f \in F$

Languages and Machines

A language $L \subseteq \Sigma^*$ is called **regular** iff there exists some DFA A such that $L = L(A)$.

Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- ▶ Even length words
- ▶ Contains abb
- ▶ Right before the last position is an a
- ▶ Contains a b and ends with aa
- ▶ Begins with a , ends with b , and has a pair of consecutive a 's
- ▶ There are two occurrences of b between which only a 's occur

Is it Regular?


$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Contains *abb*

Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:


- Contains *abb*



Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:


► Contains *abb*



Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:


- Contains *abb*



Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:


- Contains *abb*



Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:


- Contains *abb*



Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Contains *abb*



Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- ▶ Right before the last position is an a :

Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba




Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba




Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba




Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba




Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba




Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba




Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba




Is it Regular?

$\Sigma = \{a, b\}$. Consider the following languages $L \subseteq \Sigma^*$:

- Right before the last position is an a :

Examples : $ab, babbaa, bbab$

Non examples : ba, bb, aba



Deterministic Finite Automata

- ▶ Every state on every symbol goes to a **unique** state
 - ▶ $\delta : Q \times \Sigma \rightarrow Q$ is a transition **function**
- ▶ Given a string $w \in \Sigma^*$ and a state $q \in Q$, iteratively apply δ
 - ▶ $w = aab$
 - ▶ $\delta(q, a) = q_1,$

Deterministic Finite Automata

- ▶ Every state on every symbol goes to a **unique** state
 - ▶ $\delta : Q \times \Sigma \rightarrow Q$ is a transition **function**
- ▶ Given a string $w \in \Sigma^*$ and a state $q \in Q$, iteratively apply δ
 - ▶ $w = aab$
 - ▶ $\delta(q, a) = q_1, \delta(\delta(q, a), a) = \delta(q_1, a) = q_2,$

Deterministic Finite Automata

- ▶ Every state on every symbol goes to a **unique** state
 - ▶ $\delta : Q \times \Sigma \rightarrow Q$ is a transition **function**
- ▶ Given a string $w \in \Sigma^*$ and a state $q \in Q$, iteratively apply δ
 - ▶ $w = aab$
 - ▶ $\delta(q, a) = q_1, \delta(\delta(q, a), a) = \delta(q_1, a) = q_2,$
 $\delta(\delta(\delta(q, a), a), b) =$


Deterministic Finite Automata

- ▶ Every state on every symbol goes to a **unique** state
 - ▶ $\delta : Q \times \Sigma \rightarrow Q$ is a transition **function**
- ▶ Given a string $w \in \Sigma^*$ and a state $q \in Q$, iteratively apply δ
 - ▶ $w = aab$
 - ▶ $\delta(q, a) = q_1, \delta(\delta(q, a), a) = \delta(q_1, a) = q_2,$
 $\delta(\delta(\delta(q, a), a), b) = \delta(\delta(q_1, a), b) =$


Deterministic Finite Automata

- ▶ Every state on every symbol goes to a **unique** state
 - ▶ $\delta : Q \times \Sigma \rightarrow Q$ is a transition **function**
- ▶ Given a string $w \in \Sigma^*$ and a state $q \in Q$, iteratively apply δ
 - ▶ $w = aab$
 - ▶ $\delta(q, a) = q_1, \delta(\delta(q, a), a) = \delta(q_1, a) = q_2,$
 $\delta(\delta(\delta(q, a), a), b) = \delta(\delta(q_1, a), b) = \delta(q_2, b) = q_3$
 - ▶ $\hat{\delta} : Q \times \Sigma^* \rightarrow Q$ extension of δ to strings
 - ▶ $\hat{\delta}(q, \epsilon) = q$
 - ▶ $\hat{\delta}(q, wa) = \delta(\hat{\delta}(q, w), a)$

DFA : Transition Function on Words



DFA : Transition Function on Words



- ▶ $\hat{\delta}(q, wa) = s = \delta(\hat{\delta}(q, w), a) = \delta(r, a)$
- ▶ $\hat{\delta}(q, wb) = t = \delta(\hat{\delta}(q, w), b) = \delta(r, b)$


DFA Acceptance

- ▶ $w \in \Sigma^*$ is accepted iff $\hat{\delta}(q_0, w) \in F$
- ▶ $w \in \Sigma^*$ is rejected iff $\hat{\delta}(q_0, w) \notin F$
- ▶ Any string $w \in \Sigma^*$ is either accepted or rejected by a DFA A
- ▶ $L(A) = \{w \in \Sigma^* \mid \hat{\delta}(q_0, w) \in F\}$
- ▶ $\Sigma^* = L(A) \cup \overline{L(A)}$

Language Acceptance : Proof

Prove that the following automaton accepts the language

$L := \{w \in \{a, b\}^* \mid w \text{ has odd number of } a\text{'s \& even number of } b\text{'s}\}$




► Prove by induction on $|w|$

Language Acceptance : Proof

Prove that the following automaton accepts the language

$L := \{w \in \{a, b\}^* \mid w \text{ has odd number of } a\text{'s \& even number of } b\text{'s}\}$




- ▶ Prove by induction on $|w|$
- ▶ Base case : For $|w| = \epsilon$, $\hat{\delta}(q_{00}, \epsilon) = q_{00}$

Language Acceptance : Proof


Prove that the following automaton accepts the language

$L := \{w \in \{a, b\}^* \mid w \text{ has odd number of } a\text{'s \& even number of } b\text{'s}\}$




- ▶ Prove by induction on $|w|$
- ▶ Base case : For $|w| = \epsilon$, $\hat{\delta}(q_{00}, \epsilon) = q_{00}$
- ▶ Assume the claim for $x \in \Sigma^*$, and show it for xc , $c \in \{a, b\}$.

Language Acceptance : Proof




- ▶ By induction hypothesis, $\hat{\delta}(q_{00}, x) = q_{ij}$ iff
 - ▶ parity of i and $|x|_a$ are the same
 - ▶ parity of j and $|x|_b$ are the same

Language Acceptance : Proof



- ▶ By induction hypothesis, $\hat{\delta}(q_{00}, x) = q_{ij}$ iff
 - ▶ parity of i and $|x|_a$ are the same
 - ▶ parity of j and $|x|_b$ are the same
- ▶ $\hat{\delta}(q_{00}, xc) = \delta(\hat{\delta}(q_{00}, x), c)$

Language Acceptance : Proof



- ▶ Case Analysis : If $|x|_a$ odd and $|x|_b$ even, then $i = 1, j = 0$
 - ▶ $\delta(q_{10}, a) = q_{00}, \delta(q_{10}, b) = q_{11}$
 - ▶ $|xa|_a$ is even and $|xa|_b$ is even
 - ▶ $|xb|_a$ is odd and $|xb|_b$ is odd
- ▶ Other Cases : Similar
- ▶ $\hat{\delta}(q_{00}, x) = q_{10}$ iff $|x|_a$ odd and $|x|_b$ even

Closure Properties : DFA

Closure under Complementation

If L is regular, is $\overline{L}$ also regular?

Closure under Complementation


- ▶ If L is regular, so is $\bar{L}$
 - ▶ Let $A = (Q, q_0, \Sigma, \delta, F)$ be the DFA such that $L = L(A)$
 - ▶ For every $w \in L$, $\hat{\delta}(q_0, w) = f$ for some $f \in F$
 - ▶ For every $w \notin L$, $\hat{\delta}(q_0, w) = q$ for some $q \notin F$

Closure under Complementation

- ▶ If L is regular, so is $\bar{L}$
 - ▶ Let $A = (Q, q_0, \Sigma, \delta, F)$ be the DFA such that $L = L(A)$
 - ▶ For every $w \in L$, $\hat{\delta}(q_0, w) = f$ for some $f \in F$
 - ▶ For every $w \notin L$, $\hat{\delta}(q_0, w) = q$ for some $q \notin F$
 - ▶ Construct $\bar{A} = (Q, q_0, \Sigma, \delta, Q - F)$
 - ▶ $w \in L(\bar{A})$ iff $\hat{\delta}(q_0, w) \in Q - F$ iff $w \notin L(A)$
 - ▶ $L(\bar{A}) = \bar{L(A)}$


Closure under Intersection

► *aaab*




Closure under Intersection

► *aaab*




Closure under Intersection

► *aaab*




Closure under Intersection

► $aaab$




Closure under Intersection

► aaa^b




Closure under Intersection

► *aabba*




Closure under Intersection

► *aabba*




Closure under Intersection

► *aabba*




Closure under Intersection

► *aabba*




Closure under Intersection

► *aabba*



Closure under Intersection

► *aabb***a**



Closure under Intersection

- ▶ $A_1 = (Q_1, \Sigma, \delta_1, q_0, F_1)$
- ▶ $A_2 = (Q_2, \Sigma, \delta_2, s_0, F_2)$
- ▶ $A = (Q_1 \times Q_2, \Sigma, \delta, (q_0, s_0), F),$
 - ▶ $\delta((q, s), a) = (\delta_1(q, a), \delta_2(s, a))$
 - ▶ $F = F_1 \times F_2$

Closure under Intersection

- ▶ $A_1 = (Q_1, \Sigma, \delta_1, q_0, F_1)$
 - ▶ $A_2 = (Q_2, \Sigma, \delta_2, s_0, F_2)$
 - ▶ $A = (Q_1 \times Q_2, \Sigma, \delta, (q_0, s_0), F)$,
 - ▶ $\delta((q, s), a) = (\delta_1(q, a), \delta_2(s, a))$
 - ▶ $F = F_1 \times F_2$
 - ▶ Show that for all $x \in \Sigma^*$, $\hat{\delta}((p, q), x) = (\hat{\delta}_1(p, x), \hat{\delta}_2(q, x))$
- $x \in L(A)$ iff $\hat{\delta}((q_0, s_0), x) \in F$

Closure under Intersection

- ▶ $A_1 = (Q_1, \Sigma, \delta_1, q_0, F_1)$
 - ▶ $A_2 = (Q_2, \Sigma, \delta_2, s_0, F_2)$
 - ▶ $A = (Q_1 \times Q_2, \Sigma, \delta, (q_0, s_0), F)$,
 - ▶ $\delta((q, s), a) = (\delta_1(q, a), \delta_2(s, a))$
 - ▶ $F = F_1 \times F_2$
 - ▶ Show that for all $x \in \Sigma^*$, $\hat{\delta}((p, q), x) = (\hat{\delta}_1(p, x), \hat{\delta}_2(q, x))$
- $x \in L(A)$ iff $\hat{\delta}((q_0, s_0), x) \in F$ iff $(\hat{\delta}_1(q_0, x), \hat{\delta}_2(s_0, x)) \in F_1 \times F_2$

Closure under Intersection

- ▶ $A_1 = (Q_1, \Sigma, \delta_1, q_0, F_1)$
- ▶ $A_2 = (Q_2, \Sigma, \delta_2, s_0, F_2)$
- ▶ $A = (Q_1 \times Q_2, \Sigma, \delta, (q_0, s_0), F)$,
 - ▶ $\delta((q, s), a) = (\delta_1(q, a), \delta_2(s, a))$
 - ▶ $F = F_1 \times F_2$

- ▶ Show that for all $x \in \Sigma^*$, $\hat{\delta}((p, q), x) = (\hat{\delta}_1(p, x), \hat{\delta}_2(q, x))$

$x \in L(A)$ iff $\hat{\delta}((q_0, s_0), x) \in F$ iff $(\hat{\delta}_1(q_0, x), \hat{\delta}_2(s_0, x)) \in F_1 \times F_2$ iff
 $\hat{\delta}_1(q_0, x) \in F_1$ and $\hat{\delta}_2(s_0, x) \in F_2$

Closure under Intersection

- ▶ $A_1 = (Q_1, \Sigma, \delta_1, q_0, F_1)$
- ▶ $A_2 = (Q_2, \Sigma, \delta_2, s_0, F_2)$
- ▶ $A = (Q_1 \times Q_2, \Sigma, \delta, (q_0, s_0), F)$,
 - ▶ $\delta((q, s), a) = (\delta_1(q, a), \delta_2(s, a))$
 - ▶ $F = F_1 \times F_2$

- ▶ Show that for all $x \in \Sigma^*$, $\hat{\delta}((p, q), x) = (\hat{\delta}_1(p, x), \hat{\delta}_2(q, x))$

$x \in L(A)$ iff $\hat{\delta}((q_0, s_0), x) \in F$ iff $(\hat{\delta}_1(q_0, x), \hat{\delta}_2(s_0, x)) \in F_1 \times F_2$ iff
 $\hat{\delta}_1(q_0, x) \in F_1$ and $\hat{\delta}_2(s_0, x) \in F_2$ iff $x \in L(A_1)$ and $x \in L(A_2)$

Closure under Union

- ▶ $A_1 = (Q_1, \Sigma, \delta_1, q_0, F_1)$
- ▶ $A_2 = (Q_2, \Sigma, \delta_2, s_0, F_2)$
- ▶ $A = (Q_1 \times Q_2, \Sigma, \delta, (q_0, s_0), F),$
 - ▶ $\delta((q, s), a) = (\delta_1(q, a), \delta_2(s, a))$

Closure under Union

- ▶ $A_1 = (Q_1, \Sigma, \delta_1, q_0, F_1)$
 - ▶ $A_2 = (Q_2, \Sigma, \delta_2, s_0, F_2)$
 - ▶ $A = (Q_1 \times Q_2, \Sigma, \delta, (q_0, s_0), F)$,
 - ▶ $\delta((q, s), a) = (\delta_1(q, a), \delta_2(s, a))$
 - ▶ $F = (F_1 \times Q_2) \cup (Q_1 \times F_2)$
 - ▶ Show that for all $x \in \Sigma^*$, $\hat{\delta}((p, q), x) = (\hat{\delta}_1(p, x), \hat{\delta}_2(q, x))$
- $x \in L(A)$ iff $x \in L(A_1)$ or $x \in L(A_2)$