

Project Design Phase-II
Functional Requirement Template

Date	06 October 2022
Team ID	PNT2022TMID01161
Project Name	Project – Real -Time Communication System Powered By AI For Specially Abled
Maximum Marks	2 Marks

Functional Requirements:

- Here , **Desktop along with Camera** is presented as black box.
- Deaf/Dumb is the person, who will **show different signs based on the type of information being conveyed**. □ **Normal Person** is the passive user of the desktop.

The **System requirements** that are required are specified below,

- Deaf/Dumb person should be able to **perform a sign that represents digit/number**.
- Deaf/Dumb person should be able to **perform a sign that represents a character**.
- Deaf/Dumb person should be able to **perform a sign , where group of characters forms a word**.
- Deaf/Dumb person should be able to **perform a sign, where group of words forms a sentence**.
- Especially Deaf person should be able to **see the translation of sign to text format**.
- Dumb person should be able to **understand the conversion of text into voice mode**.
- **Normal user should be able to understand the corresponding information conveyed by disabled through sign language**.

Default Operation:

- User of the app **faces the camera and perform the concerned hand sign to convey information**.
- System/Desktop **analyses the sign made by the user**.

- Once analysis gets finished, then the **concerned signs together** are shown as a text based and also through voice.

Unexpected Operations:

- **Desktop indicates that user's hand sign is not within the frame or in Region of Interest(ROI).**
 1. User of the app **show the hand sign towards the camera.**
 2. Desktop shows that **sign is not within ROI.**
 3. Still User , make sure to present his/her sign within frame.
 4. At last, **Desktop finally detect the hand sign.**

□ Signs are not recognized

1. **Excepts the signs that are trained and included in the dataset, the Desktop will never detect the sign rather than this.**
2. User Performs the sign and see that after 50ms, **the concerned letter occupy in the space of text.**

□ Speech/Voice assistant is implemented

Speech assistant is to be implemented in order to **convert the output text into voice .**