

KEY SPECIFICATIONS

FEATURES

WHAT'S IN THE BOX?

DOCUMENTS

PRODUCT CODE: PTEKLED028

LIGHT DISTRIBUTION: 120° (Beam Angle)

LIGHT SOURCE: Higher Spec Osram

INPUT VOLTAGE: 208-400 V AC, 50-60 Hz^(*)

INPUT POWER: 1061 W (4.6 A @230 V AC), 1054 W (2.7 A @400 V AC)

EFFICACY: 3.4 µmol/J (230 V AC), 3.5 µmol/J (400 V AC)

PPF: 3600 µmol/s (230 V AC), 3675 µmol/s (400 V AC)

POWER FACTOR: > 0.98 (230 V AC), > 0.98 (400 V AC)

DIMMING: 20%-100%

EXTERNAL CONTROL: With Photontek or any Universal Controllers 0-10 V

DAISY CHAIN: Yes

WEIGHT: 29 lbs

DIMENSIONS: 28.7" x 12.8" x 4.4"

SPECTRUM: Red + Blue

THERMAL MANAGEMENT: Passive

LIFETIME: L90 > 50000 hrs

WARRANTY: 3 Years

IP RATING: IP65

CERTIFICATIONS: CSA, FCC and IC

() another voltage range available upon request.*