

- PRODUCT CODE: PTEKLED029
- LIGHT DISTRIBUTION: 120° (Beam Angle)
- LIGHT SOURCE: Higher Spec Osram and Seoul Semiconductor
- INPUT VOLTAGE: 208-400 V AC, 50-60 Hz^(*)
- INPUT POWER: 860 W (3.7 A @230 V AC), 850 W (2.2 A @400 V AC)
- EFFICACY: 2.6 µmol/J (230 V AC), 2.7 µmol/J (400 V AC)
- PPF: 2250 µmol/s (230 V AC), 2295 µmol/s (400 V AC)
- POWER FACTOR: > 0.98 (230 V AC), > 0.98 (400 V AC)
- DIMMING: 20%-100%
- EXTERNAL CONTROL: With Photontek or any Universal Controllers 0-10 V
- DAISY CHAIN: Yes
- WEIGHT: 29 lbs
- DIMENSIONS: 28.7" x 12.8" x 4.4"
- SPECTRUM: Full Spectrum
- THERMAL MANAGEMENT: Passive
- LIFETIME: L90 > 50000 hrs
- WARRANTY: 5 Years
- IP RATING: IP65
- CERTIFICATIONS: CSA, FCC and IC

^(*) another voltage range available upon request.