

# CS 611: Theory of Computation

Hongmin Li

Department of Computer Science  
California State University, East Bay

# Non-Context Free Languages

## Question

Are there languages that are not context-free?

# Non-Context Free Languages

## Question

Are there languages that are not context-free? What about  $L = \{a^n b^n c^n \mid n \geq 0\}$ ?

# Non-Context Free Languages

## Question

Are there languages that are not context-free? What about  $L = \{a^n b^n c^n \mid n \geq 0\}$ ?

## Answer

$L$  is not context-free, because

- Recognizing if  $w \in L$  requires remembering the number of  $as$  seen,  $bs$  seen and  $cs$  seen
- We can remember one of them on the stack (say  $as$ ), and compare them to another (say  $bs$ ) by popping, but not to both  $bs$  and  $cs$

# Non-Context Free Languages

## Question

Are there languages that are not context-free? What about  $L = \{a^n b^n c^n \mid n \geq 0\}$ ?

## Answer

$L$  is not context-free, because

- Recognizing if  $w \in L$  requires remembering the number of  $as$  seen,  $bs$  seen and  $cs$  seen
- We can remember one of them on the stack (say  $as$ ), and compare them to another (say  $bs$ ) by popping, but not to both  $bs$  and  $cs$

The precise way to capture this intuition is through the pumping lemma

# Pumping Lemma for CFLs

## Informal Statement

For all sufficiently long strings  $z$  in a context free language  $L$ , it is possible to find **two** substrings, not too far apart, that can be **simultaneously** pumped to obtain more words in  $L$ .

# Pumping Lemma for CFLs

## Formal Statement

### Lemma

*If  $L$  is a CFL, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w, x, y$  such that  $z = uvwxy$*

# Pumping Lemma for CFLs

## Formal Statement

### Lemma

*If  $L$  is a CFL, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w, x, y$  such that  $z = uvwxy$*

①  $|vwx| \leq p$



# Pumping Lemma for CFLs

## Formal Statement

### Lemma

*If  $L$  is a CFL, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w, x, y$  such that  $z = uvwxy$*

①  $|vwx| \leq p$

②  $|vx| > 0$

# Pumping Lemma for CFLs

## Formal Statement

### Lemma

*If  $L$  is a CFL, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w, x, y$  such that  $z = uvwxy$*

- ①  $|vwx| \leq p$
- ②  $|vx| > 0$
- ③  $\forall i \geq 0. uv^iwx^iy \in L$

# Two Pumping Lemmas side-by-side

## Context-Free Languages

If  $L$  is a CFL, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w, x, y$  such that  $z = uvwxy$

- 1  $|vwx| \leq p$
- 2  $|vx| > 0$
- 3  $\forall i \geq 0. uv^iwx^iy \in L$

# Two Pumping Lemmas side-by-side

## Context-Free Languages

If  $L$  is a CFL, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w, x, y$  such that  $z = uvwxy$

- ①  $|vwx| \leq p$
- ②  $|vx| > 0$
- ③  $\forall i \geq 0. uv^iwx^iy \in L$

## Regular Languages

If  $L$  is a regular language, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w$  such that  $z = uvw$

- ①  $|uv| \leq p$
- ②  $|v| > 0$
- ③  $\forall i \geq 0. uv^iw \in L$

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

**Defender**

**Challenger**

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

### Challenger

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

**Defender**

Pick pumping length  $p$

$\xrightarrow{p}$

**Challenger**



# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

$\xrightarrow{p}$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

$$\begin{array}{c} \xrightarrow{p} \\ \xleftarrow{z} \end{array}$$

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

Divide  $z$  into  $u, v, w, x, y$

s.t.  $|vwx| \leq p$ , and  $|vx| > 0$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

$\xrightarrow{p}$   
 $\xleftarrow{z}$

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

Divide  $z$  into  $u, v, w, x, y$

s.t.  $|vwx| \leq p$ , and  $|vx| > 0$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

 $\xrightarrow{p}$ 
 $\xleftarrow{z}$ 
 $\xrightarrow{u,v,w,x,y}$

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$


Divide  $z$  into  $u, v, w, x, y$

s.t.  $|vwx| \leq p$ , and  $|vx| > 0$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

Pick  $i$ , s.t.  $uv^iwx^iy \notin L$



# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

Divide  $z$  into  $u, v, w, x, y$

s.t.  $|vwx| \leq p$ , and  $|vx| > 0$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

Pick  $i$ , s.t.  $uv^iwx^iy \notin L$

 $\xrightarrow{p}$ 
 $\xleftarrow{z}$ 
 $\xrightarrow{u,v,w,x,y}$ 
 $\xleftarrow{i}$

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

Divide  $z$  into  $u, v, w, x, y$

s.t.  $|vwx| \leq p$ , and  $|vx| > 0$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

Pick  $i$ , s.t.  $uv^iwx^iy \notin L$

**Pumping Lemma:** If  $L$  is CFL, then there is always a winning strategy for the defender (i.e., challenger will get stuck).

# Pumping Lemma for CFLs

## Game View

Game between **Defender**, who claims  $L$  satisfies the pumping condition, and **Challenger**, who claims  $L$  does not.

### Defender

Pick pumping length  $p$

Divide  $z$  into  $u, v, w, x, y$

s.t.  $|vwx| \leq p$ , and  $|vx| > 0$

### Challenger

Pick  $z \in L$  s.t.  $|z| \geq p$

Pick  $i$ , s.t.  $uv^iwx^iy \notin L$

**Pumping Lemma:** If  $L$  is CFL, then there is always a winning strategy for the defender (i.e., challenger will get stuck).

**Pumping Lemma (in contrapositive):** If there is a winning strategy for the challenger, then  $L$  is not CFL.



# Consequences of Pumping Lemma

- If  $L$  is context-free then  $L$  satisfies the pumping lemma.

# Consequences of Pumping Lemma

- If  $L$  is context-free then  $L$  satisfies the pumping lemma.
- If  $L$  satisfies the pumping lemma that **does not** mean  $L$  is context-free

# Consequences of Pumping Lemma

- If  $L$  is context-free then  $L$  satisfies the pumping lemma.
- If  $L$  satisfies the pumping lemma that **does not** mean  $L$  is context-free
- If  $L$  does not satisfy the pumping lemma (i.e., challenger can win the game, *no matter* what the defender does) then  $L$  is not context-free.

# Example I

## Proposition

$L_{anbncn} = \{a^n b^n c^n \mid n \geq 0\}$  is not a CFL.

# Example I

## Proposition

$L_{anbncn} = \{a^n b^n c^n \mid n \geq 0\}$  is not a CFL.

## Proof.

Suppose  $L_{anbncn}$  is context-free. Let  $p$  be the pumping length.

# Example I

## Proposition

$L_{anbncn} = \{a^n b^n c^n \mid n \geq 0\}$  is not a CFL.

## Proof.

Suppose  $L_{anbncn}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p \in L_{anbncn}$ .

# Example I

## Proposition

$L_{anbncn} = \{a^n b^n c^n \mid n \geq 0\}$  is not a CFL.

## Proof.

Suppose  $L_{anbncn}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p \in L_{anbncn}$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .

# Example I

## Proposition

$L_{anbncn} = \{a^n b^n c^n \mid n \geq 0\}$  is not a CFL.

## Proof.

Suppose  $L_{anbncn}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p \in L_{anbncn}$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .
- Since  $|vwx| \leq p$ ,  $vwx$  cannot contain all three of the symbols  $a, b, c$ , because there are  $p$   $b$ s. So  $vwx$  either does not have any  $a$ s or does not have any  $b$ s or does not have any  $c$ s.





# Example 1

## Proposition

$L_{anbncn} = \{a^n b^n c^n \mid n \geq 0\}$  is not a CFL.

## Proof.

Suppose  $L_{anbncn}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p \in L_{anbncn}$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .
- Since  $|vwx| \leq p$ ,  $vwx$  cannot contain all three of the symbols  $a, b, c$ , because there are  $p$   $b$ s. So  $vwx$  either does not have any  $a$ s or does not have any  $b$ s or does not have any  $c$ s. Suppose, (wlog)  $vwx$  does not have any  $a$ s.



# Example I

## Proposition

$L_{anbncn} = \{a^n b^n c^n \mid n \geq 0\}$  is not a CFL.

## Proof.

Suppose  $L_{anbncn}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p \in L_{anbncn}$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .
- Since  $|vwx| \leq p$ ,  $vwx$  cannot contain all three of the symbols  $a, b, c$ , because there are  $p$   $b$ s. So  $vwx$  either does not have any  $a$ s or does not have any  $b$ s or does not have any  $c$ s. Suppose, (wlog)  $vwx$  does have any  $a$ s. Then  $uv^0 wx^0 y = uwy$  contains more  $a$ s than either  $b$ s or  $c$ s. Hence  $uwy \notin L$ .  $\square$

## Example II

### Proposition

$L_{a=c \wedge b=d} = \{a^i b^j c^i d^j \mid i, j \geq 0\}$  is not a CFL.

## Example II

### Proposition

$L_{a=c \wedge b=d} = \{a^i b^j c^i d^j \mid i, j \geq 0\}$  is not a CFL.

### Proof.

Suppose  $L_{a=c \wedge b=d}$  is context-free. Let  $p$  be the pumping length.

## Example II

### Proposition

$L_{a=c \wedge b=d} = \{a^i b^j c^i d^j \mid i, j \geq 0\}$  is not a CFL.

### Proof.

Suppose  $L_{a=c \wedge b=d}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p d^p \in L$ .

## Example II

### Proposition

$L_{a=c \wedge b=d} = \{a^i b^j c^i d^j \mid i, j \geq 0\}$  is not a CFL.

### Proof.

Suppose  $L_{a=c \wedge b=d}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p d^p \in L$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .

## Example II

### Proposition

$L_{a=c \wedge b=d} = \{a^i b^j c^i d^j \mid i, j \geq 0\}$  is not a CFL.

### Proof.

Suppose  $L_{a=c \wedge b=d}$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = a^p b^p c^p d^p \in L$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .
- Since  $|vwx| \leq p$ ,  $v, x$  cannot contain both  $as$  and  $cs$ , nor can it contain both  $bs$  and  $ds$ . Further  $|vx| > 0$ . Now  $uv^0 wx^0 y = uwy \notin L$ , because it either contains fewer  $as$  than  $cs$ , or fewer  $cs$  than  $as$ , or fewer  $bs$  than  $ds$ , or fewer  $ds$  than  $bs$ . □

## Example III

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.



## Example III

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

# Example III

## Wrong Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1 0^p 1 \in L$ .

# Example III

## Wrong Proof


### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1 0^p \in L$ .
- $z$  can be pumped if we make the following division.



# Example III

## Wrong Proof


### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1 0^p \in L$ .
- $z$  can be pumped if we make the following division.



- So is  $E$  CFL?

# Example III

## Wrong Proof


### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1 0^p \in L$ .
- $z$  can be pumped if we make the following division.



- So is  $E$  CFL? No!

# Example III

## Wrong Proof


### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1 0^p \in L$ .
- $z$  can be pumped if we make the following division.



- So is  $E$  CFL? No! Does  $E$  satisfy the pumping lemma?

# Example III

## Wrong Proof


### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1 0^p \in L$ .
- $z$  can be pumped if we make the following division.



- So is  $E$  CFL? No! Does  $E$  satisfy the pumping lemma? No!

# Example III

## Corrected Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.



# Example III

## Corrected Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

# Example III

## Corrected Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1^p 0^p 1^p \in L$ .

# Example III

## Corrected Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1^p 0^p 1^p \in L$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .

# Example III

## Corrected Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1^p 0^p 1^p \in L$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .
- $vwx$  must straddle the midpoint of  $z$ .

# Example III

## Corrected Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1^p 0^p 1^p \in L$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .
- $vwx$  must straddle the midpoint of  $z$ .
  - Suppose  $vwx$  is only in the first half. Then in  $uv^2 wx^2 y$  the second half starts with 1. Thus, it is not of the form  $ww$ .

# Example III

## Corrected Proof

### Proposition

$E = \{ww \mid w \in \{0,1\}^*\}$  is not a CFL.

### Proof.

Suppose  $E$  is context-free. Let  $p$  be the pumping length.

- Consider  $z = 0^p 1^p 0^p 1^p \in L$ .
- Since  $|z| > p$ , there are  $u, v, w, x, y$  such that  $z = uvwxy$ ,  $|vwx| \leq p$ ,  $|vx| > 0$  and  $uv^i wx^i y \in L$  for all  $i \geq 0$ .
- $vwx$  must straddle the midpoint of  $z$ .
  - Suppose  $vwx$  is only in the first half. Then in  $uv^2wx^2y$  the second half starts with 1. Thus, it is not of the form  $ww$ .
  - Case when  $vwx$  is only in the second half. Then in  $uv^2wx^2y$  the first half ends in a 0. Thus, it is not of the form  $ww$ .  $\dots \rightarrow$

# Example III

## Corrected Proof

Proof (contd).

# Example III

## Corrected Proof

Proof (contd).

- Suppose  $vwx$  straddles the middle.



# Example III

## Corrected Proof

### Proof (contd).

- Suppose  $vwx$  straddles the middle. Then  $uv^0wx^0y$  must be of the form  $0^p1^i0^j1^p$ , where either  $i$  or  $j$  is not  $p$ .

# Example III

## Corrected Proof

### Proof (contd).

- Suppose  $vx$  straddles the middle. Then  $uv^0wx^0y$  must be of the form  $0^p1^i0^j1^p$ , where either  $i$  or  $j$  is not  $p$ . Thus,  $uv^0wx^0y \notin E$ . □

# Proof of Pumping Lemma

Recall ...

## Lemma

*If  $L$  is a CFL, then  $\exists p$  (pumping length) such that  $\forall z \in L$ , if  $|z| \geq p$  then  $\exists u, v, w, x, y$  such that  $z = uvwxy$*


- ①  $|vwx| \leq p$
- ②  $|vx| > 0$
- ③  $\forall i \geq 0. uv^iwx^iy \in L$

# Proof Idea

Let  $G$  be a CFG in **Chomsky Normal Form** such that  $L(G) = L$ .  
Let  $z$  be a “very long” string in  $L$  (“very long” made precise later).

# Proof Idea


Let  $G$  be a CFG in **Chomsky Normal Form** such that  $L(G) = L$ .  
Let  $z$  be a “very long” string in  $L$  (“very long” made precise later).



- Since  $z \in L$  there is a parse tree for  $z$

# Proof Idea

Let  $G$  be a CFG in **Chomsky Normal Form** such that  $L(G) = L$ .  
Let  $z$  be a “very long” string in  $L$  (“very long” made precise later).




Parse Tree for  $z$

- Since  $z \in L$  there is a parse tree for  $z$
- Since  $z$  is very long, the parse tree (which is a binary tree) must be “very tall”

# Proof Idea


Let  $G$  be a CFG in **Chomsky Normal Form** such that  $L(G) = L$ .  
Let  $z$  be a “very long” string in  $L$  (“very long” made precise later).



- Since  $z \in L$  there is a parse tree for  $z$
- Since  $z$  is very long, the parse tree (which is a binary tree) must be “very tall”
- The longest path in the tree, by pigeon hole principle, must have some variable (say)  $A$  repeat.

# Proof Idea

Let  $G$  be a CFG in **Chomsky Normal Form** such that  $L(G) = L$ .  
Let  $z$  be a “very long” string in  $L$  (“very long” made precise later).




Parse Tree for  $z$

- Since  $z \in L$  there is a parse tree for  $z$
- Since  $z$  is very long, the parse tree (which is a binary tree) must be “very tall”
- The longest path in the tree, by pigeon hole principle, must have some variable (say)  $A$  repeat. Let  $u, v, w, x, y$  be as shown.




# Pumping down




Pumping zero times

# Pumping down and up




Pumping zero times




Pumping two times

# Pumping down and up



Pumping zero times



Pumping two times

- Thus,  $uv^iwx^iy$  has a parse tree, for any  $i$ .

# Proof of Pumping Lemma

Existence of tall parse trees

## Proof.

Let  $G$  be a grammar in **Chomsky Normal Form** with  $k$  variables such that  $L(G) = L$ . Take  $p = 2^k$ . Consider  $z \in L$  such that  $|z| \geq p = 2^k$ .

# Proof of Pumping Lemma

## Existence of tall parse trees

### Proof.

Let  $G$  be a grammar in **Chomsky Normal Form** with  $k$  variables such that  $L(G) = L$ . Take  $p = 2^k$ . Consider  $z \in L$  such that  $|z| \geq p = 2^k$ .

- Consider a parse tree for  $z$ . Height of this tree is at least  $k + 1$

# Proof of Pumping Lemma

Existence of tall parse trees

## Proof.

Let  $G$  be a grammar in **Chomsky Normal Form** with  $k$  variables such that  $L(G) = L$ . Take  $p = 2^k$ . Consider  $z \in L$  such that  $|z| \geq p = 2^k$ .

- Consider a parse tree for  $z$ . Height of this tree is at least  $k + 1$ 
  - Parse trees of  $G$  are binary trees

# Proof of Pumping Lemma

## Existence of tall parse trees

### Proof.

Let  $G$  be a grammar in **Chomsky Normal Form** with  $k$  variables such that  $L(G) = L$ . Take  $p = 2^k$ . Consider  $z \in L$  such that  $|z| \geq p = 2^k$ .

- Consider a parse tree for  $z$ . Height of this tree is at least  $k + 1$ 
  - Parse trees of  $G$  are binary trees
  - **Fact:** A binary tree of height  $h$  has at most  $2^{h-1}$  leaves

# Proof of Pumping Lemma

## Existence of tall parse trees

### Proof.

Let  $G$  be a grammar in **Chomsky Normal Form** with  $k$  variables such that  $L(G) = L$ . Take  $p = 2^k$ . Consider  $z \in L$  such that  $|z| \geq p = 2^k$ .

- Consider a parse tree for  $z$ . Height of this tree is at least  $k + 1$ 
  - Parse trees of  $G$  are binary trees
  - **Fact:** A binary tree of height  $h$  has at most  $2^{h-1}$  leaves
  - $|z| = \text{Number of leaves in parse tree of } z = 2^{h-1} \geq 2^k$ . Thus,  
 $h \geq k + 1$ .





# Proof of Pumping Lemma

## Repeated Variables

Proof (contd).

# Proof of Pumping Lemma

## Repeated Variables

### Proof (contd).

- A parse tree for  $z$  has a path of length  $k + 1$

# Proof of Pumping Lemma

## Repeated Variables

### Proof (contd).

- A parse tree for  $z$  has a path of length  $k + 1$
- A path of length  $k + 1$  has  $k + 2$  vertices, out of which the last one is leaf that is labelled by a terminal

# Proof of Pumping Lemma

## Repeated Variables

### Proof (contd).

- A parse tree for  $z$  has a path of length  $k + 1$
- A path of length  $k + 1$  has  $k + 2$  vertices, out of which the last one is leaf that is labelled by a terminal; thus, there are at least  $k + 1$  internal vertices on path.

# Proof of Pumping Lemma

## Repeated Variables

### Proof (contd).

- A parse tree for  $z$  has a path of length  $k + 1$
- A path of length  $k + 1$  has  $k + 2$  vertices, out of which the last one is leaf that is labelled by a terminal; thus, there are at least  $k + 1$  internal vertices on path.
- Thus, there must be two vertices  $n_1$  and  $n_2$  on this path such that  $n_1$  and  $n_2$  have the same label (say  $A$ ) and  $n_1$  is an ancestor of  $n_2$ .

# Proof of Pumping Lemma

## Repeated Variables

### Proof (contd).

- A parse tree for  $z$  has a path of length  $k + 1$
- A path of length  $k + 1$  has  $k + 2$  vertices, out of which the last one is leaf that is labelled by a terminal; thus, there are at least  $k + 1$  internal vertices on path.
- Thus, there must be two vertices  $n_1$  and  $n_2$  on this path such that  $n_1$  and  $n_2$  have the same label (say  $A$ ) and  $n_1$  is an ancestor of  $n_2$ .
- Let the yield of tree rooted at  $n_2$  be  $w$ , and yield of  $n_1$  be  $VWX$ .

# Proof of Pumping Lemma

## Repeated Variables

### Proof (contd).

- A parse tree for  $z$  has a path of length  $k + 1$
- A path of length  $k + 1$  has  $k + 2$  vertices, out of which the last one is leaf that is labelled by a terminal; thus, there are at least  $k + 1$  internal vertices on path.
- Thus, there must be two vertices  $n_1$  and  $n_2$  on this path such that  $n_1$  and  $n_2$  have the same label (say  $A$ ) and  $n_1$  is an ancestor of  $n_2$ .
- Let the yield of tree rooted at  $n_2$  be  $w$ , and yield of  $n_1$  be  $vw$ . Yield of the root =  $z$  is say  $uvwxy$ . ...→

# Proof of Pumping Lemma

Properties of  $u, v, w, x, y$

Proof (contd).



# Proof of Pumping Lemma

Properties of  $u, v, w, x, y$

Proof (contd).

- Height of  $n_1$  can be assumed to be at most  $k + 1$

# Proof of Pumping Lemma

Properties of  $u, v, w, x, y$

## Proof (contd).

- Height of  $n_1$  can be assumed to be at most  $k + 1$ ; thus, the yield of  $n_1 (vwx)$  is at most  $2^k = p$ .

# Proof of Pumping Lemma

Properties of  $u, v, w, x, y$

## Proof (contd).

- Height of  $n_1$  can be assumed to be at most  $k + 1$ ; thus, the yield of  $n_1 (vwx)$  is at most  $2^k = p$ .
- $n_1 \neq n_2$ .

# Proof of Pumping Lemma

Properties of  $u, v, w, x, y$

## Proof (contd).

- Height of  $n_1$  can be assumed to be at most  $k + 1$ ; thus, the yield of  $n_1$  ( $vwx$ ) is at most  $2^k = p$ .
- $n_1 \neq n_2$ . Since the grammar has no  $\epsilon$ -productions and no unit-productions,  $vwx \neq w$ . i.e.,  $|vx| > 0$ .

...

# Proof of Pumping Lemma

## Pumping the strings

### Proof (contd).

Based on the parse tree for  $z$ , and definitions of  $u, v, w, x, y$ , we have

# Proof of Pumping Lemma

## Pumping the strings

### Proof (contd).

Based on the parse tree for  $z$ , and definitions of  $u, v, w, x, y$ , we have

- There is a parse tree with yield  $uAy$  and root  $S$ , obtained by not expanding  $n_1$ . Thus,  $S \xRightarrow{*} uAy$ .

# Proof of Pumping Lemma

## Pumping the strings

### Proof (contd).

Based on the parse tree for  $z$ , and definitions of  $u, v, w, x, y$ , we have

- There is a parse tree with yield  $uAy$  and root  $S$ , obtained by not expanding  $n_1$ . Thus,  $S \xRightarrow{*} uAy$ .
- There is a parse tree with yield  $vAx$  and root  $A$ , obtained from  $n_1$  and not expanding  $n_2$ . Thus,  $A \xRightarrow{*} vAx$ .

# Proof of Pumping Lemma

## Pumping the strings

### Proof (contd).

Based on the parse tree for  $z$ , and definitions of  $u, v, w, x, y$ , we have

- There is a parse tree with yield  $uAy$  and root  $S$ , obtained by not expanding  $n_1$ . Thus,  $S \xRightarrow{*} uAy$ .
- There is a parse tree with yield  $vAx$  and root  $A$ , obtained from  $n_1$  and not expanding  $n_2$ . Thus,  $A \xRightarrow{*} vAx$ .
- There is a parse tree with yield  $w$  and root  $A$ ; this is the tree rooted at  $n_2$ . Thus,  $A \xRightarrow{*} w$ .



# Proof of Pumping Lemma

## Pumping the strings

### Proof (contd).

Based on the parse tree for  $z$ , and definitions of  $u, v, w, x, y$ , we have

- There is a parse tree with yield  $uAy$  and root  $S$ , obtained by not expanding  $n_1$ . Thus,  $S \xRightarrow{*} uAy$ .
- There is a parse tree with yield  $vAx$  and root  $A$ , obtained from  $n_1$  and not expanding  $n_2$ . Thus,  $A \xRightarrow{*} vAx$ .
- There is a parse tree with yield  $w$  and root  $A$ ; this is the tree rooted at  $n_2$ . Thus,  $A \xRightarrow{*} w$ .

Putting it together, we have

$$S \xRightarrow{*} uAy \xRightarrow{*} uvAxy \xRightarrow{*} uvvAxxxy \xRightarrow{*} \dots \xRightarrow{*} uv^i Ax^i y \xRightarrow{*} uv^i wx^i y \quad \square$$