

CS 611: Theory of Computation

Hongmin Li

Department of Computer Science
California State University, East Bay

Union of CFLs

Let L_1 be language recognized by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language recognized by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

Is $L_1 \cup L_2$ a context free language?

Union of CFLs

Let L_1 be language recognized by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language recognized by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

Is $L_1 \cup L_2$ a context free language? Yes.

Union of CFLs

Let L_1 be language recognized by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language recognized by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

Is $L_1 \cup L_2$ a context free language? Yes.

Just add the rule $S \rightarrow S_1 | S_2$

Union of CFLs

Let L_1 be language recognized by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language recognized by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

Is $L_1 \cup L_2$ a context free language? Yes.

Just add the rule $S \rightarrow S_1 | S_2$

But make sure that $V_1 \cap V_2 = \emptyset$ (by renaming some variables).

Union of CFLs

Let L_1 be language recognized by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language recognized by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

Is $L_1 \cup L_2$ a context free language? Yes.

Just add the rule $S \rightarrow S_1 | S_2$

But make sure that $V_1 \cap V_2 = \emptyset$ (by renaming some variables).

Closure of CFLs under Union

$G = (V, \Sigma, R, S)$ such that $L(G) = L(G_1) \cup L(G_2)$:

- $V = V_1 \cup V_2 \cup \{S\}$ (the three sets are disjoint)
- $\Sigma = \Sigma_1 \cup \Sigma_2$
- $R = R_1 \cup R_2 \cup \{S \rightarrow S_1 | S_2\}$

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Proof.

Let L_1 be language generated by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language generated by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Proof.

Let L_1 be language generated by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language generated by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

- Concatenation:

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Proof.

Let L_1 be language generated by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language generated by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

- **Concatenation:** $L_1 L_2$ generated by a grammar with an additional rule $S \rightarrow S_1 S_2$

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Proof.

Let L_1 be language generated by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language generated by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

- **Concatenation:** $L_1 L_2$ generated by a grammar with an additional rule $S \rightarrow S_1 S_2$
- **Kleene Closure:**

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Proof.

Let L_1 be language generated by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language generated by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

- **Concatenation:** $L_1 L_2$ generated by a grammar with an additional rule $S \rightarrow S_1 S_2$
- **Kleene Closure:** L_1^* generated by a grammar with an additional rule $S \rightarrow S_1 S | \epsilon$

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Proof.

Let L_1 be language generated by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language generated by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

- **Concatenation:** $L_1 L_2$ generated by a grammar with an additional rule $S \rightarrow S_1 S_2$
- **Kleene Closure:** L_1^* generated by a grammar with an additional rule $S \rightarrow S_1 S | \epsilon$

As before, ensure that $V_1 \cap V_2 = \emptyset$. S is a new start symbol.

Concatenation, Kleene Closure

Proposition

CFLs are closed under concatenation and Kleene closure

Proof.

Let L_1 be language generated by $G_1 = (V_1, \Sigma_1, R_1, S_1)$ and L_2 the language generated by $G_2 = (V_2, \Sigma_2, R_2, S_2)$

- **Concatenation:** $L_1 L_2$ generated by a grammar with an additional rule $S \rightarrow S_1 S_2$
- **Kleene Closure:** L_1^* generated by a grammar with an additional rule $S \rightarrow S_1 S | \epsilon$

As before, ensure that $V_1 \cap V_2 = \emptyset$. S is a new start symbol.
(Exercise: Complete the Proof!)



Intersection

Let L_1 and L_2 be context free languages.

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Proposition

*CFLs are **not** closed under intersection*

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Proposition

*CFLs are **not** closed under intersection*

Proof.

- $L_1 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Proposition

*CFLs are **not** closed under intersection*

Proof.

- $L_1 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aXb \mid \epsilon$;
 $Y \rightarrow cY \mid \epsilon$.

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Proposition

*CFLs are **not** closed under intersection*

Proof.

- $L_1 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aXb \mid \epsilon$;
 $Y \rightarrow cY \mid \epsilon$.
- $L_2 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL.

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Proposition

*CFLs are **not** closed under intersection*

Proof.

- $L_1 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aXb \mid \epsilon$;
 $Y \rightarrow cY \mid \epsilon$.
- $L_2 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL.
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aX \mid \epsilon$;
 $Y \rightarrow bYc \mid \epsilon$.

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Proposition

*CFLs are **not** closed under intersection*

Proof.

- $L_1 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aXb \mid \epsilon$;
 $Y \rightarrow cY \mid \epsilon$.
- $L_2 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL.
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aX \mid \epsilon$;
 $Y \rightarrow bYc \mid \epsilon$.
- But $L_1 \cap L_2 =$

Intersection

Let L_1 and L_2 be context free languages. $L_1 \cap L_2$ is **not necessarily** context free!

Proposition

CFLs are **not** closed under intersection

Proof.

- $L_1 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aXb \mid \epsilon$;
 $Y \rightarrow cY \mid \epsilon$.
- $L_2 = \{a^i b^j c^j \mid i, j \geq 0\}$ is a CFL.
 - Generated by a grammar with rules $S \rightarrow XY$; $X \rightarrow aX \mid \epsilon$;
 $Y \rightarrow bYc \mid \epsilon$.
- But $L_1 \cap L_2 = \{a^n b^n c^n \mid n \geq 0\}$ is not a CFL. □

Intersection with Regular Languages

Proposition

*If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.*

Intersection with Regular Languages

Proposition

*If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.*

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R .

Intersection with Regular Languages

Proposition

*If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.*

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R . A new PDA P' will simulate P and M simultaneously on the same input and accept if both accept. Then P' accepts $L \cap R$.

Intersection with Regular Languages

Proposition

*If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.*

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R . A new PDA P' will simulate P and M simultaneously on the same input and accept if both accept. Then P' accepts $L \cap R$.

- The stack of P' is the stack of P

Intersection with Regular Languages

Proposition

If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R . A new PDA P' will simulate P and M simultaneously on the same input and accept if both accept. Then P' accepts $L \cap R$.

- The stack of P' is the stack of P
- The state of P' at any time is the pair (state of P , state of M)

Intersection with Regular Languages

Proposition

If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R . A new PDA P' will simulate P and M simultaneously on the same input and accept if both accept. Then P' accepts $L \cap R$.

- The stack of P' is the stack of P
- The state of P' at any time is the pair (state of P , state of M): $Q_{P'} = Q_P \times Q_M$

Intersection with Regular Languages

Proposition

If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R . A new PDA P' will simulate P and M simultaneously on the same input and accept if both accept. Then P' accepts $L \cap R$.

- The stack of P' is the stack of P
- The state of P' at any time is the pair (state of P , state of M): $Q_{P'} = Q_P \times Q_M$
- These determine the transition function of P'

Intersection with Regular Languages

Proposition

If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R . A new PDA P' will simulate P and M simultaneously on the same input and accept if both accept. Then P' accepts $L \cap R$.

- The stack of P' is the stack of P
- The state of P' at any time is the pair (state of P , state of M): $Q_{P'} = Q_P \times Q_M$
- These determine the transition function of P'
- The final states of P' are those in which both the state of P and state of M are accepting:

Intersection with Regular Languages

Proposition

If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.

Proof.

Let P be the PDA that accepts L , and let M be the DFA that accepts R . A new PDA P' will simulate P and M simultaneously on the same input and accept if both accept. Then P' accepts $L \cap R$.

- The stack of P' is the stack of P
- The state of P' at any time is the pair (state of P , state of M): $Q_{P'} = Q_P \times Q_M$
- These determine the transition function of P'
- The final states of P' are those in which both the state of P and state of M are accepting: $F_{P'} = F_P \times F_M$



Intersection with Regular Languages

Proposition

*If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.*

Intersection with Regular Languages

Proposition

If L is a CFL and R is a **regular** language then $L \cap R$ is a CFL.

Proof.

More formally, let $M = (Q_1, \Sigma, \delta_1, q_1, F_1)$ be a DFA such that $L(M) = R$, and $P = (Q_2, \Sigma, \Gamma, \delta_2, q_2, F_2)$ be a PDA such that $L(P) = L$. Then consider $P' = (Q, \Sigma, \Gamma, \delta, q_0, F)$ such that

- $Q = Q_1 \times Q_2$
- $q_0 = (q_1, q_2)$
- $F = F_1 \times F_2$
- $\delta((p, q), x, a) = \{((p', q'), b) \mid p' = \delta_1(p, x) \text{ and } (q', b) \in \delta_2(q, x, a)\}.$



Why does this construction not work for intersection of two CFLs?



Complementation

Let L be a context free language. Is \bar{L} context free?

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation.

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

- \bar{L}_1 and \bar{L}_2 are CFL.

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL.

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.
- i.e., $L_1 \cap L_2$ is a CFL

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.
- i.e., $L_1 \cap L_2$ is a CFL

i.e., CFLs are closed under intersection. Contradiction! □

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.
- i.e., $L_1 \cap L_2$ is a CFL

i.e., CFLs are closed under intersection. Contradiction! □

Proof 2.

$L = \{x \mid x \text{ not of the form } ww\}$ is a CFL.

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then for any two CFLs L_1, L_2 , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.
- i.e., $L_1 \cap L_2$ is a CFL

i.e., CFLs are closed under intersection. Contradiction! □

Proof 2.

$L = \{x \mid x \text{ not of the form } ww\}$ is a CFL.

- L generated by a grammar with rules

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then **for any two CFLs L_1, L_2** , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.
- i.e., **$L_1 \cap L_2$ is a CFL**

i.e., CFLs are closed under intersection. Contradiction! □

Proof 2.

$L = \{x \mid x \text{ not of the form } ww\}$ is a CFL.

- L generated by a grammar with rules $X \rightarrow a|b$, $A \rightarrow a|XAX$, $B \rightarrow b|XBX$, $S \rightarrow$

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then **for any two CFLs L_1, L_2** , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.
- i.e., **$L_1 \cap L_2$ is a CFL**

i.e., CFLs are closed under intersection. Contradiction! □

Proof 2.

$L = \{x \mid x \text{ not of the form } ww\}$ is a CFL.

- L generated by a grammar with rules $X \rightarrow a|b$, $A \rightarrow a|XAX$, $B \rightarrow b|XBX$, $S \rightarrow A|B|AB|BA$

Complementation

Let L be a context free language. Is \bar{L} context free? No!

Proof 1.

Suppose CFLs were closed under complementation. Then **for any two CFLs L_1, L_2** , we have

- \bar{L}_1 and \bar{L}_2 are CFL. Then, since CFLs closed under union, $\bar{L}_1 \cup \bar{L}_2$ is CFL. Then, again by hypothesis, $\overline{\bar{L}_1 \cup \bar{L}_2}$ is CFL.
- i.e., **$L_1 \cap L_2$ is a CFL**

i.e., CFLs are closed under intersection. Contradiction! □

Proof 2.

$L = \{x \mid x \text{ not of the form } ww\}$ is a CFL.

- L generated by a grammar with rules $X \rightarrow a|b$, $A \rightarrow a|XAX$, $B \rightarrow b|XBX$, $S \rightarrow A|B|AB|BA$

But $\bar{L} = \{ww \mid w \in \{a, b\}^*\}$ is not a CFL! (Why?) □ ↺ ↻ ↶ ↷

Set Difference

Proposition

*If L_1 is a CFL and L_2 is a CFL then $L_1 \setminus L_2$ is **not necessarily** a CFL*

Set Difference

Proposition

*If L_1 is a CFL and L_2 is a CFL then $L_1 \setminus L_2$ is **not necessarily** a CFL*

Proof.

Because CFLs not closed under complementation, and complementation is a special case of set difference. (How?) ☐

Set Difference

Proposition

If L_1 is a CFL and L_2 is a CFL then $L_1 \setminus L_2$ is *not necessarily* a CFL

Proof.

Because CFLs not closed under complementation, and complementation is a special case of set difference. (How?) ☐

Proposition

If L is a CFL and R is a *regular* language then $L \setminus R$ is a CFL

Set Difference

Proposition

If L_1 is a CFL and L_2 is a CFL then $L_1 \setminus L_2$ is *not necessarily* a CFL

Proof.

Because CFLs not closed under complementation, and complementation is a special case of set difference. (How?) ☐

Proposition

If L is a CFL and R is a *regular* language then $L \setminus R$ is a CFL

Proof.

$$L \setminus R = L \cap \overline{R}$$
☐

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism.

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism. A grammar $G' = (V', \Gamma, R', S')$ for generating $h(L)$:

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism. A grammar $G' = (V', \Gamma, R', S')$ for generating $h(L)$:

- Include all variables from G (i.e., $V' \supseteq V$), and let $S' = S$

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism. A grammar $G' = (V', \Gamma, R', S')$ for generating $h(L)$:

- Include all variables from G (i.e., $V' \supseteq V$), and let $S' = S$
- Treat terminals in G as variables.

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism. A grammar $G' = (V', \Gamma, R', S')$ for generating $h(L)$:

- Include all variables from G (i.e., $V' \supseteq V$), and let $S' = S$
- Treat terminals in G as variables. i.e., for every $a \in \Sigma$
 - Add a new variable X_a to V'

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism. A grammar $G' = (V', \Gamma, R', S')$ for generating $h(L)$:

- Include all variables from G (i.e., $V' \supseteq V$), and let $S' = S$
- Treat terminals in G as variables. i.e., for every $a \in \Sigma$
 - Add a new variable X_a to V'
 - In each rule of G , if a appears in the RHS, replace it by X_a

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism. A grammar $G' = (V', \Gamma, R', S')$ for generating $h(L)$:

- Include all variables from G (i.e., $V' \supseteq V$), and let $S' = S$
- Treat terminals in G as variables. i.e., for every $a \in \Sigma$
 - Add a new variable X_a to V'
 - In each rule of G , if a appears in the RHS, replace it by X_a
- For each X_a , add the rule $X_a \rightarrow$

Homomorphism

Proposition

Context free languages are closed under homomorphisms.

Proof.

Let $G = (V, \Sigma, R, S)$ be the grammar generating L , and let $h : \Sigma^* \rightarrow \Gamma^*$ be a homomorphism. A grammar $G' = (V', \Gamma, R', S')$ for generating $h(L)$:

- Include all variables from G (i.e., $V' \supseteq V$), and let $S' = S$
- Treat terminals in G as variables. i.e., for every $a \in \Sigma$
 - Add a new variable X_a to V'
 - In each rule of G , if a appears in the RHS, replace it by X_a
- For each X_a , add the rule $X_a \rightarrow h(a)$

G' generates $h(L)$. (Exercise!)



Homomorphism

Example

Let G have the rules $S \rightarrow 0S0 \mid 1S1 \mid \epsilon$.

Consider the homomorphism $h : \{0, 1\}^* \rightarrow \{a, b\}^*$ given by

$h(0) = aba$ and $h(1) = bb$.

Rules of G' s.t. $L(G') = h(L(G))$:

Homomorphism

Example

Let G have the rules $S \rightarrow 0S0|1S1|\epsilon$.

Consider the homomorphism $h : \{0, 1\}^* \rightarrow \{a, b\}^*$ given by $h(0) = aba$ and $h(1) = bb$.

Rules of G' s.t. $L(G') = h(L(G))$:

$$S \rightarrow X_0SX_0|X_1SX_1|\epsilon$$

Homomorphism

Example

Let G have the rules $S \rightarrow 0S0|1S1|\epsilon$.

Consider the homomorphism $h : \{0, 1\}^* \rightarrow \{a, b\}^*$ given by $h(0) = aba$ and $h(1) = bb$.

Rules of G' s.t. $L(G') = h(L(G))$:

$$\begin{aligned} S &\rightarrow X_0 S X_0 | X_1 S X_1 | \epsilon \\ X_0 &\rightarrow aba \end{aligned}$$

Homomorphism

Example

Let G have the rules $S \rightarrow 0S0|1S1|\epsilon$.

Consider the homomorphism $h : \{0, 1\}^* \rightarrow \{a, b\}^*$ given by $h(0) = aba$ and $h(1) = bb$.

Rules of G' s.t. $L(G') = h(L(G))$:

$$\begin{aligned} S &\rightarrow X_0 S X_0 | X_1 S X_1 | \epsilon \\ X_0 &\rightarrow aba \\ X_1 &\rightarrow bb \end{aligned}$$

Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof Idea

For regular language L : the DFA for $h^{-1}(L)$ on reading a symbol a , simulated the DFA for L on $h(a)$.

Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof Idea

For regular language L : the DFA for $h^{-1}(L)$ on reading a symbol a , simulated the DFA for L on $h(a)$. Can we do the same with PDAs?

Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof Idea

For regular language L : the DFA for $h^{-1}(L)$ on reading a symbol a , simulated the DFA for L on $h(a)$. Can we do the same with PDAs?

- Key idea: store $h(a)$ in a “buffer” and process symbols from $h(a)$ one at a time (according to the transition function of the original PDA), and the next input symbol is processed only after the “buffer” has been emptied.

Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof Idea

For regular language L : the DFA for $h^{-1}(L)$ on reading a symbol a , simulated the DFA for L on $h(a)$. Can we do the same with PDAs?

- Key idea: store $h(a)$ in a “buffer” and process symbols from $h(a)$ one at a time (according to the transition function of the original PDA), and the next input symbol is processed only after the “buffer” has been emptied.
- Where to store this “buffer”?

Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof Idea

For regular language L : the DFA for $h^{-1}(L)$ on reading a symbol a , simulated the DFA for L on $h(a)$. Can we do the same with PDAs?

- Key idea: store $h(a)$ in a “buffer” and process symbols from $h(a)$ one at a time (according to the transition function of the original PDA), and the next input symbol is processed only after the “buffer” has been emptied.
- Where to store this “buffer”? In the state of the new PDA!

Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof Idea

For regular language L : the DFA for $h^{-1}(L)$ on reading a symbol a , simulated the DFA for L on $h(a)$. Can we do the same with PDAs?

- Key idea: store $h(a)$ in a “buffer” and process symbols from $h(a)$ one at a time (according to the transition function of the original PDA), and the next input symbol is processed only after the “buffer” has been emptied.
- Where to store this “buffer”? In the state of the new PDA!

Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof.

Let $P = (Q, \Delta, \Gamma, \delta, q_0, F)$ be a PDA such that $L(P) = L$. Let $h : \Sigma^* \rightarrow \Delta^*$ be a homomorphism such that $n = \max_{a \in \Sigma} |h(a)|$, i.e., every symbol of Σ is mapped to a string under h of length at most n . Consider the PDA $P' = (Q', \Sigma, \Gamma, \delta', q'_0, F')$ where

- $Q' = Q \times \Delta^{\leq n}$, where $\Delta^{\leq n}$ is the collection of all strings of length at most n over Δ .
- $q'_0 = (q_0, \epsilon)$
- $F' = F \times \{\epsilon\}$



Inverse Homomorphisms

Recall: For a homomorphism h , $h^{-1}(L) = \{w \mid h(w) \in L\}$

Proposition

If L is a CFL then $h^{-1}(L)$ is a CFL

Proof.

- δ' is given by $\delta'((q, v), x, a) =$

$$\begin{cases} \{((q, h(x)), \epsilon)\} & \text{if } v = a = \epsilon \\ \{((p, u), b) \mid (p, b) \in \delta(q, y, a)\} & \text{if } v = yu, x = \epsilon, \text{ and } y \in \Delta \end{cases}$$

and $\delta'(\cdot) = \emptyset$ in all other cases.

