

# CS 611: Theory of Computation

Hongmin Li

Department of Computer Science  
California State University, East Bay

# Restricted Infinite Memory: The Stack

# Restricted Infinite Memory: The Stack

- So far we considered automata with finite memory
- In the end, we will consider machines with infinite memory

# Restricted Infinite Memory: The Stack

- So far we considered automata with finite memory
- In the end, we will consider machines with infinite memory
- Today: automata with access to an infinite **stack** — infinite memory but restricted access

# Restricted Infinite Memory: The Stack

- So far we considered automata with finite memory
- In the end, we will consider machines with infinite memory
- Today: automata with access to an infinite **stack** — infinite memory but restricted access
- The stack can contain an unlimited number of characters.

# Restricted Infinite Memory: The Stack

- So far we considered automata with finite memory
- In the end, we will consider machines with infinite memory
- Today: automata with access to an infinite **stack** — infinite memory but restricted access
- The stack can contain an unlimited number of characters.  
But
  - can read/erase only the top of the stack: **pop**

# Restricted Infinite Memory: The Stack

- So far we considered automata with finite memory
- In the end, we will consider machines with infinite memory
- Today: automata with access to an infinite **stack** — infinite memory but restricted access
- The stack can contain an unlimited number of characters.  
But
  - can read/erase only the top of the stack: **pop**
  - can add to only the top of the stack: **push**

# Restricted Infinite Memory: The Stack

- So far we considered automata with finite memory
- In the end, we will consider machines with infinite memory
- Today: automata with access to an infinite **stack** — infinite memory but restricted access
- The stack can contain an unlimited number of characters.  
But
  - can read/erase only the top of the stack: **pop**
  - can add to only the top of the stack: **push**
- On longer inputs, automaton may have more items in the stack



# Keeping Count Using the Stack

- An automaton can use the stack to recognize  $\{0^n 1^n\}$

# Keeping Count Using the Stack

- An automaton can use the stack to recognize  $\{0^n 1^n\}$ 
  - On reading a 0, push it onto the stack

# Keeping Count Using the Stack

- An automaton can use the stack to recognize  $\{0^n 1^n\}$ 
  - On reading a 0, push it onto the stack
  - After the 0s, on reading each 1, pop a 0

# Keeping Count Using the Stack

- An automaton can use the stack to recognize  $\{0^n 1^n\}$ 
  - On reading a 0, push it onto the stack
  - After the 0s, on reading each 1, pop a 0
  - (If a 0 comes after a 1, reject)

# Keeping Count Using the Stack

- An automaton can use the stack to recognize  $\{0^n 1^n\}$ 
  - On reading a 0, push it onto the stack
  - After the 0s, on reading each 1, pop a 0
  - (If a 0 comes after a 1, reject)
  - If attempt to pop an empty stack, reject

# Keeping Count Using the Stack

- An automaton can use the stack to recognize  $\{0^n 1^n\}$ 
  - On reading a 0, push it onto the stack
  - After the 0s, on reading each 1, pop a 0
  - (If a 0 comes after a 1, reject)
  - If attempt to pop an empty stack, reject
  - If stack not empty at the end, reject

# Keeping Count Using the Stack

- An automaton can use the stack to recognize  $\{0^n 1^n\}$ 
  - On reading a 0, push it onto the stack
  - After the 0s, on reading each 1, pop a 0
  - (If a 0 comes after a 1, reject)
  - If attempt to pop an empty stack, reject
  - If stack not empty at the end, reject
  - Else accept

# Matching Parenthesis Using the Stack

- An automaton can use the stack to recognize balanced parenthesis



# Matching Parenthesis Using the Stack

- An automaton can use the stack to recognize balanced parenthesis
- e.g.  $((()))()$  is balanced, but  $(())()$  and  $((()$  are not

# Matching Parenthesis Using the Stack

- An automaton can use the stack to recognize balanced parenthesis
- e.g.  $((()))()$  is balanced, but  $(())()$  and  $((()$  are not
  - On seeing a ( push it on the stack

# Matching Parenthesis Using the Stack

- An automaton can use the stack to recognize balanced parenthesis
- e.g.  $((()))()$  is balanced, but  $(())()$  and  $((()$  are not
  - On seeing a ( push it on the stack
  - On seeing a ) pop a ( from the stack

# Matching Parenthesis Using the Stack

- An automaton can use the stack to recognize balanced parenthesis
- e.g.  $((()))()$  is balanced, but  $(())()$  and  $((()$  are not
  - On seeing a ( push it on the stack
  - On seeing a ) pop a ( from the stack
  - If attempt to pop an empty stack, reject


# Matching Parenthesis Using the Stack

- An automaton can use the stack to recognize balanced parenthesis
- e.g.  $((()))()$  is balanced, but  $(())()$  and  $((()$  are not
  - On seeing a ( push it on the stack
  - On seeing a ) pop a ( from the stack
  - If attempt to pop an empty stack, reject
  - If stack not empty at the end, reject

# Matching Parenthesis Using the Stack


- An automaton can use the stack to recognize balanced parenthesis
- e.g.  $((()))()$  is balanced, but  $(())()$  and  $((()$  are not
  - On seeing a ( push it on the stack
  - On seeing a ) pop a ( from the stack
  - If attempt to pop an empty stack, reject
  - If stack not empty at the end, reject
  - Else accept

# Pushdown Automata (PDA)



A Pushdown Automaton

# Pushdown Automata (PDA)




A Pushdown Automaton

- Like an **NFA with  $\epsilon$ -transitions**, but with a stack




# Pushdown Automata (PDA)



A Pushdown Automaton

- Like an **NFA with  $\epsilon$ -transitions**, but with a stack
  - Stack depth unlimited: not a finite-state machine

# Pushdown Automata (PDA)



A Pushdown Automaton

- Like an **NFA with  $\epsilon$ -transitions**, but with a stack
  - Stack depth unlimited: not a finite-state machine
  - Non-deterministic: accepts if any thread of execution accepts

# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control

# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control
- At every step:

# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control
- At every step:
  - Consume next input symbol (or none)

# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control
- At every step:
  - Consume next input symbol (or none) and pop the **top symbol on stack** (or none)

# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control
- At every step:
  - Consume next input symbol (or none) and pop the **top symbol on stack** (or none)
  - Based on current state, consumed input symbol and popped stack symbol, do (non-deterministically):

# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control
- At every step:
  - Consume next input symbol (or none) and pop the **top symbol on stack** (or none)
  - Based on current state, consumed input symbol and popped stack symbol, do (non-deterministically):
    - 1 push a symbol onto stack (or push none)




# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control
- At every step:
  - Consume next input symbol (or none) and pop the **top symbol on stack** (or none)
  - Based on current state, consumed input symbol and popped stack symbol, do (non-deterministically):
    - 1 push a symbol onto stack (or push none)
    - 2 change to a new state

# Pushdown Automata (PDA)


- Has a non-deterministic finite-state control
- At every step:
  - Consume next input symbol (or none) and pop the **top symbol on stack** (or none)
  - Based on current state, consumed input symbol and popped stack symbol, do (non-deterministically):
    - 1 push a symbol onto stack (or push none)
    - 2 change to a new state



If at  $q_1$ , with next input symbol  $a$  and top of stack  $x$ , then **can** consume  $a$ , pop  $x$ , push  $y$  onto stack and move to  $q_2$

# Pushdown Automata (PDA)

- Has a non-deterministic finite-state control
- At every step:
  - Consume next input symbol (or none) and pop the **top symbol on stack** (or none)
  - Based on current state, consumed input symbol and popped stack symbol, do (non-deterministically):
    - 1 push a symbol onto stack (or push none)
    - 2 change to a new state




If at  $q_1$ , with next input symbol  $a$  and top of stack  $x$ , then **can** consume  $a$ , pop  $x$ , push  $y$  onto stack and move to  $q_2$  (any of  $a, x, y$  may be  $\epsilon$ )

# Pushdown Automata (PDA): Formal Definition


A PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  where

- $Q$  = Finite set of states
- $\Sigma$  = Finite input alphabet
- $\Gamma$  = Finite stack alphabet
- $q_0$  = Start state
- $F \subseteq Q$  = Accepting/final states
- $\delta : Q \times (\Sigma \cup \{\epsilon\}) \times (\Gamma \cup \{\epsilon\}) \rightarrow \mathcal{P}(Q \times (\Gamma \cup \{\epsilon\}))$

# Matching Parenthesis: PDA construction




# Matching Parenthesis: PDA construction




- First push a “bottom-of-the-stack” symbol  $\$$  and move to  $q$

# Matching Parenthesis: PDA construction



- First push a “bottom-of-the-stack” symbol \$ and move to  $q$
- On seeing a ( push it onto the stack


# Matching Parenthesis: PDA construction



- First push a “bottom-of-the-stack” symbol  $\$$  and move to  $q$
- On seeing a  $($  push it onto the stack
- On seeing a  $)$  pop if a  $($  is in the stack




# Matching Parenthesis: PDA construction




- First push a “bottom-of-the-stack” symbol  $\$$  and move to  $q$
- On seeing a  $($  push it onto the stack
- On seeing a  $)$  pop if a  $($  is in the stack
- Pop  $\$$  and move to final state  $q_F$


# Matching Parenthesis: PDA execution




# Matching Parenthesis: PDA execution




# Matching Parenthesis: PDA execution




# Matching Parenthesis: PDA execution




## Matching Parenthesis: PDA execution



## Matching Parenthesis: PDA execution




# Matching Parenthesis: PDA execution






# Palindrome: PDA construction




# Palindrome: PDA construction




- First push a “bottom-of-the-stack” symbol \$ and move to a pushing state

# Palindrome: PDA construction




- First push a “bottom-of-the-stack” symbol \$ and move to a pushing state
- Push input symbols onto the stack

# Palindrome: PDA construction




- First push a “bottom-of-the-stack” symbol  $\$$  and move to a pushing state
- Push input symbols onto the stack
- Non-deterministically move to a popping state (with or without consuming a single input symbol)

# Palindrome: PDA construction




- First push a “bottom-of-the-stack” symbol \$ and move to a pushing state
- Push input symbols onto the stack
- Non-deterministically move to a popping state (with or without consuming a single input symbol)
- If next input symbol is same as top of stack, pop

# Palindrome: PDA construction




- First push a “bottom-of-the-stack” symbol \$ and move to a pushing state
- Push input symbols onto the stack
- Non-deterministically move to a popping state (with or without consuming a single input symbol)
- If next input symbol is same as top of stack, pop
- If \$ on top of stack move to accept state

# Palindrome: PDA execution




# Palindrome: PDA execution







# Palindrome: PDA execution




# Palindrome: PDA execution




# Palindrome: PDA execution



# Palindrome: PDA execution



# Palindrome: PDA execution



# Instantaneous Description

In order to describe a machine's execution, we need to capture a “snapshot” of the machine that completely determines future behavior

# Instantaneous Description

In order to describe a machine's execution, we need to capture a “snapshot” of the machine that completely determines future behavior

- In the case of an NFA (or DFA), it is the state

# Instantaneous Description

In order to describe a machine's execution, we need to capture a “snapshot” of the machine that completely determines future behavior

- In the case of an NFA (or DFA), it is the state
- In the case of a TM, it is the state, head position, and tape contents



# Instantaneous Description

In order to describe a machine's execution, we need to capture a “snapshot” of the machine that completely determines future behavior

- In the case of an NFA (or DFA), it is the state
- In the case of a TM, it is the state, head position, and tape contents
- In the case of a PDA, it is the state + stack contents

# Instantaneous Description

In order to describe a machine's execution, we need to capture a “snapshot” of the machine that completely determines future behavior

- In the case of an NFA (or DFA), it is the state
- In the case of a TM, it is the state, head position, and tape contents
- In the case of a PDA, it is the state + stack contents

## Definition

An **instantaneous description** of a PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  is a pair  $\langle q, \sigma \rangle$ , where  $q \in Q$  and  $\sigma \in \Gamma^*$

# Computation

## Definition

For a PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$ , string  $w \in \Sigma^*$ , and instantaneous descriptions  $\langle q_1, \sigma_1 \rangle$  and  $\langle q_2, \sigma_2 \rangle$ , we say  $\langle q_1, \sigma_1 \rangle \xrightarrow{w}_P \langle q_2, \sigma_2 \rangle$  iff there is a sequence of instantaneous descriptions  $\langle r_0, s_0 \rangle, \langle r_1, s_1 \rangle, \dots, \langle r_k, s_k \rangle$  and a sequence  $x_1, x_2, \dots, x_k$ , where for each  $i$ ,  $x_i \in \Sigma \cup \{\epsilon\}$ , such that

- $w = x_1 x_2 \cdots x_k$ ,

# Computation

## Definition

For a PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$ , string  $w \in \Sigma^*$ , and instantaneous descriptions  $\langle q_1, \sigma_1 \rangle$  and  $\langle q_2, \sigma_2 \rangle$ , we say  $\langle q_1, \sigma_1 \rangle \xrightarrow{w}_P \langle q_2, \sigma_2 \rangle$  iff there is a sequence of instantaneous descriptions  $\langle r_0, s_0 \rangle, \langle r_1, s_1 \rangle, \dots, \langle r_k, s_k \rangle$  and a sequence  $x_1, x_2, \dots, x_k$ , where for each  $i$ ,  $x_i \in \Sigma \cup \{\epsilon\}$ , such that

- $w = x_1 x_2 \cdots x_k$ ,
- $r_0 = q_1$ , and  $s_0 = \sigma_1$ ,

# Computation

## Definition

For a PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$ , string  $w \in \Sigma^*$ , and instantaneous descriptions  $\langle q_1, \sigma_1 \rangle$  and  $\langle q_2, \sigma_2 \rangle$ , we say  $\langle q_1, \sigma_1 \rangle \xrightarrow{w}_P \langle q_2, \sigma_2 \rangle$  iff there is a sequence of instantaneous descriptions  $\langle r_0, s_0 \rangle, \langle r_1, s_1 \rangle, \dots, \langle r_k, s_k \rangle$  and a sequence  $x_1, x_2, \dots, x_k$ , where for each  $i$ ,  $x_i \in \Sigma \cup \{\epsilon\}$ , such that

- $w = x_1 x_2 \cdots x_k$ ,
- $r_0 = q_1$ , and  $s_0 = \sigma_1$ ,
- $r_k = q_2$ , and  $s_k = \sigma_2$ ,

# Computation


## Definition

For a PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$ , string  $w \in \Sigma^*$ , and instantaneous descriptions  $\langle q_1, \sigma_1 \rangle$  and  $\langle q_2, \sigma_2 \rangle$ , we say  $\langle q_1, \sigma_1 \rangle \xrightarrow{w}_P \langle q_2, \sigma_2 \rangle$  iff there is a sequence of instantaneous descriptions  $\langle r_0, s_0 \rangle, \langle r_1, s_1 \rangle, \dots, \langle r_k, s_k \rangle$  and a sequence  $x_1, x_2, \dots, x_k$ , where for each  $i$ ,  $x_i \in \Sigma \cup \{\epsilon\}$ , such that

- $w = x_1 x_2 \cdots x_k$ ,
- $r_0 = q_1$ , and  $s_0 = \sigma_1$ ,
- $r_k = q_2$ , and  $s_k = \sigma_2$ ,
- for every  $i$ ,  $(r_{i+1}, b) \in \delta(r_i, x_{i+1}, a)$  such that  $s_i = as$  and  $s_{i+1} = bs$ , where  $a, b \in \Gamma \cup \{\epsilon\}$  and  $s \in \Gamma^*$

# Example of Computation


## Example



$\langle q_0, \epsilon \rangle \xrightarrow{(()(} \langle q, ((\$) \text{ because}$

# Example of Computation

## Example



$\langle q_0, \epsilon \rangle \xrightarrow{(()} \langle q, ((\$) \text{ because}$

$\langle q_0, \epsilon \rangle \xrightarrow{x_1=\epsilon} \langle q, \$ \rangle \xrightarrow{x_2=(} \langle q, (\$ \rangle \xrightarrow{x_3=(} \langle q, ((\$ \rangle \xrightarrow{x_4=)} \langle q, (\$ \rangle \xrightarrow{x_5=(} \langle q, ((\$ \rangle$



# Acceptance/Recognition

## Definition

A PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  **accepts** a string  $w \in \Sigma^*$  iff

# Acceptance/Recognition

## Definition

A PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  **accepts** a string  $w \in \Sigma^*$  iff for some  $q \in F$  and  $\sigma \in \Gamma^*$ ,  $\langle q_0, \epsilon \rangle \xrightarrow{w}_P \langle q, \sigma \rangle$

# Acceptance/Recognition

## Definition

A PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  **accepts** a string  $w \in \Sigma^*$  iff for some  $q \in F$  and  $\sigma \in \Gamma^*$ ,  $\langle q_0, \epsilon \rangle \xrightarrow{w}_P \langle q, \sigma \rangle$

## Definition

The **language recognized/accepted** by a PDA

$P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  is  $L(P) = \{w \in \Sigma^* \mid P \text{ accepts } w\}$ .

# Acceptance/Recognition

## Definition

A PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  **accepts** a string  $w \in \Sigma^*$  iff for some  $q \in F$  and  $\sigma \in \Gamma^*$ ,  $\langle q_0, \epsilon \rangle \xrightarrow{w}_P \langle q, \sigma \rangle$

## Definition

The **language recognized/accepted** by a PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$  is  $L(P) = \{w \in \Sigma^* \mid P \text{ accepts } w\}$ . A language  $L$  is said to be **accepted/recognized** by  $P$  if  $L = L(P)$ .

# Expressive Power of CFGs and PDAs

CFGs and PDAs have equivalent expressive powers. More formally,  
...

# Expressive Power of CFGs and PDAs

CFGs and PDAs have equivalent expressive powers. More formally,  
...

## Theorem

*For every CFG  $G$ , there is a PDA  $P$  such that  $L(G) = L(P)$ . In addition, for every PDA  $P$ , there is a CFG  $G$  such that  $L(P) = L(G)$ .*

# Expressive Power of CFGs and PDAs

CFGs and PDAs have equivalent expressive powers. More formally,  
...

## Theorem

*For every CFG  $G$ , there is a PDA  $P$  such that  $L(G) = L(P)$ . In addition, for every PDA  $P$ , there is a CFG  $G$  such that  $L(P) = L(G)$ . Thus,  $L$  is context-free iff there is a PDA  $P$  such that  $L = L(P)$ .*

# Expressive Power of CFGs and PDAs

CFGs and PDAs have equivalent expressive powers. More formally,  
...

## Theorem

*For every CFG  $G$ , there is a PDA  $P$  such that  $L(G) = L(P)$ . In addition, for every PDA  $P$ , there is a CFG  $G$  such that  $L(P) = L(G)$ . Thus,  $L$  is context-free iff there is a PDA  $P$  such that  $L = L(P)$ .*

## Proof.

Skipped. □