



Router

```
Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#int e0/0
Router(config-if)#
Router(config-if)#
Router(config-if)#ip add 50.0.0.1 255.0.0.0
Router(config-if)#no shu
*Aug 23 15:42:47.588: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
Router(config-if)#no shut
Router(config-if)#
Router(config-if)#exit
Router(config)#
Router(config)#int e0/1
Router(config-if)#
Router(config-if)#ip add 60.0.0.1 255.0.0.0
Router(config-if)#no shut
Router(config-if)#exit
Router(config)#
Router(config)#exit
Router#
*Aug 23 15:44:25.663: %SYS-5-CONFIG_I: Configured from console by console
Router#
Router#sh ip int brief
Interface      IP-Address      OK? Method Status      Prot
Ethernet0/0    50.0.0.1        YES manual up          up
Ethernet0/1    60.0.0.1        YES manual up          up
Ethernet0/2    unassigned      YES TFTP  down        down
Ethernet0/3    unassigned      YES TFTP  down        down
Router#
```

31°C
Mostly cloudy

ENG IN 21:16
23-08-2026

```

C:\WINDOWS\system32\cmd.exe
Ping statistics for 60.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>route print
Interface List
0x1 ..... MS TCP Loopback interface
0x2 ... 50 fe 9c 89 4f 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:
    Network Destination        Netmask          Gateway             Interface          Metric
    50.0.0.0                    255.0.0.0        50.0.0.10           50.0.0.10          10
    50.0.0.10                   255.255.255.255  127.0.0.1           127.0.0.1          10
    50.255.255.255              255.255.255.255  50.0.0.10           50.0.0.10          10
    127.0.0.0                   255.0.0.0        127.0.0.1           127.0.0.1          1
    224.0.0.0                   240.0.0.0        50.0.0.10           50.0.0.10          10
    255.255.255.255            255.255.255.255  50.0.0.10           50.0.0.10          1

Persistent Routes:
    None

C:\Documents and Settings\user>route add 60.0.0.0 mask 255.0.0.0 50.0.0.1
C:\Documents and Settings\user>route print
Interface List
0x1 ..... MS TCP Loopback interface
0x2 ... 50 fe 9c 89 4f 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:
    Network Destination        Netmask          Gateway             Interface          Metric
    50.0.0.0                    255.0.0.0        50.0.0.10           50.0.0.10          10
    50.0.0.10                   255.255.255.255  127.0.0.1           127.0.0.1          10
    50.255.255.255              255.255.255.255  50.0.0.10           50.0.0.10          10
    60.0.0.0                    255.0.0.0        50.0.0.1            50.0.0.10          1
    127.0.0.0                   255.0.0.0        127.0.0.1           127.0.0.1          1
    224.0.0.0                   240.0.0.0        50.0.0.10           50.0.0.10          10
    255.255.255.255            255.255.255.255  50.0.0.10           50.0.0.10          1

Persistent Routes:
    None

C:\Documents and Settings\user>ping 60.0.0.10
Pinging 60.0.0.10 with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 60.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>

```

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

Notifications

QEMU (Win1)

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.
C:\Documents and Settings\User>ipconfig
Windows IP Configuration

Ethernet adapter Local Area Connection:

 Connection-specific DNS Suffix . :
 IP Address. : 50.0.0.10
 Subnet Mask : 255.0.0.0
 Default Gateway :

C:\Documents and Settings\User>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.

Ping statistics for 60.0.0.10:
 Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\User>route print

Interface List
0x1 MS TCP Loopback interface
0x2 ...50 fe 9c 09 4f 00 Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:
 Network Destination Netmask Gateway Interface Metric
 50.0.0.0 255.0.0.0 50.0.0.10 50.0.0.10 10
 50.0.0.10 255.255.255.255 127.0.0.1 127.0.0.1 10
 50.255.255.255 255.255.255.255 50.0.0.10 50.0.0.10 10
 127.0.0.0 255.0.0.0 127.0.0.1 127.0.0.1 1
 224.0.0.0 240.0.0.0 50.0.0.10 50.0.0.10 10
 255.255.255.255 255.255.255.255 50.0.0.10 50.0.0.10 1

Persistent Routes:
 None

C:\Documents and Settings\User>route add 60.0.0.0 mask 255.0.0.0 50.0.0.1
C:\Documents and Settings\User>route print

Interface List
0x1 MS TCP Loopback interface
0x2 ...50 fe 9c 09 4f 00 Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:
 Network Destination Netmask Gateway Interface Metric
 50.0.0.0 255.0.0.0 50.0.0.10 50.0.0.10 10

Win2
60.0.0.10

Start

C:\WINDOWS\system32\cmd.exe

4:56 PM

Rain warning
In effect

Search

Physical

01 : 00 : 00

START

ENG IN

21:26
23-08-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

Notifications

QEMU (Win1)

C:\WINDOWS\system32\cmd.exe

Scheduler Miniport

Active Routes:

Network	Destination	Netmask	Gateway	Interface	Metric
50.0.0.0	255.0.0.0	255.0.0.0	50.0.0.1	50.0.0.10	10
50.0.0.10	255.255.255.255	255.255.255.255	127.0.0.1	127.0.0.1	10
50.255.255.255	255.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	10
127.0.0.0	255.0.0.0	255.0.0.0	127.0.0.1	127.0.0.1	1
224.0.0.0	240.0.0.0	240.0.0.0	50.0.0.10	50.0.0.10	10
255.255.255.255	255.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	1

Persistent Routes:

None

C:\Documents and Settings\user>route print

Interface List

0x1 MS ICP Loopback interface

0x2 Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:

Network	Destination	Netmask	Gateway	Interface	Metric
0.0.0.0	0.0.0.0	0.0.0.0	50.0.0.1	50.0.0.10	10
50.0.0.10	255.255.255.255	255.255.255.255	127.0.0.1	127.0.0.1	10
50.255.255.255	255.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	10
127.0.0.0	255.0.0.0	255.0.0.0	127.0.0.1	127.0.0.1	1
224.0.0.0	240.0.0.0	240.0.0.0	50.0.0.10	50.0.0.10	10
255.255.255.255	255.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	1

Default Gateway:

50.0.0.1

Persistent Routes:

None

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Reply from 60.0.0.10: bytes=32 time=2ms TTL=127

Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>ping 60.0.0.10_

Win2

0.0.10

Start

C:\WINDOWS\system...

5:09 PM

Start

C:\WINDOWS\system...

5:09 PM

Physical

01 : 00 : 00

START

30°C

Light rain

21:39

23-08-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

Notifications

QEMU (Win1)

C:\WINDOWS\system32\cmd.exe

```
C:\Documents and Settings\user>route print
=====
Interface List
0x1 ..... MS TCP Loopback interface
0x2 ...50 fa 9c 09 4f 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport
=====
Active Routes:
Network Destination        Netmask          Gateway           Interface         Metric
-----
50.0.0.0                    255.0.0.0        50.0.0.10        50.0.0.10        10
50.0.0.10                   255.255.255.255  127.0.0.1        127.0.0.1        1
50.255.255.255              255.255.255.255  50.0.0.10        50.0.0.10        10
60.0.0.0                    255.0.0.0        50.0.0.10        50.0.0.10        1
127.0.0.0                   255.0.0.0        127.0.0.1        127.0.0.1        1
224.0.0.0                   240.0.0.0        50.0.0.10        50.0.0.10        10
255.255.255.255             255.255.255.255  50.0.0.10        50.0.0.10        1
=====
Persistent Routes:
None

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 60.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:
Reply from 60.0.0.10: bytes=32 time<1ms TTL=127
Reply from 60.0.0.10: bytes=32 time<1ms TTL=127
Reply from 60.0.0.10: bytes=32 time<1ms TTL=127
Reply from 60.0.0.10: bytes=32 time<1ms TTL=127

Ping statistics for 60.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Documents and Settings\user>
```

Win2

0.0.10

Physical

01 : 00 : 00

START

30°C

Light rain

21:31

23-08-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

Notifications

QEMU (Win2)

```
C:\WINDOWS\system32\cmd.exe
C:\Documents and Settings\user>route print
-----
Interface List
0x1 ..... MS TCP Loopback interface
0x2 ..50 86 5f 09 50 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport
-----
Active Routes:
Network Destination    Netmask          Gateway         Interface      Metric
0.0.0.0                0.0.0.0          0.0.0.0         0.0.0.0        10
60.0.0.10             255.255.255.255  127.0.0.1       127.0.0.1       10
60.255.255.255        255.255.255.255  60.0.0.10      60.0.0.10      10
127.0.0.0              255.0.0.0        127.0.0.1       127.0.0.1       1
127.0.0.0              248.0.0.0        60.0.0.10      60.0.0.10      10
255.255.255.255       255.255.255.255  60.0.0.10      60.0.0.10      1

Persistent Routes:
None

C:\Documents and Settings\user>route print
-----
Interface List
0x1 ..... MS TCP Loopback interface
0x2 ..50 86 5f 09 50 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport
-----
Active Routes:
Network Destination    Netmask          Gateway         Interface      Metric
0.0.0.0                0.0.0.0          0.0.0.0         0.0.0.0        10
60.0.0.10             255.255.255.255  127.0.0.1       127.0.0.1       10
60.255.255.255        255.255.255.255  60.0.0.10      60.0.0.10      10
127.0.0.0              255.0.0.0        127.0.0.1       127.0.0.1       1
127.0.0.0              248.0.0.0        60.0.0.10      60.0.0.10      10
255.255.255.255       255.255.255.255  60.0.0.10      60.0.0.10      1

Default Gateway:
60.0.0.1

Persistent Routes:
None

C:\Documents and Settings\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127

Ping statistics for 50.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\Documents and Settings\user>_
```

Win2
0.0.10

Physical

01 : 00 : 00

START

30°C
Light rain

Search

ENG
IN

21:40
23-08-2026