

PNETLab | TopologyStatic Route

labs.surenetwork.com/legacy/topology

Ask Gemini

Notifications

QEMU (Win-1)

```
Pinging 40.0.0.10 with 32 bytes of data:
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.

Ping statistics for 40.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 6ms, Maximum = 6ms, Average = 6ms

C:\Documents and Settings\User>route print

Interface List
0x1 ..... MS TCP Loopback interface
0x2 ...50 cf ch 01 aa 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:
Network Destination        Netmask          Gateway           Interface         Metric
0.0.0.0                    0.0.0.0          10.0.0.1          10.0.0.10         10
10.0.0.0                   255.255.255.255  10.0.0.1          10.0.0.10         10
10.255.255.255             255.255.255.255  10.0.0.1          10.0.0.10         10
127.0.0.0                  255.0.0.0        127.0.0.1         127.0.0.1         1
224.0.0.0                  240.0.0.0        10.0.0.1          10.0.0.10         10
255.255.255.255           255.255.255.255  10.0.0.1          10.0.0.10         1
Default Gateway:          10.0.0.1

Persistent Routes:
    None

C:\Documents and Settings\User>
C:\Documents and Settings\User>ping 40.0.0.10

Pinging 40.0.0.10 with 32 bytes of data:
Reply from 40.0.0.10: bytes=32 time=14ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125

Ping statistics for 40.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 14ms, Average = 5ms

C:\Documents and Settings\User>
```

Win-110.0.0.10

Win-240.0.0.10

Static Route

Physical

29°C Partly cloudy

Search

ENG IN

23:07 23-08-2026

PNETLab | TopologyStatic Route

labs.surennetwork.com/legacy/topology

Ask Gemini

Notifications

QEMU (Win-1)

Pinging 40.0.0.10 with 32 bytes of data:
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Ping statistics for 40.0.0.10:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\Documents and Settings\user>route print

Interface List

0x1 MS TCP Loopback interface

0x2 Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:

Network Destination Netmask Gateway Interface Metric

0.0.0.0 0.0.0.0 10.0.0.1 10.0.0.10 10

10.0.0.0 255.0.0.0 10.0.0.1 10.0.0.10 10

10.0.0.10 255.255.255.255 127.0.0.1 127.0.0.1 10

10.255.255.255 255.255.255.255 10.0.0.1 10.0.0.10 10

127.0.0.0 255.0.0.0 127.0.0.1 127.0.0.1 1

224.0.0.0 240.0.0.0 10.0.0.1 10.0.0.10 10

255.255.255.255 255.255.255.255 10.0.0.1 10.0.0.10 1

Default Gateway:

10.0.0.1

Persistent Routes:

None

C:\Documents and Settings\user>

C:\Documents and Settings\user>

10.0.1

30.0.0.2

40.0.0.1

R3

Win-2

40.0.0.10

Static Route

Physical

01 : 00 : 00

START

30°C
Partly cloudy

Search

ENG
IN

22:51
23-08-2026

PNETLab | Topology Static Route

labs.surennetwork.com/legacy/topology

Static Route

Physical 01 : 00 : 00 START

29°C Partly cloudy

23:05 23-08-2026

R1#
*Aug 23 17:26:27.096: %SYS-5-CONFIG_I: Configured from console by console
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
Gateway of last resort is not set
10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 10.0.0.0/8 is directly connected, Ethernet0/0
L 10.0.0.1/32 is directly connected, Ethernet0/0
C 20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
L 20.0.0.0/8 is directly connected, Ethernet0/1
S 30.0.0.0/8 [1/0] via 20.0.0.2
S 40.0.0.0/8 [1/0] via 20.0.0.2

R2#
*Aug 23 17:30:40.523: %SYS-5-CONFIG_I: Configured from console by console
R2#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
Gateway of last resort is not set
10.0.0.0/8 [1/0] via 20.0.0.1
C 20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 20.0.0.0/8 is directly connected, Ethernet0/0
L 20.0.0.2/32 is directly connected, Ethernet0/0
C 30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 30.0.0.0/8 is directly connected, Ethernet0/1
L 30.0.0.1/32 is directly connected, Ethernet0/1
S 40.0.0.0/8 [1/0] via 30.0.0.2

R3#
*Aug 23 17:34:48.405: %SYS-5-CONFIG_I: Configured from console by console
R3#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
Gateway of last resort is not set
S 10.0.0.0/8 [1/0] via 30.0.0.1
S 20.0.0.0/8 [1/0] via 30.0.0.1
C 30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 30.0.0.0/8 is directly connected, Ethernet0/1
L 30.0.0.2/32 is directly connected, Ethernet0/1
C 40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 40.0.0.0/8 is directly connected, Ethernet0/0
L 40.0.0.1/32 is directly connected, Ethernet0/0

Win-1 10.0.0.10

Win-2 40.0.0.10

