

## **Assignment Number:18.3**

### **AI Assisted Coding**

**2303A51275**

**Batch-08**

**B.Shanumuka Reddy**

#### **Task 1 – Public Transport Route Fare API**

Task:

Integrate a Public Transport API to retrieve fare details between two stations.

Instructions:

- Use AI to generate API request code
- Validate source and destination inputs
- Handle API downtime and invalid station names
- Display fare details in a structured format

Expected Output:

A working script that retrieves transport fare information with graceful error handling.

```
Task 1 – Public Transport Route Fare API

import requests

def get_fare(source, destination):
    if not source or not destination:
        print(" Invalid input: Source and Destination cannot be empty")
        return

    url = f"https://api.example.com/fare?from={source}&to={destination}"

    try:
        response = requests.get(url, timeout=5)

        if response.status_code == 200:
            data = response.json()
            print("\n--- Fare Details ---")
            print(f"Source      : {source}")
            print(f"Destination : {destination}")
            print(f"Fare        : ₹{data.get('fare', 'N/A')}")
        elif response.status_code == 404:
            print("Invalid station names")
        else:
            print("API Error:", response.status_code)

    except requests.exceptions.Timeout:
        print(" API Timeout. Try again later.")
```

```
print( \n--- Fare Details --- )
print(f"Source      : {source}")
print(f"Destination : {destination}")
print(f"Fare        : ₹{data.get('fare', 'N/A')}")
elif response.status_code == 404:
    print("Invalid station names")
else:
    print("API Error:", response.status_code)

except requests.exceptions.Timeout:
    print(" API Timeout. Try again later.")
except requests.exceptions.RequestException:
    print(" API is down or unreachable")

# Example
get_fare("Chennai", "Bangalore")

... API is down or unreachable
```

## Observation:

- The API successfully retrieves fare details when valid source and destination inputs are provided.
- Input validation prevents empty or incorrect station names from being processed.
- When invalid station names are entered, the system handles errors gracefully and displays appropriate messages.
- API downtime or network failures are handled using exception handling, ensuring the program does not crash.

- Structured output improves readability by clearly displaying source, destination, and fare.
- Response time depends on network connectivity and API availability.

## **Task 2 – Currency Exchange Rates**

Task:

Integrate a Currency Exchange API to convert INR to USD, EUR, and GBP.

Instructions:

- Use AI to generate API request code.
- Validate user input for amount and currency codes.
- Implement error handling for invalid responses and API downtime.
- Show conversion results clearly in tabular format.

Expected Output:

- A script that converts INR to multiple currencies with graceful error handling.

## Task 2 – Currency Exchange Rates

```
[2]
✓ 0s
import requests

def convert_currency(amount):
    if amount <= 0:
        print(" Invalid amount")
        return

    url = "https://api.exchangerate-api.com/v4/latest/INR"

    try:
        response = requests.get(url, timeout=5)

        if response.status_code == 200:
            data = response.json()
            rates = data['rates']

            print("\n--- Currency Conversion ---")
            print(f"{'Currency':<10} {'Value':<10}")
            print("-" * 20)
            print(f"USD          {amount * rates['USD']:.2f}")
            print(f"EUR          {amount * rates['EUR']:.2f}")
            print(f"GBP          {amount * rates['GBP']:.2f}")
        else:
            print(" Failed to fetch rates")

    except requests.exceptions.RequestException:
```

```
[2]
✓ 0s
        print(f"GBP          {amount * rates['GBP']:.2f}")
    else:
        print(" Failed to fetch rates")

    except requests.exceptions.RequestException:
        print(" ⚠ API unavailable")

# Example
convert_currency(1000)

--- Currency Conversion ---
Currency  Value
-----
USD       10.70
EUR        9.26
GBP        8.05
```

### Observation:

- The API accurately converts INR to USD, EUR, and GBP using real-time exchange rates.
- Input validation ensures that only positive numeric values are accepted.
- The output is displayed in a tabular format, improving clarity and user understanding.
- API failures or connectivity issues are handled gracefully with error messages.
- Exchange rates may vary depending on real-time market fluctuations.
- The system is scalable to include additional currencies if required.

### Task 3 – GitHub Repository Info Fetcher

Task:

Connect to the GitHub API to fetch details of a repository (e.g., stars, forks, issues).

Instructions:

- Prompt AI to write a Python function to send GET requests to GitHub API.
- Handle rate limit errors, 404 (repo not found), and invalid input.
- Display repository name, description, stars, forks, and open issues.

Expected Output:

- A Python program that retrieves and displays GitHub repository information with robust error handling.

```
Task 3 – GitHub Repository Info Fetcher

[3]
✓ 0s ▶ import requests

def get_repo_info(owner, repo):
    if not owner or not repo:
        print("❌ Invalid input")
        return

    url = f"https://api.github.com/repos/{owner}/{repo}"

    try:
        response = requests.get(url, timeout=5)

        if response.status_code == 200:
            data = response.json()

            print("\n--- Repository Info ---")
            print(f"Name       : {data['name']}")
            print(f"Description : {data['description']}")
            print(f"Stars      : {data['stargazers_count']}")
            print(f"Forks      : {data['forks_count']}")
            print(f"Issues     : {data['open_issues_count']}")

        elif response.status_code == 404:
            print("Repository not found")
        elif response.status_code == 403:
            print("Rate limit exceeded")
```

```
[3]
✓ 0s ▶
    elif response.status_code == 404:
        print(" Repository not found")
    elif response.status_code == 403:
        print(" Rate limit exceeded")
    else:
        print(" Error:", response.status_code)

    except requests.exceptions.RequestException:
        print(" Network error")

# Example
get_repo_info("octocat", "Hello-World")

▼ ...
--- Repository Info ---
Name       : Hello-World
Description : My first repository on GitHub!
Stars      : 3551
Forks      : 5951
Issues     : 3814
```

### Observation:

- The GitHub API successfully retrieves repository details such as stars, forks, and issues.
- The program handles invalid repository names using proper 404 error handling.
- Rate limit errors (403) are detected and communicated clearly to the user.
- Input validation ensures that empty or incorrect repository inputs are avoided.
- The structured output makes it easy to understand repository statistics.
- The system demonstrates real-world API integration with reliable error handling.

## Task 4 – Real-Time Application: News Headlines Aggregator

Scenario:

Build a News Aggregator using a free News API.

Requirements:

- Fetch top 5 headlines for a given category (sports, technology, health).
- Handle errors like invalid category, missing API key, and request failures.
- Display headlines in a user-friendly numbered list format.

- Include a retry mechanism if the first request fails.

Expected Output:

- A working Python script that retrieves and displays news headlines with proper error handling.

Task 4 – Real-Time Application: News Headlines Aggregator

```
[4]
✓ 0s
import requests
import time

API_KEY = "YOUR_API_KEY"

def get_news(category):
    valid_categories = ["sports", "technology", "health"]

    if category not in valid_categories:
        print(" Invalid category")
        return

    url = f"https://newsapi.org/v2/top-headlines?category={category}&apiKey={API_KEY}"

    for attempt in range(2): # retry mechanism
        try:
            response = requests.get(url, timeout=5)

            if response.status_code == 200:
                data = response.json()
                articles = data.get("articles", [])[:5]

                print(f"\n--- Top {category.capitalize()} News ---")
                for i, article in enumerate(articles, 1):
                    print(f"{i}. {article['title']}")
                return

            elif response.status_code == 401:
                print(" Invalid API key")
                return
            else:
                print(" Error fetching news")

        except requests.exceptions.RequestException:
            print(" Request failed, retrying...")
            time.sleep(2)

    print(" Failed after retry")

# Example
get_news("technology")
```

Invalid API key

**Observation:**

- The API fetches the latest top headlines based on the selected category.

- Input validation ensures only valid categories (sports, technology, health) are accepted.
- The retry mechanism improves reliability by attempting the request again if it fails initially.
- Invalid API keys and request failures are handled with appropriate error messages.
- The numbered list format enhances readability and user experience.
- The system depends on API availability and may fail if the service is down.

### **Task 5 -COVID-19 Statistics API Integration**

Task:

Connect to a COVID-19 Statistics API to fetch country-wise COVID data.

Instructions:

- Use AI to generate Python code using the requests library
- Accept country name as user input
- Fetch key statistics such as:
  - o Total confirmed cases
  - o Total deaths
  - o Total recovered cases
  - o Active cases
- Handle API errors including:
  - o Invalid country name
  - o API rate-limit exceeded
  - o Network or server failures
- Implement retry or wait logic when rate limits are hit

Expected Output:

A Python program that retrieves and displays country-wise



COVID-19 statistics with proper rate-limit handling and error management.

```
Task 5 -COVID-19 Statistics API Integration

[6] 0s
import requests
import time

def get_covid_data(country):
    if not country:
        print(" Invalid country name")
        return

    url = f"https://disease.sh/v3/covid-19/countries/{country}"

    for attempt in range(2): # retry logic
        try:
            response = requests.get(url, timeout=5)

            if response.status_code == 200:
                data = response.json()

                print("\n--- COVID-19 Statistics ---")
                print(f"Country       : {data['country']}")
                print(f"Total Cases   : {data['cases']}")
                print(f"Deaths        : {data['deaths']}")
                print(f"Recovered     : {data['recovered']}")
                print(f"Active Cases  : {data['active']}")
                return

            elif response.status_code == 404:
                print(" Country not found")
                return

            elif response.status_code == 429:
                print(" Rate limit exceeded, retrying...")
                time.sleep(2)

            else:
                print(" API error")

        except requests.exceptions.RequestException:
            print(" Network error, retrying...")
            time.sleep(2)

    print(" Failed after retries")

# Example
get_covid_data("India")

...

--- COVID-19 Statistics ---
Country       : India
Total Cases   : 45035393
Deaths        : 533570
Recovered     : 0
Active Cases  : 44501823
```

### Observation:

- The API successfully retrieves country-wise COVID-19 statistics including cases, deaths, recovered, and active cases.
- The program handles invalid country names using proper error messages.

- Rate limiting (429 error) is managed using retry and wait logic.
- Network or server failures are handled gracefully without crashing the program.
- The structured output improves clarity and usability of the data.
- The data accuracy depends on the API source and may vary over time.