Data: RRAW.SGY (same data file used in the training session for testing the FK filter)

Coordinates: Common Shot gather recorded with a 59 channels off-end spread. The group interval is about 12.3m and the first group is 33m far from the source while the last group is at 747m from the source.

Objective: to process these data by applying the following processing sequence

- Data import
- Resampling at 1 ms
- Passband filter to remove the low frequency components (lower than 10Hz, mostly due to Ground Roll)
- FK filter to remove the residual Ground Roll and to attenuate first arrivals (paying attention to preserve the near-surface reflections at long offsets)
- Muting of the remaining energy associated to noise and linear events arriving earlier than the first reflections
- Velocity analysis. Activating the CMP option but sorting the data with shot as sorting option and offset as second axis. Then, following the suggestions of the training session. For the construction of the Velocity Spectrum try to optimize the time window (by default 1ms) exploring the effect of increasing this parameter to values comparable to the wavelet duration. Conclude the analysis by generating and saving a 2D velocity model (although consisting of flat layers) as suggested in the training session.
- NMO corrections and Stack, saving the single trace stack.
- Deconvolution with the Spectral Whitening function to improve the resolution (compare either the stack trace or its amplitude spectrum before and after deconvolution)

Prepare the PowerPoint report to illustrate the intermediate results and parameter windows of any processing step.