



A Bayesian approach to feedback control for hyperbolic balance laws

Markus Bambach , Shaoshuai Chu , Michael Herty & Yunong Lin

To cite this article: Markus Bambach , Shaoshuai Chu , Michael Herty & Yunong Lin (10 Aug 2026): A Bayesian approach to feedback control for hyperbolic balance laws, International Journal of Control, DOI: [10.1080/00207179.2026.2713732](https://doi.org/10.1080/00207179.2026.2713732)

To link to this article: <https://doi.org/10.1080/00207179.2026.2713732>



© 2026 The Author(s). Published by Informa UK Limited, trading as Taylor & Francis Group.



Published online: 10 Aug 2026.



Submit your article to this journal [↗](#)



View related articles [↗](#)



View Crossmark data [↗](#)

A Bayesian approach to feedback control for hyperbolic balance laws

Markus Bambach^a, Shaoshuai Chu^b, Michael Herty^{b,c} and Yunong Lin^a

^aDepartment of Mechanical and Process Engineering, ETH Zürich, Zürich, Switzerland; ^bDepartment of Mathematics, RWTH Aachen University, Aachen, Germany; ^cDepartment of Mathematics and Applied Mathematics, University of Pretoria, Hatfield, South Africa

ABSTRACT

We propose a Bayesian framework for feedback boundary control of hyperbolic balance laws. The method propagates a probability distribution over feedback parameters using Lyapunov decay estimates as a likelihood. For linear models, it recovers available analytical stability results and extends to nonlinear regimes where theory is limited. Using first-order local Lax–Friedrichs (LLF) discretisations, we validate the approach on the decoupled wave system and the linearised Saint-Venant equations, reproducing known stability intervals and mixed boundary couplings. We then treat nonlinear and stochastic problems, including the nonlinear Saint-Venant system, one- and two-dimensional Burgers equations, Burgers equation with random initial data, and nonconservative perturbations with source terms, and show that the inferred stability domains are robust with respect to the indicator and the prior. Finally, we demonstrate transfer to a second-order semi-discrete LLF scheme and to a two-parameter feedback model for laser powder bed fusion with power regulation.

ARTICLE HISTORY

Received 3 February 2026
Accepted 29 July 2026

KEYWORDS

Hyperbolic systems of balance laws; exponential stability; boundary feedback control

2020 MATHEMATICS

SUBJECT

CLASSIFICATIONS

93C20; 93D15; 93D05; 35L65; 65M12; 65M08

1. Introduction

This paper focuses on the stabilisation of hyperbolic systems, which in the one-dimensional (1-D) case read as

$$U_t + F(U)_x = S(U), \quad (1)$$

where $x \in \Omega$ is a spatial variable, $t \geq 0$ is the time, $U \in \mathbb{R}^d$ is a vector of unknown functions, $F: \mathbb{R}^d \rightarrow \mathbb{R}^d$ denotes the (generally nonlinear) flux and $S: \mathbb{R}^d \rightarrow \mathbb{R}^d$ the source term.

We consider the stabilisation of the dynamics near a stationary state of the system (1) by means of boundary feedback control. This topic has attracted considerable attention due to applications in shallow-water systems, gas flow, traffic flow, and many other areas; see, e.g. Bastin and Coron (2016) and Coron (2007). On the analytical side, a substantial body of work has been devoted to the design of stabilising boundary conditions and feedback laws for hyperbolic systems, typically based on Lyapunov or energy methods that yield exponential decay estimates and admissible ranges of feedback parameters; see, for instance, Bastin et al. (2007), Coron (2007) and Coron et al. (2008, 2007). Further developments, including the treatment of source terms, nonlinear couplings, and networked configurations, can be found in Herty and Yong (2016), Li (2005), Li and Rao (2009), Li et al. (2008), Li and Yu (2003) and Xu and Sallet (2002).

These continuous results are complemented by analytical and numerical analyses, as well as discretisations that are required to inherit the stabilisation properties at the semi-discrete or fully discrete level; see, e.g. Bardos et al. (1979) and Banda and Herty (2013). Many of the above contributions develop Lyapunov-type methodologies both for the continuous system (1) and, in some cases, for its numerical approximations, thereby providing explicit decay estimates and conditions on the feedback parameters.

Using a suitable Lyapunov function, the exponential stabilisation inequality (4) has been established for linear deterministic hyperbolic systems. The analysis of the Lyapunov function yields explicit estimates for the feedback control parameter κ ; see Equation (2). In the linear case, these estimates take the form of dissipativity conditions on κ that guarantee exponential stability; see, e.g. Diagne et al. (2017) and Coron et al. (2008). In the discrete setting, carefully constructed Lyapunov functionals lead to stability proofs and explicit decay rates consistent with the continuous theory; see Banda and Herty (2013), Bastin and Coron (2016), Meurer (2013), Chu et al. (2026) and Diagne et al. (2012). The Saint-Venant system for shallow-water flows is a canonical example, in which source terms and variable topography are intrinsic. At the continuous level, dissipative boundary conditions for one-dimensional nonlinear

systems were established in Coron et al. (2008), and coupled models such as the Saint-Venant–Exner system were treated via backstepping in Diagne et al. (2017). On the numerical side, boundary feedback for non-uniform balance laws was proposed in Banda and Weldegiyorgis (2020).

Although appropriate boundary controls can be derived for specific systems, most of them concern linearised hyperbolic balance laws. Determining stabilising controls in more complex settings, such as fully nonlinear, nonconservative, or multidimensional problems, remains highly challenging. To address this difficulty, we propose a Bayesian framework. Instead of working with a single feedback parameter, we numerically evolve a probability density on the feedback parameters; see Equation (2). Starting from a prior distribution, we update this density using Bayes' theorem. As a likelihood function, we employ the observed decay rate of an L^2 -based Lyapunov functional; see (4). The resulting posterior distribution identifies the range of stabilising feedback parameters. Since this approach requires repeated simulations of the underlying hyperbolic balance law, we present the Bayesian framework directly in the discretised setting below. The approach is non-intrusive: it can be applied to a given scheme and does not require the design of alternative Lyapunov functionals. We first consider linear deterministic models (linear advection/wave and the linearised Saint-Venant system) and verify that the recovered stability domains agree with the theoretical predictions. We then treat nonlinear problems (nonlinear Saint-Venant and Burgers), followed by stochastic variants, a nonconservative case, and a second-order local Lax–Friedrichs (LLF) discretisation; see, e.g. Kurganov and Tadmor (2000) and Rusanov (1961). Finally, we examine the evolution of the thermal field during a single-track scanning process in laser powder bed fusion and recover its stability region via the same Bayesian update. These experiments demonstrate both the accuracy and robustness of the proposed method and indicate its potential for more complex systems.

The paper is organised as follows. In Section 2, we introduce the Bayesian boundary feedback framework, including the first-order LLF discretisation and the probability-update algorithm with damping and normalisation. In Section 3, we present a comprehensive suite of experiments: linear deterministic tests (wave and linearised Saint-Venant), nonlinear benchmarks (nonlinear Saint-Venant and Burgers), stochastic variants, a nonconservative case, a second-order semi-discrete LLF discretisation, and the evolution of the thermal field during a single-track scanning process in laser powder bed fusion,

all assessed within the proposed Bayesian boundary feedback framework. Finally, Section 4 contains concluding remarks and perspectives.

2. A Bayesian boundary feedback method

In this section, we introduce the Bayesian feedback control method for the studied hyperbolic system (1) with specific boundary conditions.

2.1 First-order local Lax-Friedrichs scheme

Assume the computational domain is covered with uniform cells $C_j := [x_{j-\frac{1}{2}}, x_{j+\frac{1}{2}}]$ with $x_{j+\frac{1}{2}} - x_{j-\frac{1}{2}} \equiv \Delta x$ centred at $x_j = (x_{j-\frac{1}{2}} + x_{j+\frac{1}{2}})/2$, $j = 1, \dots, N_x$, and the cell average values

$$\bar{U}_j(t) \approx \frac{1}{\Delta x} \int_{C_j} U(x, t) dx$$

are available at a certain time level $t \geq 0$.

The computed cell averages $\bar{U}_j$ of the 1-D system (1) are evolved in time by the first-order LLF scheme:

$$\bar{U}_j^{n+1} = \bar{U}_j^n - \frac{\Delta t}{\Delta x} \left(\mathcal{F}_{j+\frac{1}{2}} - \mathcal{F}_{j-\frac{1}{2}} \right) + \Delta t \mathcal{S}(\bar{U}_j^n),$$

where $\mathcal{F}_{j+\frac{1}{2}}$ stands for a finite-volume numerical flux and in this paper, we use the central (local Lax–Friedrichs, Rusanov; see, e.g. Kurganov & Tadmor, 2000; Rusanov, 1961) fluxes

$$\mathcal{F}_{j+\frac{1}{2}} = \frac{1}{2} (F(\bar{U}_j) + F(\bar{U}_{j+1})) - \frac{\alpha_{j+\frac{1}{2}}}{2} (\bar{U}_{j+1} - \bar{U}_j),$$

with the local speeds of propagation estimated using the eigenvalues $\lambda_1(\mathcal{A}) \leq \dots \leq \lambda_d(\mathcal{A})$ of the matrix $\mathcal{A} = \frac{\partial F}{\partial U}$:

$$\alpha_{j+\frac{1}{2}} = \max \{ |\lambda_1(\bar{U}_j)|, |\lambda_1(\bar{U}_{j+1})|, \dots, |\lambda_d(\bar{U}_j)|, |\lambda_d(\bar{U}_{j+1})| \}.$$

Finally, the time step Δt is computed by the CFL condition, $\Delta t = \text{CFL} \frac{\Delta x}{\max_j \{\alpha_{j+\frac{1}{2}}\}}$.

Remark 2.1: It is straightforward to verify that, for linear systems, the first-order LLF scheme coincides with the corresponding upwind scheme.

2.2 Evolution of the probability distribution

For simplicity, we work on the one-dimensional spatial domain $[0, 1]$. We assume that, in a neighbourhood of the stationary state of interest, the incoming and outgoing

characteristic fields are well defined. More precisely, let $\Lambda_i(A)$, $i = 1, \dots, d$, denote the eigenvalues of the Jacobian matrix $A = \frac{\partial F}{\partial U}$ at the stationary state, and assume that

$$\Lambda_i(A) > 0, \quad i = 1, \dots, m, \quad \Lambda_i(A) < 0, \\ i = m + 1, \dots, d.$$

Then the first m characteristic fields enter the domain at $x=0$ and leave at $x=1$, whereas the remaining $d-m$ characteristic fields enter the domain at $x=1$ and leave at $x=0$. This assumption is made only to simplify the presentation of the boundary feedback law; the Bayesian update procedure itself only requires an admissible feedback parametrisation and a nonnegative stability indicator. We therefore impose boundary conditions at discrete time levels $t = t^n$ in the form

$$\bar{U}_0^{(p)}(t^n) = \kappa^{(p)} \bar{U}_{N_x}^{(p)}(t^n), \quad p = 1, \dots, m, \quad (2)$$

and

$$\bar{U}_{N_x+1}^{(p)}(t^n) = \kappa^{(p)} \bar{U}_1^{(p)}(t^n), \quad p = m + 1, \dots, d. \quad (3)$$

Here, $U^{(p)}$ denotes the p -th characteristic component of the solution variable, obtained after local diagonalisation near the stationary state. For diagonal systems, this notation coincides with the physical components of U . Here, $\kappa^{(p)}$ is the p -th component of the feedback parameters κ . For clarity of presentation, we first describe the algorithm for a single scalar parameter κ and omit the component index; the case of several parameters is treated in complete analogy.

We are interested in those values of κ for which the solution of the closed-loop system (1)–(3) satisfies an exponential decay estimate in $L^2(\Omega)$, in the following sense.

Definition 2.1 ((Exponential stabilisation)): Fix a feedback parameter κ and consider the corresponding closed-loop system (1)–(3). We say that κ is (continuously) exponentially stabilising in $L^2(\Omega)$ if there exist constants $C_1 \geq 1$ and $\nu > 0$, independent of t and of the initial datum $U(\cdot, 0) \in L^2(\Omega)$, such that

$$\|U(\cdot, t)\|_{L^2(\Omega)}^2 \leq C_1 e^{-\nu t} \|U(\cdot, 0)\|_{L^2(\Omega)}^2, \quad t \geq 0.$$

In the semi-discrete setting, this corresponds to

$$\Delta x \sum_{j=1}^{N_x} \|U_j(t)\|_2^2 \leq C_1 e^{-\nu t} \Delta x \sum_{j=1}^{N_x} \|U_j(0)\|_2^2, \quad t \geq 0. \quad (4)$$

In the numerical experiments, this decay is monitored by Lyapunov-type indicators.

Definition 2.2 ((Lyapunov-type indicators)): Let $\bar{U}_j^n(\kappa) = (\bar{u}_j^{(1),n}(\kappa), \dots, \bar{u}_j^{(d),n}(\kappa))^T$ denote the numerical solution of the LLF scheme of Section 2.1 at time t^n in cell C_j , obtained with boundary parameter κ . For fixed constants $\mu_i > 0$, $i = 1, \dots, d$, we define the discrete Lyapunov functional

$$\mathcal{L}_{\text{Lyapunov}}^n(\kappa) = \Delta x \sum_{i=1}^m \sum_{j=1}^{N_x} e^{-\mu_i x_j} \left(\bar{u}_j^{(i),n}(\kappa) \right)^2 \\ + \Delta x \sum_{i=m+1}^d \sum_{j=1}^{N_x} e^{\mu_i x_j} \left(\bar{u}_j^{(i),n}(\kappa) \right)^2, \quad (5)$$

and the discrete energy

$$\mathcal{L}_{\text{Energy}}^n(\kappa) = \Delta x \sum_{i=1}^d \sum_{j=1}^{N_x} \left(\bar{u}_j^{(i),n}(\kappa) \right)^2. \quad (6)$$

Any quantity of the form $\mathcal{L}^n(\kappa)$ obtained from (5) or (6) will be referred to as a Lyapunov-type indicator. In Section 3 we simply write $\mathcal{L}^n(\kappa)$ for the chosen indicator. At the same time, one can easily verify

$$\tilde{C}_2 \mathcal{L}_{\text{Lyapunov}}^n(\kappa) \leq \mathcal{L}_{\text{Energy}}^n(\kappa) \leq \tilde{C}_1 \mathcal{L}_{\text{Lyapunov}}^n(\kappa), \quad (7)$$

where $\tilde{C}_1$ and $\tilde{C}_2$ are two positive constants, which are independent of n and κ . Therefore, both indicators can be used since they are equivalent by (7).

Proposition 2.3 ((Discrete exponential stabilisation for the LLF scheme)): Assume that the deterministic system (1) with boundary conditions (2)–(3) satisfies the hypotheses of Coron (2007), Banda and Herty (2013) and that the numerical solution is computed by the first-order LLF scheme of Section 2.1. Then there exist constants $\nu > 0$ and $\tilde{C} \geq 0$, depending only on the system and the feedback law, such that for every feedback parameter κ in the corresponding stability domain the numerical solution satisfies

$$\mathcal{L}_{\text{Lyapunov}}^n(\kappa) \leq e^{-\nu t^n} \mathcal{L}_{\text{Lyapunov}}^0(\kappa), \quad n \geq 0, \quad (8)$$

and, in addition, the exponential stabilisation inequality in the discrete L^2 -norm

$$\mathcal{L}_{\text{Energy}}^n(\kappa) \leq \tilde{C} e^{-\nu t^n} \mathcal{L}_{\text{Energy}}^0(\kappa), \quad n \geq 0. \quad (9)$$

An analogous statement for stochastic systems is obtained in Chu et al. (2026). In particular, the indicators (5)–(6) are consistent discrete realisations of the continuous Lyapunov estimate (4) and can be used to detect stabilising feedback parameters.

The estimates (8)–(9) are proved in Banda and Herty (2013, Theorem 3.2) for deterministic systems and

extended to the random setting in Chu et al. (2026, Theorem 4.2). The proofs are based on discrete Lyapunov functionals with weights $e^{-\mu_i x_j}$ and $e^{\mu_i x_j}$, which are precisely the weights used in (5). We therefore refer to these references for the details.

Formally, the Bayesian feedback procedure can be viewed as an iteration on a family of posterior distributions $\{\mathcal{P}^n\}_{n \geq 0}$ supported on a compact parameter set. At each time step, the decay behaviour of the indicator $\mathcal{L}^n(\kappa)$ provides information on whether the chosen value of κ is stabilising.

Definition 2.4 ((Probability distributions of feedback parameters)): Let $\kappa \in [a, b]^d$ denote the feedback parameters and let $\mathcal{P}^n : [a, b]^d \rightarrow [0, \infty)$ be a nonnegative function. If

$$\int_{[a, b]^d} \mathcal{P}^n(\kappa) d\kappa = 1, \quad (10)$$

then $\mathcal{P}^n$ is called a probability density function of κ on $[a, b]^d$. To obtain a discrete representation, let $\{\kappa_\ell\}_{\ell=0}^{N_\kappa} \subset [a, b]^d$ be a finite grid of feedback parameters and let $\omega_\ell > 0$ denote the corresponding quadrature weights. A vector $\mathcal{P}^n = (\mathcal{P}^n(\kappa_0), \dots, \mathcal{P}^n(\kappa_{N_\kappa}))$ with $\mathcal{P}^n(\kappa_\ell) \geq 0$ for all ℓ and

$$\sum_{\ell=0}^{N_\kappa} \omega_\ell \mathcal{P}^n(\kappa_\ell) = 1 \quad (11)$$

is called a discrete probability mass function on the grid $\{\kappa_\ell\}_{\ell=0}^{N_\kappa}$. For a uniform one-dimensional grid, one may take $\omega_\ell = \Delta\kappa$, up to the usual endpoint convention. We interpret $\mathcal{P}^n$ and its discrete counterpart as the posterior distribution of κ after the n -th update.

Definition 2.5 ((Bayes' formula)): Bayes' formula provides the rule for updating probabilities when new information becomes available. Given an event space $A \in \mathcal{X}$ and observed data B with $\mathbb{P}(B) > 0$, Bayes' formula reads

$$\mathbb{P}(A | B) = \frac{\mathbb{P}(B | A) \mathbb{P}(A)}{\mathbb{P}(B)}. \quad (12)$$

Here, $\mathbb{P}(A)$ is the prior probability of A , $\mathbb{P}(B | A)$ is the likelihood of observing B under the hypothesis A , and $\mathbb{P}(A | B)$ is the posterior probability after taking the information B into account. If the event space is discretised with the events A_n , then (12) leads to

$$\mathbb{P}(A_k | B) = \frac{\mathbb{P}(B | A_k) \mathbb{P}(A_k)}{\sum_{i=0}^{N_\kappa} \mathbb{P}(B | A_i) \mathbb{P}(A_i)}, \quad k = 0, \dots, N_\kappa.$$

In our setting, the hypotheses are the grid values $\{\kappa_\ell\}_{\ell=0}^{N_\kappa}$ and the data B are the observed values of the Lyapunov-type indicator at time t^{n+1} .

Definition 2.6 ((Bayesian update operator)): Given a prior $\mathcal{P}^n$ as in (10) and (11) and a non-negative likelihood $\Lambda^{n+1}(\kappa) > 0$, the Bayesian update of the feedback distribution is defined by

$$\mathcal{P}^{n+1}(\kappa) = \frac{\Lambda^{n+1}(\kappa) \mathcal{P}^n(\kappa)}{\int_{[a, b]^d} \Lambda^{n+1}(\kappa) \mathcal{P}^n(\kappa) d\kappa}, \quad (13)$$

and

$$\mathcal{P}^{n+1}(\kappa_\ell) = \frac{\Lambda^{n+1}(\kappa_\ell) \mathcal{P}^n(\kappa_\ell)}{\sum_{m=0}^{N_\kappa} \omega_m \Lambda^{n+1}(\kappa_m) \mathcal{P}^n(\kappa_m)}. \quad (14)$$

Proposition 2.7 ((Positivity and normalisation)): In the continuous case, assume that $\mathcal{P}^n$ satisfies (10) and that the denominator in (13) is positive. Then $\mathcal{P}^{n+1}$ defined by (13) is nonnegative and satisfies (10). In the discrete case, assume that $\mathcal{P}^n$ satisfies (11) and that the denominator in (14) is positive. Then $\mathcal{P}^{n+1}$ defined by (14) is nonnegative and satisfies (11). Moreover, if $\Lambda^{n+1} = 1$ on a set of stabilising parameters and $\Lambda^{n+1} = \alpha \in (0, 1)$ on its complement, then the total probability mass assigned to the stabilising set is non-decreasing with respect to the time level n .

Proof: Positivity and normalisation follow immediately from (13) in the continuous case and from (14) together with (11) in the discrete case. In the two-level case $\Lambda^{n+1} \in \{1, \alpha\}$ with $\alpha \in (0, 1)$, the probability mass on the stabilising set is multiplied by 1 at each step, whereas mass on the complement is multiplied by α and subsequently renormalised. A direct computation shows that the fraction of total mass carried by the stabilising set is therefore non-decreasing. ■

In the computations below, one can choose the likelihood $\Lambda^{n+1}(\kappa)$ as simple functions of the indicator $\mathcal{L}_{\text{Lyapunov}}^{n+1}(\kappa)$ and its initial value $\mathcal{L}_{\text{Lyapunov}}^0(\kappa)$. One can adopt

$$\Lambda^{n+1}(\kappa) := \begin{cases} 1, & \mathcal{L}_{\text{Lyapunov}}^{n+1}(\kappa) \leq C_1 e^{-\nu t^{n+1}} \mathcal{L}_{\text{Lyapunov}}^0(\kappa), \\ \alpha, & \text{otherwise,} \end{cases} \quad (15)$$

where $\alpha \in (0, 1)$ and $C_1 > 0$ is a constant. Thus, parameters with non-increasing indicators retain their weight, whereas parameters with increasing indicators are penalised by the damping factor α . However, this likelihood is directly applicable only to systems for which Lyapunov functionals and the corresponding decay rates are available. For systems whose Lyapunov stability analysis is very complicated, it is too challenging to use the method in (15).

To address this issue, we therefore adopt

$$\Lambda^{n+1}(\kappa) := \begin{cases} 1, & \mathcal{L}^{n+1}(\kappa) \leq \mathcal{L}^0(\kappa), \\ \alpha, & \mathcal{L}^{n+1}(\kappa) > \mathcal{L}^0(\kappa), \end{cases} \quad (16)$$

where $\mathcal{L}$ can be the Lyapunov function $\mathcal{L}_{\text{Lyapunov}}$ or the energy function $\mathcal{L}_{\text{Energy}}$. In this manner, one can numerically identify candidate stabilising domains for a given system without requiring an explicit analytical decay rate. The numerical results reported in Section 3 show that both (15) and (16) yield the same stability domains for κ .

In the numerical implementation, the distribution $\mathcal{P}^n$ is approximated by a discrete probability mass function on the uniform grid $\{\kappa_\ell\}_{\ell=0}^{N_\kappa} \subset [a, b]$. Given a prior $\mathcal{P}^0(\kappa_\ell) > 0$ satisfying (11), reference indicator values $\mathcal{L}^0(\kappa_\ell)$, a damping factor $\alpha \in (0, 1)$, and a tolerance $\varepsilon_0 > 0$, we employ the following algorithm, which is the concrete realisation of the Bayesian update (13) with the choice (16).

Algorithm 1 Bayesian update of the feedback parameter distribution

- 1: Choose a parameter grid $\{\kappa_\ell\}_{\ell=0}^{N_\kappa} \subset [a, b]^d$.
 - 2: Prescribe a prior $\mathcal{P}^0(\kappa_\ell) > 0$ with $\sum_{\ell=0}^{N_\kappa} \omega_\ell \mathcal{P}^0(\kappa_\ell) = 1$.
 - 3: Compute reference indicator values $\mathcal{L}_\ell^0 = \mathcal{L}^0(\kappa_\ell)$.
 - 4: Fix a damping factor $\alpha \in (0, 1)$ and a tolerance $\varepsilon_0 > 0$.
 - 5: **for** $n = 0, 1, 2, \dots$ **do**
 - 6: Random choice of $\ell \in \{0, \dots, N_\kappa\}$.
 - 7: Advance $U_j^n(\kappa_\ell) \rightarrow U_j^{n+1}(\kappa_\ell)$ with the LLF scheme in Section 2.1.
 - 8: **if** $\mathcal{L}^{n+1}(\kappa_\ell) \leq \mathcal{L}^0(\kappa_\ell)$ **then**
 - 9: $\tilde{\mathcal{P}}^{n+1}(\kappa_\ell) \leftarrow \mathcal{P}^n(\kappa_\ell)$
 - 10: **else**
 - 11: $\tilde{\mathcal{P}}^{n+1}(\kappa_\ell) \leftarrow \alpha \mathcal{P}^n(\kappa_\ell)$
 - 12: **end if**
 - 13: Normalise the probabilities as in (14).
 - 14: Compute the variation of the distribution $\mathcal{V}^{n+1} = \|\mathcal{P}^{n+1} - \mathcal{P}^n\|_{\ell^1}$.
 - 15: **if** $\mathcal{V}^{n+1} \leq \varepsilon_0$ **then**
 - 16: **break**
 - 17: **end if**
 - 18: **end for**
-

In all numerical experiments reported in Section 3, we use $\varepsilon_0 = 10^{-12}$ and $\alpha = \frac{1}{2}$. Parameters κ_ℓ in the unstable region satisfy $\mathcal{P}^n(\kappa_\ell) \approx 0$ in the limiting distribution, whereas stabilising parameters satisfy $\mathcal{P}^n(\kappa_\ell) \gg 0$.

Remark 2.2: In place of the reference value $\mathcal{L}^0(\kappa_\ell)$ used in the algorithm, one may also compare $\mathcal{L}^{n+1}(\kappa_\ell)$ with

the previous indicator value $\mathcal{L}^n(\kappa_\ell)$ and modify the damping step as follows:

$$\begin{aligned} \text{if } \mathcal{L}^{n+1}(\kappa_\ell) \leq \mathcal{L}^n(\kappa_\ell) &\Rightarrow \tilde{\mathcal{P}}^{n+1}(\kappa_\ell) \leftarrow \mathcal{P}^n(\kappa_\ell), \\ \text{if } \mathcal{L}^{n+1}(\kappa_\ell) > \mathcal{L}^n(\kappa_\ell) &\Rightarrow \tilde{\mathcal{P}}^{n+1}(\kappa_\ell) \leftarrow \alpha \mathcal{P}^n(\kappa_\ell). \end{aligned}$$

The subsequent normalisation and the stopping criterion based on $\mathcal{V}^{n+1}$ remain unchanged. In all experiments presented in Section 3, this alternative update leads to the same stability domains as the reference-based criterion, with only minor differences in the number of iterations needed for convergence.

Remark 2.3: The Bayesian update step does not rely on strict hyperbolicity itself. It only requires an admissible finite-dimensional feedback parametrisation and a nonnegative stability indicator. If eigenvalues coincide or vanish, the construction of characteristic variables, boundary feedback laws, and Lyapunov-type indicators becomes model-dependent. Once these ingredients are specified, the probability update and the positivity-normalisation property remain unchanged.

3. Numerical results

In this section, we assess the proposed boundary-feedback control on a suite of numerical tests. We begin with linear deterministic models (linear wave; linearised Saint-Venant) and verify that the stability domains agree with theory. We then treat nonlinear problems (nonlinear Saint-Venant; Burgers), followed by stochastic variants, a nonconservative case, and a second-order LLF discretisation. Finally, we examine the evolution of the thermal field during a single-track scanning process in laser powder bed fusion and recover its stability domain via the same Bayesian update. In Examples 1–6, we use the CFL number 1, while in Examples 7–9, we use the CFL number 0.5.

3.1 Linear deterministic examples

In this section, we consider two linear deterministic examples – the linear wave equations and the linearised Saint-Venant system – to show that the stability domains computed by the proposed method are consistent with the theoretical results in Banda and Herty (2013).

3.1.1 Example 1 – linear wave equations

In the first example taken from Banda and Herty (2013), we consider the linear wave equations

$$\begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_t + \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix} \begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_x = \begin{pmatrix} 0 \\ 0 \end{pmatrix} \quad (17)$$

with the following initial conditions:

$$u^{(1)}(x, 0) = -\frac{1}{2}, \quad u^{(2)}(x, 0) = \frac{1}{2}.$$

The boundary conditions are given by

$$u^{(1)}(0, t) = \kappa u^{(1)}(1, t), \quad u^{(2)}(1, t) = \kappa u^{(2)}(0, t).$$

For the initial probability distributions of the parameter κ , we consider the following two cases:

- Case I: $\kappa \in [-2, 2]$ and $\mathcal{P}(\kappa) = \frac{1}{4}$;
- Case II: $\kappa \in [-5, 5]$ and $\mathcal{P}(\kappa) = \frac{1}{\sigma\sqrt{2\pi}} e^{-\frac{(\kappa-\mu)^2}{2\sigma^2}}$, with $\sigma = \mu = 1$.

We first normalise the probability distributions and then compute the numerical results on a uniform mesh with $N_x = 100$ and $N_\kappa = 800$. The obtained numerical results are presented in Figure 1. Here, the values of the probability distributions are updated based on the corresponding Lyapunov function

$$\begin{aligned} \mathcal{L}(\bar{u}^{(1)}, \bar{u}^{(2)}) \\ = \Delta x \sum_{j=1}^{N_x} e^{-\mu_1 x_j} \left(\bar{u}_j^{(1)}\right)^2 + \Delta x \sum_{j=1}^{N_x} e^{\mu_2 x_j} \left(\bar{u}_j^{(2)}\right)^2, \end{aligned}$$

where μ_1 and μ_2 are two positive constants. For more details, we refer the reader to Banda and Herty (2013, (33)). As expected, the stability interval $(-1, 1)$ is recovered independently of the chosen prior, which is consistent with (Banda Herty, 2013, Theorem 2.1) and validates the proposed methodology.

As discussed above, one may also use other Lyapunov-type indicators to update the probability distribution. In this example, we also show the numerical results by measuring the corresponding discrete energy

$$\mathcal{L}(\bar{u}^{(1)}, \bar{u}^{(2)}) = \Delta x \sum_{j=1}^{N_x} \left[\left(\bar{u}_j^{(1)}\right)^2 + \left(\bar{u}_j^{(2)}\right)^2 \right]. \quad (18)$$

The numerical results are plotted in Figure 2, where one can see that the numerical results are consistent with those obtained using the Lyapunov functional.

We also present the numerical results with $N_\kappa = 100$ in Figure 3. The same stability interval is recovered, although with lower resolution.

3.1.2 Example 2 – linearised Saint-Venant system

In the second example taken from Banda and Herty (2013), we consider the linearised Saint-Venant system of shallow-water equations, which is motivated by

recent advances in the continuous setting; see, e.g. Coron et al. (1999), Bastin et al. (2007), Coron et al. (2007) and de Halleux et al. (2003). The objective is to regulate water depth and velocity in an open canal or in canal networks. External factors such as weather variations or uncontrolled inflows can cause fluctuations in water depth, which must be mitigated to maintain a predetermined target depth $\bar{h}$ and velocity $\bar{v}$. As in Coron et al. (2007) and de Halleux et al. (2003), we neglect the source terms. The target water state is a constant with $\bar{h}(x) = 4$ and $\bar{v}(x) = \frac{5}{2}$. To analyse small deviations from this steady state, the Saint-Venant system of shallow-water equations

$$\begin{pmatrix} h \\ q \end{pmatrix}_t + \begin{pmatrix} q \\ \frac{q^2}{h} + \frac{g}{2}h^2 \end{pmatrix}_x = \begin{pmatrix} 0 \\ 0 \end{pmatrix},$$

where $q = hv$, is linearised by introducing perturbations $(\delta h, \delta v)$ with $h = \bar{h} + \delta h$ and $v = \bar{v} + \delta v$. The resulting diagonalised equations for these perturbations are given by:

$$\begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_t + \begin{pmatrix} \Lambda_1 & 0 \\ 0 & \Lambda_2 \end{pmatrix} \begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_x = \begin{pmatrix} 0 \\ 0 \end{pmatrix},$$

where

$$\begin{aligned} \Lambda_1 &= \bar{v} + \sqrt{g\bar{h}}, \quad \Lambda_2 = \bar{v} - \sqrt{g\bar{h}}, \\ u^{(1)} &= \delta v + \sqrt{\frac{g}{h}}\delta h, \quad \text{and} \quad u^{(2)} = \delta v - \sqrt{\frac{g}{h}}\delta h. \end{aligned} \quad (19)$$

In this example, we consider the following initial conditions:

$$\delta h(x, 0) = \frac{1}{2} \sin(\pi x), \quad \delta v(x, 0) = \frac{20}{8 + \sin(\pi x)} - \frac{5}{2},$$

subject to the boundary conditions

$$u^{(1)}(0, t) = \kappa u^{(1)}(1, t), \quad \text{and} \quad u^{(2)}(1, t) = \kappa u^{(2)}(0, t). \quad (20)$$

For the initial probability distributions of the parameter κ , we consider the following two cases:

- Case I: $\kappa \in [-2, 2]$ and $\mathcal{P}(\kappa) = \frac{1}{4}$;
- Case II: $\kappa \in [-5, 5]$ and $\mathcal{P}(\kappa) = \frac{1}{\sigma\sqrt{2\pi}} e^{-\frac{(\kappa-\mu)^2}{2\sigma^2}}$, with $\sigma = 1, \mu = 0$.

We first normalise the probability distributions and then compute the numerical results on a uniform mesh with $N_x = 100$ and $N_\kappa = 800$. The values of the probability distributions are updated based on the discrete energy (18), and the obtained numerical results are presented in Figure 4. One can clearly see that the




Figure 1. Example 1: Initial (left) and final probability distributions for Cases I (top row) and II (bottom row).




Figure 2. Example 1: Final probability distributions for Cases I (left) and II (right).




Figure 3. Example 1: Final probability distributions for Cases I (left) and II (right) with $N_\kappa = 100$.




Figure 4. Example 2: Initial (left) and final probability distributions for Cases I (top row) and II (bottom row) for the boundary conditions (20).

stability region of the boundary control parameter is $(-1, 1)$, which is consistent with the one proved in Banda and Herty (2013, Theorem 2.1), which validates the proposed methodology.

As in Chu et al. (2026) and Banda and Herty (2013), we also compute the numerical results using the following boundary conditions:

$$u^{(1)}(0, t) = \kappa u^{(2)}(0, t), \quad u^{(2)}(1, t) = \kappa u^{(1)}(1, t). \quad (21)$$

The obtained numerical results are reported in Figure 5, where one can see that stability region of the boundary control parameter is $(-0.67, 0.67)$, which, once again, is consistent with the one proved in Banda and Herty (2013, Theorem 2.1).

3.2 Nonlinear deterministic examples

In this section, we consider two nonlinear deterministic examples – the nonlinear Saint-Venant system and the Burgers equation and compute the stable domains. It is well known that determining stability domains for nonlinear systems is challenging, and we now show that the proposed method provides a feasible route to identify them.

3.2.1 Example 3 – nonlinear Saint-Venant system

In the third example taken from Chu et al. (2026), we consider the same setting as in Example 2, but with different equations for the perturbations:

$$\begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_t + \begin{bmatrix} \bar{v} + \delta v + \sqrt{g(\bar{h} + \delta h)} \\ 0 \\ \bar{v} + \delta v - \sqrt{g(\bar{h} + \delta h)} \end{bmatrix} \begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_x = \begin{pmatrix} 0 \\ 0 \end{pmatrix}, \quad (22)$$

where $u^{(1)}$ and $u^{(2)}$ are defined by (19). Notice that the system (22) is nonlinear.

We compute the numerical results on a uniform mesh with $N_x = 100$ and $N_\kappa = 800$. The values of the probability distributions are updated based on the discrete energy (18), and the obtained numerical results are presented in Figure 6. One can clearly see that the stability region of the boundary control parameter is approximately $(-1, 1)$, slightly different from the one reported in Example 2.




Figure 5. Example 2: Final probability distributions for Cases I (left) and II (right) for the boundary conditions (21).




Figure 6. Example 3: Final probability distributions for Cases I (left) and II (right).

3.2.2 Example 4 – Burgers equation

In this example, we consider the Burgers equation

$$u_t + \left(\frac{u^2}{2} \right)_x = 0 \quad (23)$$

with the initial conditions:

$$\begin{aligned} \text{Case I : } u(x, 0) &= \begin{cases} 0.3, & \text{if } x < 0.3, \\ 0.2, & \text{if } 0.3 \leq x \leq 0.7, \\ -0.1, & \text{otherwise,} \end{cases} \\ \text{Case II : } u(x, 0) &= \begin{cases} 0.1, & \text{if } x < 0.3, \\ 0.2, & \text{if } 0.3 \leq x \leq 0.7, \\ 0.1, & \text{otherwise,} \end{cases} \end{aligned}$$

subject to the following boundary conditions:

$$\begin{cases} u(0-, t) = \kappa u(1-, t), & \text{if } u(0+, t) > 0, \\ u(0-, t) = u(0+, t), & \text{otherwise,} \\ u(1+, t) = \kappa u(0+, t), & \text{if } u(1-, t) < 0, \\ u(1+, t) = u(1-, t), & \text{otherwise.} \end{cases} \quad (24)$$

We compute the numerical results for Cases I and II on a uniform mesh with $N_x = 200$ and $N_\kappa = 400$, with the

initial probability distribution defined on $\kappa \in [-2, 2]$ by $\mathcal{P}(\kappa) = 1/4$. The values of the probability distributions are updated based on the discrete energy

$$\mathcal{L}(\bar{u}) = \Delta x \sum_{j=1}^{N_x} \bar{u}_j^2,$$

and the obtained numerical results are presented in Figure 7. One can see that for the Burgers equation with the boundary conditions defined in (24), the stable domain of the parameter κ depends on the initial conditions, and the stable domains are $(-1, 2)$ and $(-2, 1)$ for Cases I and II, respectively.

We also plot the three-dimensional numerical results for Cases I and II over time in Figure 8, where one can see that the stable domains are $(-1, 2)$ and $(-2, 1)$ for the Cases I and II, respectively, which further supports the proposed methodology for the two cases.

3.2.3 Example 5 – 2-D Burgers equation

In this example, we consider the 2-D Burgers equation

$$u_t + \left(\frac{u^2}{2} \right)_x + \left(\frac{u^2}{2} \right)_y = -0.2u$$




Figure 7. Example 4: Final probability distributions for Cases I (left) and II (right).




Figure 8. Example 4: Evolution of $\log_{10} \mathcal{L}$ for Cases I (left) and II (right).

with the initial conditions:

$$\text{Case I: } u(x, y, 0) = \begin{cases} 0.3, & \text{if } x < 0.3, \\ 0.2, & \text{if } 0.3 \leq x \leq 0.7, \\ -0.1, & \text{otherwise,} \end{cases}$$

$$\text{Case II: } u(x, y, 0) = \begin{cases} 0.1, & \text{if } x < 0.3, \\ 0.2, & \text{if } 0.3 \leq x \leq 0.7, \\ 0.1, & \text{otherwise,} \end{cases}$$

with the following boundary conditions:

$$\begin{cases} u(0-, y, t) = \kappa u(1-, y, t), & u(0+, y, t) > 0, \\ u(0-, y, t) = u(0+, y, t), & u(0+, y, t) \leq 0, \\ u(1+, y, t) = \kappa u(0+, y, t), & u(1-, y, t) < 0, \\ u(1+, y, t) = u(1-, y, t), & u(1-, y, t) \geq 0, \\ u(x, 0-, t) = \kappa u(x, 1-, t), & u(x, 0+, t) > 0, \\ u(x, 0-, t) = u(x, 0+, t), & u(x, 0+, t) \leq 0, \\ u(x, 1+, t) = \kappa u(x, 0+, t), & u(x, 1-, t) < 0, \\ u(x, 1+, t) = u(x, 1-, t), & u(x, 1-, t) \geq 0, \end{cases} \quad (25)$$

subject to the computational domain $[0, 1] \times [0, 1]$. The initial data are chosen to be x -dependent in order to

compare with Example 4, while the evolution and feedback treatment are fully two-dimensional. For simplicity, and in order to keep the feedback parameter space one-dimensional, the same feedback parameter κ is used on all four sides of the computational domain.

We compute the numerical results for Cases I and II on a uniform mesh with $N_x = N_y = 200$ and $N_\kappa = 400$, with the initial probability distribution defined on $\kappa \in [-2, 2]$ by $\mathcal{P}(\kappa) = 1/4$. The values of the probability distributions are updated based on the discrete energy

$$\mathcal{L}(\bar{u}) = \Delta x \Delta y \sum_{j=1}^{N_x} \sum_{k=1}^{N_y} \bar{u}_{j,k}^2,$$

and the obtained numerical results are presented in Figure 9. One can see that for the Burgers equation with the boundary conditions defined in (25), the stable domain of the parameter κ depends on the initial conditions, and the stable domains are approximately $(-1.4, 2)$ and $(-2, 1.6)$ for Cases I and II, respectively.

We also plot the three-dimensional numerical results for Cases I and II over time in Figure 10, where one can see that the stable domains are approximately $(-1.4, 2)$ and $(-2, 1.6)$ for the Cases I and II, respectively, which




Figure 9. Example 5: Final probability distributions for Cases I (left) and II (right).




Figure 10. Example 5: Evolution of $\log_{10} \mathcal{L}$ for Cases I (left) and II (right).

further supports the proposed methodology for the two cases. The results show that the method can be applied beyond one-dimensional test problems.

3.3 Stochastic examples

In this section, we consider two stochastic examples to demonstrate that the proposed method works well for stochastic systems. At the same time, the stable domain for the stochastic linear wave equations computed by the proposed method is consistent with the theoretical validations in Chu et al. (2026).

3.3.1 Example 6 – stochastic linear wave equations

In this example, we consider the linear wave equations (17) with the following initial conditions:

$$u^{(1)}(x, 0) = \frac{1}{4} - \frac{1}{2}\xi, \quad u^{(2)}(x, 0) = -\frac{1}{4} + \frac{1}{2}\xi. \quad (26)$$

The boundary conditions are given by

$$\begin{aligned} u^{(1)}(0, t, \xi) &= \kappa u^{(1)}(1, t, \xi), \\ u^{(2)}(1, t, \xi) &= \kappa u^{(2)}(0, t, \xi), \end{aligned} \quad (27)$$

where ξ is the random variable and $\xi \in [-0.5, 0.5]$.

We take the same initial probability distributions of the parameter κ as in Example 1 and compute the numerical results on a uniform mesh with $N_x = 100$, $N_\kappa = 800$, and $N_\xi = 100$. The obtained numerical results are presented in Figure 11. Here, the values of the probability distributions are updated based on the corresponding discrete energy

$$\mathcal{L}(\bar{u}^{(1)}, \bar{u}^{(2)}) = \Delta x \Delta \xi \sum_{j=1}^{N_x} \sum_{k=1}^{N_\xi} \left[\left(u_{j,k}^{(1)} \right)^2 + \left(u_{j,k}^{(2)} \right)^2 \right]. \quad (28)$$

As one can see, the stability region of the boundary control parameter is approximately $(-1, 1)$, which is consistent with the one proved in Chu et al. (2026, Theorem 4.1), which once again demonstrates the validity and robustness of the proposed method.

Remark 3.1: In this example, the numerical solutions of the system (17), (26)–(27) are also computed by the first-order LLF scheme; see Appendix 1.




Figure 11. Example 6: Final probability distributions for Cases I (left) and II (right).

3.3.2 Example 7 – stochastic Burgers equation

In this example, we consider the Burgers equation (23) with the following initial conditions:

$$\text{Case I: } u(x, 0, \xi) = \begin{cases} 0.3 + \xi, & \text{if } x < 0.3, \\ 0.2, & \text{if } 0.3 \leq x \leq 0.7, \\ -0.1, & \text{otherwise,} \end{cases}$$

$$\text{Case II: } u(x, 0, \xi) = \begin{cases} 0.1, & \text{if } x < 0.3, \\ 0.2 + 0.1\xi, & \text{if } 0.3 \leq x \leq 0.7, \\ 0.1, & \text{otherwise.} \end{cases}$$

The boundary conditions are given by

$$\begin{cases} u(0-, t, \xi) = \kappa u(1-, t, \xi), & \text{if } u(0+, t, \xi) > 0, \\ u(0-, t, \xi) = u(0+, t, \xi), & \text{otherwise,} \\ u(1+, t, \xi) = \kappa u(0+, t, \xi), & \text{if } u(1-, t, \xi) < 0, \\ u(1+, t, \xi) = u(1-, t, \xi), & \text{otherwise,} \end{cases}$$

where ξ is the random variable and $\xi \in [-0.5, 0.5]$.

We take the same initial probability distributions as in Example 4 and compute the numerical results for the Cases I and II on a uniform mesh with $N_x = 200$, $N_\kappa = 400$, and $N_\xi = 100$. The values of the probability distributions are updated based on the discrete energy

$$\mathcal{L}(\bar{u}) = \Delta x \Delta \xi \sum_{j=1}^{N_x} \sum_{k=1}^{N_\xi} u_{j,k}^2,$$

and the obtained numerical results are presented in Figure 12. One can see that for the Burgers equation with stochastic initial conditions, the stable domains are similar to the ones reported in Example 4.

3.4 Nonconservative system

In this section, we consider a nonconservative system and show that the stability domain computed by the proposed

method is consistent with the theoretical results in Chu et al. (2026).

3.4.1 Example 8 – linearised Saint-Venant system with source terms

In this example, we consider the boundary damping for the linearised Saint-Venant system with source terms. We take the same setting as in Example 2, but with different equations, which read as

$$\begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_t + \begin{pmatrix} \Lambda_1 & 0 \\ 0 & \Lambda_2 \end{pmatrix} \begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix}_x = - \begin{pmatrix} 0.1 & 0 \\ 0 & 0.1 \end{pmatrix} \begin{pmatrix} u^{(1)} \\ u^{(2)} \end{pmatrix},$$

where $u^{(1)}$ and $u^{(2)}$ are defined by (19).

We compute the numerical results on a uniform mesh with $N_x = 100$ and $N_\kappa = 800$. The values of the probability distributions are updated based on the discrete energy (18), and the obtained numerical results are presented in Figure 13. One can clearly see that the stability region of the boundary control parameter is consistent with the theoretical results in Chu et al. (2026).

3.4.2 Example 9 – linearised stochastic Saint-Venant system with source terms

In this example, we take the same setting as in Example 7, but with the following initial conditions:

$$\delta h(x, 0, \xi) = \frac{1}{2} \sin(\pi x) \left(-\frac{1}{2} + \xi \right),$$

$$\delta v(x, 0, \xi) = \frac{20}{8 + \sin(\pi x) \left(-\frac{1}{2} + \xi \right)} - \frac{5}{2},$$

$$\xi \in \left[-\frac{1}{2}, \frac{1}{2} \right],$$




Figure 12. Example 7: Final probability distributions for Cases I (left) and II (right).




Figure 13. Example 8: Final probability distributions of Case I (left) and II (right).

subject to the boundary conditions

$$\begin{aligned} u^{(1)}(0, t, \zeta) &= \kappa u^{(1)}(1, t, \zeta), \quad \text{and} \\ u^{(2)}(1, t, \zeta) &= \kappa u^{(2)}(0, t, \zeta), \end{aligned}$$

where ζ is the random variable and $\zeta \in [-0.5, 0.5]$.

We compute the numerical results on a uniform mesh with $N_x = 100$, $N_\kappa = 800$, and $N_\zeta = 200$. The values of the probability distributions are updated based on the discrete energy (28), and the obtained numerical results are presented in Figure 14. One can clearly see that the stability region of the boundary control parameter is approximately $(-1, 1)$, which is consistent with the theoretical results in Chu et al. (2026).

3.5 Second-order discretisation

We next employ a second-order semi-discrete LLF finite-volume scheme with piecewise linear reconstruction and SSP-RK3 time integration; see Appendix 2. The resulting stability domains coincide with those obtained by the first-order LLF scheme.

3.5.1 Example 10 – Burgers equation

In this example, we take the same setting as in Example 4, but compute the numerical results using the second-order LLF scheme. The obtained numerical results are plotted in Figure 15, where one can see that, as in the previous example, the computed stability domains coincide with those in Example 4.

We also plot the numerical results for Cases I and II over time in Figure 16, which validate the stable domains of the two cases for the studied system.

3.6 Feedback control of two parameters

In this section, we consider a more complex system – heat transfer in laser powder bed fusion (LPBF) – to show that the proposed method can give the stable domain of complex systems.

3.6.1 Example 11 – temperature field development in laser powder bed fusion with feedback power regulation

In this last example, we consider the evolution of the thermal field during a single-track scanning process in laser




Figure 14. Example 9: Final probability distributions of Case I (left) and II (right).




Figure 15. Example 10: Final probability distributions of Case I (left) and II (right).

powder bed fusion (LPBF). LPBF is an additive manufacturing process in which a laser beam heats the powder-bed substrate and locally fuses the powder; further details of the process can be found in Chowdhury et al. (2022). Figure 17 illustrates the single-track LPBF process considered in this study. One can see that the process is carried out on a cuboidal workpiece with dimensions

$$(l_x, l_y, l_z) = (1.2 \text{ mm}, 0.45 \text{ mm}, 0.35 \text{ mm}).$$

During scanning, the laser beam centre moves at a constant velocity $v = 1 \text{ m/s}$, with $(x_L(t), y_L(t)) = (vt, 0)$. The laser has a spot radius $R_L = 25 \mu\text{m}$ and a Gaussian intensity distribution, with its power regulated by a feedback control law.

For moderate laser energy input, heat transfer in the process is predominantly governed by thermal conduction. The temperature field therefore satisfies the heat




Figure 16. Example 10: Numerical results of Cases I (left) and II (right).




Figure 17. Example 11: LPBF process and defined domains at the reference state for power control and Lyapunov function definition.

conduction equation

$$T_t(x, y, z, t) = \alpha (T_{xx}(x, y, z, t) + T_{yy}(x, y, z, t) + T_{zz}(x, y, z, t)) + P(t)f_L(x - x_L(t), y - y_L(t), z), \quad (29)$$

where α denotes the thermal diffusivity, $P(t)$ is the laser power input, and f_L represents the volumetric laser power distribution relative to the moving laser position. The laser power $P(t)$ is determined by the feedback control law

$$P(t) = P_{\text{ref}} + \kappa \alpha_0(t) \sqrt{\frac{B(t)}{A}}, \quad (30)$$

where $P_{\text{ref}} = 150$ W is the reference laser power and κ is the feedback gain. The quantities $\alpha_0(t)$, $B(t)$, and A are defined in terms of the relative coordinates $(x', y') = (x - x_L(t), y - y_L(t))$ by

$$\alpha_0(t) = \frac{1}{2} \text{sgn} \left(\int_{(x', y') \in \Gamma_{\text{ref}}^+} (T(vt_{\text{ref}} + x', y', 0, t_{\text{ref}}) - T(vt + x', y', 0, t)) \, dS \right),$$

$$B(t) = \int_{(x', y') \in \Gamma_{\text{ref}}^+} (T_x(vt_{\text{ref}} + x', y', 0, t_{\text{ref}}) - T_x(vt + x', y', 0, t))^2 + (T_y(vt_{\text{ref}} + x', y', 0, t_{\text{ref}}) - T_y(vt + x', y', 0, t))^2 \, dS,$$

and

$$A = \int_{\Gamma_{\text{ref}}^-} \nu \, dS.$$

The subscript 'ref' denotes quantities evaluated at the reference state, which corresponds to a stabilised thermal field in the relative coordinate system (x', y') . This reference state is generated by applying the constant power input $P(t) \equiv P_{\text{ref}}$ for a sufficiently long time after the onset of scanning; in this study, the reference time is taken as $t_{\text{ref}} = 800$ μ s.

The domains Γ_{ref}^+ , Γ_{ref}^- , and Ω_{ref} are illustrated in Figure 17. The melting interface on the top surface, Γ_{ref}^+ , is defined as

$$\Gamma_{\text{ref}}^+ = \{(x', y') \mid T(vt_{\text{ref}} + x', y', 0, t_{\text{ref}}) = T_m \text{ and } T_t(x', y', 0, t_{\text{ref}}) \geq 0\},$$

where $T_m = 1723$ K is the melting temperature. The line segment Γ_{ref}^- separates the solid-liquid interface $T = T_m$ into melting and solidification regions and is defined as

$$\Gamma_{\text{ref}}^- = \{(x', y') \mid x' = \min(x'' \in (x'', y'') \in \Gamma_{\text{ref}}^+), \min(y'' \in (x'', y'') \in \Gamma_{\text{ref}}^+) \leq y' \leq \max(y'' \in (x'', y'') \in \Gamma_{\text{ref}}^+)\}.$$

The domain Ω_{ref} is the region on the top surface enclosed by $\Gamma_{\text{ref}}^+ \cup \Gamma_{\text{ref}}^-$. The volumetric laser heat source is given by

$$f_L(x - x_L(t), y - y_L(t), z) = \frac{2\mathcal{A}d_{\text{opt}}}{\pi R_L^2} \exp\left(-\frac{2((x - vt)^2 + y^2)}{R_L^2} + \frac{z}{d_{\text{opt}}}\right),$$

where $\mathcal{A} = 0.27$ is the laser absorptivity and $d_{\text{opt}} = 34$ μ m is the optical penetration depth.

The initial condition is set as a uniform temperature distribution $T(x, y, z, 0) = 300$ K, subject to the specified following boundary conditions. The bottom face is maintained at a constant temperature $T(x, y, -l_z, t) = 300$ K, the four lateral faces are assumed to be adiabatic $T_x(x, 0, z, t) = T_x(x, l_x, z, t) = T_y(x, \pm 0.5l_y, z, t) = 0$, and the top surface is subject to convective and radiative heat losses to the surrounding atmosphere

$$\begin{aligned} k T_z(x, y, 0, t) \\ = - \left(h (T(x, y, 0, t) - T_\infty) \right. \\ \left. + \varepsilon \sigma (T(x, y, 0, t)^4 - T_\infty^4) \right), \end{aligned}$$

where $k = 20.9 \text{ W m}^{-1} \text{ K}^{-1}$ is the thermal conductivity, $h = 20 \text{ W m}^{-2} \text{ K}^{-1}$ is the convective heat transfer coefficient, $T_\infty = 300$ K is the ambient temperature, $\varepsilon = 0.36$ is the emissivity, and σ is the Stefan–Boltzmann constant.

The resulting initial-boundary value problem is solved numerically using a finite-difference method on a uniform mesh with $(N_x, N_y, N_z) = (128, 48, 32)$. Time integration is performed using a Runge–Kutta scheme with a time step $\Delta t = 40$ ns. The objective of the feedback power regulation is to control the Lyapunov-type indicator

$$\begin{aligned} L(t) = \int_{(x', y') \in \Omega_{\text{ref}}} & (T_x(vt_{\text{ref}} + x', y', z, t_{\text{ref}}) \\ & - T_x(vt + x', y', z, t))^2 \\ & + (T_y(vt_{\text{ref}} + x', y', z, t_{\text{ref}}) \\ & - T_y(vt + x', y', z, t))^2 dx' dy', \end{aligned}$$

which quantifies the discrepancy between the temperature gradients in the x - and y -directions over a moving domain that maintains a fixed relative position with respect to the laser spot. We then apply the Bayesian update procedure of Section 2.2 (Algorithm 1), using $L(t)$ as the observed indicator, to update the discrete probability mass function over the chosen parameter grid.

In this example, we consider a two-parameter setting in which the Bayesian damping factor α in (29) and the feedback gain κ in (30) are treated as the control parameters; thus, the Bayesian procedure updates the joint distribution of (κ, α) , as illustrated in Figure 18.

To further quantify the decay behaviour of the indicator, we fit the discrete Lyapunov functions from the sub-region $[0, 1e - 4] \times [0, 3.3e - 4]$ by a power-law model $L(t) \approx C t^{-a}$ by a nonlinear least-squares procedure, and record the fitted parameters (a, C) . The corresponding top-view plots of the fitted values are shown in Figure 19.




Figure 18. Example 11: Prior and posterior (purple colour) probability distributions of the feedback parameters.

To assess the fit quality, we compute the standard deviation

$$e_{\text{deviation}} = \sqrt{\frac{1}{N} \sum_{i=1}^N (L_i - \bar{L})^2},$$

where $L_i = L(t_i)$ and $\bar{L} = \frac{1}{N} \sum_{i=1}^N L_i$. The values of $e_{\text{deviation}}$ and $\log_{10}(e_{\text{deviation}})$ are plotted in Figure 20.

Finally, Figure 21 shows thresholded regions (black) where $e_{\text{deviation}}$ falls below prescribed tolerances, providing an additional diagnostic for identifying parameter regimes that exhibit a consistent decay trend.

These results indicate that the proposed algorithm remains effective in a two-parameter system, with κ and α treated as the unknown parameters to be identified via the Bayesian update.

4. Conclusions

In this paper, we have introduced a Bayesian feedback framework for identifying stabilising boundary controls in hyperbolic balance laws. The core idea is to iteratively update a prior over control parameters using solution-driven diagnostics (Lyapunov functionals or discrete energies), coupled with a damping and normalisation step that concentrates probability on stabilising regimes. This yields an efficient, nonintrusive post-processing layer that can be placed atop standard finite-volume solvers. On linear benchmarks (advection/wave equations and the linearised Saint-Venant system), the method reproduces analytically known stability domains, including mixed boundary couplings. On nonlinear and stochastic tests, including the nonlinear Saint-Venant system, one- and two-dimensional Burgers equations, and Burgers equations with random inputs, the method




Figure 19. Example 11: Least-squares power-law fit parameters: fitted decay exponent α (left) and fitted prefactor C (right).




Figure 20. Example 11: Fit-quality diagnostics for the power-law model: the standard deviation $e_{\text{deviation}}$ (left) and $\log_{10}(e_{\text{deviation}})$ (right).




Figure 21. Example 11: Thresholded regions (black) where the power-law fit error satisfies $e_{\text{deviation}} < 10^{-6}$ (top left), $e_{\text{deviation}} < 10^{-7}$ (top right), $e_{\text{deviation}} < 10^{-8}$ (bottom left), and $e_{\text{deviation}} < 10^{-9}$ (bottom right).

remains robust and reveals the dependence of stabilising regions on the initial data and boundary feedback configuration. In particular, the 2-D Burgers example demonstrates that the Bayesian update can be applied to a multidimensional balance law with feedback boundary conditions imposed in both spatial directions. Extensions to a second-order LLF discretisation and the evolution of the thermal field during a single-track scanning process in laser powder bed fusion indicate that the approach is scheme-independent and applicable beyond purely conservative models. Future work will focus on a rigorous analysis of the probability iteration, including posterior concentration on the stabilising set and its relation to decay rates of the indicator, and on extensions to multi-parameter and constrained boundary controls, as well as generalisations to networks and multidimensional settings.

Author contributions

CRedit: **Markus Bambach**: Conceptualization, Funding acquisition, Investigation, Resources, Supervision; **Shaoshuai Chu**: Conceptualization, Data curation, Formal analysis, Methodology, Project administration, Software, Visualization, Writing – original draft, Writing – review & editing; **Michael Herty**: Conceptualization, Funding acquisition, Investigation, Project administration, Resources, Supervision, Writing – original draft, Writing – review & editing; **Yunong Lin**: Conceptualization, Data curation, Investigation, Software, Visualization, Writing – original draft

Disclosure statement

No potential conflict of interest was reported by the authors.

Funding

The work of S. Chu and M. Herty was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – SPP 2410 Hyperbolic Balance Laws in Fluid Mechanics: Complexity, Scales, Randomness (CoScaRa) within the Project(s) HE5386/26-1 (Numerische Verfahren für gekoppelte Mehrskalenprobleme, 525842915) and (Zufällige kompressible Euler Gleichungen: Numerik und ihre Analysis, 525853336) HE5386/27-1, and the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – SPP 2183: Eigenschaftsgeregelte Umformprozesse with the Project(s) HE5386/19-2,19-3 Entwicklung eines flexiblen isothermen Reckschmiedeprozesses für die eigenschaftsgeregelte Herstellung von Turbinenschaufeln aus Hochtemperaturwerkstoffen (424334423). Support through HE5386/33-1 Control of Interacting Particle Systems, and Their Mean-Field, and Fluid-Dynamic Limits (560288187) and HE5386/34-1 Partikelmethode für unendlich dimensionale Optimierung (561130572) is acknowledged.

Data and software availability

The data that support the findings of this study and FORTRAN/Python codes developed by the authors and used to obtain all of the presented numerical results are available from the corresponding author upon reasonable request.

References

- Banda, M. K., & Herty, M. (2013). Numerical discretization of stabilization problems with boundary controls for systems of hyperbolic conservation laws. *Mathematical Control and Related Fields*, 3(2), 121–142. <https://doi.org/10.3934/mcrf.2013.3.121>
- Banda, M. K., & Weldegiyorgis, G. Y. (2020). Numerical boundary feedback stabilisation of non-uniform hyperbolic systems of balance laws. *International Journal of Control*, 93(6), 1428–1441. <https://doi.org/10.1080/00207179.2018.1509133>
- Bardos, C., le Roux, A. Y., & Nédélec, J.-C. (1979). First order quasilinear equations with boundary conditions. *Communications in Partial Differential Equations*, 4(9), 1017–1034. <https://doi.org/10.1080/03605307908820117>
- Bastin, G., & Coron, J. M. (2016). *Stability and boundary stabilization of 1-D hyperbolic systems*, Progress in Nonlinear Differential Equations and Their Applications (Vol. 88). Birkhäuser/Springer.
- Bastin, G., Haut, B., Coron, J.-M., & D'Andréa-Novel, B. (2007). Lyapunov stability analysis of networks of scalar conservation laws. *Networks and Heterogeneous Media*, 2(4), 751–759. <https://doi.org/10.3934/nhm.2007.2.751>
- Chowdhury, S., Yadaiah, N., Prakash, C., Ramakrishna, S., Dixit, S., Gupta, L. R., & Buddhi, D. (2022). Laser powder bed fusion: A state-of-the-art review of the technology, materials, properties & defects, and numerical modelling. *Journal of Materials Research and Technology*, 20, 2109–2172. <https://doi.org/10.1016/j.jmrt.2022.07.121>
- Chu, S., Herty, M., & Kurganov, A. (2026). Numerical analysis of stabilization for random hyperbolic systems of conservation laws. *International Journal of Control*, 99(5), 1545–1560.
- Coron, J.-M. (2007). *Control and nonlinearity*, Mathematical Surveys and Monographs (Vol. 136). American Mathematical Society.
- Coron, J.-M., Bastin, G., & D'Andréa-Novel, B. (2008). Dissipative boundary conditions for one-dimensional nonlinear hyperbolic systems. *SIAM Journal on Control and Optimization*, 47(3), 1460–1498. <https://doi.org/10.1137/070706847>
- Coron, J.-M., d'Andréa Novel, B., & Bastin, G. (1999). A Lyapunov approach to control irrigation canals modeled by Saint-Venant equations. In *ECC Karlsruhe*.
- Coron, J.-M., D'Andréa-Novel, B., & Bastin, G. (2007). A strict Lyapunov function for boundary control of hyperbolic systems of conservation laws. *IEEE Transactions on Automatic Control*, 52(1), 2–11. <https://doi.org/10.1109/TAC.2006.887903>
- de Halleux, J., Prieur, C., Coron, J.-M., D'Andréa-Novel, B., & Bastin, G. (2003). Boundary feedback control in networks of open channels. *Automatica*, 39(8), 1365–1376. [https://doi.org/10.1016/S0005-1098\(03\)00109-2](https://doi.org/10.1016/S0005-1098(03)00109-2)

- Diagne, A., Bastin, G., & Coron, J.-M. (2012). Lyapunov exponential stability of 1-D linear hyperbolic systems of balance laws. *Automatica*, 48(1), 109–114. <https://doi.org/10.1016/j.automatica.2011.09.030>
- Diagne, A., Diagne, M., Tang, S., & Krstic, M. (2017). Backstepping stabilization of the linearized Saint-Venant-Exner model. *Automatica*, 76, 345–354. <https://doi.org/10.1016/j.automatica.2016.10.017>
- Gottlieb, S., Ketcheson, D., & Shu, C.-W. (2011). *Strong stability preserving Runge-Kutta and multistep time discretizations*. World Scientific Publishing Co. Pte. Ltd..
- Gottlieb, S., Shu, C.-W., & Tadmor, E. (2001). Strong stability-preserving high-order time discretization methods. *SIAM Review*, 43(1), 89–112. <https://doi.org/10.1137/S003614450036757X>
- Herty, M., & Yong, W.-A. (2016). Feedback boundary control of linear hyperbolic systems with relaxation. *Automatica*, 69, 12–17. <https://doi.org/10.1016/j.automatica.2016.02.016>
- Kurganov, A., & Tadmor, E. (2000). New high-resolution central schemes for nonlinear conservation laws and convection-diffusion equations. *Journal of Computational Physics*, 160(1), 241–282. <https://doi.org/10.1006/jcph.2000.6459>
- Li, T. (2005). Exact controllability of quasilinear hyperbolic equations (or systems). *Applied Mathematics-A Journal of Chinese Universities Series A*, 20(2), 127–146. <https://doi.org/10.1007/s11766-005-0045-1>
- Li, T., & Rao, B. (2009). Exact controllability for first order quasilinear hyperbolic systems with vertical characteristics. *Acta Mathematica Scientia Series B (English Edition)*, 29(4), 980–990. [https://doi.org/10.1016/S0252-9602\(09\)60082-5](https://doi.org/10.1016/S0252-9602(09)60082-5)
- Li, T., Rao, B., & Wang, Z. (2008). Controllabilité observabilité unilatérales de systèmes hyperboliques quasi-linéaires. *Comptes Rendus Mathématique*, 346(19-20), 1067–1072. <https://doi.org/10.1016/j.crma.2008.09.004>
- Li, T., & Yu, L. (2003). Exact controllability for first order quasilinear hyperbolic systems with zero eigenvalues. *Chinese Annals of Mathematics*, 24(04), 415–422. <https://doi.org/10.1142/S0252959903000414>
- Lie, K.-A., & Noelle, S. (2003). On the artificial compression method for second-order nonoscillatory central difference schemes for systems of conservation laws. *SIAM Journal on Scientific Computing*, 24(4), 1157–1174. <https://doi.org/10.1137/S1064827501392880>
- Meurer, T. (2013). *Control of higher-dimensional PDEs*, Communications and Control Engineering Series, Springer.
- Nessyahu, H., & Tadmor, E. (1990). Non-oscillatory central differencing for hyperbolic conservation laws. *Journal of Computational Physics*, 87(2), 408–463. [https://doi.org/10.1016/0021-9991\(90\)90260-8](https://doi.org/10.1016/0021-9991(90)90260-8)
- Rusanov, V. V. (1961). The calculation of the interaction of non-stationary shock waves with barriers. *Žhurnal Vyčislitel'noi Matematiki i Matematicheskoi Fiziki*, 1, 267–279.
- Sweby, P. K. (1984). High resolution schemes using flux limiters for hyperbolic conservation laws. *SIAM Journal on Numerical Analysis*, 21(5), 995–1011. <https://doi.org/10.1137/0721062>
- Xu, C.-Z., & Sallet, G. (2002). Exponential stability and transfer functions of processes governed by symmetric hyperbolic systems. *ESAIM: Control, Optimisation and Calculus of Variations*, 7, 421–442.

Appendices

Appendix 1. First-order local Lax–Friedrichs scheme for stochastic hyperbolic systems

We consider the first-order LLF finite-volume scheme for the stochastic system. Assume the computational domain is covered with uniform cells $C_{j,k} := [x_{j-\frac{1}{2}}, x_{j+\frac{1}{2}}] \times [\xi_{k-\frac{1}{2}}, \xi_{k+\frac{1}{2}}]$ with $x_{j+\frac{1}{2}} - x_{j-\frac{1}{2}} \equiv \Delta x$ and $\xi_{k+\frac{1}{2}} - \xi_{k-\frac{1}{2}} \equiv \Delta \xi$ centred at $(x_j, \xi_k) = ((x_{j-\frac{1}{2}} + x_{j+\frac{1}{2}})/2, (\xi_{k-\frac{1}{2}} + \xi_{k+\frac{1}{2}})/2)$, $j = 1, \dots, N_x$, $k = 1, \dots, N_\xi$ and the cell average values

$$\bar{U}_{j,k}(t) \approx \frac{1}{\Delta x \Delta \xi} \int_{C_{j,k}} U(x, t) dx d\xi$$

are available at a certain time level t .

The computed cell averages $\bar{U}_{j,k}$ of the 1-D system (1) are evolved in time by the first-order LLF scheme:

$$\bar{U}_{j,k}^{n+1} = \bar{U}_{j,k}^n - \frac{\Delta t}{\Delta x} \left(\mathcal{F}_{j+\frac{1}{2},k} - \mathcal{F}_{j-\frac{1}{2},k} \right) + \Delta t S(\bar{U}_{j,k}^n),$$

where $\mathcal{F}_{j+\frac{1}{2},k}$ stands for the finite-volume numerical flux

$$\mathcal{F}_{j+\frac{1}{2},k} = \frac{1}{2} \left(F(\bar{U}_{j,k}) + F(\bar{U}_{j+1,k}) \right) - \frac{\alpha_{j+\frac{1}{2},k}}{2} (\bar{U}_{j+1,k} - \bar{U}_{j,k}),$$

with the local speeds of propagation estimated using the eigenvalues $\lambda_1(\mathcal{A}) \leq \dots \leq \lambda_d(\mathcal{A})$ of the matrix $\mathcal{A} = \frac{\partial F}{\partial U}$:

$$\alpha_{j+\frac{1}{2},k} = \max \left\{ |\lambda_1(\bar{U}_{j,k})|, |\lambda_1(\bar{U}_{j+1,k})|, \dots, |\lambda_d(\bar{U}_{j,k})|, |\lambda_d(\bar{U}_{j+1,k})| \right\}.$$

The time step Δt is computed by the CFL condition, $\Delta t = \text{CFL} \frac{\Delta x}{\max_{j,k} \{\alpha_{j+\frac{1}{2},k}\}}$.

Appendix 2. Second-order local Lax–Friedrichs scheme

In the second-order LLF scheme, the cell averages $\bar{U}_j$ of the 1-D system (1) are evolved in time by solving the following system of ODEs:

$$\frac{d\bar{U}_j}{dt} = - \frac{\mathcal{F}_{j+\frac{1}{2}} - \mathcal{F}_{j-\frac{1}{2}}}{\Delta x} + S(\bar{U}_j), \quad (\text{A1})$$

where $\mathcal{F}_{j+\frac{1}{2}}$ stand for the second-order finite-volume numerical fluxes

$$\mathcal{F}_{j+\frac{1}{2}} = \frac{1}{2} \left(F(U_{j+\frac{1}{2}}^-) + F(U_{j+\frac{1}{2}}^+) \right) - \frac{\alpha_{j+\frac{1}{2}}}{2} \left(U_{j+\frac{1}{2}}^+ - U_{j+\frac{1}{2}}^- \right),$$

with the local speeds of propagation estimated using the eigenvalues $\lambda_1(\mathcal{A}) \leq \dots \leq \lambda_d(\mathcal{A})$ of the matrix $\mathcal{A} = \frac{\partial F}{\partial U}$:

$$\alpha_{j+\frac{1}{2}} = \max \left\{ |\lambda_1(U_{j+\frac{1}{2}}^-)|, |\lambda_1(U_{j+\frac{1}{2}}^+)|, \dots, |\lambda_d(U_{j+\frac{1}{2}}^-)|, |\lambda_d(U_{j+\frac{1}{2}}^+)| \right\}.$$

Here, $U_{j+\frac{1}{2}}^\pm$ are the one-sided point values of U at the cell interface $x = x_{j+\frac{1}{2}}$, estimated using a piecewise linear interpolant

$$\tilde{U}(x) = \bar{U}_j + (U_x)_j(x - x_j), \quad x \in C_j, \quad (\text{A2})$$

which leads to

$$\mathbf{U}_{j+\frac{1}{2}}^- = \bar{\mathbf{U}}_j + \frac{\Delta x}{2}(\mathbf{U}_x)_j, \quad \mathbf{U}_{j+\frac{1}{2}}^+ = \bar{\mathbf{U}}_{j+1} - \frac{\Delta x}{2}(\mathbf{U}_x)_{j+1}. \quad (\text{A3})$$

In order to ensure that the reconstruction (A2)–(A3) is non-oscillatory, one needs to compute the slopes $(\mathbf{U}_x)_j$ in (A2) with the help of a nonlinear limiter. In all of the numerical experiments reported in Section 3, we have used a generalised minmod limiter (Lie & Noelle, 2003; Nessyahu & Tadmor, 1990; Sweby, 1984):

$$(\mathbf{U}_x)_j = \min\text{mod}\left(\theta \frac{\bar{\mathbf{U}}_j - \bar{\mathbf{U}}_{j-1}}{\Delta x}, \frac{\bar{\mathbf{U}}_{j+1} - \bar{\mathbf{U}}_{j-1}}{2\Delta x}, \theta \frac{\bar{\mathbf{U}}_{j+1} - \bar{\mathbf{U}}_j}{\Delta x}\right), \quad \theta \in [1, 2], \quad (\text{A4})$$

applied in a component-wise manner. Here, the minmod function is defined as

$$\min\text{mod}(z_1, z_2, \dots) := \begin{cases} \min_j\{z_j\} & \text{if } z_j > 0 \quad \forall j, \\ \max_j\{z_j\} & \text{if } z_j < 0 \quad \forall j, \\ 0 & \text{otherwise.} \end{cases}$$

The parameter θ in (A4) is used to control the amount of numerical viscosity present in the resulting scheme, and larger values of θ correspond to sharper but, in general, more oscillatory reconstructions. In this paper, we use $\theta = 1.3$.

Finally, we numerically integrate the ODE systems (A1) by the three-stage third-order strong stability preserving Runge-Kutta (SSP RK3) method (see, e.g. Gottlieb et al., 2011, 2001), and the time step Δt is computed by the CFL condition, $\Delta t = \text{CFL} \frac{\Delta x}{\max_j\{a_{j+\frac{1}{2}}\}}$.