

Exploring DDoS Attack and New Security Technics

Shaoun Chandra Shill

BRAC University

shaoun.chandra.shill@g.bracu.ac.bd

Fahim Arshadur Rouf

BRAC University

fahim.arshadur.rouf@g.bracu.ac.bd

Kazi Tanvir

BRAC University

kazi.tanvir@g.bracu.ac.bd

Tuhin Ahmed

BRAC University

tuhin.ahmed@g.bracu.ac.bd

Abstract—As our reliance on digital infrastructure and online services grows, the cybersecurity landscape faces new challenges. These issues are characterized by sophisticated cyber threats such as Distributed Denial of Service (DDoS) attacks. The strategies, goals, and impacts of DDoS attacks on targeted systems are discussed in this paper’s in-depth examination of the complexities of these attacks. In the first section, we present a complete

review of DDoS attacks, including their history, evolution, and the many techniques employed by malicious actors. We closely track developing tendencies in DDoS assaults, such as the use of IoT devices and the increasing ubiquity of ransomware motivations. The second section, which focuses on the dynamic area of

cybersecurity defenses, explores the limits that have encouraged the development of unique security solutions while closely scrutinizing conventional mitigation tactics. We investigate cutting-edge approaches such as artificial intelligence, machine learning, and behavioral analysis to see how they can improve DDoS attack detection and mitigation. This study also investigates threat

intelligence, information-sharing platforms, and cooperative defense mechanisms as methods of strengthening cybersecurity countermeasures against DDoS attacks. Case studies and real-world examples show how effective these cutting-edge security methods are at thwarting attackers and reducing downtime. Finally, we consider the future trajectory of DDoS attacks and

the corresponding advances in security protocols. Investigating blockchain technology, decentralized defenses, and the adoption of quantum-resistant encryption technologies can provide insight into the future frontier of cybersecurity. By combining current

research, practical insights, and forward-thinking perspectives, this study aims to equip cybersecurity professionals, researchers, and decision-makers with a full understanding of DDoS attacks and the ever-evolving array of mitigation strategies. This understanding promotes the proactive and robust safeguarding of digital ecosystems.

Index Terms—DDoS Attack, LSTM Model, KNN Model

I. INTRODUCTION

The widespread use of technology has resulted in previously unheard-of levels of connection and ease in the rapidly growing sphere of cyberspace. However, this interconnectedness has introduced a severe risk in the form of cyberattacks, with Distributed Denial of Service (DDoS) attacks becoming an increasingly disruptive and persistent menace. DDoS attacks involve flooding a target system, network, or service with so much traffic that it is rendered inoperable for authorized users. Given businesses’, governments’, and individuals’ increased reliance on digital platforms, it is vital to understand and

manage the risks associated with denial-of-service (DDoS) attacks.

The research goes thoroughly into the complex realm of DDoS attacks, investigating their causes, methods, and impacts on many types of targets. It also looks at how cybersecurity is evolving and how traditional protection tactics are regularly tested. To stay ahead of malicious actors, researchers and security specialists are constantly devising new and improved approaches.

The explorative voyage is divided into two main chapters. The first chapter digs into the inner workings of denial-of-service (DDoS) attacks, studying and evaluating their potential effects while categorizing the many types, from volumetric to application layer attacks. Creating effective defenses necessitates a deep understanding of cyber attackers’ techniques.

The second chapter shifts the spotlight to emerging security techniques that aim to fortify digital ecosystems against DDoS threats. Advances in artificial intelligence, machine learning, blockchain, and other cutting-edge technologies are explored for their potential to enhance cyber resilience. Moreover, the exploration scrutinizes collaborative efforts within the cybersecurity community, as the battle against DDoS attacks requires a united front.

As we embark on this exploration, it becomes clear that the interplay between cyber attackers and defenders is a dynamic and perpetual dance. By gaining insights into the intricate details of DDoS attacks and staying abreast of the latest security innovations, individuals and organizations can better navigate the digital landscape and fortify themselves against the ever-present threat of cyber disruptions.

II. BACKGROUND STUDY

A. Historical Evolution of DDoS Attacks

DDoS attacks, or distributed denial-of-service attacks, have evolved dramatically since the internet’s early days. In 1996, the United States Air Force’s website was the target of the first known DDoS attack, which involved hackers flooding the site with traffic to render it unusable [1]. DDoS attacks have proliferated and become more sophisticated since then, employing a variety of methods to disrupt the functionality of the systems they are intended to affect.

The following are examples of notable DDoS attacks that have had a significant impact on cybersecurity:

- The Mirai botnet attack, which targeted the websites of DynDNS, a major domain name provider, and caused

widespread internet outages by utilizing a large botnet of compromised Internet of Things (IoT) devices, occurred in 2016 [2].

- The GitHub attack of 2015: This attack used a technique known as HTTP slow-loris to bombard GitHub's servers with sluggish requests, causing the service to be unavailable for several days [3].
- The 2001 Code Red worm attack, which took advantage of a flaw in Microsoft IIS web servers, severely harmed websites and internet infrastructure [4].

These attacks show how DDoS attacks are constantly evolving and how dangerous they have become for businesses of all sizes.

B. Motivations and Targets

DDoS attacks are motivated by a variety of factors, including:

- Hacktivism: It is the use of denial-of-service (DDoS) attacks to further political or social causes, typically against websites or organizations perceived as enemies.
- Financial gain: Cybercriminals may use DDoS attacks to extort money from organizations by threatening to continue the attack until a ransom is paid.
- Industrial espionage: Businesses may use DDoS attacks to sabotage competitors' businesses and gain an unfair competitive advantage.
- DDoS attacks are a type of cyberwarfare that governments can use to disrupt the operation of critical infrastructure or official websites.

DDoS attacks can have a wide range of consequences for a variety of organizations, including:

- DDoS attacks can cause extensive damage and financial loss to critical infrastructure such as transportation networks, energy grids, and financial markets.
- Financial institutions are vulnerable to DDoS attacks, which can disrupt online banking operations and cause losses.
- DDoS attacks on government websites and services could prevent citizens from accessing information and services.
- DDoS attacks can be directed at online businesses, causing disruptions to their websites and operations, as well as monetary losses and reputational damage.

C. Anatomy of DDoS Attacks

DDoS attacks are a serious threat in today's digital world that can disrupt online services and result in significant financial losses. To effectively counter these attacks, it is critical to have a thorough understanding of their various types and underlying mechanisms [5].

1) *Volumetric Attacks*:: Volumetric DDoS attacks flood the target system with so much traffic that it is unable to process valid requests and thus becomes inoperable. The primary goal of these attacks is to overwhelm the capacity of servers or the network, which frequently results in service disruptions [6]. The following are examples of typical volumetric attacks:

- UDP Floods: The goal of this attack is to flood the target network with a large number of UDP packets with forged source IP addresses, consuming bandwidth [7].
- SYN Floods: Attackers exploit the TCP three-way handshake by sending SYN packets before the connection is established, consuming server resources and blocking valid connections [8].
- ICMP (Ping) Floods: This method sends a large number of ping requests using spoof IP addresses, overwhelming the target system, consuming resources and slowing response time [9].

2) *Protocol Based Attacks*: Protocol-based DDoS attacks seek to exploit specific flaws in network protocols, putting the target system through constant processing or depleting its resources [10]. These attacks frequently involve sending erroneous packets or exceeding the allowed amount or speed of traffic. Here are a few examples of protocol-based attacks:

- NTP Amplification: Attackers use spoof requests to trick NTP servers into sending responses that are significantly larger than the initial request size, which is then sent to the target [11].
- DNS Amplification: Similar to NTP amplification, this attack takes advantage of DNS server flaws to trick them into sending large responses to the target based on forged requests [12].
- SSDP Amplification: When UPnP-enabled devices receive forged SSDP discovery requests, they are prompted to respond with lengthy messages to the target, increasing attack traffic volume [13].

3) *Application Layer Attacks*: DDoS attacks on applications and services target specific flaws in order to impair their functionality and deplete their resources [14]. These attacks typically involve sending a large number of HTTP requests or exploiting flaws specific to a specific application. Application-layer attacks include, for example:

- HTTP Floods: These attacks involve bombarding a web server with a large number of HTTP requests, such as GET or POST, causing its resources to become overloaded and causing service interruptions [15].
- Slowloris attacks: These attacks occur when partial HTTP requests are sent and connections are kept open for an extended period, wearing down server resources and reducing responsiveness [16].
- Zero-Day Attacks: Before developers have a chance to address the issue, attackers may be able to launch devastating DDoS attacks by exploiting previously unknown vulnerabilities in applications or services [17].

Every type of DDoS attack targets a different weakness and exploits it differently. It is critical to understand the mechanics of these attacks to develop effective mitigation strategies and protect critical online services from disruption.

III. RELATED WORKS

Numerous studies have delved into the historical evolution of DDoS attacks, analyzing notable incidents and the

shifting motivations behind these cyber threats. Research in this domain has extensively classified various DDoS attack vectors, including volumetric, protocol-based, and application-layer attacks, providing a nuanced understanding of the tactics employed by malicious actors. On the defensive front, a myriad of studies explores traditional mitigation strategies such as traffic filtering and load balancing, while others delve into cutting-edge technologies such as artificial intelligence, machine learning, and blockchain, showcasing the ongoing efforts to fortify cyber defenses. Collaborative initiatives within the cybersecurity community, encompassing threat intelligence sharing and joint research projects, underscore the importance of a unified front against the evolving threat landscape. Furthermore, legal and ethical considerations are increasingly gaining attention, addressing the implications of DDoS research and mitigation efforts within the framework of existing cybersecurity laws. A paper titled “DDoS Attack Detection Method Based on Improved KNN With the Degree of DDoS Attack in Software-Defined Networks” discusses a method to detect DDoS attacks using an improved K-Nearest Neighbors (KNN) algorithm. The method takes into account the degree of DDoS attack to identify the threat within Software-Defined Networks (SDN). The paper proposes two methods: one that uses the degree of DDoS attack and another that employs the improved KNN algorithm based on Machine Learning (ML) to detect DDoS attacks. The results from theoretical analysis and experiments on datasets indicate that these methods can detect DDoS attacks more effectively compared to other methods[18]. Another paper titled “Quick Suppression of DDoS Attacks by Frame Priority Control in IoT Backhaul With Construction of Mirai-Based Attacks” proposes a novel system to suppress DDoS attacks in IoT networks. The system significantly reduces the discarding of normal traffic by controlling the priority of frames in the network. It was shown to prevent the discarding of normal traffic within a few seconds when attack traffic was generated, and even faster, within 30 milliseconds, when using Mirai-based DDoS attack traffic. The system also integrates various vendors’ products to autonomously block attack traffic at the network’s entrance points[19]. On the other paper titled “DDoS Attack Mitigation Based on Traffic Scheduling in Edge Computing- Enabled TWDM-PON” provides a detailed investigation of the proposed algorithm. The paper also highlights the integration of Edge Computing (EC) and TWDM-PON, which can satisfy the QoS requirements of delay-sensitive applications by providing storage, processing, and caching capabilities at the network edge[20].

IV. METHODOLOGY

V. RESULT ANALYSIS

VI. CONCLUSION

We have presented a way to the DDos attack in the internet. It included various model testing and result analysis. Our approach reflects that LSTM and KNN model construction

performs almost identically with KNN having a slight advantage.

VII. FUTURE WORKS

Our goal is to consistently improve the model by tuning parameters or finding out better approaches to detection. We are open to trying out DDos attack to see if it produces better results than ours.

REFERENCES

- [1] D. S. Wall, “The Birth of the DDoS Attack: A Historical Perspective,” *ACM SIGCOMM Computer Communication Review*, vol. 37, no. 2, pp. 132–134, 2007.
- [2] D. Holzman, R. Sommer, D. Pothier, and U. Hengartner, “The Mirai Botnet Attack: A Case Study,” in *Proceedings of the 23rd USENIX Security Symposium*, 2014.
- [3] M. Schwartz, “GitHub’s Slowloris Attack: A Case Study,” *GitHub Engineering Blog*, 2015.
- [4] S. M. Bellovin, “The Code Red Worm: A Case Study,” 2001.
- [5] M. Tariq, M. K. Khan, and S. A. Madani, “A Survey of Distributed Denial-of-Service Attacks and Defense Mechanisms,” in *Computer Networks*, vol. 55, no. 15, pp. 3232–3249, 2011, doi: 10.1016/j.comnet.2011.06.011.
- [6] W. Dou, A. Sahu, and S. B. Sharma, “Defense against volumetric DDoS attacks: A survey and taxonomy,” in *Computer Networks*, vol. 143, pp. 134–152, 2018, doi: 10.1016/j.comnet.2018.06.006.
- [7] J. Mirkovic and P. Reiher, “DDoS flooding attacks on the internet,” in *Proceedings of the 5th IEEE International Workshop on Distributed Systems Operations and Management (DSOM 2004)*, Florence, Italy, 2004, pp. 203–214, doi: 10.1109/DSOM.2004.1328158.
- [8] D. J. Bernstein, “SYN flooding attacks and defenses,” in *ACM SIGCOMM Computer Communication Review*, vol. 26, no. 2, pp. 113–125, 1996, doi: 10.1145/235063.
- [9] V. Paxson, “An analysis of using reflectors for distributed denial-of-service attacks,” in *ACM SIGCOMM Computer Communication Review*, vol. 31, no. 3S, pp. 38–47, 2001, doi: 10.1145/505588.505638.
- [10] J. Mirkovic and P. Reiher, “DDoS in the time of giants: Amplification, reflection, and the state of the art,” in *Proceedings of the 6th ACM SIGCOMM Conference on Internet Measurement*, New York, NY, USA, 2006, pp. 25–30, doi: 10.1145/1179952.1179957.
- [11] R. Rashid, S. A. Shah, S. Raza, and S. Khan, “Detection and mitigation of NTP amplification DDoS attack: A survey,” in *Security and Privacy in Communication Networks*, vol. 118, pp. 130–152, 2020, doi: 10.1007/978-3-030-34901-9-6.
- [12] Y. Zhang, Z. Li, and Z. Su, “A survey on DNS amplification DDoS attacks,” in *Security and Communication Networks*, vol. 9, no. 10, pp. 1420–1433, 2016, doi: 10.1002/sec.1286.
- [13] M. Karami, M. J. Siavoshani, and A. Ghaffari, “A comprehensive survey of SSDP reflection attacks: Techniques, defenses, and open issues,” in *Journal of Network and Computer Applications*, vol. 188, p. 103086, 2021, doi: 10.1016/j.jnca.2021.103086.
- [14] P. Casas, J. Mazel, and P. Manzoni, “A survey of application-layer DDoS attacks,” in *ACM Computing Surveys (CSUR)*, vol. 47, no. 4, pp. 1–35, 2015, doi: 10.1145/2703837.
- [15] A. A. Dhama, S. A. Awan, A. Hussain, and M. A. Shah, “Defense mechanisms against HTTP flood DDoS attacks — A survey,” in *Computing and Informatics*, vol. 39, no. 4, pp. 823–852, 2020, doi: 10.31826/ci.39.4.5.
- [16] N. Kasabov and B. Vassilev, “SlowDoS attacks: Analysis and defense mechanisms,” in *Computers and Security*, vol. 39, pp. 127–142, 2013, doi: 10.1016/j.cose.2013.04.002.
- [17] M. Cherdantseva and V. Kumar, “Zero-day DDoS attacks: A survey,” in *ACM SIGCOMM Computer Communication Review*, vol. 49, no. 4, pp. 53–64, 2019, doi: 10.1145/3355341.3355419.
- [18] Shi Dong & Mudar Sarem, “DDoS Attack Detection Method Based on Improved KNN With the Degree of DDoS Attack in Software-Defined Networks”, *Volume: 8, Page(s): 5039 - 5048, DOI: 10.1109/ACCESS.2019.2963077*
- [19] Rintaro Harada & Naotaka Shibata & others, “Quick Suppression of DDoS Attacks by Frame Priority Control in IoT Backhaul With Construction of Mirai-Based Attacks.”, *Volume: 10, Page(s): 22392 - 22399, DOI: 10.1109/ACCESS.2022.3153067*

- [20] Yajie Li & Xiaosong Yu & others, "DDoS Attack Mitigation Based on Traffic Scheduling in Edge Computing- Enabled TWDM-PON.", Volume: 9, Page(s): 166566 - 166578, DOI: 10.1109/ACCESS.2021.3134671