

## Normalization – Online Order Placing

Customer Order Bill				
Customer ID	1001		Order Id	1001
Customer Name	SunBeam Infotech		Order Date	16-Apr-2018
Customer Address	Plot R/2		Delivery Date	20-Apr-2018
	Marketyard Road			
	Pune			
	411037			
Phone	020-24260308			
Product Id	Product Name	Quantity	Product Rate	Product Total
101	Notebook	4	20	80
102	Pencil	10	2	20
103	File	2	25	50
			<b>Bill Total</b>	<b>150</b>

Paper Work		
1.	CID	Int, compulsory
2.	CNAME	alphabets, compulsory
3.	CADDR	e.g. pin - 6 digits, colmulsory
4.	CPHONE	16 digits
5.	OID	Int
6.	ODATE	Date and time
7.	ODELDATE	Date
8.	PID	Int
9.	PNAME	Chars
10.	PRATE	Fractional values
11.	PQTY	Int (cannot be -ve)
12.	PTOTAL	...
13.	FTOTAL	...

<b>CUSTOMER_PLACE_ORDER</b>		
1.	CID	INT
2.	CNAME	VARCHAR(40)
3.	CAREA	VARCHAR(20)
4.	CSTREET	VARCHAR(20)
5.	CCITY	VARCHAR(20)
6.	CPIN	CHAR(6)
7.	CPHONE	VARCHAR(14)
8.	OID	INT
9.	ODATE	DATETIME
10.	OELDATE	DATE
11.	PID	INT
12.	PNAME	VARCHAR(40)
13.	PRATE	DECIMAL(7,2)
14.	PQTY	INT
15.	PTOTAL	DECIMAL(7,2)
16.	FTOTAL	DECIMAL(7,2)

<b>CUSTOMER_PLACE_ORDER --&gt; UNF</b>		
1.	CID	INT
2.	CNAME	VARCHAR(40)
3.	CAREA	VARCHAR(20)
4.	CSTREET	VARCHAR(20)
5.	CCITY	VARCHAR(20)
6.	CPIN	CHAR(6)
7.	CPHONE	VARCHAR(14)
8.	OID	INT --> PK
9.	ODATE	DATETIME
10.	OELDATE	DATE
11.	PID	INT
12.	PNAME	VARCHAR(40)
13.	PRATE	DECIMAL(7,2)
14.	PQTY	INT

Order Id	Product Id	Product Name	Quantity	Product Rate	Product Total
1001	101	Notebook	4	20	80
1001	102	Pencil	10	2	20
1001	103	File	2	25	50

ORDERED_PRODUCTS			
1.	PID	INT --> PK	
2.	PNAME	VARCHAR(40)	
3.	PRATE	DECIMAL(7,2)	
4.	PQTY	INT	

ORDERED_PRODUCTS <-- 1-NF			
1.	OID	INT --> CPK	
2.	PID	INT --> CPK	
3.	PNAME	VARCHAR(40)	
4.	PRATE	DECIMAL(7,2)	
5.	PQTY	INT	

CUSTOMER_ORDERS <-- 1-NF			
1.	CID	INT	
2.	CNAME	VARCHAR(40)	
3.	CAREA	VARCHAR(20)	
4.	CSTREET	VARCHAR(20)	
5.	CCITY	VARCHAR(20)	
6.	CPIN	CHAR(6)	
7.	CPHONE	VARCHAR(14)	
8.	OID	INT --> PK	
9.	ODATE	DATETIME	
10.	ODELDATE	DATE	

<b>ORDER_DETAILS &lt;-- 2-NF</b>		
1.	OID	INT <-- CPK
2.	PID	INT <-- CPK
3.	PQTY	INT

<b>PRODUCTS &lt;-- 2-NF</b>		
1.	PID	INT <-- PK
2.	PNAME	VARCHAR(40)
3.	PRATE	DECIMAL(7,2)

<b>CUSTOMER_ORDERS &lt;-- 2-NF</b>		
1.	CID	INT
2.	CNAME	VARCHAR(40)
3.	CAREA	VARCHAR(20)
4.	CSTREET	VARCHAR(20)
5.	CCITY	VARCHAR(20)
6.	CPIN	CHAR(6)
7.	CPHONE	VARCHAR(14)
8.	OID	INT <-- PK
9.	ODATE	DATETIME
10.	ODELDATE	DATE


CUSTOMERS			
1.	CID	INT	PK
2.	CNAME	VARCHAR(40)	
3.	CAREA	VARCHAR(20)	
4.	CSTREET	VARCHAR(20)	
5.	CCITY	VARCHAR(20)	
6.	CPIN	CHAR(6)	
7.	CPHONE	VARCHAR(14)	

ORDERS			
1.	CID	INT	FK
2.	OID	INT	PK
3.	ODATE	DATETIME	
4.	ODELDATE	DATE	

ORDER_DETAILS			
1.	OID	INT	FK
2.	PID	INT	FK
3.	PQTY	INT	

PRODUCTS			
1.	PID	INT	PK
2.	PNAME	VARCHAR(40)	
3.	PRATE	DECIMAL(7,2)	

ER-DIAGRAM



CUSTOMERS			
1.	CID	INT	PK
2.	CNAME	VARCHAR(40)	
3.	CAREA	VARCHAR(20)	
4.	CSTREET	VARCHAR(20)	
5.	CPIN	CHAR(6)	FK
6.	CPHONE	VARCHAR(14)	

PINS			
1.	PIN	CHAR(6)	PK
2.	CITY	VARCHAR(20)	

ORDERS			
1.	CID	INT	FK
2.	OID	INT	PK
3.	ODATE	DATETIME	
4.	OELDATE	DATE	

ORDER_DETAILS			
1.	OID	INT	CPK   FK
2.	PID	INT	CPK   FK
3.	PQTY	INT	

PRODUCTS			
1.	PID	INT	PK
2.	PNAME	VARCHAR(40)	
3.	PRATE	DECIMAL(7,2)	

