

MySQL - RDBMS

Agenda

- PSM / PL-SQL
 - Exception handling
 - Cursors
 - Functions
 - Triggers
- Normalization
 - SQL keys
 - UNF
 - 1-NF
 - 2-NF
 - 3-NF
 - BCNF
 - Denormalization

PSM

Stored Procedure

- Login with "root" and use "classwork" database.

```
SELECT USER(), DATABASE();  
-- | root@localhost | classwork |  
SELECT DEFINER, ROUTINE_DEFINITION FROM INFORMATION_SCHEMA.ROUTINES  
WHERE DEFINER = 'sunbeam@localhost';
```

Exception handling

- In MySQL errors are represented with error code or error state.
 - Error code
 - 1062 -- Duplicate entry
 - 1044 -- Access denied
 - 1146 -- Table doesn't exists
 - Error state
 - 23000 -- Duplicate entry
 - 42000 -- Access denied
 - 42S02 -- Table doesn't exists
 - NOT FOUND -- End of file/cursor

```
SELECT * FROM books;
```

```
INSERT INTO books VALUES (4003, 'Harry Potter', 'Rowling', 'Novell', 626.9);
-- ERROR 1062 (23000): Duplicate entry
```

- Transaction management using error handler

```
CREATE PROCEDURE sp_placeorder(...)
BEGIN
    DECLARE EXIT HANDLER FOR error
    BEGIN
        ROLLBACK;
        SELECT 'Order failed' AS msg;
    END;

    START TRANSACTION;
    INSERT INTO orders VALUES (...);
    INSERT INTO order_items VALUES (...);
    INSERT INTO payments VALUES (...);
    COMMIT;
END;
```

Cursors

- In Java, foreach loop is used to access elements one by one from a collection.

```
for(Emp e : emps) {
    // ...
}
```

- Cursor is a special variable in PSM used to access rows/values "one by one" from result of "SELECT" statement.
- Programming Steps
 - 1. Declare handler for end of cursor (like end-of-file). Error code: "NOT FOUND".
 - 2. Declare cursor variable with its SELECT statement.
 - 3. Open cursor.
 - 4. Fetch (current row) values from cursor into some variables & process them.
 - 5. Repeat process all rows in SELECT output. At the end error handler will be executed.
 - 6. Exit the loop and close the cursor.

```
DECLARE v_flag INT DEFAULT 0;
DECLARE CONTINUE HANDLER FOR NOT FOUND -- 1
BEGIN
    SET v_flag = 1;
END;
```

```

DECLARE v_cur CURSOR FOR SELECT ...; -- 2

OPEN v_cur; -- 3

label: LOOP
    FETCH v_cur INTO variable(s); -- 4
    IF v_flag = 1 THEN -- 5
        LEAVE label; -- 6
    END IF;
    process variables; -- 4
END LOOP;

CLOSE v_cur; -- 6

```

Cursor - use case

- T1 (C1) --> 1, 2, 3, 4
- T2 (C2) --> 10, 22, 35, 46

```

DECLARE v_cur1 CURSOR FOR SELECT c1 FROM t1;
DECLARE v_cur2 CURSOR FOR SELECT c2 FROM t2;

OPEN v_cur1;
OPEN v_cur2;

SET v_i = 1;

again: LOOP
    FETCH v_cur1 INTO v1;
    IF v_flag = 1 THEN
        LEAVE again;
    END IF;

    FETCH v_cur2 INTO v2;
    IF v_flag = 1 THEN
        LEAVE again;
    END IF;

    INSERT INTO result VALUES (v_i, CONCAT(v1, ' - ', v2));
    SET v_i = v_i + 1;
END LOOP;

CLOSE v_cur1;
CLOSE v_cur2;

```

Characteristics of "MySQL Cursors"

- Readonly
 - We can use cursor only for reading from the table.

- Cannot update or delete from the cursor.
 - SET v_cur1 = (1, 'NewName'); -- not allowed
- To update or delete programmer can use UPDATE/DELETE queries.
- Non-scrollable
 - Cursor is forward only.
 - Reverse traversal or random access of rows is not supported.
 - When FETCH is done, current row is accessed and cursor automatically go to next row.
 - We can close cursor and reopen it. Now it again start iterating from the start.
- Asensitive
 - When cursor is opened, the addresses of all rows (as per SELECT query) are recorded into the cursor (internally). These rows are accessed one by one (using FETCH).
 - While cursor is in use, if other client modify any of the rows, then cursor get modified values. Because cursor is only having address of rows.
 - Cursor is not creating copy of the rows. Hence MySQL cursors are faster.

User-defined Functions

- DETERMINISTIC
 - If input is same, output will remain same ALWAYS.
 - Internally MySQL cache input values and corresponding output.
 - If same input is given again, directly output may return to speedup execution.
- NOT DETERMINISTIC
 - Even if input is same, output may differ.
 - Output also depend on current date-time or state of table or database settings.
 - These functions cannot be speedup.

Triggers

- Stored Procedure and Functions
 - PSM syntax
 - Stored on server disk
 - Processed on server side
 - Reusable
 - Called by user
 - CALL sp_name()
 - SELECT fn_name()
- Trigger is MySQL program (PSM syntax). It's execution is triggered (caused) by some event -- DML operation on a table.
 - BEFORE INSERT
 - AFTER INSERT
 - BEFORE UPDATE
 - AFTER UPDATE
 - BEFORE DELETE
 - AFTER DELETE
- If multiple rows are INSERT/UPDATE/DELETE, then trigger will be executed once "for each row".
- The affected rows can be accessed using NEW and OLD keywords.
 - INSERT --> NEW row

- DELETE --> OLD row
- UPDATE --> NEW and OLD row
- It is never called explicitly by the user. It cannot have arguments or return value. It's output is not printed console.

```
DROP TABLE IF EXISTS accounts;
```

```
CREATE TABLE accounts(id INT PRIMARY KEY, type CHAR(10), balance DECIMAL(9,2));  
INSERT INTO accounts VALUES  
(1, 'Saving', 0.0),  
(2, 'Saving', 0.0),  
(3, 'Saving', 0.0);
```

```
CREATE TABLE transactions(id INT PRIMARY KEY AUTO_INCREMENT, acc_id INT, type  
CHAR(20), amount DECIMAL(9,2));
```

```
CREATE TRIGGER update_balance  
AFTER INSERT ON transactions  
FOR EACH ROW  
BEGIN  
    IF NEW.type = 'Deposit' THEN  
        UPDATE accounts SET balance = balance + NEW.amount WHERE id = NEW.acc_id;  
    ELSE  
        UPDATE accounts SET balance = balance - NEW.amount WHERE id = NEW.acc_id;  
    END IF;  
END;
```

```
-- cascading trigger  
CREATE TRIGGER balance_check  
AFTER UPDATE ON accounts  
FOR EACH ROW  
BEGIN  
    IF NEW.balance < 0 THEN  
        -- error  
    END IF;  
END;
```

```
INSERT INTO transactions(acc_id, type, amount) VALUES (1, 'Deposit', 2000.0);  
INSERT INTO transactions(acc_id, type, amount) VALUES (2, 'Deposit', 10000.0);  
INSERT INTO transactions(acc_id, type, amount) VALUES (2, 'Withdraw', 1000.0);
```